



NOMINAL SIZE		1/4 (.250)		5/16 (.312)		3/8 (.375)		7/16 (.437)*		1/2 (.500)	
Threads Per Inch		20 UNC-3B	28 UNF-3B	18 UNC-3B	24 UNF-3B	16 UNC-3B	24 UNF-3B	14 UNC-3B	20 UNF-3B	13 UNC-3B	20 UNF-3B
B Width Across Flats	Nom	.437		.500		.562		.687		.750	
	Max	.4385		.5020		.5645		.6895		.7520	
	Min	.428		.489		.551		.675		.736	
C Width Across Corners	Ref	.488		.557		.628		.768		.840	
H Thickness	Max	.328		.359		.469		.524		.609	
	Min	.212		.258		.320		.365		.427	
Prevailing Torque In. Lb.	Max	40		80		107		133		200	
Prevailing Torque Inch Lb. Min	1st Removal	6.0		10.5		16		23		30	
	5th Removal	4.5		7.5		11.5		16		20	
Axial Strength Lb.	Min	4,750	5,450	7,850	8,700	11,600	13,200	16,000	17,800	21,300	24,000
MATERIAL AND PROTECTIVE COATING		DASH NO.	DASH NO.	DASH NO.	DASH NO.	DASH NO.	DASH NO.	DASH NO.*	DASH NO.*	DASH NO.	DASH NO.
STEEL, PHOSPHATE COATED		1	2	3	4	5	6	7*	8*	9	10
STEEL, CADMIUM PLATED		31	32	33	34	35	36	37*	38*	39	40
STEEL, UNCOATED			70*			71*	72*				

NOMINAL SIZE		9/16 (.562)*		5/8 (.625)		3/4 (.750)		7/8 (.875)*		1 (1.000)	
Threads Per Inch		12 UNC-3B	18 UNF-3B	11 UNC-3B	18 UNF-3B	10 UNC-3B	16 UNF-3B	9 UNC-3B	14 UNF-3B	8 UNC-3B	12 UNF-3B
B Width Across Flats	Nom	.875		.937		1.125		1.312		1.500	
	Max	.8770		.9395		1.1270		1.3145		1.5020	
	Min	.861		.922		1.088		1.269		1.450	
C Width Across Corners	Ref	.982		1.051		1.240		1.447		1.653	
H Thickness	Max	.656		.765		.890		.999		1.124	
	Min	.473		.535		.617		.724		.831	
Prevailing Torque In. Lb.	Max	266		400		533		800		1070	
Prevailing Torque Inch Lb. Min	1st Removal	40		52		78		117		160	
	5th Removal	28		36		54		82		112	
Axial Strength Lb.	Min	27,300	30,500	33,900	38,400	50,100	56,000	69,300	76,300	91,000	99,500
MATERIAL AND PROTECTIVE COATING		DASH NO.*	DASH NO.*	DASH NO.	DASH NO.	DASH NO.	DASH NO.	DASH NO.*	DASH NO.*	DASH NO.	DASH NO.
STEEL, PHOSPHATE COATED		11*	12*	13	14	15	16	17*	18*	19	20
STEEL, CADMIUM PLATED		41*	42*	43	44	45	46	47*	48*	49	50

* INACTIVE FOR NEW DESIGN AFTER 23 JUNE 1976.

© ENTIRE STANDARD REVISED

APPROVED 24 JUNE 63 REVISED (A) 24 MAY 66 (B) 17 MAY 68 (C) 23 JUNE 1976

REVIEWER: EL AT AV MI EA MU PA GL WV YD MC
USER: ME MC

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A. WC
Other Cust 82
OS

TITLE
NUT, SELF-LOCKING, HEXAGON - PREVAILING TORQUE, FOR CRITICAL INSTALLATIONS, 250°F, UNC-3B AND UNF-3B

MILITARY STANDARD
MS51943

PROCUREMENT SPECIFICATION
MIL-N-45913

SUPERSEDES: BBSX5 and BBSX2, BBSX3, BBSX4 in part, and BBWX7

SHEET 1 OF 2

DD FORM 1 SEP 67 672-1 (coordination) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5310-0805

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:14Z
Check the source to verify that this is the current version before use.

NOMINAL SIZE		1-1/8(1.125)		1-1/4(1.250)		1-3/8(1.375)	1-1/2(1.500)			
Threads Per Inch		7 UNC-3B	12 UNF-3B	7 UNC-3B	12 UNF-3B	6 UNC-3B	6 UNC-3B	12 UNF-3B		
B Width Across Flats	Nom	1.687		1.875		2.062	2.250			
	Max	1.6895		1.8770		2.0645	2.2520			
	Min	1.631		1.812		1.994	2.175			
C Width Across Corners	Ref	1.859		2.066		2.273	2.480			
H Thickness	Max	1.281		1.422		1.609	1.671			
	Min	.939		1.030		1.138	1.245			
Prevailing Torque In. Lb.	Max	1200		1333		1600	1800			
Prevailing Torque Inch Lb. Min	1st Removal	200		250		293	346			
	5th Removal	140		176		205	242			
Axial Strength Lb.	Min	115,000	128,000	145,000	161,000	173,000	211,000	237,000		
MATERIAL AND PROTECTIVE COATING		DASH NO.	DASH NO.	DASH NO.	DASH NO.	DASH NO.*	DASH NO.	DASH NO.		
STEEL, CADMIUM PLATED		51	52	53	54	~~55*~~	56	57		

NOTE: To be used for critical installations such as tank track, suspension, running gear, and turret attachments and all other installations using heat treated bolts Grade 5 to 8 or equivalent. For general purpose use MS-51922.

MATERIAL: Steel, carbon or alloy steel, Grade C, in accordance with procurement specification. Insert, nylon or equivalent.

PROTECTIVE COATING: Steel, Carbon, Cadmium Plated QQ-P-416, Type II Class 3, Phosphate Coating MIL-P-16232 Type "Z" Class 2.

VIBRATION LIFE: Minimum vibration life requirement in accordance with MIL-N-25027.

DIMENSIONS: All dimensions in inches.

THREADS: UNC-3B and UNF-3B.

PART NUMBER: The MS part number consists of the MS number, plus the dash number. Example: MS51943-1.

NOTES: (1) Referenced documents shall be of the issue in effect on date of invitations for bid.
(2) This standard takes precedence over documents referenced herein.

* INACTIVE FOR NEW DESIGN AFTER 23 JUNE 1976.

INTERCHANGEABILITY TABLE

The nuts covered by the following dash numbers given in previous issue of this standard are cancelled after 24 May 66. The cancelled nuts should be used for maintenance purposes until existing stock is depleted. Use only the superseding nuts for new design and replacement after stock depletion. Replacement shall be in accordance with the following table:

PART NUMBERS	
CANCELLED	SUPERSEDING
MS51943 REVISION A	MS51943 CURRENT ISSUE
DASH NO.	DASH NO.
21	51
22	52
23	53
24	54
25	55
26	56
27	57

REVIEWER: AT AV MC MI MU PA WV YD
USER: EL ME EA GL

APPROVED 24 JUNE 63 REVISED (A) 24 MAY 66 (B) 17 MAY 68 (C) FOR CHANGES SEE SHEETS 1 AND 2

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A. WC
Other Cust 82
OS

TITLE
NUT, SELF-LOCKING, HEXAGON-PREVAILING TORQUE, FOR CRITICAL INSTALLATIONS, 250°F, UNC-3B AND UNF-3B

MILITARY STANDARD
MS51943

PROCUREMENT SPECIFICATION
MIL-N-45913

SUPERSEDES: BBSX5 and BBSX2, BBSX3, BBSX4 in part, and BBWX7

DD FORM SEP 67 672-1 (COVER SHEET) SUPERSEDES PREVIOUS EDITION OF THIS FORM WHICH MAY BE USED. 5310-0805

Source: https://assist.dla.mil - Downloaded: 2026-10-23T18:14Z
Check the source to verify that this is the current version before use.