MIL-C-63227A (AR)
AMENDMENT 2
5 MARCH 1984
SUPERSEDING
AMENDMENT 1
17 June 1982

MILITARY SPECIFICATION

CONTAINER, AMMUNITION, METAL, PA 101 FOR
PROJECTILE, 155MM, HE, GUIDED,
CANNON LAUNCHED, M712 AND TRAINING M823

This amendment forms a part of Military Specification MIL-C-63227A, dated 9 September 1981, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Title: Delete the phrase "155MM, HE, Guided, Cannon Launched" and substitute the phrase "155MM: Heat, Cannon Launched Guided".

* 1.1 Delete the phrase "155MM, HE, Guided, Cannon Launched" and substitute the phrase "155MM: Heat, Cannon Launched Guided".

* 2.1 Government documents. Add under STANDARDS as follows:

"MIL-STD-1188 - Commercial Packaging of Supplies and Equipment."

Delete "FSC: 1320" and substitute "FSC 8140" at the right hand corner at the bottom of the page.

PAGE 2

* 2.1 Drawings. Delete the following:

"US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

9300440 - Container, Ammunition, Metal, PA101, for Projectile, 155MM, HE, Guided Cannon Launched, M712 and Training M823"

FSC 8140

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

and substitute:

"US ARMY RESEARCH AND DEVELOPMENT CENTER

9300440 - Container, Ammunition, Metal, PA101, for Projectile, 155MM: HEAT, Cannon Launched Guided, M712, and Training, M823"

* Add the following:

"9305335 - Packaging Assembly for Projectile, 155MM: Heat, Cannon Launched Guided, M712, and Training, M823, with Packing and Marking Instructions.

US ARMY DEFENSE AMMUNITION CENTER AND SCHOOL

19-48-4159-20PM-1003 - Unitization Procedures for 155MM Copperhead Separate Loading Projectiles, Packed One Per Metal Container, Unitized 6 Containers Per Special 4-Way Entry Pallet"

* 3.4 Delete in its entirety and substitute the following:

"3.4 Environmental conditions. The container shall be laden with one Projectile, Training, M823 according to drawing 9305335. The Dummy Card, Label, and stenciling may be omitted. The Bands, Adjustment Handle, and Lifting Straps supplied inside the container shall be used as the internal packaging. Any prior damage exhibited by the projectile shall be recorded by markings, photographs, or documented list. The laden container shall withstand exposure to the tests and inspections as specified in Table I - First Article Inspection or Paragraph 4.4.2.27 of Quality Conformance Inspection - whichever is applicable. The sequence of tests and inspections shall occur in the order as listed. No adjustments shall be made to the barrel nuts on the latches throughout the entire test and inspection sequence.

Examination shall commence with the unpacking of the projectile. The container lid shall be unlatched and opened without the use of a bar or any other device. There shall be no damage to or displacement of the gasket. The tailstop should be backed off without the use of any tool, except the adjustment handle. The projectile shall be manually removed from the container using lifting straps, and without prying.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

There shall be no weld cracks visible except those allowable on containers which have been subjected to fragility shock exposure. There shall be no physical damage to the projectile and/or any one of the elements of the container assembly which would render them unserviceable as determined by the procuring agency. Minor dents, scratches and other forms of permanent deformations to the container that do not obstruct handling, assembly or ability of the container to protect its contents through its continued use shall not constitute cause for rejection.

Examination shall be complete when the projectile is repacked, as above, in the tested container.

The Government shall select the sample for mid test examination.

PAGE 4

* Delete Table 1, First Article Inspection, and substitute new Table 1 attached.

PAGE 9

* 4.4.2.4, Major 103: Delete "Saml1" and substitute "Small".

PAGE 12

* 4.4.2.8 Major Category: Add a new major defect as follows:

Major 109	Defective threads (like sharp crest of threads, burrs, etc.)	0.40%	3.2	Visual

Minor Category 202: Delete the item in its entirety.

PAGE 13

* 4.4.2.9, Major Category: Add a new major defect as follows:

Major 107	Defective threads (like sharp crest of threads, burrs, etc.)	0.40%	3.2	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

PAGE 16

* 4.4.2.12: Delete the title "Pin, Latch" and substitute "Pin, Cage".

Major 102: Delete "Length of Small ID" and substitute "Length of Small OD."

PAGE 17

* 4.4.2.13, Minor Category: Add a new defect as follows:

202	Grooved pin properly centered within the drawbolt	1.0%	3.2	Visual

PAGE 25

* 4.4.2.21, Delete Page 25 for "Tab, Pre-Load", and substitute new Page 25 for "Band, Preload" attached.

PAGE 27

* 4.4.2.23, Major 106 Material Properties: Delete "0.40%" under heading AQL.

PAGE 28

* 4.4.2.24, Major Category:

Major 102: Delete the item in its entirety.

Major 103: Delete the item and substitute the following:

103	Location of cover stops (at 6 places).

PAGE 29

* 4.4.2.25, Major Category: Add major defects as follows:

Major 107	Anti-seize compound not clearly visible over entire threaded surface of aft bulk-head and tail stop	0.40%	3.2	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

Major 108	Absence of properly applied anti-seize compound on both tail stop and aft bulkhead	0.40%	3.2	Visual
Major 109	Presence of paint on threaded surface of both tail stop and aft bulkhead	0.40%	3.2	Visual

PAGE 30

* 4.4.2.26, Major 104: Delete the item in its entirety.

PAGE 30-A

* 4.4.2.27: Delete Page 30A added by Amendment 1, and substitute a new Page 30A attached.

PAGE 31

* 4.4.3, Change paragraph number from "4.4.2.26" to "4.4.2.27".

* 5.4.1.4, Change paragraph number from "5.4.1.4" to "4.5.1.4".

* 5.4.1.5, Change paragraph number from "5.4.1.5" to "4.5.1.5".

PAGE 32

* 5.2 Delete in its entirety and substitute the following:

"5.2 Packing. Packing shall be commercial. The containers shall be prepared in accordance with paragraph 2.3.1 of MIL-STD-1188. Ordinary skids or 2-way pallets may be used. A maximum of twelve containers may be strapped to each pallet. Fiberboard or wooden separators shall be placed between the containers."

* 5.3, Alternate packing. Delete the number "1948 415920 PM1003" and substitute the number "19-48-4159-20PM-1003".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63227A(AR)
AMENDMENT 2

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Assemblies and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Container Assemblies (Dwg 9300440)				
	a. Examination for defects	4	100%	3.2	4.4.2.26
	b. Handle pull test	1		3.3	4.5.3
	c. Salt fog test	4	100%	3.4.1	4.5.1.1
	d. Transportation vibration test	4	100%	3.4.2	4.5.1.2
	e. Loose cargo vibration test	4	100%	3.4.3	4.5.1.3
	f. Transit drop test	4	100%	3.4.4	4.5.1.4
	g. Leakage test 1/	1		3.2	4.5.2
	h. Mid test examinations 1/	1		3.4	Visual
	i. Leakage test 1/	1		3.2	4.5.2
	j. Fragility shock test	4	100%	3.4.5	4.5.1.5
	k. Leakage test	4	100%	3.2	4.5.2
	l. Post test examinations 2/	4	100%	3.4	Visual
	Detailed Parts (Dwg - See para 4.4.2.1 - 4.4.2.25)				
	Examination for defects	5 ea	100%	3.2	4.4.2.1 thru 4.4.2.25

NOTES: 1/ Same one sample unit shall be subjected to the tests and examinations indicated by g, h, and i above.

2/ Crack criteria for welding. After completion of fragility shock and leakage tests, the following criteria shall apply:

	On Each Side of Bulkhead	On Each TIG Weld	Around Each Cover Stop
Maximum number of cracks	2	1	1
Shortest distance in inches between two nearest cracks allowable	4	--	--
Maximum length of individual crack	0.5	0.25	0.25

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET OF	DRAWING NUMBER
4.4.2.21	Band, preload		9301827
			NEXT HIGHER ASSEMBLY 9300440

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Tab overall height		0.40%	3.2	Gage
102	Tab overall width		0.40%	3.2	Gage
103	Friction between tabs and band	Note a	0.40%	3.2	Manual
104	Location of tabs		0.40%	3.2	Gage
105	Strength requirements		0.40%	dwg	Test
106	Material properties			3.2	Certificate of Conformance
Minor					
201	Tab overall length		0.65%	3.2	Gage
202	Drawbolt thread engagement throughout entire length of torque nut		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.0%	3.7	Visual

NOTES:
a. Lack of friction shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.27	Container assembly				9300440
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	a. Transportation vibration test	Note a	Note b	3.4.2	4.5.1.2
102	b. Loose cargo vibration test	Note a	Note b	3.4.3	4.5.1.3
103	c. Transit drop test	Note a	Note b	3.4.4	4.5.1.4
104	d. Handle pull test	Note c	Note b	3.3	4.5.3
105	e. Leakage test	Note a	Note b	3.2	4.5.2
106	f. Post test examinations			3.4	3.4
Minor	None defined				

NOTES:
a. For lot size 2 to 50 - 2 samples; for lot size 51 to 500 - 3 samples; for lot size 501 to 3200 - 5 samples.

b. There shall not be any failure in any of the samples.

c. One sample in five lots.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.

Delete "Project no. 1320" and substitute "Project no. 8140".

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army-AR

Preparing activity:
Army-AR

Project 8140-A629

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:26Z
Check the source to verify that this is the current version before use.