MIL-C-82724
AMENDMENT 1
14 January 1988

MILITARY SPECIFICATION

CARTRIDGE, IMPULSE, CCU-44/B

This amendment forms a part of MIL-C-82724, dated 9 February 1983 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1 Delete entire paragraph and substitute the following:

2.1.1 Specifications and standards. The following specifications and standards form and part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

Change bottom of Page 1 as follows:

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization Branch (3730), Indian Head, MD 20640-5000.

AMSC N/A FSC 1377

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

PAGE 2

Add the following after MIL-STD-453.

DOD-STD-2101(OS) Classification of Characteristics

PAGE 3

Under Publications delete WR-43 in its entirely (see DOD-STD-2101(OS)).

2.1.2 Under "5184845" add "5184850 Cartridge, Impulse, Assembly CCU-44/B".

2.2. Delete entire paragraph and substitute the following:

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Jnless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:22Z
Check the source to verify that this is the current version before use.

2.3. Add the following at the end of the last sentence:

Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Paragraph 3.2 Conformance to documents line 4, after "Respective Drawings: Delete Remainder of this paragraph in its entirety.

PAGE 4

Add new paragraph "3.4.5 Electrode recess. The electrode recess shall be verified 100 percent during acceptance testing. If one or more samples fail to meet requirements, the contractor shall be required to screen the entire lot represented (see 4.7.3.6).

PAGE 5

3.5.3 Delete paragraph in its entirety and substitute: "The upper limit of thrust shall be 12200 lbf".

3.5.4 Delete paragraph in its entirety and substitute: "Lower limit of velocity shall be 22ft/sec". (See 6.3.8)

PAGE 6

4.1.1 Add the following paragraph:

"4.1.1 Responsibility for compliance. This item must meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection systems or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material."

PAGE 6

4.5 Line 3 Delete: "WR-43" and substitute: "DOD-STD-2101(OS)".

PAGE 7

4.6 In the 4th Column Delete subheading: "WR-43" and substitute: "DOD-STD-2101".

4.6 Add the following entry to the listing below "Ignition element".

Cartridge	Electrode recess	3.4.5, 4.7.3.6	(M110)

4.6 Change existing classification of "M110, M111, and M112" to "M111, M112, and M113", respectively.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:22Z
Check the source to verify that this is the current version before use.

PAGE 9

4.7.3.6 Change existing "4.7.3.6" to "4.7.3.7" and add new paragraph "4.7.3.6 Electrode recess. The electrode shall be below the cartridge surface 0.005 "to 0.011", as detailed on Drawing 5184850."

PAGE 10

4.8.1, line 2: Delete "4.7.3.5" and substitute "4.7.3.6".

4.8.2, line 6: Delete "4.7.3.6" and substitute "4.7.3.7".

PAGE 13

Add the following paragraphs:

6.4 First article. When first article inspection is required the item(s) should be a first article sample, selected from the first five production items, or it may be a standard production item from the contractor's current inventory as specified 4.3.2 and 4.3.3. The first articles should consist of five or more, unit(s). The contracting officer should include specific instructions in acquisition documents regarding inspection, approval of first article test results and disposition of first articles. Invitations for bids should provide, that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is currently appropriate for the pending contract".

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Add paragraph 6.5:

6.6 Subject term(s) (Key Word Listing).

Military Specification
Cartridge
Cartridge-Explosives
Cartridge-Propellants
CCU-44/B
Impulse, Cartridge

Custodians:
Navy - OS
Air Force - 99

Preparing Activity:
Navy - OS
(Project No. 1377-0907)

Review Activities
Navy - AS
Air Force - 70

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:22Z
Check the source to verify that this is the current version before use.