MIL-G-49369A(ER)
AMENDMENT 3
25 October 1984
SUPERSEDING
AMENDMENT 2
27 September 1982

MILITARY SPECIFICATION
GENERATOR DIRECT CURRENT
G-76(V)/G WITH ACCESSORIES

This amendment forms a part of Military Specification MIL-G-49369A(ER) dated 19 June 1981, and is approved for use by the ERADCOM, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title, line 2. Delete "G-76 ( )/G" and substitute "G-76(V)/G."
Paragraph 1.1, line 2. Delete "G-76( )/G" and substitute "G-76(V)/G."

PAGE 2

Paragraph 2.1. Under drawings, Delete "G-76( )/G" and substitute "G-76(V)/G." (3 places) lines 2, 4 and 7.

PAGE 3 and 4

Delete Paragraph

3.2.2 "Accessories. Accessories shall be required as specified in the contract. Accessories include:

11738242	Accessory Kit, Field Radio Equipment, MK-2120/G
11738243	Accessory Kit, Permissive Action Link, MK-2121/G
11733296	Cable Assembly, Special Purpose, Electrical, CX- 13175/G
11733297	Cable Assembly, Special Purpose, Electrical, CX- 13176/G
11733365	Bag, Carrying
11733985	Adapter, Connector, MX-2122/G
11738274	Cover Assembly, Plate, Non Skid"

Add Paragraph

3.2.2 "Generator and accessories.

11738282 Generator, D.C., G-76(V)I/G
- 11733326 Generator, D.C. G-76/G
- 11738242 Accessory Kit, Field Radio Equipment MK-2120/G
  - 11733296 Cable Assembly, Special Purpose, Electrical, CX-13175/G
  - 11733297 Cable Assembly, Special Purpose, Electrical, CX-13176/G
  - 11733365 Bag, Carrying

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

11738283 Generator, D.C., G-76(V) 2/G
11733326 Generator, D.C., G-76/G
11738243 Accessory Kit, Permissive Action Link and Fuze Setter, MK-2121/G
11741868 Cable Assembly, Special Purpose, Electrical, CX-13205/G
11733985 Adapter, Connector, MS-2122/G
11733365 Bag, Carrying
11738274 Cover Assembly, Plate, Non Skid"

PAGE 5

Paragraph 3.2.5.1 Serial numbers, line 2. Delete "G-76( )/G" and substitute "G-76(V)/G."

PAGE 6

Paragraph 3.4.2.2 Unregulated output. Delete "100 RPM" and substitute "105 RPM."

Paragraph 3.4.4 Indicators. Delete portion of last sentence "2 amperes ± 10 percent" and substitute "2 amperes ± 15 percent."

PAGE 7

Paragraph 3.5.4 Immersion. Delete "The unit shall meet performance requirements 3.4 after being immersed in water for 10 minutes. There shall be no bubbles coming from within the equipment (See 4.8.18)." and substitute "The unit shall meet performance requirements (3.4) after being immersed in water. There shall be no leakage within the Generator Head or the Power Conditioning Unit (See 4.8.18)."

Paragraph 3.7 Reliability. Delete lines a and c and substitute "a. Temperature shall be a minimum of 104° (40°) or a maximum of 145°F (63°C) as measured in the Generator Head" and substitute ". Unless otherwise specified, the environment will be fixed ground as defined in MIL-STD-781."

PAGE 14

Paragraph 4.6.1.1 Generator head and handle assembly (11733321). Under Minor, delete line 202 in its entirety and number "203" and substitute number "202".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

PAGE 15

Paragraph 4.6.1.1.4 High speed shaft assembly (11733288). Under Major, add lines 102, 103 and 104 as shown below.

Category Defect	Method	Acceptance Criteria
"102 Proper bearing lubrication	visual (minimum magnification of 7X)	100% inspection"
"103 Proper assembly of shaft bearing and rotor	visual (minimum magnification of 7X)	100% inspection"
"104 No damage to shaft, bearing or rotor	visual (minimum magnification of 7X)	100% inspection"

PAGE 16

Paragraph 4.6.1.2 Power conditioning unit (11733425). Under Minor add:

"202 Interchangeability of power output connector	DS-5	2 samples/lot accept 0/reject 1"

PAGE 18

Paragraph 4.6.2 Defect summary. Add "DS-5 To check the quality of the assembly, connector (HDL 11738229) shall be inserted and removed from the power output connector of the Power Conditioning Unit with no undue effort."

Paragraph 4.8.1 Burn in, line 3. Delete "and be operated over a 3 hour period (one hour on, one hour off, one hour on)" and substitute "and be operated over a 3.5 hour period (one-half hour on, one hour off, one-half hour on, one hour off, one-half hour on)" at a speed of 68 RPM."

* Paragraph 4.8.2 Bounce Preconditioning. Line 8, delete "preconditioning for 1 minute." and substitute "preconditioning for 10 minutes."

PAGE 19

Paragraph 4.8.5 Heavy load. Add to line 6, "with 5 minute intervals between tests during which time the generator assembly shall not be cranked at all."

PAGE 20

Paragraph 4.8.10 Low temperature. Delete "At least once during the 10°F portion of the test, the unit shall undergo the output voltage test (4.8.4) and meet the requirements of 3.4.2." and substitute "At least once during the -10°F portion of the test, while cranking into a 10 ohm load, the unit shall undergo the output voltage test (4.8.4). After cranking for 4.5 ± 0.5 minutes, the unit shall meet the requirements of 3.4.2."

Source: https://assist.dla.mil -- Downloaded: 20260-22T20:03Z
Check the source to verify that this is the current version before use.

PAGE 22

Paragraph 4.8.13 Shock (transit drop) test. Add to the end of first sentence starting on line 3 "Procedure II (See 3.5.2), except that the total number of drops shall be reduced from 26 to 17, the 9 drops on the 4 rear corners, 4 rear edges and rear face are not required."

PAGE 23

Paragraph 4.8.18 Immersion test. Delete starting on line 2 "Procedure IV. The equipment shall be pressurized to 4 PSIG for a minimum of 10 minutes. The unit shall meet the requirements of 3.4.1 and 3.5.4 after conditioning before opening the unit." and substitute "Procedure 1. The equipment shall meet the requirements of 3.4 after conditioning before opening the Generator Head or Power Conditioning Unit. There shall be no evidence of leakage after opening these items."

Paragraph 4.8.23 Reliability test. Add "Each unit shall meet the requirements of 3.4.1 upon completion of test."

PAGE 24

Paragraph 6.1 Item definition. Delete "G-76( )/G" and substitute "G-76(V)/G."

Paragraph 6.1.1 Interface definition. Delete "G-76( )/G" and substitute "G-76(V)/G."

PAGE 25

Delete Paragraph

6.2.4 Level of packaging. "The contract should specify Level A or B preservation and packing (See section 5). In addition to the generator, the carrying bag and technical literature, the normal pack shall include:

Part No.	Nomenclature
11733296	Cable Assembly, Special Purpose, Electrical, CX-13175/G
11733297	Cable Assembly, Special Purpose, Electrical, CX-13176/G

As an option, the pack may include only Part Number 11733985, Adapter, Connector, MS-2122/G and Part Number 11738274, Cover, Plate, Nonskid, Assembly, instead of cables."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.

Add Paragraph

6.2.4 Level of packaging. "The contract should specify Level A or B preservation and packing (See Section 5). In addition to the generator and accessories (See Section 3.2.2) the normal pack shall include:

TM-11-6115-470-10 Operators Manual
TM-11-6115-470-10HR Hand Receipt Manual"

Paragraph 6.3.1 Harmonic drives, line 2. Delete "G-76( )/G" and substitute "G-76(V)/G".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing Activity
Army - ER

Project No. 6115-A491

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:03Z
Check the source to verify that this is the current version before use.