MILITARY SPECIFICATION

PROJECTILE, 155MM: INERT, M483A1
LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the US Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the loading, assembling and packing for one type of projectile designated as Projectile, 155MM, Inert, M483A1.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standards. Unless otherwise specified, the following specifications and standards, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	- Ammuntion, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-410	- Nondestructive Testing Personnel - Qualification and Certification

FSC 1320

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

MIL-STD-1235 - Single and Multi-level Continuous Sampling Procedures and Tables for Inspection by Attributes

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein.

DRAWINGS (See 6.6)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

PRODUCT AND PACKING DRAWINGS

9381450 - Projectile, 155MM: Inert, M483A1
8837839 - Pallet for Projectile, 155MM, HE: and GB, Hollow Base Type

INSPECTION EQUIPMENT DRAWINGS

8841732 - Test Fixture
9202990 - Operating Instructions

CODE OF FEDERAL REGULATIONS

TITLE 49 - Transportation, Parts 100-199

(Copies of specifications, standards, handbooks, drawings and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM E 18 - Standard Test Methods for Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

3. REQUIRMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Projectile. The projectile assembly and all components thereof shall comply with all requirements specified on Drawing 9381450, all associated drawings, and with all requirements specified in applicable specifications.

3.3 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.4 Records of results of contractor conducted examinations and tests. The contractor shall maintain records of the results of all examinations or tests required by this specification. (See 6.5)

3.5 Workmanship. All parts and assemblies shall be fabricated, loaded and assembled in a thorough workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous; however, a few light scratches not exposing base material and protective coating missing per paragraph 4.4.2.10 are permitted. All required marking and stamping shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the contracting officer for evaluation in

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part description	Drawings	Quantity
Projectile	9381450	12
Steel Shim	9215397	25

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70476 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Projectile and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Projectile (Dwg 9381450) Examination for Defects per 4.4.2.10	12	-	3.2	
	Steel Shim (Dwg 9215397) Examination for Defects 4.4.2.3	25		3.2	

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot shall contain:

a. Grenades (M42) from one finally accepted lot interfix number from one manufacturer.
b. Grenades (M46) from one finally accepted lot interfix number from one manufacturer.
c. Projectile metal parts (body assembly) from one lot interfix number from one manufacturer.
d. Base and cap assemblies from one lot interfix number from one manufacturer.
e. Adapters from one lot interfix number from one manufacturer.
f. Forward plates from one lot interfix number from one manufacturer.
g. Sleeves from one lot interfix number from one manufacturer.
h. Spacers from one lot interfix number from one manufacturer.
i. Splines from one lot interfix number from one manufacturer.
j. Loaded projectiles of one weight zone (see Note 1)

Note 1: Projectiles falling out of the inspection lot criteria due to the zone weight restriction may be accumulated into a hybrid lot provided they originally met all other lotting restrictions during manufacture and the original lot passed all acceptance tests.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Continuous sampling in accordance with MIL-STD-1235 may be utilized if approved by the Procuring Activity.

b. Automatic gaging. Facilities equipped with Government furnished automatic gaging capable of performing 100% inspection of any characteristic shall utilize this capability in accordance with the contract.

c. Alternate inspection procedures. The contractor may propose the use of alternate inspection procedures in lieu of conducting sampling inspection for defects listed in this specification (See paragraph 6.8).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70476 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9215380
4.4.2.1	Adapter				NEXT HIGHER ASSEMBLY 9381450
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Verification of heat treatment of adapter		100%	3.2	4.5.1
Minor	None defined				

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70476 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 10542902-1
4.4.2.2	Projectile Metal Parts Assembly, Prior to Loading				NEXT HIGHER ASSEMBLY 9381450
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Threads damaged at base end		0.40%	3.2	Visual
102	Threads damaged at nose end		0.40%	3.2	Visual
103	Internal lubricant applied improperly		0.40%	3.2	Visual
Minor					
201	Foreign matter on interior surface of body		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70476 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9215397
4.4.2.3	Shim, Steel				NEXT HIGHER ASSEMBLY 9381450
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Hardness		0.40%	3.2	4.5.2
102	Diameter, min.		0.40%	3.2	Gage
103	Thickness, min.		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70476 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Assembly, Forward Plate and O-Ring				None
					NEXT HIGHER ASSEMBLY
					9381450
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	O-ring not greased		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70476 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Grenade Assembly, Prior to Loading				9381451 or 9381454
					NEXT HIGHER ASSEMBLY
					9381450
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Inert marking missing, incomplete or illegible		100%	3.2	Visual
Major					
101	Safety clip not removed		0.40%	3.2	Visual
102	Ribbon unwound		0.40%	3.2	Visual
103	Tape not completely inserted in slots of stiffener		0.40%	3.2	Visual
104	Slider lock cracked, incomplete, missing or improperly positioned		100%	3.2	Visual
Minor	None defined				

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70476 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Projectile, After Removal of Safety Pins From Grenade Assembly, After Each Layer is Inserted Into the Projectile	1 OF 1	None
			NEXT HIGHER ASSEMBLY: 9381450

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Grenade type incorrect (1-8 layers only)		0.40%	3.2	Visual
102	Safety pin not removed from each grenade (all layers)		0.40%	3.2	Visual
103	Stiffener or tape improperly positioned (all layers)		0.40%	3.2	Visual
104	Slide assembly protruding from grenade fuze housing indicating armed or partially armed (all layers)		100%	3.2	Visual
105	Grenade type incorrect as evidenced by protective coating or lack of yellow marking (9-11 layers only)		100%	3.2	Visual
106	Slider lock broken, incomplete, missing or improperly positioned		100%	3.2	Visual
107	Grenade missing or improperly positioned (all layers)		100%	3.2	Visual
108	Any sleeve, spacer or spline missing, improperly positioned or incorrect length (all layers)		100%	3.2	Visual
Minor	None defined				

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70476 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Projectile and Base, After Assembly of Adapter and Immediately Prior to Assembly of Base and Seal Ring	1 OF 1	None
			NEXT HIGHER ASSEMBLY: 9381450

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Depth between projectile face and adapters or shims as applicable at specified load		100%	3.2	4.5.6
102	Adapter missing or improperly assembled		100%	3.2	Visual
103	Any sleeve, spacer or spline missing, improperly positioned or incorrect length		100%	3.2	Visual
104	Seal ring missing or wrong type		0.40%	3.2	Visual
105	Seal ring not greased		0.40%	3.2	Visual
106	Sealant missing on threads of base		0.40%	3.2	Visual
107	Threads damaged on base of projectile body		0.40%	3.2	Visual
108	Foreign material on threads		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRSMC-0A (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70476 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.8	Projectile, Prior to Assembly of Expulsion Charge Assembly and Grommet Assembly		None
			NEXT HIGHER ASSEMBLY
			9381450

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Gap between projectile body and base 360°, max.		100%	3.2	Gage
102	Bare spots in anodic coating on base		100%	3.2	Visual
103	Disassembly torque test of base	(a)	0.40%	3.2	4.5.3
104	Depth from surface of projectile to expulsion charge cup, min.		0.40%	3.2	Gage
105	True position of min. internal diameter of expulsion charge cup to pitch diameter of ogive threads		0.40%	3.2	Gage
106	Expulsion charge cup improperly staked		0.40%	3.2	Visual/Manual
107	Obturator missing or damaged		100%	3.2	Visual
108	Evidence of axial movement of obturator		100%	3.2	Manual
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:
(a) Sample size per MIL-STD-105, Inspection Level I.

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70476 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Projectile, Prior to Assembly of Grommet Assembly Gasket and Lifting Plug Assembly				None
					NEXT HIGHER ASSEMBLY
					9381450
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Weight		100%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70476 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Projectile		9881450
			NEXT HIGHER ASSEMBLY: None

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Lifting plug assembly wrong type (not fusible)		100%	3.2	Visual
102	Gasket missing or damaged		100%	3.2	Visual
103	Disassembly torque test of lifting plug assembly	(a)	0.40%	3.2	4.5.4
104	Air pressure test	(b)	0.40%	3.2	4.5.5
105	Diameter of bourrelet, max (applicable after paint on projectile has been retouched)		100%	3.2	Gage
106	Zone marking missing, incorrect or unidentifiable		0.40%	3.2	Visual
107	Diamond marking missing, incorrect or unidentifiable		0.40%	3.2	Visual
Minor					
201	Any part missing or damaged		0.65%	3.2	Visual
202	Rotating band damaged		0.65%	3.2	Visual
203	Protective coating with bare area in excess of 1/4 square inch		0.65%	3.2	Visual
204	Marking missing or unidentifiable		0.65%	3.2	Visual
205	Evidence of poor workmanship		0.65%	3.5	Visual

NOTE:
(a) Sample size per MIL-STD-105, Inspection Level I.
(b) Sample size per MIL-STD-1235, CSP-1, Code Letter F.

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2020-10-20 09:09 GMT
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70476 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Pallet Assembly				8837839
					NEXT HIGHER ASSEMBLY: None
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Inert marking of projectile missing or illegible or incomplete		100%	3.2	Visual
Major					
101	Incorrect strapping or improperly assembled		0.40%	3.2	Visual
102	Seal strapping missing		0.40%	3.2	Visual
103	Lifting plug of projectile missing or damaged		0.40%	3.2	Visual
104	Cover support missing (8 places)		100%	3.2	Visual
Minor					
201	Board broken or split		0.65%	3.2	Visual
202	FSN number missing or unidentifiable		0.65%	3.2	Visual
203	Any other marking missing incorrect or unidentifiable		0.65%	3.2	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance tables.

4.4.4 Inspection equipment. For the inspection equipment required to perform the examinations and tests prescribed herein the contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078; paragraph 6.3 and paragraph 6.7 herein.

4.5 Methods of inspection.

4.5.1 Verification of heat treatment of adapter (non-destructive. This inspection shall employ the eddy current method, or any other equivalent method approved by the procurement agency. If the eddy current method is used, all personnel operating and calibrating this equipment shall be qualified and certified in accordance with MIL-STD-410. The hardness limits shall be established and submitted to the Quality Assurance representative for approval prior to use. If any adapter fails to comply with the requirements specified on the applicable drawing, it shall be classed defective and removed from production.

4.5.2 Hardness test of shim (dwg. 9215397) (non-destructive). This test shall be performed in accordance with ASTM E 18 using the standard penetrator for the specified hardness scale. Three readings shall be taken approximately 120° apart. If any reading fails the requirement on the applicable drawing that shim shall be classed defective.

4.5.3 Disassembly torque test of base. The projectile with base assembled, shall be subjected to the disassembly torque specified on the applicable drawing. Any unit that fails to withstand the disassembly torque shall be classed defective.

4.5.4 Disassembly torque test of lifting plug assembly. The projectile with lifting plug assembled, shall be subjected to the disassembly torque specified on the applicable drawing. Any unit that fails to withstand the disassembly torque shall be classed defective.

4.5.5 Air pressure test of projectile. The assembled projectile, with lifting plug, shall be placed in one or more chambers, (the base to body, body to ogive and ogive to lifting plug joints must be tested) and a pre-determined volume of air shall be delivered to produce the specified pressure between the inside of the chamber and the outside of the projectile. After initiation of test, the pressure must achieve the required level and maintain that level for the specified time interval. Failure to meet either criteria shall be cause for rejection, and that projectile shall be suitably identified and removed from the lot to prevent mixing with acceptable projectiles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

All equipment used in this test shall be capable of performing the test accurately and consistently. Equipment shall be calibrated at the start of each shift and thereafter, at intervals of not more than four (4) hours of continuous operation. It shall also be calibrated prior to restarting the operation after a layoff of three (3) hours or more. If it is found that the gage is out of calibration in such a direction that the test pressure was actually lower than that specified on the drawing, projectiles tested since the last satisfctory calibraton shall be retested after the gage error has been corrected.

4.5.6 Depth to adapters or shims. This measurement shall be performed using automatic or semi-automatic inspection equipment. The design of this equipment shall be "fail-safe" to the extent that the projectile cannot be released for further processing until the proper number of shims have been inserted. Verification that the proper number of shims have been inserted shall be accomplished by re-inspection of this depth.

5. PACKAGING

5.1 Packing

5.1.1 Level A. The projectile shall be palleted in accordance with Dwg. 8837839.

5.2 Marking. Marking shall be in accordance with Dwg. 8837839 and Code of Federal Regulations, Title 49, Parts 100-199.

5.3 Shipping. When projectiles from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. Not applicable to this specification.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, USA ARDC, ATTN: AMSMC-QAR-I (D), Dover, NJ 07801-5001.

6.4 Submission of data cards. In addition to the normal distribution of records, when the projectile is procured by the U.S. Army Armament Material and Readiness Command, one (1) copy of all ammunition data cards shall be forwarded to: Commander, USA, ARDC, ATTN: AMSMC-QAR-Q (D), Dover, NJ 07801-5001.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

6.5 Data requirements. Data item descriptions (DID) required for submission under this specification are as follows:

Paragraph	Data requirements	Applicable D.I.D.
4.5.1, 4.5.2, 4.5.3, 4.5.4, 4.5.5	Quality Inspection Defect Report	DI-R-1721
6.8	Procedure Report	*DI-T-5372 (Tailored)

*Delete a, b, c, d of pargraph 1 block 10, DD Form 1664, and substitute contractor designated parameters and limits.

The above data shall be forwarded in accordance with the requirements of the contract to Commander, ARDC, ATTN: AMSMC-QAR-Q (D), Dover, NJ 07801.

6.6 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research and Development Center (ARDC) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal, or US Army Armament Research and Development Command (ARRADCOM) drawings. Technical data originally prepared by these activities is now under the cognizance of ARDC.

6.7 Automatic inspection equipment. All automatic test and inspection equipment when utilized by the contractor shall be subjected to a periodic verification and calibration check at frequent intervals during normal production. The procedures shall include as a minimum: frequency, method of verification, and the method of retrieval of items produced between verification/calibration. These procedures shall be included in the operation/calibration procedures as required by paragraph 4.4.4.

6.8 Alternate inspection procedures.

6.8.1 Justification for alternate inspection procedures. Submitted documentation must include sufficient information to indicate an economic benefit, and must also clearly identify that there is no reduction in product quality.

6.8.2 Alternate inspection procedures. The alternate inspection procedures as a minimum must include:

a. Frequency (production interval) for validating equipment functioning.

b. Proposed method of validation to include process and inspection drawings.

c. Description of material control procedures to be imposed during the production interval between validations (Note: Under these provisions final acceptance will be withheld from material produced during the producton interval until conducting satisfactory validation.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.

6.8.3 Approval of alternate inspection procedures. Proposed plans shall be submitted per para. 6.4 for approval.

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1320-A814)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:30Z
Check the source to verify that this is the current version before use.