INCH-POUND

MIL-R-82689
17 May 1994
SUPERSEDING
FA-PD-MI-2273
27 September 1960

MILITARY SPECIFICATION

RELEASE, FIRING PIN, GAS ACTUATED, M1A1 ASSEMBLY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for the M1A1 Gas Actuated Firing Pin Release (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplements thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-A-2550	Ammunition, General Specification For

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures And Tables For Inspection By Attributes
MIL-STD-109	Quality Assurance Terms And Definitions
MIL-STD-129	Marking for Shipment and Storage

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Standardization Branch (Code 3730), 101 Strauss Avenue, Indian Head, MD 20640-5035, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by sending a letter.

AMSC N/A FSC 1377

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.

MIL-STD-453	Inspection, Radiographic
MIL-STD-1168	Ammunition Lot Numbering

(Unless otherwise indicated, copies of federal and military specifications and standards are available from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following Government drawings form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation (see 6.2).

DRAWINGS

Indian Head Division, Naval Surface Warfare Center (CAGE Code 19200)

DL5184966	Release, Firing Pin, Gas Actuated, M1A1

U.S. Air Force

SPI 00-731-9272	Release, Firing Pin, Gas Actuated, M1A1

(Application for copies should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, 101 Strauss Avenue, Data Control Branch (Code 3720), Indian Head, MD 20640-5035.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order (see 6.2), a sample shall be subjected to the first article inspection (see 4.4 and 6.3).

3.2 Materials. All materials used in the manufacture of the removers and release mechanisms shall conform to the specifications referred to on the respective drawings unless specific approval in writing covering a departure therefrom has been obtained from the cognizant Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.3 Hardness and other physical properties. Hardness and other physical properties required by the drawing shall be uniform throughout the part within specified tolerances. Requirements for all alloy steel parts shall be achieved by quenching and tempering.

3.4 Hydrostatic pressure. The cylinder and housing shall withstand an internal hydrostatic pressure of 7,500 pounds per square inch (psi) for a minimum of 30 seconds without deformation or mechanical failure (see 6.4.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.

3.5 Protective finish. Protective finish shall be in accordance with the applicable specification and drawings and shall apply to all surfaces of the component regardless of contour configuration and includes internal surfaces. Special internal electrodes may be required to get the proper internal coating.

3.6 Radiographic inspection. Each release shall be radiographically examined for defects (see 4.5.3.7).

3.7 Metal parts assembly. When the firing pin release metal parts assembly is complete, except for the dust seal, the operating rod shall remain extended in the locked position while complying with the following conditions:

a. The operating rod shall be free to rotate 360 degrees with respect to the assembly and there shall be no evidence of binding or intermittent resistance to rotation, resulting from variation in the locking components or the presence of foreign matter.

b. The metal parts assembly shall be free to rotate 360 degrees with respect to the operating rod under a load application of 20 pounds. Load application shall be in the direction tending to cause retraction of the operating rod along the central axis of the assembly.

c. After rotation under load, the operating rod shall be free to rotate 360 degrees with respect to the assembly and there shall be no evidence of binding or intermittent resistance to rotation.

3.8 Functioning. When the operating rod of the assembled firing pin release is held firmly and a gas source having a maximum pressure of 250 psi is applied to the housing gas intake port, the firing pin release body and cylinder assembly shall move completely over the release operating rod. The operating rod shall be returned to the original extended position. Complete and positive locking shall be assured.

3.9 Breakaway torque. The cylinder of each firing pin release assembly, prior to sealing of the four cylinder holes, shall withstand a breakaway torque of 50 inch pounds with respect to the firing pin release housing.

3.10 Residual magnetism. The firing pin release assembly shall not deflect the indicator of the compass more than five degrees in either direction using procedures in 4.6.4.

3.11 Workmanship. Releases shall be free of cracks, splits, or other defects which might prevent proper mating with connecting parts or proper functioning of the RAU-3/A Remover.

3.11.1 Metal defects. All components shall be free from cracks, splits, cold shuts, inclusions, porosity, or any similar defect.

3.11.2 Burr. No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.11.3 Foreign matter. No part or assembly shall contain chips, dirt, grease, rust, corrosion, or other foreign matter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.

3.11.4 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required by MIL-A-2550.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements (see 6.2).

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements; however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Quality assurance terms and definitions. Reference shall be made to MIL-STD-109 to define the quality assurance terms used.

4.1.3 Inspections. Inspections shall be in accordance with MIL-A-2550.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4)
b. Quality conformance inspection (see 4.5)

4.3 Inspection conditions. Unless otherwise specified (see 6.2), all inspections shall be performed under the following conditions:

a. Temperature: room ambient (68 to 77°F)
b. Altitude: sea level
c. Humidity: 50 percent relative, maximum
d. Atmospheric pressure: 14.7 psi

4.4 First article inspection. At the beginning of regular production, the contractor shall submit an initial production sample to a Government approved facility for evaluation. The sample shall consist of five metal parts assemblies, nine sets of unassembled parts, and one set of unassembled parts without plating or final protective finish. The sample shall be manufactured in the same manner, using the same materials,

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.

equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, must be the same as will be used for regular production and shall be obtained from the same source of supply. After inspection and provisional acceptance at source, the first article sample shall be inspected for all requirements of the drawings and specifications. The Government reserves the right to require new first article samples until an acceptable sample is submitted (see 6.3).

4.5 Quality conformance inspection.

4.5.1 Lot.

4.5.1.1 Submission of product. Unless otherwise specified by the contracting activity, formation and identification of lots shall be in accordance with MIL-STD-105.

4.5.1.2 Size of lot. The production lot size shall be as specified in the contract.

4.5.2 Examination. One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects. Four power (4x) magnification may be used in performing visual examination for such defects as burr and foreign matter. When compliance with the applicable requirement is in doubt as a result of visual examination, the characteristic shall be measured or gaged to determine acceptability. All nonconforming material shall be rejected.

4.5.2.1 Cylinder, Drawing 5184973, covering a detail of Drawing 5184966.

Characteristics	Defect	Method of Inspection
Critical		
None defined		
Major		
101	Pitch diameter of thread, max	Gage
102	Minor diameter of thread, max	Gage
103	Concentricity of counterbore with pitch diameter of thread	Gage
104	Concentricity of cavity with pitch diameter of thread	Gage
105	Perpendicularity of seat of counterbore to seat of cavity, min	Gage
106	Diameter of counterbore, max	Gage
107	Diameter of cavity, max	Gage
108	Depth to seat of counterbore, min	Gage
109	Depth to counterbore, max	Gage
110	Depth to seat of counterbore to seat of cavity, min	Gage
111	Wall thickness, min	Gage
112	Metal defective	Visual
113	Protective finish inadequate or defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.

Minor

201	Pitch diameter of thread, min	Gage
202	Diameter of counterbore, min	Gage
203	Diameter of cavity, min	Gage
204	Diameter of recess at seat of cavity	Gage
205	Diameter of exhaust holes	Gage
206	Diameter of shoulder	Gage
207	Depth to seat of counterbore, max	Gage
208	Depth of counterbore, min	Gage
209	Depth from seat of counterbore to seat of cavity	Gage
210	Length of effective thread, min	Gage
211	Total length	Gage
212	Thickness of base	Gage
213	Wall thickness, max	Gage
214	Radial location of exhaust holes	Gage
215	Diameter of ineffective thread or undercut	Measure
216	Length of shoulder	Measure
217	Radius missing or illegible	Visual
218	Thread damaged or not full	Visual
219	Burr	Visual
220	Foreign matter	Visual

4.5.2.2 Housing, Drawing 5184967, covering a detail of Drawing 5184966.

Critical
None defined

Major

101	Pitch diameter of large thread, min	Gage
102	Major diameter of large thread, min	Gage
103	Pitch diameter of gas port thread, min	Gage
104	Major diameter of gas port thread, min	Gage
105	Concentricity of hole in gas port with small thread	Gage
106	Concentricity of boss with cavity	Gage
107	Concentricity of cavity with pitch diameter of large thread	Gage
108	Perpendicularity, face of flange with cavity	Gage
109	Perpendicularity, face at open end with cavity	Gage
110	Symmetry of flats behind flange with boss	Gage
111	Symmetry of mounting holes with boss	Gage
112	Diameter of small cavity	Gage
113	Diameter of large cavity	Gage
114	Diameter of gas port holes	Gage
115	Diameter of undercut, min	Gage
116	Diameter of gas port holes	Gage
117	Depth of cavity to rod hole	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.

118	Depth of cavity to internal shoulder, min	Gage
119	Length of large thread pilot, max	Gage
120	Wall thickness, min	Gage
121	Location of rod hole	Gage
122	Diameter of rod hole, min	Measure
123	Location of gas port hole	Measure
124	Thread damaged or not full	Visual
125	Metal defective	Visual
126	Protective finish inadequate or defective	Visual
127	Surface finish improper	Visual
128	Burr	Visual
129	Foreign matter	Visual
Minor		
201	Pitch diameter of large thread, max	Gage
202	Pitch diameter of gas port thread, max	Gage
203	Diameter of boss	Gage
204	Diameter of pilot, large end	Gage
205	Diameter of mounting holes	Gage
206	Diameter of gas port thread, pilot, max	Gage
207	Length from open end to face of flange	Gage
208	Length to end of large thread	Gage
209	Length of flat behind flange, min	Gage
210	Length of large thread, pilot, min	Gage
211	Length to gas port thread	Gage
212	Length of flat and flange	Gage
213	Width of flange	Gage
214	Width of undercut	Gage
215	Width across flats behind flange	Gage
216	Location of datum diameter	Gage
217	Location of mounting holes	Gage
218	Height from end of gas port to body	Gage
219	Diameter of chamfer at large cavity	Measure
220	Diameter of body at gas port base	Measure
221	Diameter of rod hole, max	Measure
222	Diameter of body	Measure
223	Diameter of flange	Measure
224	Total length	Measure
225	Width of flat Measure	
226	Thickness of flange	Measure
227	Height from end of gas port to center mounting	Measure
228	Radii, chamfer missing or incorrect	Visual
229	Surface finish improper	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.

4.5.2.3 Piston, Unlocking, Drawing 5184968, covering a detail of Drawing 5184966.

Critical
None defined

Major		
101	Concentricity of O-ring groove with flange	Gage
102	Concentricity of guide hole with flange	Gage
103	Concentricity of small counterbore with guide hole	Gage
104	Concentricity of large counterbore with guide hole	Gage
105	Concentricity of body at O-ring end with guide hole	Gage
106	Symmetry of O-ring groove	Gage
107	Diameter of flange, min	Gage
108	Diameter of O-ring groove	Gage
109	Diameter of guide hole, max	Gage
110	Diameter of small counterbore, min	Gage
111	Diameter of large counterbore, min	Gage
112	Depth to bottom of small counterbore, min	Gage
113	Depth of large counterbore	Gage
114	Sharp corners missing in large and small counterbores	Gage
115	Sharp corners present on O-ring groove	Visual
116	Metal defective	Visual
117	Protective finish inadequate or defective	Visual
118	Surface finish of small counterbore and O-ring flange improper	Visual
119	Burr	Visual
120	Foreign matter	Visual
Minor		
201	Diameter of flange, max	Gage
202	Diameter of guide hole, min	Gage
203	Diameter of small counterbore, max	Gage
204	Diameter of large counterbore, max	Gage
205	Diameter of body at O-ring end	Gage
206	Diameter of body at midsection	Gage
207	Diameter of body at open end	Gage
208	Depth to bottom of small counterbore, max	Gage
209	Total length	Gage
210	Length to flange	Gage
211	Length across flange	Gage
212	Length of outside diameter	Gage
213	Width of O-ring groove	Gage
214	Radii or chamfer missing or incorrect	Visual
215	Surface finish improper, except as otherwise classified	Visual
216	Burr	Visual
217	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.

4.5.2.4 Sleeve, Retainer, Drawing 5184971, covering a detail of Drawing 5184966.

Critical
None defined

Major		
101	Concentricity of body with guide holes	Gage
102	Concentricity of flange with guide hole	Gage
103	Perpendicularity of flange face with guide hole	Gage
104	Diameter of guide hole, max	Gage
105	Diameter of body, min	Gage
106	Diameter of flange, min	Gage
107	Thickness of flange, min	Gage
108	Metal defective	Visual
109	Protective finish inadequate or defective	Visual
110	Surface finish of flange face improper	Visual
111	Burr	Visual
112	Foreign matter	Visual

Minor		
201	Diameter of guide hole, min	Gage
202	Diameter of body, max	Gage
203	Diameter of flange, max	Gage
204	Diameter of holes in flange	Gage
205	Diameter of body holes	Gage
206	Total length	Gage
207	Thickness of flange, max	Gage
208	Location of holes in flange	Gage
209	Location of body holes	Gage
210	Surface finish improper, except as otherwise classified	Visual
211	Burr	Visual
212	Foreign matter	Visual

4.5.2.5 Rod and Piston Assembly, Drawing 5184969, covering a detail of Drawing 5184966.

Critical
None defined

Major		
101	Concentricity of piston with rod	Gage
102	Length from face of piston to center line of radial groove	Gage
103	Staking missing or insecure	Visual
104	Metal defective	Visual
105	Protective finish inadequate or defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.

106	Burr	Visual
107	Foreign matter	Visual
Minor		
201	Staking not coated	Visual

4.5.2.6 Rod, Operating, Drawing 5184972, covering a detail of Drawing 5184969.

Critical
None defined

Major		
101	Concentricity of radial groove with body	Gage
102	Diameter of radial groove	Gage
103	Location of radial groove	Gage
104	Radial profile of end	Measure
105	Metal defective	Visual
106	Surface finish	Visual
107	Burr	Visual
Minor		
201	Diameter	Gage
202	Total length	Measure
203	Profile of radial groove incorrect	Measure
204	Protective finish inadequate or defective	Visual
205	Foreign matter	Visual

4.5.2.7 Piston, Operating, Drawing 5184970, covering a detail of Drawing 5184969.

Critical
None defined

Major		
101	Concentricity of O-ring groove with outside diameter	Gage
102	Diameter of body	Gage
103	Diameter of O-ring groove, min	Visual
104	Radii missing or incorrect	Visual
105	Metal defective	Visual
106	Protective finish inadequate or defective	Visual
107	Surface finish improper	Visual
108	Burr or sharp corner	Visual
109	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.

Minor		
201	Diameter of hole	Gage
202	Diameter of O-ring groove, max	Gage
203	Total length	Gage
204	Location of O-ring groove	Gage
205	Width of O-ring groove	Measure
206	Sharp cornersVisual	
207	Chamfer present on either end of hole	Visual

4.5.2.8 Spring, Compression, Drawing 5184974, covering a detail of Drawing 5184966.

Critical
None defined

Major		
101	Load at specified height incorrect	Gage
102	Ends incorrect	Visual
103	Metal defective	Visual
104	Protective finish inadequate or defective	Visual
105	Burr, sharp corner, or sliver	Visual
106	Foreign matter	Visual
Minor		
201	Outside diameter closed, max	Gage
202	Length closed, max	Gage
203	Inside diameter, min	Gage

4.5.2.9 Assembly, Drawing 5184966.

Critical		
1	Any part missing	Visual
2	Gas port obstructed	Visual
3	Disc missing or improperly sealed	Visual
Major		
101	Total length, max	Gage
102	Rod bent or damaged	Visual
103	Marking missing, incorrect, or illegible	Visual
104	Metal tab insecurely mounted	Visual
105	Metal defective	Visual
106	Burr	Visual
107	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.

4.5.3 Inspection testing. The following tests shall be performed in accordance with 4.6.

4.5.3.1 Hardness. Fifty units from each heat treated lot of components shall be tested for compliance with the requirements on the applicable drawing. Failure of any unit to comply with the drawing requirements shall be cause for rejection of the lot of components.

4.5.3.2 Hydrostatic pressure. Each cylinder and housing shall be subjected to the internal hydrostatic pressure test. Failure of any unit to comply with 3.4 shall be cause for rejection.

4.5.3.3 Protective finish. Each batch of plated hardware shall be tested in accordance with the applicable specification. Failure of any sample to comply with the requirements of the applicable specification shall be cause for rejection of the lot.

4.5.3.4 Residual magnetism. Each assembly shall be subjected to the test for excessive residual magnetism as specified in 4.6.4. Failure of any unit in the inspection sample to comply with 3.10 shall be cause for rejection of the lot.

4.5.3.5 Static load. Each rod and piston subassembly shall be subjected to an axial static load test as specified on the appropriate drawing. Any failure to comply with the requirements shall be cause for rejection of the subassembly.

4.5.3.6 Metal parts assembly. Each firing pin release assembly, except for the dust seal, shall be subjected to tests as specified in 3.7. Failure of any assembly to comply with the requirements of 3.7 shall be cause for rejection of the assembly.

4.5.3.7 Radiographic inspection. All assembled release mechanisms shall be radiographically examined in accordance with MIL-STD-453. Any observable imperfection in components or assembly shall be cause for rejection of that unit. The release shall be positioned for the most revealing exposure with the long axis of each assembly perpendicular to the rays of the X-ray machine. All releases shall be identified with serial numbers prior to X-ray examination. The serial numbers shall be in consecutive numerical order beginning with the number (001) in each production lot. Any missing serial numbers are to be identified on the X-ray plates. The releases shall be arranged on boards or trays in consecutive order and each radiograph shall carry a permanent identification of the units displayed thereon. The radiographic identification shall include item nomenclature, the complete lot number assigned to that lot and the span of serial numbers displayed. Radiographs of the entire production lot shall accompany the ballistic sample to the activity conducting the production lot acceptance tests. Defective releases found during X-ray review are to be marked on the x-ray prior to shipment and those defective items shall be removed from the production lot. Film interpretation of the radiographs shall verify the presence and correct positioning of the following parts:

(1) Cylinder
(2) Housing
(3) Piston, Unlocking
(4) Sleeve, Retaining
(5) Rod and piston assembly
(6) Spring

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.

(7) Ball, metal, MS 19060-1004
(8) 0-ring, MS 28775-008
(9) 0-ring, MS 28775-010

4.5.3.8 Breakaway torque. Each firing pin release assembly shall be subjected to the breakaway torque test. Failure of any assembly to comply with the requirements of 3.9 shall be cause for rejection of the assembly.

4.5.3.9 Functioning. Each firing pin release assembly shall be functionally tested. Failure of any assembly to comply with the requirements of 3.8 shall be cause for rejection of the assembly.

4.6 Test methods and procedures.

4.6.1 Hardness. Prior to the application of protective finish, a hardness tester shall be used to determine compliance with the requirements of the applicable drawing.

4.6.2 Hydraulic pressure. Prior to application of protective finish the cylinder and housing shall be mounted in the device, using a fixture for properly sealing all openings, and subjected to the internal hydrostatic pressure to determine compliance with 3.4.

4.6.3 Protective finish. Test procedures for protective finish shall be in accordance with the applicable specification referenced on the applicable drawing.

4.6.4 Residual magnetism. The assembly shall be tested for excessive residual magnetism using an approved compass in an area free of local magnetic effects by placing the assembly 5 inches from the end and at the same height as the compass, in a north-south horizontal position (cylinder end south) with the compass set in an east-west heading. The assembly shall be moved at a speed no greater than 10 feet per minute past the compass for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass. This procedure shall be repeated for each 90 degree rotation of the assembly for four full passes.

4.6.5 Static load. The rod of the rod and piston subassembly shall be secured in a fixture. The piston shall be attached to a second fixture which contains a load cell calibrated to show the amount of load applied to the end of the rod.

4.6.6 Metal parts assembly. The assembly is to be rotated freely 360 degrees and then rotated with a 20 pound resistive load trying to push the rod in 360 degrees and after the load is removed tested for free rotation 360 degrees again.

4.6.7 Breakaway torque. The cylinder of each firing pin release assembly, prior to sealing of the 4 cylinder holes, shall withstand a breakaway torque of 50 inch pounds with respect to the firing pin release housing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.

4.6.8 Functioning. When the operating rod of the assembled firing pin release is held firmly and a gas source, having a maximum pressure of 250 psi, is applied to the housing gas intake port the firing pin release body and cylinder assembly shall move completely over the operating rod. The operating rod shall be returned to the original extended position. Complete and positive locking shall be assured.

4.7 Inspection of packaging. The sampling and inspection of the packaging, packing, and container marking shall be in accordance with the requirements of section 5.

5. PACKAGING

5.1 Packaging, packing, and marking. Packaging, packing, and marking shall be Level A or C, as specified by the contracting activity (see 6.2). Packaging, packing, and marking shall be in accordance with SPI 00-731-9272.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The firing pin release assembly is used to release the precocked firing mechanism of the RAU-3/A Remover and allow the remover to fire.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification

b. Issue of DODISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced (see 2.1.1 and 2.1.2)

c. If first article inspection is required (see 3.1 and 6.3)

d. The responsible inspection activity (see 4.1)

e. Any special instruction requirements (see 4.3)

f. Level of packing and marking (see 5.1)

6.3 First article. When a first article inspection is required, the contracting officer should provide specific guidance to offerors that the items should be a first article sample. The first article should consist of 5 metal parts assemblies, 9 sets of unassembled parts, and 1 set of unassembled parts without plating or final protective finish. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examination, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.

test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Definition.

6.4.1 Mechanical failure. Mechanical failure is any deformation or breakage of a part, the occurrence of which is other than a design function.

6.5 Subject term (keyword) listing.

Ejection systems, aircrew
Emergency escape systems, aircrew
Escape systems, aircrew
Life-saving systems, aircrew

6.6 Changes from previous issue. Marginal notations are not used to identify changes with respect to the previous issue because of the extensiveness of the changes.

Custodian:
Navy - OS

Preparing activity
Navy - OS
(Project 1377-0E08)

Review activity:
Air Force – 70

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:21Z
Check the source to verify that this is the current version before use.