MILITARY SPECIFICATION

WARHEAD, 2.75 INCH ROCKET, TEST, EMPTY, MODIFIED: PXR6358 WITH FLASH, PARTS AND ASSEMBLY

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the quality assurance provisions and special requirements not covered by the drawings for parts and assembly of the PXR6358 Test Warhead.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-810	Environmental Test Methods
MIL-STD-1167	Ammunition Data Cards

FSC 1340

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn. DRSMC-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

New Jersey 07801 by using the self-addressed Standardization
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents and publications form a part of this specification to the extent specified herein.

Code of Federal Regulations

Title 49 - Transportation, Parts 100-199

(The Code of Federal Regulations is available from the Superintendent of Documents, U S. Government Printing Office, Washington, D.C. 20402; orders shall specify 49 CFR 100-199.)

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

PRODUCT AND PACKAGE DRAWINGS

9224841	Container, Ammo, Fiber, PA26 for Warhead, 2.75 Inch Rocket HE: M229
9224842	Box, Packing, Ammunition, for Warhead, 2.75 Inch Rocket, HE: M229
9362895	Warhead, 2.75 Inch Rocket, Test, Empty, Modified: PXR6358 with Flash for Test Fuze, Rocket: M439

INSPECTION DRAWINGS

9260704	Fuze, Rocket, M439

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on Drawing 9362895 and associated drawings and with all requirements specified in applicable specifications and standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

3.3 Electrical continuity. Maximum resistance of the umbilical cable assembly shall be 100 milliohms.

3.4 Function. A static acceptance test shall be performed on the smoke cartridge at -50°F ± 5°F and at +160°F ± 5°F.

3.5 Secured cargo vibration. The warhead shall withstand exposure to secured cargo vibration as specified in 4.5.2.

3.6 Data requirements. The contractor shall generate data in accordance with the requirements of the data item descriptions cited in 4.5.4.

3.7 First article inspection. This specification makes provisions for first article inspection Requirements for submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship. Unless otherwise specified on the drawing, all parts and assemblies shall be free from burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, porosity, warpage, burn marks, checks, blisters, excess flash, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. Surface coating shall be continuous except for a few slight scratches not exposing base material. The loading and assembly operations shall be performed in a thorough, workmanlike manner consistent with the best practices of the industry. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibilities for inspections. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the Contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the government. The government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are made a part of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. Unless otherwise specified herein or in the contract, the following types of inspection shall be conducted on this item.

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated:

Part Description	Drawing	Quantity
Plug, Base	9362880	25
Disk, Closure	9362892	15
Umbilical Cable Assembly	9362886	15
Wire Cable Assembly	9362885	15
Canister, Flash: Metal Parts	9362890	15
Canister, Flash	9362893	230
Housing, Booster	8883682	15
Housing, Booster Modified	9362887	15
Fuze, Body Assembly	9215611	15
Fuze, Body Subassembly: Modified	9362888	15
Nose/Umbilical Cable Assembly	9362889	25
Warhead, 2.75 Inch Rocket, M229, Metal Parts Assembly	9238883	15
Warhead, 2.75 Inch Roacket: M229 Modified, Metal Parts	9362894	25
Warhead, 2.75 Inch Rocket, Test, Empty, Modified: PXR6358 with Flash for Test Fuze, Rocket: M439	9362895	36

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70434 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 3		DRAWING NUMBER
	Warhead, 2.75 Inch Rocket: Test, Empty, Modified: PXR6358 w/Flash for Test Fuze, Rocket: M439				Listed Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Plug, Base (Dwg. 9362880) Examination for defects	25		3.2	4.4.2.1
	Disk Closure (Dwg. 9362892) Examination for defects	15		3.2	4.4.2.2
	Umbilical Cable Assembly (Dwg. 9362886) Examination for defects	15		3.2	4.4.2.3
	Wire Cable Assembly (Dwg. 9362885) Examination for defects	15		3.2	4.4.2.4
	Canister, Flash: Metal Parts (Dwg. 9362890) Examination for defects	15		3.2	4.4.2.5

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70434 (AR)

PARAGRAPH	TITLE: Warhead, 2.75 Inch Rocket: Test, Empty, Modified: PXR6358 w/Flash for Test Fuze, Rocket: M439		SHEET 2 OF 3		DRAWING NUMBER: Listed Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Canister, Flash				
	(Dwg. 9362893)				
	Examination for defects	25		3.2	4.4.2.6
	Function test, hot	115		3.4	4.5.1
	Function test, cold	115		3.4	4.5.1
	Housing, Booster				
	(Dwg. 8883682)				
	Examination for defects	15		3.2	4.4.2.7
	Housing, Booster Modified				
	(Dwg. 9362887)				
	Examination for defects	15		3.2	4.4.2.8
	Fuze, Body Assembly				
	(Dwg. 9215611)				
	Examination for defects	15		3.2	4.4.2.9
	Fuze, Body Subassembly: Modified				
	(Dwg. 9362888)				
	Examination for defects	15		3.2	4.4.2.10

NOTES:

DRDAR-QA Form 160 Jul 77 -

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70434 (AR)

PARAGRAPH	TITLE Warhead, 2.75 Inch Rocket: Test, Empty, Modified: PXR6358 w/Flash for Test Fuze, Rocket: M439		SHEET 3 OF 3		DRAWING NUMBER Listed Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Nose/Umbilical Cable Assembly (Dwg. 9362889) Examination for defects	25		3.2	4.4.2.11
	Warhead, 2.75 Inch Rocket, M229, Metal Parts Assembly (Dwg. 9238883) Examination for defects	15		3.2	4.4.2.12
	Warhead, 2.75 Inch Rocket: M229 Modified, Metal Parts (Dwg. (9362894 Examination for defects	25		3.2	4.4.2.13
	Warhead, 2.75 Inch Rocket: Test, Empty, Modified: PXR6358 w/Flash for Test Fuze, Rocket: M439 (Dwg. 9362895) Examination for defects Secured cargo vibration	36 36		3.2 3.5	4.4.2.14 4.5.2

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling Plans. Unless otherwise specified in the Classification of Defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70434 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9362880
4.4.2.1	Plug, Base				NEXT HIGHER ASSEMBLY 9362895
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	True position of threads		0.40%	3.2	Gage
102	Seal diameter		0.40%	3.2	Gage
103	Fuze cavity, small diameter		0.40%	3.2	Gage
104	Fuze cavity, large diameter		0.40%	3.2	Gage
MINOR					
201	Spanner hole diameter, 2 places		0.65%	3.2	Gage
202	Location of spanner holes		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.8	Visual
204	Identification missing		0.65%	3.2	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

Quality Conformance Inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70434 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9362892
4.4.2.2	Disc Closure				NEXT HIGHER ASSEMBLY 9362893
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Diameter		0.40%	3.2	Gage
MINOR					
201	Evidence of poor workmanship		0.65%	3.8	Visual
202	Identification missing		0.65%	3.2	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

Quality Conformance Inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70434 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9362886
4.4.2.3	Umbilical Cable Assembly				NEXT HIGHER ASSEMBLY 9362889
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Smaller diameter of molded assembly		0.40%	3.2	Gage
102	Total length, Min.		0.40%	3.2	Gage
103	Poor solder connections		0.40%	3.2	Visual
104	Electrical continuity		0.40%	3.3	Milliohmmeter
MINOR					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

Quality Conformance Inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70434 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9362885
4.4.2.4	Wire Cable Assembly				NEXT HIGHER ASSEMBLY 9362889
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Longer length, Min.		0.40%	3.2	Gage
102	Poor solder connections		0.40%	3.2	Visual
MINOR					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil - 2 Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9362890
4.4.2.5	Canister, Flash: Metal Parts				NEXT HIGHER ASSEMBLY 9362893
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Outside diameter		0.40%	3.2	Gage
102	Length		0.40%	3.2	Gage
103	Width of fuze cavity		0.40%	3.2	Gage
104	Location of fuze cavity		0.40%	3.2	Gage
105	Thickness of web		0.40%	3.2	Gage
106	Distance between slots		0.40%	3.2	Gage
107	Hole diameter		0.40%	3.2	Gage
108	Location of hole		0.40%	3.2	Gage
MINOR					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

Quality Conformance Inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70434 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9362893
4.4.2.6	Canister, Flash				NEXT HIGHER ASSEMBLY 9362895
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Length, max		0.40%	3.2	Gage
102	Crimp not complete or not properly sealed		0.40%	3.2	Visual
103	Function test, hot	16		3.4	4.5.1
104	Function test, cold	16		3.4	4.5.1
MINOR					
201	Identification missing		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70434 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8883682
4.4.2.7	Housing, Booster				NEXT HIGHER ASSEMBLY 9362887
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Total length		0.40%	3.2	Gage
102	Width of "O" ring groove		0.40%	3.2	Gage
103	Diameter of "O" ring groove		0.40%	3.2	Gage
104	Major diameter of threads		0.40%	3.2	Gage
105	Concentricity of "O" ring groove with pitch diameter		0.40%	3.2	Gage
106	Finish of "O" ring groove		0.40%	3.2	Gage
MINOR					
201	Width across wrench flats		0.65%	3.2	Gage
202	Symmetry of wrench flats		0.65%	3.2	Gage
203	Inside diameter at crimp section		0.65%	3.2	Gage
204	Wall thickness at crimp section		0.65%	3.2	Gage
205	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

Quality Conformance Inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70434 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9362887
4.4.2.8	Housing, Booster: Modified				NEXT HIGHER ASSEMBLY 9362889
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Cable hole diameter		0.40%	3.2	Gage
102	Location of pin hole		0.40%	3.2	Gage
103	Pin hole diameter		0.40%	3.2	Gage
MINOR					
201	Identification missing		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70434 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9215611
4.4.2.9	Fuze, Body Assembly				NEXT HIGHER ASSEMBLY 9362888
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Depth of crimp		0.40%	3.2	Gage
102	Crimp not complete		0.40%	3.2	Visual
MINOR					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

Quality Conformance Inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70434 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9362888
4.4.2.10	Fuze, Body Subassembly: Modified				NEXT HIGHER ASSEMBLY 9362889
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Hole diameter		0.40%	3.2	Gage
102	Location of hole		0.40%	3.2	Gage
103	Paint on threads		0.40%	3.2	Visual
MINOR					
201	Identification missing		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

Quality Conformance Inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70434 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9362889
4.4.2.11	Nose/Umbilical Cable Assembly				NEXT HIGHER ASSEMBLY 9362895
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Pin hole diameter		0.40%	3.2	Gage
102	Location of pin hole		0.40%	3.2	Gage
103	Terminal lug extends beyond booster housing outside diameter		0.40%	3.2	Visual
104	Pin above flush		0.40%	3.2	Visual
105	Poor solder connections		0.40%	3.2	Visual
MINOR					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

Quality Conformance Inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70434 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9238883
4.4.2.12	Warhead, 2.75 Inch Rocket, M229, Metal Parts Assembly				NEXT HIGHER ASSEMBLY 9362894
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Pitch diameter of fuze thread		0.40%	3.2	Gage
102	Minor diameter of fuze thread, max		0.40%	3.2	Gage
103	Pitch diameter of rear thread		0.40%	3.2	Gage
104	Major diameter of rear thread, min		0.40%	3.2	Gage
105	Thread damaged or not full		0.40%	3.2	Visual
106	Foreign matter in cavity		0.40%	3.2	Visual
MINOR					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70434 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9362894
4.4.2.13	Warhead, 2.75 Inch Rocket: M229 Modified, Metal Parts				NEXT HIGHER ASSEMBLY 9362895
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	True position of flash canister holes (2 places)		0.40%	3.2	Gage
102	Diameter of flash canister holes (2 places)		0.40%	3.2	Gage
103	Perpendicularity of hole		0.40%	3.2	Gage
104	Pitch diameter of inside threads		0.40%	3.2	Gage
105	Bourrelet diameter after painting, Max.		0.40%	3.2	Gage
106	Paint on threads or fuze seating face		0.40%	3.2	Visual
MINOR					
201	Identification missing		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

Quality Conformance Inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-70434 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.14	Warhead, 2.75 Inch Rocket, Test, Empty, Modified: PXR6358 w/Flash for Test, Fuze Rocket: M439		9362895
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Diameter of pin hole		0.40%	3.2	Gage
102	Location of pin hole		0.40%	3.2	Gage
103	Base plug missing		0.40%	3.2	Visual
104	Flash canister missing, loose, or improperly adhering		0.40%	3.2	Visual
105	Bourrelet diameter after painting, Max.		0.40%	3.2	Gage/Visual
106	Pin above flush		0.40%	3.2	Visual
107	Electrical continuity		0.40%	3.3	Milliohmmeter
108	Secured cargo vibration (a)	36		3.5	4.5.2
MINOR					
201	Band missing or wrong color		0.65%	3.2	Visual
202	Entire warhead not painted or wrong color		0.65%	3.2	Visual
203	Identification missing		0.65%	3.2	Visual
204	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES: (a) First article only.

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in tables starting with 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein. The contractor shall submit all inspection equipment designs to the government for evaluation and approval prior to fabrication of such equipment.

4.5 Test methods and procedures.

PRECAUTION: This specification covers sampling and testing of chemical, toxic, or explosive materials which are potentially hazardous to personnel. Accordingly, it is emphasized that all applicable safety rules, regulations, and procedures must be followed in handling and processing these materials.

4.5.1 Functional test. The smoke cartridges shall be subjected to a static acceptance test using a hard-wired M439 Fuze. Half the sample shall be conditioned at a temperature of $-50^{o}F \pm 5^{o}F$ and the other half shall be conditioned at $+160^{o}F \pm 5^{o}F$ for a minimum of four hours prior to functioning. If one smoke cartridge fails to function, the lot shall be rejected.

4.5.2 Secured cargo vibration. The secured cargo vibration test shall be performed on each of 36 warheads for first article testing only. The sample warheads shall be packed and packaged in accordance with 5.1. The warheads shall be equally divided and temperature conditioned to $-50^{o}F \pm 5^{o}F$, $+70^{o}F \pm 15^{o}F$, and $+160^{o}F \pm 5^{o}F$. The conditioning time shall be 8 hours minimum and 24 hours maximum. The packed shipping boxes shall be subjected to the vibration test in accordance with Method 514.2, Equipment Category g, Procedure X, Table 514.2-VII and Figure 514.2-7 Curve AW of MIL-STD-810. Resonance testing does not apply. Following the vibration test, each round shall be visually examined to verify that all components are secure and no loose smoke mixture is present.

4.5.3 Data requirements. The contractor shall submit a quality inspection test demonstration and evaluation report in accordance with Data Item Descriptions DI-R-1721 and DI-R-1724 giving the detailed test results.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging and marking. The Warheads shall be packed and marked in accordance with Drawing 9224841, and shall comply with CFR49, Parts 100-199. Descriptive nomenclature shall be: Warhead, 2.75 Inch Rocket, Test, Empty, Modified: PXR6358 with Flash.

5.2 Packing and marking. The packaged warheads shall be packed in accordance with the Drawing 9224842. Descriptive nomenclature shall be: 4-Warhead, 2.75 Inch Rocket, Test, Empty, Modified: PXR6358 with Flash. The DOT marking shall be: Explosive Projectiles.

5.3 Ammunition data cards. Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 Intended use. The Warheads covered by this specification are intended for testing the M439 Fuze.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment for design approval. See 6.2 of MIL-A-48078. Submit designs as required to Commander, U.S. Army Armament Research and Development Center, US Army Armament, Munitions and Chemical Command, ATTN: DRSMC-QAF-I(D), Dover, NJ 07801.

6.4 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of DAR 7-104.9 (n) (2) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs.

Paragraph No.	Data Requirement Title	Applicable DID No.
4.5.3	Quality Inspection Defect Report	DI-R-1721
4.5.3	Quality Inspection Test Demonstration and Evaluation Report	DI-R-1724

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.

(Data item descriptions related to this specification, and identified in Section 6 will be approved and listed as such in DoD 5000.19L, Vol II, AMSDL. Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.5 First article. When a first article is required for inspection and approval, see 3.7 and 4.3.

6.6 Source control and specification control drawings. Certificates of conformance from the supplier certifying that the item complies with the drawing requirements shall be provided to the government representative.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-A657)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:26Z
Check the source to verify that this is the current version before use.