MILITARY SPECIFICATION SHEET

CABLE ASSEMBLY W41-AP-1E1

The complete requirements for procuring the cable assembly described herein shall consist of this document and the latest issue of specification MIL-C-50288(MU).

1. SCOPE

1.1 This specification covers detail requirements, quality assurance provisions and preparation for delivery for production and repair parts for Cable Assembly W41-AP-1E1.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-50288(MU) - Cable Assemblies for War Reserve Atomic Demolition Charges, General Specification for

STANDARDS

MILITARY

MS3137E-19S - Connector
MS3182-19C - Cap, Protective
MS15795-204 - Washer
MS20450C8AD12 - Rivet
MS25281-8W - Clamp
MS51025-10 - Set Screw

DRAWINGS

ORDNANCE CORPS

8800545 - Bag, Packing, Ammunition, for Cable Assembly
8808362 - Packing and Marking for Storage and Shipments
8823708 - Connector
8838865 - Shell Molding
8838930 - Cap, Protective
8861465 - Stop, Switch
8861466 - Shell, Molding
8881768 - Polyurethane Molding Compound

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

8881769 - Primer, Polyurethane Molding Compound
9216400 - Cable Assembly W41-AP-1E1
9216518 - Stop, Switch Assembly
9216773 - Tubing, Silastic
9216774 - Molding Compound
9216787 - Ink
ET-9216400 - Equipment Tabulation

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with MIL-C-50288(MU).

3.2 Circuit resistance. The cable assembly circuit resistance shall be in accordance with Table I.

Table I

Circuit resistance (see dwg 9216400)

From P42-2 Connector Pin	To P5-1 Connector Pin	Ohms max
A	6	0.2
B	4	0.2
C	12	0.2
D	3	0.2
E	11	0.2
G	1	0.2
L	9	0.2
M	19	0.2
J	5	0.2
K	5	0.2
Shell	Shell	0.2

4. QUALITY ASSURANCE PROVISIONS

4.1 Quality assurance provisions. Quality assurance provisions shall be in accordance with MIL-C-50288(MU) and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.2 Classification of characteristics.

4.2.1 Connector (see dwg 8823708); cap, protective (see dwg 8838930); polyurethane molding compound (see dwg 8881768); primer, polyurethane molding compound (see dwg 8881769); tubing, silastic (see dwg 9216773); molding compound (see dwg 9216774); ink (see dwg 9216787); connector (see MS3137E-19S); cap, protective (see MS3182-19C); washer (see MS15795-204); rivet (see MS20450C8AD12); clamp (see MS25281-8W); set screw (see MS51025-10); covering details of dwgs 9216400 and 9216518.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Objective evidence (see Objective evidence, section 6, MIL-C-50288(MU) available for component in accordance with applicable drawing or standard.....Visual

Minor: None defined.

4.2.2 Stop, switch (see dwg 8861465) covering a detail of dwg 9216518.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:

101. Length of short side.....Gage
102. Diameter of small holes, min.....Gage
103. C'sink present top and bottom of small holes.....Visual
104. Length of projection.....Gage
105. Length of long side.....Gage
106. Depth of projection.....Gage
107. Diameter of large hole.....Gage
108. Location of large hole.....Gage
109. Width of small slot.....Gage
110. Location of small slot.....Gage
111. Pitch diameter of threaded hole, max.....Gage
112. Minor diameter of threaded hole, max.....Gage
113. Location of threaded hole.....Gage
114. Thickness, min.....*Measure
115. Material (see Material, section 3, MIL-C-50288(MU).....Visual
116. Objective evidence (see Objective evidence, section 6, MIL-C-50288(MU) available for proper finish in accordance with dwg 8861465.....Visual

* Measure on suitable scale.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

Minor:
201. Workmanship (see Workmanship, section 3, MIL-C-50288(MU).....Visual-Manual

4.2.3 Stop, switch assembly (see dwg 9216518) covering a detail of dwg 9216400.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Lacing correctly tied.....Visual
102. Materials (see Material, section 3, MIL-C-50288(MU).....Visual
103. Knots sealed.....Visual

Minor: None defined.

4.2.4 Shell molding (see dwg 8861466 covering a detail of dwg 9216400.

Categories	Characteristics	Method of inspection

Critical: None defined.

Major:
101. Length.....Gage
102. Length to flange.....Gage
103. Inside diameter.....Gage
104. Angle of taper.....Gage
105. Pitch diameter of thread, min.....Gage
106. Major diameter of thread, max.....Gage
107. Location of holes.....Gage
108. Diameter of holes, min.....Gage
109. Inside diameter tapered end.....Gage
110. Materials (see Material, section 3, MIL-C-50288(MU).....Visual
111. Objective evidence (see Objective evidence, section 6, MIL-C-50288(MU) available for protective finish in accordance with dwg 8861466.....Visual

Minor:
201. Workmanship (see Workmanship, section 3, MIL-C-50288(MU).....Visual-Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.2.5 Shell molding (see dwg 8838865) covering a detail of dwg 9216400.

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Inside diameter	Gage
102.	Pitch diameter of thread, max.	Gage
103.	Minor diameter of thread, max.	Gage
104.	Length	Gage
105.	Angle of taper	Gage
106.	Diameter of holes, min.	Gage
107.	Location of holes	Gage
108.	Depth of inside diameter	Gage
109.	Materials (see Material, section 3, MIL-C-50288(MU)	Visual
110.	Objective evidence (see Objective evidence, section 6, MIL-C-50288(MU) available for protective finish in accordance with dwg 8838865	Visual
111.	Exterior finish	Visual
Minor:		
201.	Workmanship (see Workmanship, section 3, MIL-C-50288(MU)	Visual-Manual

4.2.6 Cable assembly W41-AP-1E1 (see dwg 9216400).

Categories	Characteristics	Method of inspection
Critical: None defined.		
Major:		
101.	Length of mold	*Measure
102.	Thickness of mold	Gage
103.	Location of polorizing keway	Gage
104.	Alignment of stop, switch groove	Gage
105.	Marking	Visual

* Measure with suitable scale.

Minor:		
201.	Serialization (see Serialization, section 3, MIL-C-50288(MU)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

4.3 Acceptance inspection equipment. Acceptance inspection equipment shall be in accordance with MIL-C-50238(MU) and ET-9216400.

4.4 Insulation resistance. The cable assembly insulation resistance shall be tested in accordance with Table II.

Table II

Insulation resistance (see dwg 9216400)

Positive potential applied to P42-2 Connector Pin	Minus potential to all other pins and shells except Connector P5-1 pin or shell
A	6
B	4
C	12
D	3
E	11
G	1
L	9
M	19
J	5
K	5
Shell	Shell

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery for production cable assemblies. Preparation for delivery for production cable assemblies shall be in accordance with MIL-C-50288(MU).

5.2 Preparation for delivery for repair cable assemblies.

5.2.1 Preservation and packaging. Preservation and packaging shall be as specified in MIL-C-50288(MU).

5.2.1.1 Level A. The cable assembly shall be packaged in accordance with dwgs 8800545 and 8808362 and as specified in MIL-C-50288(MU).

5.2.1.2 Level C. The cable assembly shall be packaged in accordance with dwg 8808362 and MIL-C-50288(MU).

5.2.2 Packing.

5.2.2.1 Levels A and C. The cable assembly shall be packed in accordance with dwgs 8800545 and 8808362 and MIL-C-50288(MU).

5.2.3 Marking. Marking shall be as specified in dwgs 8800545 and 8808362 and MIL-C-50288(MU).

6. NOTES

6.1 Notes. Notes shall be in accordance with MIL-C-50288(MU).

Custodian:
Army - MU

Preparing Agency
Army - MU
Project No. - 1125-A047

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-NR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-C-50288/9(MU) Cable Assembly W41-AP-1E1

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:20Z
Check the source to verify that this is the current version before use.