MIL-C-50880(MU)
Amendment 1
1 July 1972

MILITARY SPECIFICATION

CONNECTORS, ELECTRICAL, MINATURE
QUICK DISCONNECT

This amendment forms a part of Military Specification MIL-C-50880 (MU), dated 16 November 1970 and is mandatory for use by the Munitions Command.

Page 1: Title - Change Munition to Munitions.
Paragraph 1.2.1 - Fourth sentence - Delete and substitute. In addition, one Series shall be designed so that electrical continuity is initiated and maintained between mated shells prior to establishment of conductor circuits by mating of pin and socket contacts, and in the reverse order during the disconnecting operation and to have the contacts so located as to be protected from handling damage inadvertent electrical contact.

Page 2: Paragraph 1.2.2 - Second sentence - Change power to proper.
Paragraph 1.2.2 - Third sentence - Delete and substitute: In addition, one Series shall be designed so that electrical continuity is initiated and maintained between mated shells prior to establishment of conductor circuits by mating of pin and socket contacts, and in the reverse order during the disconnecting operation and to have the contacts so located as to be protected from handling damage and inadvertent electrical contact.
Paragraph 1.3.1 - Section a - Delete and substitute:
a. Series I - Grounded Scoop Proof:
IA 150°C (302°F) max operating temperature -
Series II - Low Silhouette:
IIA 150°C (302°F) max operating temperature
IIB High Temperature - 200°C (392°F) max operating temperature.

Page 3: Paragraph 1.3.1 - Section b(1) Delete and substitute:
(a) Line
(b) Straight
(c) Straight, Grounded

Page 4: Paragraph 1.3.2 a - Add "max operating temp" after (351°F)
Paragraph 1.3.2 c - Change "c." to "b."
Paragraph 1.3.2 d - Change "d." to "c."

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

Paragraph 1.3.2 b - Change "b." to "d."

After (1) Bright Cadmium and "Plate". After (2) Olive Drab add "Cadmium Plate".

Page 5: Paragraph 2.1 - Delete second sentence and substitute: "Except as otherwise specified, the issue current at the date of release of this specification or revision thereto shall apply, but in the case of conflict, this specification shall govern."
Paragraph 2.1 - Delete QQ-S-365. General Requirements For, and substitute: "QQ-S-365 Silver Plating, Electrodeposited, General Requirements For.

Page 6: STANDARDS - Delete MILITARY and substitute Military.
STANDARDS - Add MIL-STD-810 - Environmental Test Methods.
STANDARDS - Add MIL-STD-1169 - Packaging, Packing, and Marking for Shipment of Inert Ammunition Components.

Page 7: Paragraph 3.1 - Last line - Add "(QPL)."

Page 8: Paragraph 3.3 - Last line - Change "quaranty" to "guaranty".

Page 9: Paragraph 3.3.2.1.2 c. - Delete and substitute:
c. Contacts
(1) Style P - Nickel-iron B52 alloy or equivalent.
(2) Style S - Nickel-iron B52 alloy or equivalent.

Page 11: Paragraph 3.4.1.1.1 Second sentence: Change "Y" to "H".
Paragraph 3.4.1.2 Second sentence: Change "figure 3" to "figure 2".

Page 12: Figure 1 - Change "Y" to "H".

Page 13: Change "Figure 3" to "Figure 2".

Page 15: 3.4.3.2 - Line 2 - Change "fig 2" to "fig 3".

Page 18: 3.4.6.2 - Third line - Change "proper" to "positive".
3.4.6.4 - First line - Change "Position" to "Positioning".
3.4.6.5.1 - Second line- Change "with a suitable lubricant" to "with a lubricant conforming to MIL-G-3545".

Page 21: 3.4.7.1 - Add "The compound shall form a continuous bond, shall be visible, and shall not inpair the legibility of the contact lettering."

Page 23: 3.4.8.6 - First line - delete "Coupling Ring, Hex Jam Nut, Potting Ring".
Fifth line - Change "finish D" to "finish A".
3.4.8.7 First line - Change "Gounding" to "Grounding".
3.6.1 a Fourth line- Change "og 150°C." to "of 150°C (302°F)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

Page 24: 3.6.1 (2) Delete and substitute "(2) Variety B. Temperature from -55°C (-67°F) to 177°C (351°F) for Series I, and from -55°C (-67°F) to 150°C (302°F) for Series II.

3.6.1b - Third line Change "20." to "20g".

3.6.1c - Delete and substitute "c - Altitudes from sea level to 300,000 feet."

3.6.1d - Delete and substitute "d - Shock as represented by a six millisecond base half-sine wave peaking at 300g's".

3.6.1j - First line - Change "100" to "50".

Page 25: 3.6.1k Second line - Change "155 db" to "150 db for two minutes".

Page 27: 3.6.13 Third line - Delete "for two pairs of mated contacts".

Page 28: 3.6.15.1.1 Delete and substitute "Class H Receptacles, when subjected to a pressure differential of one atmosphere across the connector, shall exhibit an air leakage rate of not more than 0.1 micron cubic foot per hour (1 X 10^{-6}cc/sec)."

3.7.1 Delete in its entirety.

3.7.1.1 Delete in its entirety.

Page 29: 3.7.1.2 - Delete in its entirety.

3.8 - Delete a and substitute "a. Identification"

MS27467	E	13	A	8	P	A
Specification Sheet Number	Class	Shell Size	Finish	Insert Arrangement	Style	Polarization (no letter required for normal).

Page 30: 3.9 - Sixth line - Delete and substitute - "adajacent equipment or cause injury to personnel."

4.1 - last sentence - "Delete and substitute" "The Government reserves the right to perform any of the inspections and tests set forth in the specifications where such inspections or tests are deemed necessary to assure supplies and services conform to prescribed requirements."

4.2 c. Delete in its entirety.

Page 32: 4.2.1.1.1 Change "Class Y" to "Class H" throughout.

Page 34: 4.2.1.2a. - Second line change "Waterproff" to "Waterproof".

Page 35: 4.2.1.2c - Add: Contact Size 22D
Wire AWG 22, 24, 26, 28

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

Page 41: 4.2.2.2 Second line - Change "MIL-STD'105D: to "MIL-STD-105".

4.2.2.3 Fourth line Change "Samples shall be selected as shown following:" to "Sample sizes shall be determined as shown below:"

4.2.2.4 Last line Change "are" to "is".

Page 42: Table III - Group I.
Examination of product - fourth line - Add "4.5.1".
Table III - Group 2 - Grounding Spring Force - Add "0.25 1/".
Page 43: Table III - Group 3 - Coupling Torque - Add ")".

Page 46 4.5.1 Detailed Inspection Criteria Fourth line Add ")".
4.5.1 Detailed Inspection Minor Change "open lines" to "cracks".

Page 47: 4.6.1 Table - Shell Size - Change "26" to "16".

Page 49: 4.6.5.1 Second line - Change "firection" to "direction" Add "22D 20" to table.
4.6.6 Fourth line - Change "still" to "steel".

Page 51: 4.6.9 Table - Change "Sizes 22 and 22M" to"Sizes 22, 22M and 22D", two places.

Page 52: 4.6.11 Delete first sentence and substitute "Mated connectors and unmated connector halves with pin contacts shall be places in a suitable chamber capable of simulating altitudes of sea level, 50,000 feet, 70,000 feet, 110,000 feet, 200,000 feet and 300,000 feet."

4.6.11 Eleventh line: Change ".05" to ".5".

Page 53: Table - Add

"200,000feet	800	100	1000	100	1000	100
250,000feet	800	100	1000	100	1000	100
300,000feet	800	100	1000	100	1000	100"

Page 55: 4.6.15.1.1 Third line - Change "STS" to "STD".

Page 58: 4.6.17 Delete Second sentence and substitute "Connectors shall be tested in accordance with Method 213 of MIL-STD-202, Test Condition C, with the following exceptions:

a. Peak value shall be 300g's
b. Duration shall be six milliseconds."

Page 62: 4.6.25 Tenth line - Change "within one minute" to "in not less than twenty seconds."

Page 63: 4.6.26 Fourth line - Change "MIL-STD-202C" to MIL-STD-202."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

4.6.26 Sixth line - Change "100 Hz" to "50 Hz".

4.6.27 Delete in its entirety and substitute "Mated connectors shall be mounted on the acoustical noise test fixture by normal means. Connectors shall be wired as shown in figure 5. Connectors shall be tested in accordance with the acoustical noise test, Method 515, MIL-STD-810, Test Condition B with the following exception:

Duration of the test shall be two minutes.

A current of 100-150 milliamperes shall be allowed to flow through the connector before, during, and after the test. A current discontinuity which exceeds one microsecond or any evidence of mechanical damage shall be cause for rejection."

Page 67: 4.8 Reliability Life Testing - Delete in its entirely, 4.8.1 through 4.8.8

Page 71: 5.1 Second line - Change "prtected" to "Protected".

Page 72: 5.2 Second line - Add "packed and " after "shall be".
5.3.1 Change "5.3.1" to "5.3".
5.3.1.1 Change "5.3.1.1" to "5.3.1".

Page 74: 6.3 First line Change "SMUPA-TN4" to "SMUPA-ND-N".
6.3 Second line Change "obrained" to "obtained".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.