INCH-POUND

MIL-DTL-60508B(OS)
19 December 2025
SUPERSEDING
MIL-I-60508A
3 January 1989

DETAIL SPECIFICATION

INITIATOR, CARTRIDGE-ACTUATED, DELAY, M6A1, M26, M33, M44, METAL PARTS ASSEMBLY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for the cartridge-actuated delay initiators M6A1, M26, M33, M44, metal parts assembly (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-A-2550 - Ammunition, General Specification For

(Copies of this document are available online at https://quicksearch.dla.mil.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

NAVAL SURFACE WARFARE CENTER, INDIAN HEAD DRAWINGS (CAGE CODES 19200 AND 19203)

8593313 - Retainer, Cartridge

8593314 - Chamber, Initiator

8593315 - Initiator, Cartridge Actuated, Delay, Metal Parts Assembly

8594744 - Pin, Firing

8594745 - Pin, Shear

Comments, suggestions, or questions on this document should be addressed to Commander, Naval Sea Systems Command, ATTN: SEA 05S, 1333 Isaac Hull Avenue, SE, Stop 5160, Washington Navy Yard, DC 20376-5160 or emailed to CommandStandards@navy.mil, with the subject line "Document Comment". Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 1377

Distribution Statement A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.

8594858 - Housing, Firing Pin

8595254 - Cap

8796826 - Box, Fiberboard (Inner) Packing, Ammunition for Initiators, Cartridge Actuated, Delay, M4A1, M6A1, M12A1, M26, M33, M44, M45A1 or M49A1

8796827 - Box, Packing, Ammunition, for Initiator, Cartridge Actuated, Delay, M4A1, M6A1, M12A1, M26, M33, M44, M45A1 or M49A1, in Fiber Container, M375

(Copies of these documents are available from Commander, Indian Head Division, Naval Surface Warfare Center, CAD/PAD Data Management Branch [Code E26], 4393 Benson Road, BLDG 1557, Indian Head, MD 20640-5092. Refer questions, inquires, or problems to nswc_iheodtd_dmo@navy.mil.)

AEROSPACE INDUSTRIES ASSOCIATION (AIA)

AIA NAS832 - Cap, Protective, Flared Fitting (Plastic)

AIA NAS845 - Plug, Machine Screw, Protective, Plastic

(Copies of these documents are available online at www.aia-aerospace.org.)

AMERICAN SOCIETY FOR QUALITY (ASQ)

ASQ/ANSI Z1.4 - Sampling Procedures and Tables for Inspection by Attributes

(Copies of this document are available online at https://asq.org.)

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION (ISO)

ISO 3601-3 - Fluid power systems – O-rings – Part 3: Quality Acceptance Criteria

(Copies of this document are available online at www.iso.org.)

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.3 and 6.3.

3.2 Materials. All materials used in the manufacture of the initiators shall conform strictly to the specifications referred to on the respective drawings cited in section 2 unless specific approval in writing covering a departure therefrom has been obtained from the Technical Authority prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.3 Raw material. The contractor shall be responsible for selecting from the classification list contained in the raw material specification, located in the applicable drawing, based on the surface and physical condition of the raw material intended for use in manufacture.

3.4 Physical properties. Physical properties required by the respective component drawings shall be uniform throughout the part within specified tolerances. Requirements for all alloy steel parts shall be achieved by quenching and tempering.

3.5 Hydrostatic pressure. The initiator chamber and cap shall withstand a hydrostatic pressure of 5,500 to 6,500 pounds per square inch (psi) for 15 seconds, minimum, without deformation or mechanical failure (see 6.4.1).

3.6 Shear pin strength. The shear pin, after application of protective finish, shall shear when a load of 41±5 pounds is applied at the steady rate of 0.125 inch per minute.

3.7 Metal parts assembly. Parts shall be combined to produce an assembly that conforms to the requirements of the metal parts assembly Drawing 8593315. All threaded joints shall be assembled hand tight.

3.8 Protective finish. Protective finish shall be in accordance with the applicable specifications and shall apply to all surfaces of the component regardless of contour configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.

3.9 Residual magnetism. The metal parts assembly shall not deflect the indicator of the compass more than 5 degrees in either direction using procedures in 4.6.5.

3.10 Workmanship. The requirements for workmanship are as specified in the applicable drawings, referenced specifications, and the following:

3.10.1 Metal defects. All components shall be free from cracks, splits, cold shuts, inclusions, porosity, or any similar defect.

3.10.2 Burr. No part shall have a burr that might interfere with the assembly or function of the item, or that might be injurious to personnel handling the item.

3.10.3 Foreign matter. No part or assembly shall contain chips, dirt, grease, rust, corrosion, or other foreign matter.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Conformance inspection (see 4.4).

4.2 Inspection conditions. Unless otherwise specified (see 6.6), all inspections shall be performed under the following conditions:

a. Temperature: Room ambient, 68 to 77 °F

b. Humidity: 50 percent relative, maximum

4.2.1 Inspection. Inspection shall be in accordance with MIL-A-2550.

4.3 First article inspection. Unless otherwise specified (see 6.2), a first article sample shall consist of 5 metal parts assemblies, 9 sets of unassembled parts, 1 set of unassembled parts without plating or final protective finish, and 50 shear pins from the same lot of shear pins tested shall be subjected to first article testing. The sample shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as used in regular production. All parts and materials, including packaging and packing, shall be the same as those to be used for regular production and shall be obtained from the same source of supply. The inspection shall include the examination of 4.5 and the tests of 4.6 to ensure compliance with the applicable drawing. Failure of any part to meet the requirements of the drawings or specifications shall be cause for rejection of the first article lot represented.

4.4 Conformance inspection.

4.4.1 Lot.

4.4.1.1 Submission of product. Unless otherwise specified by the contracting activity, the formation and identification of lots shall be in accordance with ASQ/ANSI Z1.4.

4.4.1.2 Size of lot. For the purpose of identification and shipment, the shipping lots of metal parts assemblies shall consist of 1,200 assemblies, maximum, provided the homogeneity requirements of inspection lots have been retained.

4.5 Examination. One-hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with classification of defects (see tables I through XI). All nonconforming material shall be rejected. Four power (4×) magnification may be used in performing visual examination for defects such as burr and foreign matter. Inspection for rubber O-rings shall be in accordance with ISO 3601-3. When compliance with the applicable requirement is in doubt as a result of visual examination, the characteristics shall be measured or gaged to determine acceptability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.

TABLE I. Retainer, Cartridge, Drawing 8593313, Covering a Detail of Drawing 8593315.

Characteristic	Defect	Method of Inspection
Critical		
1	Metering slots in base missing	Visual
Major		
101	Pitch diameter of thread, max	Gage
102	Minor diameter of thread, max	Gage
103	Concentricity of cavity with pitch diameter of thread	Gage
104	Concentricity of counterbore with cavity	Gage
105	Perpendicularity of pitch diameter of thread with base	Gage
106	Symmetry of metering slots in base with body	Gage
107	Diameter of cavity, max	Gage
108	Depth of cavity	Gage
109	Depth to bottom of counterbore	Gage
110	Depth of metering slots in base	Gage
111	Length of effective thread, min	Gage
112	Length of thread, max	Gage
113	Internal radius at mouth of cavity	Gage
114	Total length	Measure
115	Width of metering slots in base	Measure
116	Drill point in base, max	Measure
117	Number of elongated slots incorrect	Visual
118	Thread damaged or not full	Visual
119	Metal defective	Visual
120	Protective finish inadequate or defective	Visual
121	Surface finish on internal radius and base improper	Visual
122	Burr	Visual
123	Foreign matter present	Visual
Minor		
201	Pitch diameter of thread, min	Gage
202	Diameter of cavity, min	Gage
203	Diameter of counterbore	Gage
204	Diameter of head	Gage
205	Depth of counterbore	Gage
206	Diameter of body	Measure
207	Length of elongated slots	Measure
208	Length of head	Measure
209	Width of elongated slots	Measure
210	Location of elongated slots	Measure
211	Angle between head and body	Measure

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.

TABLE I. Retainer, Cartridge, Drawing 8593313, Covering a Detail of Drawing 8593315 – Continued.

Characteristic	Defect	Method of Inspection
212	Angular location of metering slots	Visual
213	Marking missing, incorrect, or illegible	Visual
214	Profile of elongated slots	Visual
215	Radius missing or incorrect	Visual
216	Surface finish improper, except as otherwise classified	Visual

TABLE II. Chamber, Initiator, Drawing 8593314, Covering a Detail of Drawing 8593315.

Characteristic	Defect	Method of Inspection
Critical		
None defined		
Major		
101	Pitch diameter of large thread, min	Gage
102	Major diameter of large thread, min	Gage
103	Pitch diameter of small thread, min	Gage
104	Major diameter of small thread, min	Gage
105	Concentricity of counterbore with pitch diameter of large thread	Gage
106	Concentricity of datum diameter with small thread	Gage
107	Diameter of counterbore	Gage
108	Depth of cavity	Gage
109	Thickness of wall, min	Gage
110	Location of datum diameter	Gage
111	Profile of gas port	Gage
112	Thread damaged or not full	Visual
113	Chamfer at base of cavity missing or incorrect	Visual
114	Metal defective	Visual
115	Protective finish inadequate or defective	Visual
116	Surface finish at end of gas port improper	Visual
117	Burr	Visual
118	Foreign matter present	Visual
Minor		
201	Pitch diameter of large thread, max	Gage
202	Pitch diameter of small thread, max	Gage
203	Diameter of cavity	Gage
204	Diameter of hole	Gage
205	Diameter of small thread pilot	Gage
206	Diameter of large thread pilot	Gage
207	Length of large thread pilot	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.

TABLE II. Chamber, Initiator, Drawing 8593314, Covering a Detail of Drawing 8593315 – Continued.

Characteristic	Defect	Method of Inspection
208	Length of gas port	Gage
209	Thickness of wall, max	Gage
210	Location of small thread	Gage
211	Depth of counterbore	Measure
212	Total length	Measure
213	Length to end of large thread	Measure
214	Marking missing, incorrect, or illegible	Visual
215	Radius or chamfer missing or incorrect, except as otherwise classified	Visual
216	Surface finish improper, except as otherwise classified	Visual

TABLE III. Pin, Shear, Drawing 8594745, Covering a Detail of Drawing 8593315.

Characteristic	Defect	Method of Inspection
Critical		
None defined		
Major		
101	Diameter, max	Gage
102	Total length, min	Measure
103	Metal defective	Visual
104	Protective finish inadequate or defective	Visual
105	Surface finish improper	Visual
106	Burr	Visual
107	Foreign matter present	Visual
Minor		
201	Total length, max	Measure
202	Profile of end	Measure

TABLE IV. Cap, Drawing 8595254, Covering a Detail of Drawing 8593315.

Characteristic	Defect	Method of Inspection
Critical		
None defined		
Major		
101	Pitch diameter of thread, max	Gage
102	Minor diameter of thread, max	Gage
103	Concentricity of pitch diameter of thread with center hole, including perpendicularity with base of cavity	Gage
104	Symmetry of flats with pitch diameter of thread	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.

TABLE IV. Cap, Drawing 8595254, Covering a Detail of Drawing 8593315 – Continued.

Characteristic	Defect	Method of Inspection
105	Diameter of hole	Gage
106	Depth of cavity	Gage
107	Length of effective thread, min	Gage
108	Length to thread centerline	Gage
109	Thickness of base	Gage
110	Height, max	Gage
111	Profile of body	Measure
112	Internal radius at base of large thread cavity missing or incorrect	Visual
113	Thread damaged or not full	Visual
114	Metal defective	Visual
115	Protective finish inadequate or defective	Visual
116	Burr	Visual
117	Foreign matter present	Visual
Minor		
201	Pitch diameter of thread, min	Gage
202	Pitch diameter of set screw thread	Gage
203	Minor diameter of set screw thread, max	Gage
204	Diameter of flange holes	Gage
205	Length between flange holes	Gage
206	Width across body flats	Gage
207	Location of flange holes	Measure
208	Length of flange	Measure
209	Width of flange	Measure
210	Thickness of flange	Measure
211	Location of set screw holes	Measure
212	Marking missing, incorrect, or illegible	Visual
213	Radius or chamfer, missing, or incorrect, except as otherwise classified	Visual
214	Surface finish improper	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.

TABLE V. Housing, Firing Pin, Drawing 8594858, Covering a Detail of Drawing 8593315.

Characteristic	Defect	Method of Inspection
Critical		
1	Surface finish of cavity	Gage
Major		
101	Pitch diameter of internal thread, max	Gage
102	Minor diameter of internal thread, max	Gage
103	Pitch diameter of external thread, min	Gage
104	Major diameter of external thread, min	Gage
105	Concentricity of pitch diameter of internal thread with cavity	Gage
106	Concentricity of groove with flange	Gage
107	Concentricity of boss cavity with cavity	Gage
108	Concentricity of pitch diameter of external thread with cavity	Gage
109	Concentricity of cavity with flange	Gage
110	Concentricity of striker hole with cavity	Gage
111	Concentricity of body, flange end, with flange	Gage
112	Perpendicularity of flange face with cavity	Gage
113	Perpendicularity of face of boss with pitch diameter of external thread	Gage
114	Symmetry of pin hole with cavity	Gage
115	Symmetry of width across flat with body, flange end	Gage
116	Diameter of cavity, max	Gage
117	Diameter at datum location	Gage
118	Diameter of pin hole, max	Gage
119	Diameter of groove	Gage
120	Diameter of flange, min	Gage
121	Depth of counterbore, internal thread	Gage
122	Depth of thread cavity	Gage
123	Length of effective internal thread, min	Gage
124	Angle at datum diameter	Gage
125	Height of boss	Gage
126	Diameter of chamfer at internal thread cavity	Measure
127	Length of internal thread, max	Measure
128	Angle at bottom of thread cavity, min	Measure
129	Angles at mouth of internal thread cavity	Measure
130	Radius at root of boss	Measure
131	Profile of groove	Measure
132	Thread damaged or not full	Visual
133	Metal defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.

TABLE V. Housing, Firing Pin, Drawing 8594858, Covering a Detail of Drawing 8593315 – Continued.

Characteristic	Defect	Method of Inspection
134	Protective finish inadequate or defective	Visual
135	Surface finish of cavity chamfer, thread cavity improper	Visual
136	Burr or sharp corner	Visual
137	Foreign matter present	Visual
Minor		
201	Pitch diameter of internal thread, min	Gage
202	Pitch diameter of external thread, max	Gage
203	Pitch diameter of pin hole thread	Gage
204	Minor diameter of pin hole thread, max	Gage
205	Diameter of cavity, min	Gage
206	Diameter of boss cavity	Gage
207	Diameter of body, flange end	Gage
208	Diameter of pin hole, min	Gage
209	Diameter of counterbore, internal thread	Gage
210	Diameter of undercut in cavity, if applicable	Gage
211	Diameter of flange, max	Gage
212	Diameter of striker hole	Gage
213	Depth of striker hole	Gage
214	Depth of drill hole, pin thread, max	Gage
215	Total length	Gage
216	Length of effective thread, pin hole	Gage
217	Length from rear flange to boss face	Gage
218	Length from bottom of cavity to boss face	Gage
219	Width across flats	Gage
220	Location of pin hole	Gage
221	Diameter of body, midsection	Measure
222	Length of body, midsection	Measure
223	Length across flanges	Measure
224	Length of flat, flange end	Measure
225	Width of rear flange	Measure
226	Width of groove	Measure
227	Width of undercut in cavity, if applicable	Measure
228	Marking missing, incorrect, or illegible	Visual
229	Radius and/or chamfer, missing or incorrect, except as otherwise classified	Visual
230	Surface finish improper, except as otherwise classified	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.

TABLE VI. Pin, Firing, Drawing 8594744, Covering a Detail of Drawing 8593315.

Characteristic	Defect	Method of Inspection
Critical		
None defined		
Major		
101	Concentricity of groove with body	Gage
102	Concentricity of striker with body	Gage
103	Concentricity of striker shoulder with body	Gage
104	Symmetry of pin hole with body	Gage
105	Diameter of body, min	Gage
106	Diameter of groove	Gage
107	Diameter of striker, max	Gage
108	Diameter of pin hole, max	Gage
109	Depth of pin hole, max	Measure
110	Profile of striker	Measure
111	Profile of groove	Measure
112	Metal defective	Visual
113	Protective finish inadequate or defective	Visual
114	Surface finish of body and striker tip improper	Visual
115	Burr or sharp corner	Visual
116	Foreign matter present	Visual
Minor		
201	Diameter of body, max	Gage
202	Diameter of striker shoulder	Gage
203	Diameter of pin hole, min	Gage
204	Depth of pin hole, min	Gage
205	Length from body to tip of striker	Gage
206	Length of striker	Gage
207	Location of pin hole	Gage
208	Location of groove	Gage
209	Depth of slot in base	Measure
210	Total length	Measure
211	Width of groove	Measure
212	Width of slot in base	Measure
213	Location of slot in base	Visual
214	Marking missing, incorrect, or illegible	Visual
215	Radius missing or incorrect	Visual
216	Surface finish improper, except as otherwise classified	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.

TABLE VII. Assembly, Less Shear Pin, Cap, Cartridge Retainer and Chamber, Drawing 8593315, Less Drawings 8594745, 8595254, 8593313, and 8593314.

Characteristic	Defect	Method of Inspection
Critical		
1	Protrusion of firing pin	Gage
2	O-ring missing	Visual
Major		
None defined		
Minor		
201	O-ring not lubricated	Visual

TABLE VIII. Assembly, Less Cap, Chamber, Cartridge Retainer, Protective Plug and Protective Cap, Drawing 8593315, Less Drawings 8595254, 8593314, 8593313, and AIA NAS832 and AIA NAS845.

Characteristic	Defect	Method of Inspection
Critical		
1	Shear pin not engaged in firing pin	Visual/Manual
2	Shear pin set screw missing	Visual
Major		
101	O-ring missing or not lubricated	Visual
102	Thread damaged	Visual
103	Foreign matter present	Visual
Minor		
None defined		

TABLE IX. Assembly, Drawing 8593315.

Characteristic	Defect	Method of Inspection
Critical		
1	Any part missing, except as otherwise classified	Visual
2	Marking missing, incorrect, or illegible	Visual
Major		
None defined		
Minor		
201	Protective cap or plug missing	Visual
202	Protective finish inadequate or defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.

TABLE X. Box, Fiberboard (Inner) Packing Ammunition, Drawing 8796826.

Characteristic	Defect	Method of Inspection
Critical		
None defined		
Major		
None defined		
Minor		
201	Contents loose	Manual
202	Box damaged	Visual
203	Marking missing, incorrect, or illegible	Visual
204	Cut, damaged, or improperly sealed bag	Visual

TABLE XI. Box, Packing, Ammunition, Drawing 8796827.

Characteristic	Defect	Method of Inspection
Critical		
None defined		
Major		
None defined		
Minor		
201	Contents loose	Visual/Manual
202	Strapping missing, loose, broken, or improperly assembled	Visual/Manual
203	Contents of box exposed	Visual
204	Box damaged	Visual
205	Marking missing, incorrect, or illegible	Visual
206	Number of units incorrect	Visual

4.6 Inspection testing. The following tests shall be performed:

4.6.1 Hardness. Prior to the application of protective finish, a hardness tester shall be used to determine compliance with the requirements of the applicable drawing. Fifty units from each heat-treated lot of components shall be tested for compliance with the requirements on the applicable drawing. Failure of any unit to comply with the drawing requirements shall be cause for rejection of lot of components.

4.6.2 Hydrostatic pressure. Prior to the application of protective finish, the cap and chamber shall be mounted in the device, using a fixture for properly sealing all openings and subjected to the internal hydrostatic pressure to determine compliance with the requirement of 3.5. Each chamber and cap shall be subjected to the hydrostatic pressure test. Failure of any cap or chamber subassembly to comply with the requirement of 3.5 shall be cause for rejection of the subassembly.

4.6.3 Shear pin strength. After application of protective finish, the pin shall be subjected to the shear pin strength test to determine compliance with 3.6. The test shall be performed in a fixture in conjunction with a tensile testing machine. Fifty pins from each lot of shear pins shall be tested for shear strength. Failure of any shear pin to comply with the requirement of 3.6 shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.

4.6.4 Protective finish. Test procedures for protective finish shall be in accordance with the applicable specification referenced on the applicable drawing. The number of units for protective finish tests shall be in accordance with the applicable specification. Failure of any unit in the inspection sample to comply with the requirements of the applicable specification shall be cause for rejection of the lot.

4.6.5 Residual magnetism. The assembly shall be tested for excessive residual magnetism using an approved compass in an area free of local magnetic effects by placing the assembly 5 inches from the end and at the same height as the compass, in a north-south horizontal position (cap end at south) with the compass set in an east-west heading. The assembly shall be moved at a speed no greater than 10 feet per minute past the compass for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass. This procedure shall be repeated for each 90-degree rotation of the assembly for 4 full passes. Each assembly shall be subjected to the test for excessive residual magnetism. Failure of any unit in the inspection sample to comply with the requirement of 3.9 shall be cause for rejection of the assembly.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The assembly will ultimately be loaded and used in conjunction with other propellant-actuated devices in aircrew emergency escape systems.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. When first article inspection is required (see 3.1 and 6.3).

6.3 First article. When a first article inspection is required, the items should be a first article sample. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Definitions.

6.4.1 Mechanical failure. Mechanical failure is any deformation or breakage of a part, the occurrence of which is other than a design function.

6.4.2 Technical Authority. The Technical Authority has the authority, responsibility, and accountability to establish, monitor, and approve technical standards, tools, and processes in conformance to higher authority policy, requirements, architectures, and standards. NAVSEA 05S may be contacted to determine the appropriate Technical Authority for any given requirement related to equipment and systems of U.S. Navy ships and submarines.

6.5 Quality assurance terms and definitions. Reference may be made to ANSI/ISO/ASQ Q9000 to define the quality assurance terms used.

6.6 Inspection conditions. Local altitude and atmospheric conditions are acceptable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.

6.7 Subject term (key word) listing.

Ejection systems, aircrew
Emergency escape systems, aircrew
Escape systems, aircrew
Life-saving systems, aircrew

6.8 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

CONCLUDING MATERIAL

Custodians:
Navy – OS

Preparing activity:
Navy – OS
(Project 1377-2025-012)

Review activity:
Air Force – 70

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.