MIL-C-43830B
12 February 1985
SUPERSEDING
MIL-C-43830A
11 December 1980

MILITARY SPECIFICATION

COVER, FIELD PACK, CAMOUFLAGE, LC-1

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers the material, design and fabrication of a field pack cover.

1.2 Classification. The field pack cover shall be one type and in the following classes (see 6.2):

Class 1 - Snow camouflage, white, arctic
Class 2 - Desert Camouflage Pattern, Daytime
Class 3 - Woodland Camouflage Pattern

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8465

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:31Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

V-T-285	-	Thread, Polyester
UU-P-268	-	Paper, Kraft, Wrapping
DDD-L-20	-	Label: For Clothing, Equipage, and Tentage (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-C-3924	-	Cloth, Oxford, Cotton Warp and Nylon Filling, Quarpel Treated
MIL-C-43701	-	Cord, Elastic, Nylon
MIL-C-44031	-	Cloth, Camouflage Pattern: Woodland, Cotton and Nylon
MIL-C-44034	-	Cloth, Twill, Camouflage Pattern, Cotton and Nylon For Desert Uniform

STANDARDS

FEDERAL

FED-STD-751	-	Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Load

DRAWING

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

2-2-310	-	Cover, Field Pack, Camouflage, LC-1

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:31Z
Check the source to verify that this is the current version before use.

B 633 - Electrodeposited Coatings of Zinc on Iron and Steel
D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herin, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Samples.

3.1.1 Guide sample. Samples of the end item when furnished are solely for guidance and information to the contractor (see 6.3). Variation from this document may appear in the sample, in which case this document shall govern.

3.1.2 First article. When specified, a sample shall be subjected to first artical inspection (see 4.3, 6.2, and 6.4).

3.2 Materials and components. Materials (see 6.7) and components shall be as specified herein. For materials or components for which it is stated "or equal", if the contractor proposes to use an item considered to be equal to the material or component specified, prior to its use the contractor shall furnish a sample of the material or component with supporting data to the contracting officer for subsequent evaluation by the responsible military agency.

3.2.1 Cloth, basic.

3.2.1.1 Class 1 cover. Cloth for the class 1 cover shall be cotton warp and nylon filling oxford cloth, quarpel treated, conforming to class 1, bleached white of MIL-C-3924.

3.2.1.2 Class 2 cover. Cloth for the class 2 cover shall be cloth, desert camouflage pattern, cotton and nylon conforming to class 1 of MIL-C-44034.

3.2.1.3 Class 3 cover. Cloth for the class 3 cover shall be cloth, Woodland Camouflage Pattern, Cotton and Nylon conforming to class 2 of MIL-C-44031.

3.2.2 Thread, polyester. The thread shall be type I, class 1, sub-class A, size E conforming to V-T-285.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:31Z
Check the source to verify that this is the current version before use.

3.2.2.1 Color. Color of thread for the specific class of cover shall be as follows:

Class 1 - Bleached White, AH, C.A. 66050
Class 2 - Khaki P-1, C.A. 66019
Class 3 - Dyed Olive Drab S-1, C.A. 66022

3.2.2.2 Colorfastness. The dyed thread required for the class 2 and 3 shall show colorfastness to laundering equal to or better than the standard sample. When no standard sample is available, the dyed thread shall show "good" fastness to laundering.

3.2.3 Cord, elastic, nylon. The nylon elastic cord used in the hem of the cover shall be natural color and shall conform to type I of MIL-C-43701.

3.2.4 Adhesive. The adhesive for dipping the cord ends shall conform to Bostick - Adhesive No. 7008 or equal (see 6.5).

3.2.5 Clamp, steel. The steel clamp, and steel setting tool used for clamping the cord ends shall conform to Stimpson company, Inc., Part No. D3525 or equal (see 3.3.3 and 6.6) except the clamp shall be finished with a zinc coating conforming to type IV finish, SCI of ASTM B 633.

3.3 Construction. The construction shall conform in all respects to Drawing 2-2-310 and shall be as specified herein.

3.3.1 Stitches, seams and stitching. All seams and stitching shall conform to FED-STD-751 as follows:

For all stitching except zigzag	- Type 301, 8 to 10 stitches per inch
For zigzag stitching	- Type 304 or 308, 10 to 14 stitches per inch

3.3.1.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched not less than 1 inch except where ends are turned under or caught in other seams or stitching. Thread tensions shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be imbedded in the materials sewn.

3.3.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during stitching, the stitching shall be repaired by restarting the stitching a minimum of 1 inch back of the end of the stitching. 1/

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:31Z
Check the source to verify that this is the currentversion before use.

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area, continue over the defective area and continue a minimum of 1 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.3.1.2 Types 304 and 308 stitching. Thread tension shall be maintained so that there will be no loose stitching. All repairs shall be in accordance with 3.3.1.1.1a and 3.3.1.1.1b except wherever "1 inch" appears delete and substitute "three stitches".

3.3.1.3 Thread ends. All thread ends shall be trimmed to 1/4 inch maximum length.

3.3.2 Dipping of cord ends. The cord ends shall be dipped in the adhesive specified in 3.2.4 for a minimum length of 1/2 inch. The dipped ends shall be smooth in finish without any uncoated areas.

3.3.3 Clamping of cord ends. The cord ends shall be clamped together by using a steel clamp setting tool (see 3.2.5 and 6.6). The clamp shall be securely set in a manner that will prevent slippage of the cord within the clamp, or, cutting of the surrounding material. The clinched clamp shall be fee of burrs and rough or raised surfaces.

3.4 Marking. The identification marking shall be applied in the location shown on Drawing 2-2-310 and shall conform to type IV, class 5 of DDD-L-20. The letters "US" shall be applied in the size characters and in the location indicated on the drawing and shall conform to type IV, class 9 of DDD-L-20. Fastness of class 9 marking shall be as specified for class 5 marking.

3.5 Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects or damages that are classified as defects in 4.4.3, shall be removed from production and replaced with nondefective and properly matched components.

3.6 Repairs. Repairing the cover by mending, patching or darning is not allowed.

3.7 Workmanship. The finished cover shall conform to the quality of product established by this document. The occurrence of defects shall not exceed the applicable acceptable quality levels.

Source: https://assist.dla.mil -- Downloaded: 2026l0-21T22:31Z
Check the source to verify that this is the currentversion before use.

DLAM 4155.3 ATTACHMENT 47 28 NOVEMBER 1994

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.2 In-process inspection. In-process inspection shall be made to ascertain that the following conform to the specified requirements. Whenever nonconformance is noted, corrections shall be made to the parts affected and lot in-process. Parts which cannot be corrected shall be removed form production.

Requirement	Requirement reference
Cut dimensions of body	Drawing 2-2-310
Cut length of cord	Drawing 2-2-310
Stitching for joining cord ends	Drawing 2-2-310
Overlap of ends of cord	Drawing 2-2-310
Dipping of cord ends	Drawing 2-2-310 and 3.3.2
Clamping of ends of cord 1/	Drawing 2-2-310 and 3.3.3
Clamp on cord ends not finished, not free of burrs and rough or raised surfaces	3.2.5 and 3.3.3

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:31Z
Check the source to verify that this is the current version before use.

1/ The clamped cord ends shall be tested for proper assembly by hand-stretching the cord to its full elastic limit two times. While the cord is stretched to its elastic limit for the second time, the examination for cuts and for slippage of cord ends shall be made.

4.4.3 End item visual examination. The end item shall be examined for the defects listed in table I. The lot size shall be expressed in units of covers of one class only. The sample unit shall be one completely fabricated cover. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 1.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Cloth	Any hole, cut, tear, or smash.	X	
	Any abrasion mark, open place, broken or missing yarn, or multiple floats, clearly visible at normal inspection distance (approximately 3 feet).		X
Open seams	1/2 inch or less.		X
	More than 1/2 inch	X	
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or runoff stitches occur.		
Runoffs	(See "Open seams").		
Raw edges	More than 1/2 inch when securely caught in stitching.		X
	NOTE: Raw edge not securely caught in stitching shall be classified as an open seam.		
Seam and stitch type	Wrong seam or stitch type.	X	
Stitch tension	Loose resulting in loose bobbin or top thread.		X
	Excessively tight resulting in puckering of fabric.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:31Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Stitches per inch	Up to two stitches less than minimum specified.		X
	Three or more stitches less than minimum specified.	X	
	One or more stitches in excess of maximum specified.		X
	Variation in the number of stitches per inch, caused by the operator's speeding up the machine and pulling the fabric in order to sew over heavy places or in turning corners, shall be classified as follows:		
	a. Within the major defect classification - Minor defect.		
	b. Within the minor defect classification - No defect.		
Stitching gage and margin	Not as specified.		X
Stitching ends	Not secured as specified.		X
Thread breaks, skipped stitches, or run-offs	Overstitched less than 1 inch in each direction beyond the defective stitching area.		X
	NOTE: Thread breaks or two or more consecutive skipped or run-offs stitches not overstitched shall be classified as open seams.		
Marking identification and US	Omitted, illegible, incorrect, misplaced, or size of characters not as specified.		X
Cleanness	Thread ends not trimmed as specified.		X
	Any spot or stain.		X
Components and assembly	Any required part or operation omitted (unless otherwise classified herein).	X	

Source: https://assist.dla.mil -- Downloaded: 20260-21T22:31Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
	Camouflage print on class 2 or 3 cover is not on outside surface.	X	
	Hem noticeably twisted or pleated.		X
	Body assembled with more than two pieces of material.		X
	Any portion of elastic cord caught in hem stitching.	X	
	Any mend, darn, or patch.		X

4.4.4 Packaging inspection. An examination shall be made to determine that the preservation, packing, and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged. The lot size shall be the number of shipping containers in the inspection lot. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and unit pack)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as incomplete closure of container flap, improper taping, loose strapping, or inadequate stapling. Bulged or distorted container.
Content	Number of bundles per container is more or less than required. Number of covers per bundle is more or less than required. 1/

1/ For this defect, two bundles from each shipping container in the sample shall be examined.

4.4.5 Palletization examination. An examination shall be made to determine that the palletization complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully packaged. The lot size shall be the number of

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:31Z
Check the source to verify that this is the current version before use.

palletized unit loads in the end item inspection lot. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Each cover shall be laid out flat with the hem positioned along one side. Ten covers of one class only, with the hems alternatively reversed shall be neatly stacked in a bundle. Each bundle shall be securely cross tied with cotton tape or twine.

5.1.2 Commercial. The covers shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B or Commercial, as specified (see 6.2).

5.2.1 Level A packing. Thirty covers of one class only, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15C of PPP-B-636. Level A unit packs shall be packed flat, three in depth within the shipping container. Inside dimensions of each shipping container shall approximate 23-1/2 inches in length, 15 inches in width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30 pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method III, waterproofed with method V, and reinforced as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:31Z
Check the source to verify that this is the current version before use.

5.2.2 Level B packing. Thirty covers of one class only, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Level A unit packs shall be packed flat, three in depth within the shipping container. Inside dimensions of each shipping container shall approximate 23-1/2 inches in length, 15 inches in width, and 15 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30 pound minimum basis weight kraft paper conforming to type I, grade B of UU-P-268. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except the inspection shall be in accordance with 4.4.4.

5.2.3 Commercial packing. Covers, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), (covers), packed as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with the bonding means K and L or film bonding means O or P. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147. The pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951 as applicable. Each unit pack shall have attached a manila colored paper shipping tag for the identification information.

6. NOTES

6.1 Intended use. The covers are intended to be used over the medium and large field packs to provide camouflage.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Class required (see 1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:31Z
Check the source to verify that this is the current version before use.

c. When a first article sample is required (see 3.1.2, 4.3, and 6.4).
d. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).

6.3 Samples. For access to samples, address the contracting activity issuing the invitation for bids.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provision of FAR 52.209. The first article should be a preproduction sample consisting of one finished cover. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for inspection and approval of the first article.

6.5 Adhesive supply source. A source of supply for the adhesive specified in 3.2.4 is the United Shoe Machinery Corp., Chemical Div., Middletown, MA 01949.

6.6 Clamp supply source. A source of supply for the clamp specified in 3.2.5 and the clamp setting tool specified in 3.3.3 is the Stimpson Co., Inc., Bayport, NY 11705.

6.7 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.2).

6.8 International standardization agreements. Certain provisions of this document are the subject of international standardization agreement number STANAG 2311. When amendment, revision, or cancellation of this document is proposed which will effect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

6.9 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:31Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - NU

Review activities:

Army - MD
Navy - MC
DLA - CT

User activity:

Air Force - 45

Preparing activity:

Army - GL

Project No. 8465-0896

☆ U.S. GOVERNMENT PRINTING OFFICE: 1985—505-038/21124

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:31Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: STRNC-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:31Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-43830B	Cover, Field Pack, Camouflage, LC-1

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 20260-21T22:31Z
Check the source to verify that this is the current version before use.

bridge cases;