MIL-C-43831B
26 February 1988
SUPERSEDING
MIL-C-43831A
28 October 1976

MILITARY SPECIFICATION

CARRIER, INTRENCHING TOOL, HAND, FOLDING,

LIGHTWEIGHT, PLASTIC, LC-1

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type and size of plastic carrier for the intrenching tool.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

A-A-203	-	Paper, Kraft, Untreated
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:32Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-H-9890 - Hardware, Individual Load Carrying Equipment: and Hardware, Miscellaneous
MIL-F-10884 - Fasteners, Snap
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For
MIL-I-43684 - Intrenching Tool, Hand, Folding, Lightweight and Carrier

STANDARDS

FEDERAL

FED-STD-595 - Colors

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

8-2-316 - Carrier, Intrenching Tool, Hand, Folding, Lightweight, Plastic, LC-1; Assembly Complete

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 638 - Tensile Properties of Plastics
D 747 - Stiffness of Plastics by Means of a Cantilever Beam
D 1505 - Density of Plastics by Density-Gradient Technique
D 1525 - Vicat Softening Point of Plastics
D 3951 - Standard Practice for Commercial Packaging

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:32Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Samples.

3.1.1 Guide samples. Guide samples of the end item when furnished are solely for guidance and information to the contractor (see 6.3). Variation from this document may appear in the sample, in which case this document shall govern.

3.1.2 First article. When specified in the contract or purchase order, the contractor shall furnish one finished carrier from each mold cavity for first article inspection (see 4.3, 6.2, and 6.4).

3.2 Materials (see 6.5).

3.2.1 Plastic resin. The material used to make the body of the carrier shall be a virgin ethylene-vinyl acetate copolymer resin. The vinyl acetate content shall be 18 ± 1 percent. The resin shall meet the requirements of table I when tested as specified in 4.4.1.1. A maximum of 20 percent, by weight of the blended mixture, of clean unburned plastic material in the form of imperfect parts, flash, runners, gates, sprues, or other scrap of the same composition as the virgin material and produced in the same molding or finishing operation may be reground and mixed with the virgin material.

TABLE I. Physical properties of resin

Property	Requirement	
	Minimum	Maximum
Density, g/cm^3 (natural resin)	0.935	0.945
Tensile strength, psi (at yield)	2000	-
Elongation, percent (at yield)	650	-
Vicat softening temperature, ^{o}C	57	-
Stiffness in flexure, psi	4000	6000

3.2.2 Keeper with slide. The keeper with slide shall conform to type X of MIL-H-9890.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:32Z
Check the source to verify that this is the current version before use.

* 3.2.3 Snap fasteners. The snap fasteners shall conform to style 2, finish 2 and part numbers MS 27980-1B, -6B, -7B and -8B of MIL-F-10884.

3.3 Design and construction. The design and construction of the carrier shall be as shown on Drawing 8-2-316.

* 3.3.1 Plastic carrier body. The body of the carrier shall be injection molded from the resin specified in 3.2.1. The carrier body shall have a wall thickness of 0.070 (+0.028, -0.005) inch when measured as specified in 4.4.3.2.

* 3.3.2 Setting of the metallic strap fastener. Roll of the clinched eyelet of the assembled fastener component shall not possess more than three scores (splits).

3.4 Color. The color of the carrier shall approximate color number 34087 of FED-STD-595.

* 3.5 Finish. The exterior surface of the carrier shall have an embossed lusterless stippled grain finish and the interior surface of the carrier shall have a smooth, lusterless finish. The grain and lusterless finish shall be produced by the finish on the mold cavities and core and not by protective coatings, lacquers or other materials.

3.6 Fit. The fit shall be such that the intrenching tool can be inserted or withdrawn from the carrier without binding when examined as specified in 4.4.4.

3.7 Identification marking. The carrier body shall be marked on the inside of the flap as shown on Drawing 8-2-316, by an embossed molded-in process with the year of manufacture and the contractor's name or trade mark or marking of such known character as to be readily identified with the contractor. The marking area shall be approximately 1 square inch and the markings shall be raised approximately 0.007 inch in height.

3.8 Government loaned property. One lightweight intrenching tool will be furnished to the contractor for use in the fit test (see 6.3).

* 3.9 Workmanship. The carrier body shall be clean and free from mold release compound (silicone, grease or wax) when examined as specified in 4.4.5, bubble, crack, dirt, blister, cut, sharp edge, and flash exceeding 1/32 inch width. Flash will be permitted in opening of keeper slots as long as it does not interfere with attachment of keepers. All cut edges shall be smooth. Gates shall be trimmed within 1/32 inch of the body.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:32Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

* 4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.2, 4.4.3, and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

* 4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:32Z
Check the source to verify that this is the current version before use.

be certified by the ingredient supplier or ingredient manufacturer. ... shall ...

4.4.1.1 Component testing. The resin shall be tested for the characteristics in table II. The sample unit shall be a slab, having uniform thickness of 0.075 ± 0.005 inch, 12 inches by 12 inches (or the equivalent area in 6 inch by 6 inch slabs) and compression molded from the same material used to manufacture the carrier body. The sample size (number of sample units to be tested) shall be two. There shall be no failure of any sample unit to meet the requirements as specified.

TABLE II. Component tests

Characteristic	Requirement paragraph	Test method ASTM	Number determinations per sample unit	Results reported numerically to nearest
Density	3.2.1	D 1505	Average of 3	0.001 g/cm^3
Tensile strength at yield	3.2.1	D 638	Average of 6 (3 in ea direction)	5 psi
Elongation at yield	3.2.1	D 638	Average of 6 (3 in ea direction)	5 percent
Vicat softening temperature	3.2.1	D 1525 1/	Average of 5	°C
Stiffness in flexure	3.2.1	D 747 2/	Average of 5	5 psi

1/ Rate "A" shall be used for rate of temperature increase, and retesting provisions shall not be applicable.

2/ Specimen size - 3-1/2 inches long, 1 inch wide and 0.075 inch thick.

* 4.4.1.2 Certification. The contractor shall furnish a certificate of compliance for the requirements listed below. The government reserves the right to check test such items to determine the validity of the certification.

Requirement	Requirement paragraph
Resin (vinyl acetate content)	3.2.1
Blended mixture with virgin resin	3.2.1

4.4.2 End item visual examination. The end items shall be examined for the defects listed in table III. The lot size shall be expressed in units of carriers. The sample unit shall be one carrier. The inspection level shall be 1 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 6.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:32Z
Check the source to verify that this is the current version before use.

* TABLE III. End item visual defects

Examine	Defect
Design and construction	Varies from specified design or construction shown on specified drawing or approved sample
	Core pin holes not as shown in drawing; not properly located
Appearance and finish	Color not as specified
	Color not uniform, streaky
	Exterior surface of carrier not embossed lusterless stippled grain finish throughout
	Inside surface of flap and pocket not smooth and lusterless throughout
	Finish produced by application of coating, lacquer or other organic materials
Workmanship	Any bubble, crack, blister, cut, break, or sharp edge in carrier body
	Any gate not trimmed within 1/32 inch of carrier body
	Any flash exceeding 1/32 inch width
NOTE:	Flash permitted in opening of keeper slots as long as it does not interfere with attachment of keeper.
	Evidence of black or white spots on carrier body
	Sharp corner on closure flap
	No bead on closure flap, as shown on drawing
	Objectionable or vinegar-like odor
Cleanliness	Any dirt or foreign matter in plastic
Snap fasteners	Any fastener missing or misplaced
	Any fastener not functioning properly; i.e., fails to snap closed, provide a secure closure, or to open freely
	Improper or insecure clinching of male or female components
	Clinched excessively tight, cutting surrounding material
	Clinched loosely, permitting components to rotate freely in the hole of the material
	Incorrect style
	Roll of clinched eyelet fastener assembly contains more than three scores (splits)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:32Z
Check the source to verify that this is the current version before use.

TABLE III. End item visual defects (cont'd)

Examine	Defect
Snap fasteners (cont'd)	Socket at opening malformed (dented) in assembling operation. Socket stud tube displays a ridge or shoulder on its inside diameter. NOTE: a. Incomplete roll of the end of the socket eyelet tube and or stud eyelet tube is evidence of improper and insecure clinching. Fasteners evidencing incomplete roll will separate in use. b. Fasteners shall be snapped and unsnapped twice to determine whether parts of fastener separate freely and also affect a secure closure.
Hardware (general)	Broken or malformed, protective finish omitted or not as specified, corroded area, burr or sharp edge
Keeper	Slide component of keeper jams in open, partly closed, or closed position, or fails to effect a secure closure. Any keeper omitted. NOTE: The keepers shall be operated twice each to determine compliance with the requirements of this examination.
Marking	Incorrect; incomplete or illegible Not in proper location Not embossed molded in process, or not raised approximately 0.007 inch in height

4.4.3 End item dimensional examination. The end items shall be examined for the defects in dimensions other than wall thickness as specified in 4.4.3.1 and for wall thickness as specified in 4.4.3.2. The lot size shall be expressed in units of carriers. The sample unit shall be one carrier.

* 4.4.3.1 Examination for dimensions other than wall thickness. For this examination, the dimensions listed below shall be measured. Any dimension not within the specified tolerance shall be classified as a defect. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 1.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:32Z
Check the source to verify that this is the current version before use.

a. The width of the flap just below the radii at corners (5.625 inches)

b. The center to center distance between the snap fasteners on the flap (4 inches), and the distance from the center of the snap fastener to the top edge of the flap (0.625 inch).

c. The width between the two reinforcements just above the carrier opening (6.197 inches).

d. The radii on the flap corners (0.750R).

e. The radii where the flap widens toward the ears (0.750R inch "A").

f. The inside of the carrier at Section B-B of Drawing 8-2-316 (6.094 inches).

g. The front inside height of the carrier a the center (8.938 inches).

* 4.4.3.2 Examination for wall thickness. For this examination, the carriers shall be cut in half along the parting lines and each half cut 90° to the bottom of the parting line to form four quarters. Each quarter shall be measured along the cut edges at 1-1/2 inch intervals; two measurements shall be taken in each keeper slot with all measurements taken to the nearest 0.001 inch. A failure of any sample unit to meet the requirements specified in 3.3.1 shall be classified as a defect. Measurements on a sample unit shall not be averaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 1.0.

* 4.4.4 End item fit examination. The end items shall be examined for fit with the intrenching tool specified in MIL-I-43684 (see 6.3). Any sample unit failing to meet the requirements specified in 3.6 shall be classified as a defect. The lot size shall be expressed in units of carriers. The sample unit shall be one carrier. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 0.65.

* 4.4.5 End item examination for mold release compound. The end items shall be examined for presence of mold release compound by drawing a thin edged instrument (pocket knife, 6-inch ruler, key, etc.) perpendiculary across the back, side, front, and inside surfaces of the carrier. Any accumulation of mold release compound on the instrument shall be classified as a defect. The lot size shall be expressed in units of carriers. The sample unit shall be one carrier. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 1.0.

4.4.6 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:32Z
Check the source to verify that this is the current version before use.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; incomplete; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components; such as incomplete sealing or closure of flaps improper taping, loose strapping or inadequate stapling
Content	Number per container is more or less than required

4.4.7 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1, and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width or height exceeds specified maximum requirement.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.

5. PACKAGING

5.1 Packing. Packing shall be level A, B or Commercial as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:32Z
Check the source to verify that this is the current version before use.

* 5.1.1 Level A packing. Sixty carriers (each with the snap fasteners and keepers closed) shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each fiberboard container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. The carriers shall be packed flat, three in length, two in width, and ten in depth (alternately reversed, top to bottom) within a shipping container. Inside dimensions of each shipping container shall approximate 20-1/2 inches in length, 20-1/2 inches in width, and 16 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636, except the inspection shall be in accordance with 4.4.6. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

* 5.1.2 Level B packing. Sixty carriers (each with the snap fasteners and keepers closed) shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each fiberboard container shall be fitted with a taped box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. The carriers shall be packed flat, three in length, two in width, and ten in depth (alternately reversed, top to bottom) within a shipping container. Inside dimensions of each shipping container shall approximate 20-1/2 inches in length, 20-1/2 inches in width, and 16 inches in depth. Approximate dimensions are furnished as a guide only. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each shipping container shall be closed in accordance with method II as specified in the appendix of the container specification except that the inspection shall be in accordance with 4.4.6.

* 5.1.2.1 Weather-resistant fiberboard container. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636 except that the inspection shall be in accordance with 4.4.6.

5.1.3 Commercial packing. Carriers shall be packed in accordance with ASTM D 3951.

5.2 Palletization. When specified (see 6.2), carriers, packed as specified in 5.1.2 or 5.1.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Each prepared load shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:32Z
Check the source to verify that this is the current version before use.

bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 90 in accordance with the appendix of MIL-STD-147.

5.3 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951 as applicable.

6. NOTES

6.1 Intended use. The carrier is designed as a suitable carrier for Intrenching Tool, Hand, Folding, Lightweight covered by MIL-I-43684.

* 6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1).
c. Selection of applicable levels of packing (see 5.1).
d. Type and class of unit load required (see 5.1.1).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.1.2.1).
f. When palletization is required (see 5.2).

6.3 Samples. For access to guide samples and intrenching tool required for fit examination (see 4.4.4), address the contracting activity issuing the invitation for bids.

* 6.4 First article. When a first article sample is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

* 6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.2).

* 6.6 Subject term (key word) listing.

Carrier
Intrenching tool

* 6.7 Changes from previous issue. The margins of this document have been marked with an asterisk (*) to indicate where changes (additions, modification, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:32Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Review activities:

Army - MD
Navy - MC
Air Force - 82
DLA - CT

User activities:

Navy - YD
Air Force - 45

Preparing activity:

Army - GL

Project No. 8465-0972

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:32Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:32Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-43831B	Carrier, Intrenching Tool, Hand, Folding, Lightweight, Plastic, LC-1

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:32Z
Check the source to verify that this is the current version before use.