MILITARY SPECIFICATION

DISPENSER, CONDIMENT, PUMP TYPE, MANUALLY OPERATED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE AND CLASSIFICATION

1.1 This specification covers two types of manually operated pump type condiment dispensers capable of dispensing both light and heavy dressings.

1.2 Classification. The dispenser pump shall be the following types, as specified (see 6.2).

Type I - For use with 4-11/16 inch diameter and 3-1/2" diameter mouth 1-gallon glass or plastic jars.

Type II - For use with standard number 10 can.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

EE-M-131	-	Mayonnaise and Salad Dressing
PPP-B-636	-	Box, Fiberboard
PPP-C-96	-	Cans, Metal, 28 Gage and Lighter

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection of Attributes
MIL-STD-129	-	Marking for Shipment and Storage

FSC 7320

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:34Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal, shall apply:

American Society for Testing and Materials (ASTM)

Designation A167-70 - Stainless and Heat-Resisting Chromium - Nickel Steel Plate, Sheet and Strip, Specification for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103).

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies).

National Sanitation Foundation (NSF)

Standard No. 2 - Food Service Equipment

Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, NSF Building, Ann Arbor, Michigan 48105).

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, D.C. 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:34Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified, the supplier shall furnish a sample for first article inspection and approval (see 4.2, 6.2 and 6.3).

3.2 Standard product. The condiment dispensers delivered under this specification shall be the manufacturer's standard current commercial product except for any changes necessary to comply with specification requirements.

3.3 Code and standards. The dispenser shall conform to the applicable requirements of NSF Standard No. 2.

3.3.1 NSF certification. The supplier shall submit satisfactory evidence to the contracting officer or his authorized representative that the dispenser he proposes to furnish under this specification meets the applicable requirements of NSF Std. No. 2 as follows:

(1) Listing in the current edition of the NSF "Listing of Food Service Equipment" or display of the NSF seal on the finished dispenser shall be submitted prior to the approval of the first article if one is submitted, or prior to commencing production, or:

(2) A certification for the dispenser issued by NSF under their special one-time contract evaluation certification service shall be submitted prior to the approval of the first article, if one is submitted, or prior to commencing production, or:

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the dispensers are being procured, indicating that the dispensers have been tested and conform to NSF Std. No. 2 shall be submitted prior to the approval of the first article, if one is submitted, or prior to commencing production.

3.4 Materials. Materials not definitely specified shall be of the quality normally used by the manufacturer for his current commercially available dispenser, provided the completed item complies with all provisions of this specification.

3.4.1 Stainless steel. Stainless steel shall conform to type 302 or 304 of ASTM A-167-70.

3.5 Design and construction. The dispenser pump shall be type I, or type II as specified (see 1.1). The dispenser pump shall be hand operated and the lid shall fit the applicable condiment container. When the dispenser is attached to the container, the condiment being dispensed shall be fully enclosed. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:34Z
Check the source to verify that this is the current version before use.

dispensing nozzle shall extend beyond the outside surface of the container. The dispenser shall be made of stainless steel as specified in 3.4.1. The dispenser shall operate without use of excessive force and without evidence of binding or malfunctioning when tested as specified in 4.4.1. The dispenser, when attached and operated on both a full or empty container, shall be stable and shall not cause tipping or upsetting of the container. The dispenser shall be adjustable, without use of tools, to dispense small and large portions. The smallest portion dispensed shall be 1/2 fluid ounce +0 or -1/4 per stroke of the pump; the largest portion dispensed shall be 1 fluid ounce or more per stroke of the pump when tested in accordance with 4.4.2. The dispenser shall be easily disassembled without use of tools for cleaning. The tye I dispenser shall fit plastic or glass threaded 1-gallon jars with 3-1/2 inch and 4-11/16 inch nominal diameter mouths. The dispenser shall be provided with a retaining device to prevent crushing, collapsing or accidental removal of the lid from the container when attached and operated on a plastic jar. The type II dispenser shall fit the standard commercial No. 10 can conforming to PPP-C-96.

3.6 Marking for identification. Each condiment dispenser shall be permanently and legibly marked with the manufacturer's name, trade name or trademark easily identifiable with said manufacturer.

3.7 Finish. All surfaces shall conform to NSF Standard No. 2.

3.8 Workmanship. Each dispenser shall be clean and shall be free of scratches, sharp edges, grinding and pit marks. Finished items shall not be buckled, malformed or damaged. Welds shall be round and blended with adjacent surfaces. Scale and flux deposits shall be removed.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to insure supplies and services conform to prescribed requirements.

4.2 First article inspection. When a first article is required, (see 3.1 and 6.2), it shall be examined for the defects in table I and tested in accordance with 4.4.1 and 4.4.2. Failure of any test shall be cause for rejection of the first article. The presence of any defect listed in table I shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:34Z
Check the source to verify that this is the current version before use.

4.3 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Components and materials inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.3.2 End item inspection. The inspection lot shall consist of all dispensers of the same type offered for inspection at one time. The sample unit shall be one completely assembled dispenser.

4.3.2.1 Visual examination. Examination shall be made of the end item for defects listed in table I. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Standard product	Item not in accordance with manufacturer's standard product except for changes necessary to comply with specification requirements	X	
Design	Cannot be disassembled without tools	X	
	Does not fit applicable container	X	
	Spigot does not extend beyond container	X	
Construction and workmanship	Scratches, sharp edges, grinding and pit marks		X
	Welds not smooth		X
	Scale and flux deposits		X
Marking identification	Missing, incomplete, illegible	X	
Material	Not as specified	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:34Z
Check the source to verify that this is the current version before use.

4.3.2.2 End item testing. When a first article is not required, the initial production unit shall be tested in accordance with 4.4.1 and 4.4.2. Any nonconformance shall be cause for rejection of the dispenser. The supplier shall perform tests on production units in accordance with 4.4.1 using an inspection level S-2 and an AQL of 2.5 expressed in terms of defects per hundred units.

4.3.3 Examination of preparation for delivery. An examination shall be made to determine that packaging, packing and marking as required by section 5 of this specification are complied with. Defects shall be as indicated in table II. The sample unit shall be one shipping container fully prepared for delivery. The lot size shall be the number of containers in the inspection lot. The inspection level shall be S-4 with an AQL of 2.5 defects, expressed in terms of defects per hundred units.

TABLE II. Examination of preparation for delivery

Examine	Defect
Markings	Omitted, incorrect, illegible, of improper size, location, sequence or method of application.
Materials	Component missing, damaged or otherwise defective.
Workmanship	Cushioning inadequate, improper, or missing.
Contents	Contents per container are more or less than required.

4.3.3.1 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in closure, waterproofing and strapping shall be in accordance with PPP-B-636.

4.3.4 Proof of compliance with the requirements of 3.3.1 shall be submitted to the Government representative.

4.4 Tests.

4.4.1 Functional test. When applicable, place type I dispenser on both 4-11/16 inch and 3-1/2 inch nominal diameter mouth 1-gallon jars and place type II dispenser on standard No. 10 can. Check for secure fit. The dispenser shall operate freely and without binding. Check type I dispenser for accidental removal of lid from plastic container during operation. The container shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:34Z
Check the source to verify that this is the current version before use.

remain stable and upright while the dispenser is in use (see 3.5). Any non-conformance with the requirements of 3.5 shall constitute failure of this test.

4.4.2 Performance. Fill container with French dressing conforming to type III of EE-M-131. Set dispenser adjustment at the smallest portion. Dispense the condiment by operating the dispenser ten (10) strokes and check for compliance with volume dispensing requirements of 3.5. Set adjustment at largest portion setting; operate dispenser for ten (10) strokes and check for compliance with 3.5. Repeat above procedure using salad dressing conforming to type II of EE-M-131. Failure to meet any requirements of 3.5 shall constitute failure of this test.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Each dispenser shall be packaged in a snug-fitting box conforming to style RSC, type CF, variety SW, or type SF, class domestic of PPP-B-636. The dispenser shall be cushioned by means of fiberboard pads or other suitable means to prevent movement and damage while in transit. Box closure shall be in accordance with PPP-B-636.

5.1.2 Level C. The dispenser shall be packaged to afford adequate protection against damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Twelve dispensers, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type V3s of PPP-B-636. Each shipping container shall be closed, waterproofed by means of tape and reinforced with flat strapping or tape banding in accordance with PPP-B-636.

5.2.2 Level B. Twelve dispensers, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard container conforming to style RSC, type CF, variety SW or type SF, class domestic of PPP-B-636. Each shipping container shall be closed in accordance with method II of the appendix of PPP-B-636.

5.2.2.1 When specified (see 6.2), the shipping container shall be V3c, V3s, or V4s fabricated and closed in accordance with PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:34Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. Dispensers, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules, or National Motor Freight Classification Rules, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The pump dispensers covered by this specification are intended for use in feeding lines to dispense condiments.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Type of dispenser required (see 1.1).
c. When a first article is required (see 3.1, 4.2 and 6.3).
d. Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article should be a preproduction sample, initial production item or other specific item described under the definition of a first article in the ASPR. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all procurement instruments regarding arrangements for inspection and approval of the first article.

Custodians:

Army - GL
Navy - YD
Air Force - 84

Preparing activity:

Army - GL

Project No. 7320-0534

Review activities:

Army - MD
DSA-GS

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:34Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

Dispenser, Condiment, Pump Type, Manually Operated MIL-D-43840

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD, FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:34Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. ARMY NATICK LABORATORIES
NATICK, MASS. 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

AMXRET-EQS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314

U.S.MAIL

Commander
US Army Natick Laboratories
ATTN: AMXRET-EQS
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:34Z
Check the source to verify that this is the current version before use.