MIL-D-43845A
27 January 1978
SUPERSEDING
MIL-D-43845
20 March 1973

MILITARY SPECIFICATION

DISPENSER, ICED TEA

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a counter model, self-contained iced tea dispenser.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard

MILITARY

MIL-T-3527 - Tea, Instant
MIL-B-35023 - Beverage Base, Powder

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Command, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7310

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:35Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads for 40" x 48" Pallets

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

AMERICAN NATIONAL STANDARDS INSTITUTE, INC. (ANSI)

C73.1 - Outlet Receptacles, Attachment Plug Caps and Appliance Plugs

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

NATIONAL SANITATION FOUNDATION (NSF)

Listing of Food Service Equipment

Standard No. 18 - Manual Food and Beverage Dispensing Equipment

(Application for copies should be addressed to the National Sanitation Foundation, NSF Building, Ann Arbor, MI 48105.)

UNDERWRITERS LABORATORIES, INC.

UL 73 - Motor Operated Appliances

(Application for copies should be addressed to Underwriters Laboratories, Inc., 207 East Ohio Street, Chicago, IL 60611; 1655 Scott Boulevard, Santa Clara, CA 95050; 333 Pfingsten Road, Northbrook, IL 60062; Walt Whitman Road, Melville, L.I., NY 11746 or 2602 Tampa East Blvd., Tampa, FL 33619.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:35Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard product. The dispenser delivered under this specification shall be the manufacturer's standard commercial product, except for any changes necessary to comply with specification requirements. All like items furnished on any one contract, including parts and subassemblies, shall be new and interchangeable.

3.2 Codes and standards. The complete dispenser shall conform to the applicable requirements of NSF No. 18 and UL 73, as applicable.

3.2.1 Compliance. Prior to approval of the first shipment, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the dispensers he proposes to furnish under this specification meet the applicable requirements of NSF and UL as follows:

3.2.1.1 UL. Acceptable evidence of meeting the requirements of UL shall be the UL label, a UL listing mark, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the dispensers have been tested and conform to UL 73.

3.2.1.2 NSF. Acceptable evidence of meeting the requirements of NSF shall be:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seal on the finished dispenser.

(2) A certification for the dispenser issued by NSF under their special one-time contract evaluation/certification service.

(3) A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the dispensers are being procured, indicating that the dispensers have been tested and conform to NSF Standard No. 18.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:35Z
Check the source to verify that this is the current version before use.

3.3 Materials. Materials not definitely specified shall be of the quality normally used by the manufacturer for iced tea dispensers, provided the complete item complies with all provisions of this specification (see 6.6).

3.4 Design and construction. The dispenser shall be a mechanical-electrical device for dispensing the type I instant tea specified in MIL-T-3527 or type II, style 2 of MIL-B-35023 in the correct proportion with cold water 55 Fahrenheit (F) (12.8 Celcius (C)) upon manual actuation of a momentary-on type actuating switch. Tea shall be dispensed as long as the momentary-on switch is depressed. The instant tea and water shall be mixed in a chamber and an overrun of water shall cleanse the chamber of instant tea product. Maximum allowable envelope dimensions for the dispenser are: width 9 inches, depth 13 inches (229 mm and 303 mm) and height 24 inches (610 mm), respectively. Dispensing of an 8-ounce (235 milliliter (ml)) drink shall be performed in not more than 6 seconds. The dispensing nozzle shall not drip or leak when the dispenser is connected to the utilities and is not being used. A drip tray and grill shall be located beneath the dispensing nozzle and shall serve as a cup rest when the dispenser is operating. The entire unit shall be inclosed in a cabinet of corrosion-resisting material. The net weight of the dispenser shall be less than 20 pounds (9 kg). When specified (see 6.2 and 6.4), a water filter shall be provided. The base of the dispenser shall be provided with protectors to protect the surface upon which the dispenser rests, and capped holes shall be provided in the base for counter fastening. Product refilling directions, dispensing directions, and controls shall be accessible from the dispensing position. The average weight of ten product throws shall differ from the specified product throw weight (1.30 grams tea per 8 fluid ounces (235 ml) water) by not more than 10 percent when tested in 4.4.2.

3.4.1 Electrical requirements. Unless otherwise specified (see 6.2), the dispenser shall operate on nominal 120 volt, single phase, 60 Hertz (Hz) alternating current. When 50 Hertz operation is specified a UL approved, 3-wire power supply cord compatible with the dispenser shall be provided without the attachment plug cap. When specified (see 6.2), for 50 Hz, the power supply cord shall be provided with an attachment plug cap in accordance with ANSI C73.1.

3.4.2 Water supply pressure. The dispenser shall be designed to operate at a water pressure between 30 and 120 pounds per square inch (207 Pa and 828 Pa) respectively.

3.4.3 Supports. When specified (see 6.2), for Naval shipboard use, supports shall be provided with tapped holes in the feet, lugs with bolt-holes, or other means of fastening the dispenser in place. Plastic parts shall not be used for securing the mounting bolts unless metal inserts are provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:35Z
Check the source to verify that this is the current version before use.

3.4.4 Operation. The dispenser controls and electrical components shall operate through a complete cycle without malfunction, plumbing leaks, and controls shall not bind or show looseness when tested as specified in 4.4.1.

3.4.5 Inclined operation. When specified for shipboard use (see 6.2), the dispenser shall operate satisfactorily when the base is tilted at an angle of 15 degrees from the vertical in any direction with no spillage of liquid when tested as specified in 4.4.3.

3.5 Marking. Identification instructions shall be permanently and legibly marked directly on the item or on an aluminum, brass, or stainless steel plate firmly affixed to the item. Marking shall be stamped, embossed, engraved or applied by photosensitive means. The plate thickness shall be not less than 0.012 inch (0.3 mm).

3.5.1 Identification plate. Each dispenser identification plate shall include the manufacturer's model and serial number, and name, trade name or trademark of such known character as to be readily identifiable. In addition, such information as required by UL 73, as applicable, shall appear on the identification plate.

3.6 Finish Dispenser finishes shall be free from discoloration and stains. Stainless steel shall have a 2B or smoother finish.

3.7 Workmanship. All components and assemblies of the dispenser shall be free from dirt and other extraneous material, burrs, slivers, rough die, tool and grind marks, dents and cracks. Castings and molded parts if used, shall be free of sand, fins, pits, blowholes, and sprues. External surfaces shall be free from sharp edges and sharp corners.

3.7.1 Metal fabrication. Metal used in the fabrication of the dispensers shall be free from kinks. Forming and shearing shall not cause damage to the metal and the metal shall be free from trimming marks.

3.7.2 Welding. The surfaces of parts to be welded shall be free from rust, scale, paint, grease and other foreign matter. Welds shall be smooth and free from cracks, burn holes, undercuts or incomplete fusion. All scale and flux shall be removed from the finish weld area.

3.7.3 Fastening devices. Holes punched or drilled shall be free of burrs. Threaded fasteners shall not be broken, cracked or stripped and shall be drawn tight. Rivets, when used, shall fill the hole completely and the heads shall be in full contact with the surface of the member.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:35Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.2.1 Component and material inspection. The contractor shall insure that all components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards unless excluded, amended, modified, or qualified in this inspection or applicable purchase document.

4.2.2 End item inspection. The inspection lot shall consist of all dispensers offered for inspection at one time. The sample unit for this inspection shall be one completely assembled dispenser.

4.2.2.1 Visual examination. Examination shall be made of the end item for the defects listed in table I. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Standard product	Item not in accordance with manufacturers standard commercial product except for changes necessary to comply with specification requirements	X	
Finish	Not in accordance with NSF	X	
	Edges and surfaces not smooth	X	
	Not free of discoloration or stains		X
	Stainless steel not 2B or better finish	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:35Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Construction and workmanship (general)	Component missing	X	
	Any wearing part not accessible for adjustment or replacement	X	
	Any component fractured or malformed	X	
	Any component misplaced or not in alignment	X	
	Any burr, sliver, sharp edge, rough die, tool, gouge, trim, or grind marks	X	
	Any component fractured, buckled, bent, dented, punctured, or malformed	X	
	Functioning component that is inoperative or will not operate as intended	X	
	Functioning component that required abnormal force to operate	X	
	Any adjustable assembly not properly adjusted to perform the intended function	X	
	Not fabricated of material specified	X	
	Water supply connection not accessible from outside of cabinet	X	
	Base not protected to prevent damage to mounting surface	X	
	Drip tray and grill not provided	X	
	Capped mounting holes missing	X	
	Attachment plug or cable not as specified	X	
	Electric switches not as specified	X	
	Cabinet not corrosion-resisting material	X	
	Dispensing directions not accessible from dispensing position	X	
Welding and brazing (when applicable)	Missing	X	
	Not continuous, not smooth, not uniform, burn holes, cracks, fissures, incomplete fusion	X	
	Not finished to blend to adjust surface	X	
	Not free from flux, scale, paint, or foreign material	X	
Threaded fasteners	Missing, stripped or cross-threaded, fractured	X	
	Loose	X	
Rivets	Loose, not in full contact with members riveted	X	
Marking	Missing, not permanent, not legible, marking not as specified		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:35Z
Check the source to verify that this is the current version before use.

4.2.2.2 Dimensional and capacity examination. Examination shall be made of the dispenser to determine compliance with specified dimensions and net weight. Any deviation from specified requirements shall constitute a defect. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of defects per hundred units.

4.2.2.3 End item testing. One production item, selected at random from the initial lot, shall be tested in accordance with 4.4.1. Any nonconformance shall be cause for rejection of the dispenser. The contractor shall perform tests on production units in accordance with 4.4.2 and when required 4.4.3 using an inspection level S-2 and an AQL of 2.5 expressed in terms of defects per hundred units.

4.2.3 Packaging inspection. An examination shall be made to determine that the preservation-packaging, packing and marking as required by section 5 are complied with. Defects shall be as indicated in table II. The sample unit shall be one shipping container fully prepared for delivery, except it need not be closed. The lot shall be the number of shipping containers offered for inspection at one time. The inspection level shall be S-4 with an AQL of 6.5 expressed in terms of defects per hundred units.

TABLE II. Inspection of packaging

Examine	Defect
Markings	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any components missing, damaged, or not as specified
Workmanship	Bulged or distorted container. Contents not adequately cushioned or immobilized.

4.2.3.1 Inspection of shipping containers. When shipping containers are required to be in accordance with PPP-B-636, examination for defects in closure, waterproofing, and strapping shall be in accordance with PPP-B-636.

4.2.3.2 Inspection of palletization. An examination shall be made to determine that palletization is in compliance with section 5. Defects shall be as specified in table III. The sample unit for this examination shall be one palletized unit load ready for shipment. The lot shall be the number of palletized unit loads submitted for inspection at one time. The inspection level shall be S-1 with an AQL of 6.5 expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:35Z
Check the source to verify that this is the current version before use.

TABLE III. Inspection of palletization

Examine	Defect
Finished dimension	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded with required straps specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence or method of application

4.3 Certificate examination. Certificates of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of compliance with the specification requirements shall be examined and validated.

4.4 Tests. Prior to performance of the tests specified herein, the dispensers to be tested shall be operated for a period of time recommended by the manufacturer for run-in and adjustment of the units.

4.4.1 Operational. Connect the dispenser to a water supply in 70 ± 5°F (21 ± 3°C) ambient temperature and to a source of power having the same electrical characteristics as specified in 3.4.1. All controls and electrical components shall operate to insure that they function as specified in 3.4.4. During this test check for leaks at the fitting connections and when water tank is provided where plumbing enters the water tank to determine conformance with the water tightness requirements of 3.4. Any nonconformance with specified requirements shall constitute failure of this test.

4.4.2 Performance test. The dispenser shall be adjusted for the product throw specified in MIL-T-3527, type I (1.30 grams per 8 fluid ounces (235 ml) of water) or MIL-B-35023, type II, style 2 (24 grams per 8 fluid ounces (235 ml) of water). With the dispenser filled with type I tea of MIL-T-3527 or type II, style 2 tea of MIL-B-35023, ten 8-ounce (235 ml) cups shall be drawn at 25 second intervals. The dispenser shall be observed 6 seconds or less dispensing of an 8-ounce (235 ml) drink, dispensing nozzle dripping, plumbing leaks, water overrun for mixing chamber cleansing, and parts failure requirements of 3.4. The above tests shall be performed at water supply pressures

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:35Z
Check the source to verify that this is the current version before use.

of 30 psi and 120 psi (207 and 828 Pa) to check for conformance with 3.4.2. The time required to dispense an 8-ounce (235 ml) drink shall be determined, and 10 dry product throws shall be taken from the dispenser, the duration of each throw to be the time required for an 8-ounce (235 ml) draw of drink. Each product throw shall be weighed, and the average product throw weight shall be in accordance with the accuracy limit specified in 3.4. Inability of the dispenser to function in accordance with the requirements of 3.4 and 3.4.2 shall constitute failure of this test.

4.4.3 Inclined. The dispenser water storage tank shall be filled to 75 percent capacity with water. While in a fixed position, tilt the dispenser 15 degrees from vertical forward, backwards and sidewards and observe for spillage. Any nonconformance with specified requirements shall constitute failure of this test.

5. PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly. The extent of disassembly shall be determined by the manufacturer. This determination shall be based on the need for protection of parts susceptible to damage during transit or storage and for the reduction of cubage. Disassembly shall not be such that special skills or special tools are required to place the dispenser in operation.

5.1.1.2 Packaging. Each complete tea dispenser shall be packaged in a snug-fitting fiberboard box conforming to style RSC, type CF, variety SW, or type SF, class domestic of PPP-B-636. Cushioning shall be used as necessary to prevent movement or damage while in transit. Each box shall be closed with 2-inch (50.8 mm) minimum width gummed or pressure-sensitive paper tape.

5.1.2 Level C. The iced tea dispensers shall be packaged to afford adequate protection against damage during shipment from the supply source to the first receiving activity. The package and quantity per package shall be the same as that normally used by the contractor for retail distribution.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A packing. Each iced tea dispenser including disassemblied components, preserved-packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type SF, grade V2s of PPP-B-636. Fiberboard inserts, fabricated from weather-resistant grade fiberboard, shall be used to immobilize the contents and prevent damage while in transit. Each fiberboard shipping container shall be closed in accordance with method III, waterproofed in accordance with method V and reinforced as specified in the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:35Z
Check the source to verify that this is the current version before use.

5.2.2 Level B packing. Each iced tea dispenser including disassembled components, preserved-packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, variety SW, or type SF, class domestic, grade 200 of PPP-B-636. Fiberboard inserts shall be used to immobilize the contents and prevent damage while in transit. Closure shall be in accordance with method II as specified in the appendix of PPP-B-636.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be V3c, V3s, or V4s, fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III, as specified in the appendix of the box specification.

5.2.3 Level C packing. The iced tea dispensers, preserved-packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the contractor for retail distribution. Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Palletization. When specified (see 6.2), dispensers packed as specified shall be palletized in accordance with load type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L. Pallet patterns shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the pallet patterns specified in MIL-STD-147, the pallet pattern used shall first be approved by the contracting officer.

5.4 Marking. In addition to any special marking required by the contract or order, interior packages, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Dispensers are intended for use in feeding areas to dispense tea for use with ice as a cold drink.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Water filter specifications, when required (see 3.4 and 6.4).
(c) Electrical system operation, if other than specified (see 3.4.1).
(d) When 50 hertz operation is required and an ANSI electrical plug is required (see 3.4.1).
(e) When unit is required for Naval shipboard use (see 3.4.3 and 3.4.5).
(f) Selection of the applicable levels of packing and packaging (see 5.1 and 5.2).
(g) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
(h) When palletization is required (see 5.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:35Z
Check the source to verify that this is the current version before use.

6.3 Contract data requirements. Any requirements for equipment manuals for the item covered by this specification should be included in DD Form 1423 Contract Data Requirements List and cited in the contract.

6.4 Iced tea dispenser water. Iced tea dispensers require good quality water; free of undesirable impurities, tastes, or odors. If there is a water problem, professional advice should be solicited prior to procurement in order to determine a remedy by filtration or treatment.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3).

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

6.7 Metric equivalents. Metric equivalents, indicated in parentheses throughout this document, are based on practices, conversion factors, and symbols specified in ASTM E 380 Standard for Metric Practice, and are for information only. In each instance, the value stated in US customary units shall be controlling.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Preparing activity:

Army - GL

Project No. 7310-0457

Review activities:

Army - MD
Navy - SH
DLA - GS

User activities:

Army - CE
Navy - SA

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-D-43845A DISPENSER, ICED TEA

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:35Z
Check the source to verify that this is the current version before use.

FOLD

U.S. Army Natick R & D Command
Natick, Massachusetts 07160

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



U.S. Army Natick Reserach and Development Command
ATTN: DRXNM-TD
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:35Z
Check the source to verify that this is the current version before use.