MILITARY SPECIFICATION

KITCHEN EQUIPMENT, INCLUDING UNIT ASSEMBLIES,

REPAIR PARTS AND TOOLS, PREPARATION FOR

DELIVERY OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the preservation, packaging, packing and marking for shipment of kitchen equipment and related items.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

TT-P-664	-	Primer Coating, Synthetic, Rust-Inhibiting, Lacquer-Resisting.
PPP-B-591	-	Boxes, Fiberboard Wood-Cleated.
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-B-640	-	Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-B-1055	-	Barrier Material, Waterproofed, Flexible.
PPP-C-650	-	Crates, Wood, Open and Covered.
PPP-C-843	-	Cushioning, Material, Cellulosic.
PPP-F-320	-	Fiberboard; Sheet, Stock and Cut Shapes.
PPP-P-40	-	Packaging and Packing of Hand Tools.
PPP-P-291	-	Paperboard, Wrapping, Cushioning.
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, for Sealing Securing.
PPP-T-60	-	Tape; Pressure Sensitive Adhesive, Waterproof - for Packaging and Sealing.

Source: https://assist.dla.mil -- Downloaded: 202640-21T22:43Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-V-3	-	Valves, Fittings, and Flanges (Except for Systems Indicated Herein); Packaging of.
MIL-C-104	-	Crates, Wood; Lumber and Plywood Sheathed, Nailed and Bolted.
MIL-P-116	-	Preservation, Methods of.
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-B-197	-	Bearing, Antifriction, Associated Part and Sub-Assemblies, Packaging of.
MIL-V-1174	-	Varnish, Spar, Water-Resisting (Formula No. 80).
MIL-R-3593	-	Refrigeration and Cooling Equipment (Excluding Household Refrigerators), Packaging of.
MIL-C-3774	-	Crates, Wood; Open 12,000 and 16,000 Pound Capacity.
MIL-E-10062	-	Engine, Preparation for Shipment and Storage of.
MIL-C-10872	-	Cap, Flute, 4-inch, Cylindrical.
MIL-A-10957	-	Adapter Kit, Gravity Feed, Military Gasoline Can.
MIL-V-13811	-	Varnish, Waterproofing, Electrical, Ignition.
MIL-P-16298	-	Preservation, Packaging, Packing, and Marking of Electric Machines Having Rotating Parts and Associated Repair Parts.
MIL-E-17555	-	Electronic and Electrical Equipment, Accessories, and Repair Parts, Packaging and Packing of.
MIL-T-22085	-	Tape, Pressure-Sensitive Adhesive, Preservation and Sealing.
MIL-T-50036	-	Talc, Technical, Tl.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.

(Copies of specification and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:43Z
Check the source to verify that this is the currentversion before use.

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distribued among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Disassembly. The extent of disassembly shall be determined by the manufacturer. This determination shall be based on the need for protection of parts susceptible to damage during transit or storage and for the reduction in cubage. Attaching hardware shall be replaced on one of the mating parts or placed in a cloth drawstring bag and the bag attached to one of the mating parts. Parts removed shall be adequately identified or tagged. Where disassembly affects the operation of the equipment, warning tags or labels indicating the disassembly shall be attached. Instructions for assembly shall be included either as a part of the warning tag, or label, or as a separate sheet or folder attached to the equipment. Disassembly shall not be such that special skills or special tools, other than those furnished, or both, are required to place the equipment in operation.

3.2 Draining. All water or fuel containing parts, such as water cooling systems, tanks, burners, and hoses, shall be completely drained and thoroughly dried.

3.3 Cleaning. All exposed, unpainted ferrous surfaces of end item including accessories, detached parts, attachments, replacement parts, tools and including CRES shall be cleaned process C-1, and thoroughly dried in accordance with MIL-P-116.

3.4 Repainting and recoating. Painted and permanently coated surfaces from which the paint and permanent coating have been removed or on which the finish is defective shall be repainted and recoated with material identical to the original.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:43Z
Check the source to verify that this is the currentversion before use.

3.5 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.2).

3.5.1 Level A.

3.5.1.1 Lubrication. All bearings and fittings requiring lubrication shall be lubricated to capacity with the manufacturer's recommended lubricant containing a rust inhibitor.

3.5.1.2 Threaded connections. Openings shall be covered with tape conforming to type III, class 1 of PPP-T-60 or threaded metal or plastic caps or plugs.

3.5.1.3 Flange connections. Openings shall be covered with bolted blank flanges using barrier material conforming to grade A of MIL-B-121 between the flange face and the protective cover.

3.5.1.4 Sealing. Lamps, electric cable connections, receptacles, switches, terminals, openings into motors, instruction and identification plates, control boxes, gages, meters, locks, key openings, and crevices formed by covers or lids shall be completely sealed with tape conforming to MIL-T-22085. Remaining openings into the units shall also be sealed with the same type tape as specified herein. All taped parts including covered cables shall be coated with varnish conforming to MIL-V-13811.

3.5.1.5 Exposed wiring. Exposed wiring shall be coated with varnish conforming to MIL-V-13811.

3.5.1.6 General preservation. All cleaned contacting and non-contacting surfaces, except food contacting surfaces shall be coated with type P-2 or P-6 preservatives of MIL-P-116. Contacting surfaces are surfaces that contact other surfaces during operation. Non-contacting surfaces are surfaces that do not contact other surfaces during operation. All cleaned uncoated metal surfaces which will be in contact with food ingredients shall be coated with type P-14 preservative of MIL-P-116.

3.5.1.7 Protection of preservatives. Coated surfaces from which a preservative might be removed by contact with packaging and packing material shall be covered, wrapped or bagged with barrier material conforming to type I or II, as applicable, grade A of MIL-B-121. Barrier material shall be secured with twine made of jute, sisal, manila or cotton or tape conforming to type III, grade A, B, or C, as applicable of PPP-T-45 or PPP-T-60 or heat sealed when heat sealable barrier material is used.

3.5.1.8 Preservation of specified components.

3.5.1.8.1 Steam and water systems. Steam and water systems shall be flushed with type P-3 preservative of MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:43Z
Check the source to verify that this is the currentversion before use.

3.5.1.8.2 Combustion chambers and heating pipes and elbows. Interior of combustion chambers and interiors and exteriors of heating pipes and elbows shall be coated with type P-7 preservative of MIL-P-116.

3.5.1.8.3 Roller chains and critical surfaces. Exterior surfaces of roller chains and critical operating surfaces and highly finished surfaces shall be coated with type P-9 preservative of MIL-P-116.

3.5.1.8.4 Pulleys and shafts. Exposed, uncoated ferrous surfaces of pulleys and shafts shall be coated with primer conforming to TT-P-664, and thoroughly dried.

3.5.1.8.5 Belts. Drive belts shall be removed and metal lacing of belts shall be coated wtih varnish conforming to MIL-V-13811. Belts fabricated of fabric or plastic shall be dusted with talc conforming to MIL-T-50036. The belts shall then be replaced and tension relieved.

3.5.1.8.6 Nameplates and instruction plates. Nameplates and instruction plates shall be coated with varnish conforming to MIL-V-1174.

3.5.1.8.7 Thermometers. Thermometers shall be preserved method III of MIL-P-116.

3.5.1.9 Preparation and packaging of specified components.

3.5.1.9.1 Gages (removed). Removed gages shall be preserved and packaged in accordance with method 1A-8 or 1A-13 of MIL-P-116.

3.5.1.9.2 Gages (not removed). Dial glass shall be covered with fitted fiberboard or plywood and then overwrapped with barrier material conforming to type 1, grade C, class I of MIL-B-121. Overwrap shall be secured with tape conforming to type 1 of MIL-T-22085.

3.5.1.9.3 Flue caps. Flue caps shall be preserved and packaged in accordance with level A requirements of MIL-C-10872.

3.5.1.9.4 Casters. Wheel bearings shall be lubricated with manufacturer's recommended lubricant containing a rust inhibitor. Exposed, uncoated ferrous surfaces shall be cleaned process C-1 and shall be coated with type P-6 preservative of MIL-P-116. The caster shall then be wrapped individually in waterproof kraft paper or greaseproofed and waterproofed barrier material and the wrap shall be secured with tape, cord or twine in a manner to prevent entry of water, or the caster shall be placed with other hardware in a fiberboard box conforming to PPP-B-636, class domestic and the box shall be wrapped with waterproof barrier material and sealed with water-resistant adhesive.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:43Z
Check the source to verify that this is the currentversion before use.

3.5.1.9.5 Miscellaneous items and accessories. Miscellaneous items and accessories shall be preserved and packaged in accordance with the applicable requirements of the following specifications:

Motors, Electric (Removed)	MIL-E-16298
Controllers (For Electric Motor) and Repair Parts	MIL-E-17555
Valves and Fittings and Flanges (Removed)	MIL-V-3
Hand Tools	PPP-P-40
Refrigeration and Cooling Equipment	MIL-R-3593
Bearings (Repair Parts)	MIL-B-197
Gasoline Engines	Type II, MIL-E-10062

3.5.1.10 Packaging of specified components.

3.5.1.10.1 Thermometers, tee assemblies, water control valves, pipe elbows individually wrapped.

Thermometers shall be wrapped in cushioning conforming to type II, class B of PPP-C-843. Wrapped thermometers, tee assemblies, water control valves, and the disassembled pipe elbows shall be individually wrapped in cushioning paperboard conforming to type III, style 2 of PPP-P-291, and the wrap secured with tape, cord, or twine. The wrapped components, shall be secured within the cabinet, or placed in a fiberboard box conforming to style RSC, type CF or SF, class domestic of PPP-B-636. When specified (see 6.2) the box shall be V3c, V3s, or V4s, fabricated and closed in accordance with PPP-B-636.

3.5.1.10.2 Technical literature. Technical literature shall be packaged in accordance with Method 1C-1 of MIL-P-116, and secured to the parent unit.

3.5.1.10.3 Adapter kits (for gasoline cans and drums). Adapter kits shall be packaged in accordance with level A requirements of MIL-A-10957.

3.5.1.10.4 Disassembled components, tools, and accessories. Disassembled components, tools, and accessories shall be packaged in a fiberboard or nailed wood box conforming to style optional, type CF or SF class domestic of PPP-B-636, or class 1, style 2 or 4 of PPP-B-621, respectively. The weight of contents shall not exceed the weight limitations of the applicable box specification. Unless otherwise specified, contents shall be cushioned, blocked, or braced within the box to prevent movement while in transit. Additional protection for items having cutting edges and fragile sections shall be provided by means of die cuts, separation pads, or cushioning media. When specified (see 6.2) the fiberboard box shall be V3c, V3s, or V4s, fabricated and closed in accordance with PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:43Z
Check the source to verify that this is the current version before use.

3.5.1.11 Securing. Parts of the equipment that are free to move shall be secured in a fixed position to prevent movement or vibration while in transit.

3.5.2 Level C. Kitchen equipment, units, assemblies, repair parts and tools shall be preserved and packaged to afford adequate protection against corrosion, deterioration, and damage during shipment from supply source to first receiving activity. The package and the quantity per package shall be the same as that normally used by the supplier for retail distribution.

3.6 Packing. Packing shall be level A, B, or C as specified (see 6.2).

3.6.1 Level A.

3.6.1.1 Kitchen equipment not exceeding 65 pounds. Kitchen equipment, units, and assemblies not exceeding 65 pounds, preserved and packaged as specified in 3.5, shall be packed in a snug-fitting weather-resistant fiberboard shipping container conforming to style optional, V2s of PPP-B-636. Fiberboard pads, liners, or forms conforming to type weather resistant of PPP-F-320 shall be used, as required, to prevent damage of the contents during transit. Each shipping container shall be closed, waterproofed and reinforced with steel strapping or tape banding in accordance with PPP-B-636. Kitchen equipment, units, and assemblies weighing 40 pounds or less, preserved and packaged as specified in 3.5, shall be packed in containers conforming to style optional, V3s of PPP-B-636. Cushioning of contents, closure, waterproofing, and reinforcing of shipping containers shall be as specified herein. Alternatively the shipping container shall conform to overseas type of PPP-B-601. Closure and strapping shall be in accordance with PPP-B-601.

3.6.1.2 Kitchen equipment not exceeding 800 pounds, except as specified in 3.6.1.4. Kitchen equipment, units, and assemblies not exceeding 800 pounds, preserved and packaged as specified in 3.5, shall be packed in wood-cleated plywood or nailed wood shipping containers conforming to overseas type of PPP-B-601 or class 2, style 2 or 4, type 3 load of PPP-B-621, respectively. Alternatively, a shipping container as specified in 3.6.1.3 may be used at the option of the contractor for equipment, units, and assemblies weighing from 500 to 800 pounds. Contents shall be secured as specified in 3.6.1.5. The top, sides, and ends of the nailed wood shipping container conforming to style 7 of PPP-B-621 shall be lined with waterproof barrier material conforming to PPP-B-1055, with all joints having a 4-inch minimum single lap. The contents of each shipping container conforming to style 2 or 4 of PPP-B-621 shall be waterproofed in accordance with appendix of PPP-C-650. Each shipping container shall be closed and strapped in accordance with the appendix of the applicable container specification.

3.6.1.3 Kitchen equipment exceeding 800 pounds, except as specified in 3.6.1.4. Kitchen equipment, units, and assemblies exceeding 800 pounds, preserved and packaged as specified in 3.5, shall be packed in a sheathed, nailed wood crate conforming to type I, class 1 or 2, style a of MIL-C-104. Contents shall be secured as specified in 3.6.1.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:43Z
Check the source to verify that this is the current version before use.

3.6.1.4 Tables, racks, and cabinets. Equipment, such as tables, racks and cabinets which do not contain any electrical components or operating mechanical components or mechanisms preserved and packaged as specified above may be packed at the option of the contractor in an open wood crate conforming to style A of PPP-C-650. Each crate shall be closed, strapped and waterproofed in accordance with the appendix of PPP-C-650. Contents shall be cushioned, anchored, braced and blocked in accordance with PPP-C-650.

3.6.1.5 Securing. Equipment provided with bolt holes for anchoring shall be secured to the base of the shipping container by bolting through the skids. When bolt holes and the skids are not in alignment, additional skids, longitudinal sleepers, or interior load bearing members shall be provided. The minimum size of the sleepers, or interior load bearing members shall be nominal 2- by 4- inch lumber 2 feet long. Blocking and bracing shall be provided as required to prevent sway of topheavy items. When bolt holes in the equipment being packed are not available, the equipment shall be blocked and braced in a manner to prevent movement and damage while in transit. Equipment having nondetachable casters or wheels shall be blocked in such a manner as to have a minimum clearance of 1 inch between the interior base or end of the container and the casters or wheels. A clearance of not less than 1 inch shall be provided between the items and the closest member of the sides, ends, and top of the shipping containers. Cushioning and padding shall be used where necessary to prevent damage between the lumber blocking and unprotected finished surfaces. Wood blocks and braces shall be securely nailed to floorboards, headers, or other frame members when present. The blocking and bracing shall not depend on end-grain nailing alone but supplemental supporting cleats shall be provided to reinforce and prevent splitting of the blocking and bracing.

3.6.1.6 Stowage of boxed components. Boxes containing items to be shipped with a unit or assembly shall be securely fastened in an unused portion within the shipping container of that unit or assembly.

3.6.2 Level B.

3.6.2.1 Kitchen equipment not exceeding 65 pounds. Kitchen equipment, units, and assemblies not exceeding 65 pounds, preserved and packaged as specified in 3.5, shall be packed, unless otherwise specified, in a snug-fitting fiberboard shipping container conforming to style optional, type CF or SF, class domestic of PPP-B-636. Fiberboard pads, liners, or forms conforming to PPP-F-320 shall be used, as required, to prevent movement or damage of the contents during transit. When specified (see 6.2) fiberboard shipping containers conforming to style optional, V3c, V3s, or V4s of PPP-B-636 shall be used. Each shipping container shall be closed in accordance with the appendix of PPP-B-636.

3.6.2.2 Kitchen equipment not exceeding 200 pounds. Kitchen equipment, units, and assemblies not exceeding 200 pounds, preserved and packaged as specified in 3.5, shall be packed in a snug-fitting container conforming to class 2, style C of PPP-B-640. The contents shall be immobilized by suitable means to prevent movement or damage while in transit. Closure and reinforcement shall be in accordance with appendix of PPP-B-640.

Source: https://assist.dla.mil -- Downloaded: 20260-21T22:43Z
Check the source to verify that this is the current version before use.

3.6.2.3 Kitchen equipment not exceeding 400 pounds. Kitchen equipment, units, and assemblies not exceeding 400 pounds, preserved and packaged as specified in 3.5, shall be packed in a snug-fitting wood-cleated, fiberboard shipping container conforming to class I, style A or B of PPP-B-591. The contents shall be secured as specified in 3.6.1.5.

3.6.2.4 Kitchen equipment not exceeding 800 pounds. Kitchen equipment, units, and assemblies not exceeding 800 lbs., preserved and packaged as specified in 3.5, shall be packed in shipping containers conforming to domestic type, style A or B of PPP-B-601 or class 1, style 2 or 4 of PPP-B-621. The contents shall be secured as specified in 3.6.1.5.

3.6.2.5 Kitchen equipment not exceeding 4,000 pounds. Kitchen equipment, units, and assemblies not exceeding 4,000 pounds, preserved and packaged as specified in 3.5, shall be packed in a wood crate conforming to style A, of PPP-C-650. Contents shall be secured as specified in 3.6.1.5.

3.6.2.6 Kitchen equipment weighing from 4,000 to 12,000 pounds. Kitchen equipment, units, and assemblies weighing from 4,000 to 12,000 pounds, preserved and packaged as specified in 3.5, shall be packed in a wood crate conforming to type I, style A of MIL-C-3774. Contents shall be secured as specified in 3.6.1.5.

3.6.2.7 Kitchen equipment exceeding 12,000 pounds. Kitchen equipment, units, and assemblies exceeding 12,000 pounds, preserved and packaged as specified in 3.5, shall be packed in a sheathed, nailed wood crate conforming to type I, class 1 or 2, style a of MIL-C-104, except that waterproof barrier material shall not be required. Contents shall be secured as specified in 3.6.1.5.

3.6.2.8 Stowage of boxed components. Stowage of boxed components shall be as specified in 3.6.1.6.

3.6.3 Level C. Kitchen equipment, units, and assemblies, preserved and packaged as specified in 3.5, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quality per shipping container shall be the same as that normally used by the supplier for retail distribution. Containers shall comply with U.S. Postal Service, Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

3.7 Marking. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129. Set marking requirements shall apply when accessories and parts are packed separate from the unit.

3.7.1 Precautionary marking. Special handling marking requirements in MIL-STD-129 applicable to fragile items, arrows, the words "UP", "THIS SIDE UP" AND "CENTER OF BALANCE" shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:43Z
Check the source to verify that this is the current version before use.

3.8 Workmanship. Preservation, packaging, packing, and marking shall conform to the quality and grade of product established by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.2.1 Component and material inspection. In accordance with 4.1 above, the supplier is responsible for insuring that components and materials used are manufactured, tested and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified, or, if none, in accordance with this specification.

4.3 Inspection of the end item.

4.3.1 Examination of end item for preparation for delivery of. The end item shall be examined for preservation, packaging, packing, and marking in accordance with the defects set forth in tables I through IV. The sample unit for these examinations shall be one disassembled, packaged or packed item of Kitchen Equipment, as applicable, of the specified type, design, size and characteristic. The lot size shall be expressed in terms of the applicable sample unit. The inspection level for each examination shall be S-1 and the acceptable quality level (AQLs), expressed in defects per 100 units, shall be 6.5.

TABLE I. Visual examination of preservation for packaging

Examine	Defects
Disassembly (as applicable)	Detached parts or hardware not placed with mating parts as specified (see 3.1)
Matchmarking	Removed parts not identified or tagged Warning tags or labels indicating the disassembly not attached or missing Instructions for reassembly missing

Source: https://assist.dla.mil -- Downloaded: 20260-21T22:43Z
Check the source to verify that this is the current version before use.

TABLE I. Visual examination of preservation for packaging (cont'd)

Examine	Defect
Draining (as applicable)	All water or fuel not removed from fuel or water containing parts or systems
Repainting and recoating	Not repainted or recoated as needed (see 3.4)

TABLE II. Examination of preparation and packaging

Examine	Defect
Lubrication (where applicable)	Not lubricated to capacity
Threaded connections and Flange connections	Openings not covered properly
Sealing of units	Openings or crevices not sealed with tape and tape coated with varnish as specified (see 3.5.1.4)
Steam and Water Systems	Not preserved as specified
Cumbustion chambers and heating pipe and elbows	Not preserved as specified
Roller chains and critical surfaces	Not preserved as specified
Pulleys and shafts	Not preserved as specified
Drive belts	Not preserved as specified Drive belts not replaced with tension relaxed
Name plates and instruction plates	Not preserved as specified
Thermometers	Not preserved as specified
Gages (removed)	Not preserved and packaged as specified

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:43Z
Check the source to verify that this is the current version before use.

TABLE II. Examination of preparation and packaging (cont'd)

Examine	Defect
Gages (not removed)	Dial glass not covered as specified (see 3.5.1.9.2) Overwrap not secured with tape as specified
Casters	Not preserved and packaged as specified (see 3.5.1.9.4)
Thermometers, tee assembly, water control valves, pipe elbow individually wrapped	Items not wrapped and secured as specified (see 3.5.1.10.1)
Technical Literature	Missing or not secured to parent item
Disassembled components, tools and accessories	Not cushioned and securely immobilized within the box as specified (see 3.5.1.10.4)

TABLE III Examination of packing

Examine	Defect
Container	Not as specified for weight limits of equipment being packed (see 3.6.1.1 through 3.6.2.7 as applicable) Less than 1 inch clearance between item and closest member of sides, ends and top, when required
Skids or handling means (when required)	Missing Strips not bolted to base of appliance Strips not secured to bottom of container Strips do not protect the unit or container from fork lift damage Marking not as required for boxes with internal handling means
Kitchen equipment, units and assemblies	Not securely immobilized by bolting and blocking and bracing as specified Longitudinal sleepers or load bearing members missing when required

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:43Z
Check the source to verify that this is the current version before use.

TABLE III. Examination of packing (cont'd)

Examine	Defect
Kitchen equipment, units and assemblies (cont'd)	Any wood member less than size specified Bolting not positioned through the skids as specified Nailing application of blocking and bracing not as specified
Boxed components	Not secured within shipping container, when applicable

TABLE IV. Examination of the end item for marking

Examine	Defect
Marking interior packages and shipping container (as applicable)	Omitted, incorrect, illegible, or of improper size, location, sequence or method of application Set markings missing, when applicable Precautionary markings missing, or not as specified (see 3.7.1)

4.3.2 Examination of shipping containers. When shipping containers are required to be in accordance with PPP-B-591, PPP-B-601, PPP-B-621, PPP-B-636, PPP-B-640, PPP-C-650, MIL-C-104, or MIL-C-3774, examination for defects in closure, strapping, and waterproofing, when applicable, shall be in accordance with the applicable specification.

5. PREPARATION FOR DELIVERY

Not applicable.

6. NOTES

6.1 Intended use. The preservation, packaging, packing and marking of kitchen equipment and related items.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Selection of applicable levels of preservation and packaging and packing (see 3.5 and 3.6).
(c) When specific weather-resistant grade fiberboard shipping containers are required (see 3.5.1.10.1, 3.5.1.10.4, and 3.6.2.1).

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:43Z
Check the source to verify that this is the currentversion before use.

Custodians:

Army - GL
Navy - YD
Air Force - 84

Review activity:

Army - SM

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 7320-0559

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:43Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE Kitchen Equipment, Including Unit Assemblies, Repair Parts and Tools, Preparation for Delivery of MIL-K-4387

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-01-21T22:43Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK LABORATORIES
NATICK, MA 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

. STSNLT-EQS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



Commander
US Army Natick Laboratories
ATTN: STSNLT-EQS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:43Z
Check the source to verify that this is the current version before use.