MIL-S-43852B
21 December 1984
SUPERSEDING
MIL-S-43852A
12 September 1977

MILITARY SPECIFICATION

SANDWICH UNIT, MECHANICALLY REFRIGERATED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers mechanically refrigerated sandwich units.

1.2 Classification. Refrigerated sandwich units shall be of the following sizes and styles as specified (see 6.2).

Size 1	- 6 cubic foot
Size 2	- 9 cubic foot
Size 3	- 12 cubic foot
Style A	- with four swivel casters
Style B	- with adjustable legs

2. APPLICABLE DOCUMENTS

2.1 Government documents. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760-5014, by using the self-addressed standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7310

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:36Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

BB-F-1421	-	Fluorocarbon Refrigerants
FF-C-77	-	Casters, Rigid and Swivel (Institutional Duty)

MILITARY

MIL-R-3593	-	Refrigeration and Cooling Equipment (Excluding Household Refrigerators), Packaging of
MIL-P-43940	-	Pan, Food Serving, Rectangular and Insets, Round

STANDARDS

FEDERAL

FED-STD-H28	-	Screw Thread Standard for Federal Services
FED-STD-601	-	Rubber, Sampling and Testing

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-461	-	Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference
MIL-STD-462	-	Electromagnetic Interference Characteristics, Measurement of

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

UNDERWRITERS LABORATORIES INC.

Ul 62 - Flexible Cord and Fixture Wire
UL 471 - Commercial Refrigerators and Freezers

(Application for copies should be addressed to the Underwriters Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.)

NATIONAL SANITATION FOUNDATION (NSF)

Standard No. 2 - Food Service Equipment

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:36Z
Check the source to verify that this is the currentversion before use.

Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, NSF Building, Ann Arbor, MI 48105.)

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

WD - 1 General Purpose Wiring Devices

(Application for copies should be addressed to the National Electrical Manufacturers Association, 155 East 44th Street, New York, NY 10017.)

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

No. C73 - Dimensions of Attachment Plugs and Receptacles

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, NY 10018.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet and Strip
A 269 - Seamless and Welded Austenitic Stainless Steel Tubing for General Service
D 1692 - Flammability of Plastic Sheeting and Cellular Plastics

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Standard product. The refrigerated sandwich units shall be the manufacturer's commercial product, except for any changes necessary to comply with document requirements. All like items furnished on any one contract, including parts and sub-assemblies thereof, shall be new and interchangeable.

3.2 Codes and standards. The refrigerated sandwich units shall comply with the applicable requirements of UL 471 and NSF Standard No. 2.

3.2.1 Compliance. Prior to commencing production, the contractor shall submit satisfactory evidence to the contracting officer or his authorized

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:36Z
Check the source to verify that this is the current version before use.

representative that the refrigerated sandwich units he proposes to furnish under this document meet the applicable requirements of UL 471 and NSF Standard No. 2 as follows:

3.2.1.1 UL. Acceptable evidence of meeting the requirements of UL shall be the a UL listing mark, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the refrigerated sandwich units have been tested and conform' to UL 471.

3.2.1.2 NSF. Acceptable evidence of meeting the requirements of NSF shall be:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seal on the finished refrigerated sandwich unit or

(2) A certification for the refrigerated sandwich unit issued by NSF under their special one-time contract evaluation/certification service, or

(3) A test report, acceptable to the Contracting Officer with the advice of the Army Surgeon General from an independent testing laboratory, indicating that the sandwich unit has been tested and conforms to NSF.

3.3 Materials (see 6.4) and components. Materials and components shall be as specified herein. Materials and components not definitely specified shall be of the quality normally used by the manufacturer in his standard commercial refrigerated sandwich unit provided the completed item complies with all provisions of this document.

3.3.1 Stainless steel.

3.3.1.1 Sheet and strip. Stainless steel sheet and strip shall conform to type 304 of ASTM A 167.

3.3.1.2 Stainless steel tubing. Stainless steel tubing shall conform to any 300 type specified in ASTM A 269.

3.3.2 Refrigerants. The refrigerants shall conform to type 12 or 22 of BB-F-1421.

3.3.3 Insulation. Insulation shall be homogeneous throughout; and shall have a "K" factor specified below using 75°F mean temperature expressed in terms of British thermal units per hour (Btu/hr) per square foot per inch of thickness per degree F temperature difference. Loose fill type insulation will not be acceptable. Foamed-in-place insulation shall conform to ASTM D 1692 and have a manufacturer's rated "K" factor of not more than 0.15 and a density of not less than 1.9 pounds per cubic foot when tested as specified in 4.4.2.1.

3.3.4 Fasteners. Screws, bolts, nuts and other fasteners shall be stainless steel. Threads shall conform to FED-STD-H28.

Source: https://assist.dla.mil -- Downloaded: 20261O-21T22:36Z
Check the source to verify that this is the current version before use.

3.4 Design. The refrigerated sandwich unit shall be an integral unit fabricated from 22 gauge (0.029 inch) material specified in 3.3.1.1. The refrigerated sandwich unit shall consist of a completely self-contained one or two door, air cooled, refrigeration unit with a 2 shelf storage compartment. The refrigerated section shall be capable of maintaining interior temperatures of 38°F, plus or minus 2°F, in an ambient of 100°F + -2°F when tested as specified in 4.2.5.1. Each size sandwich unit shall be designed to accommodate the food pans specified in 3.9. The top shall be provided with an 8 inch wide full length removable synthetic cutting board, and shall have a smooth top surface free from openings. Screws or fastening devices shall be mounted on the underside of the cutting board. The area over the pans shall have a full access folding cover. Hinges for the cover shall be of such design to prevent the cover from becoming detached when open or closing cover. Sizes 2 and 3 sandwich units shall contain a toaster or appliance sector with a back splash and a cut out for an appliance receptacle. A stainless steel cover shall be provided and installed over the cut out for the appliance receptacle. The style A sandwich unit shall have 4 casters conforming to type II, class C, 5 inch diameter, style C, mounting A of FF-C-77. A minimum of two casters shall be equipped with brakes. The style B sandwich unit shall be provided with adjustable legs with provisions for a minimum adjustment of 1-inch.

3.4.1 Electrical characteristics. Unless otherwise specified (see 6.2), the refrigerated sandwich units shall be designed for operation on a 120 Volts, 60 Hz, 1-phase, three wire, power supply and shall be furnished with a 6 foot supply cord conforming to UL 62 and approved grounding type plug conforming to NEMA WD-1. When 50 hertz operation is required, a UL approved, 3-wire, grounding type, power supply cordconforming to UL 62, without an attachment plug, shall be provided. When specified (see 6.2), the supply cord for 50 Hz operation shall be provided with a grounding type attachment plug conforming to NEMA WD-1

3.4.2 Electromagnetic compatibility. When specified (see 6.2), the units shall be designed to conform to the electromagnetic emission and susceptibility requirements of MIL-STD-461, class C3, group 1 equipment (see 4.2.5.2).

3.4.3 Tray rail. When specified (see 6.2), a drop type tray rail, consisting of three 1-inch nominal diameter tubes, with supporting hardware, shall be supplied with each sandwich unit on the patron's side. The tray rail shall extend the full length of the sandwich unit and shall have the ends of each tube closed. The height of the tray rail from the floor shall be adjustable between 34 and 35 inches. The tubes and supporting hardware shall be secured to the sandwich unit cabinet and shall be fabricated of stainless steel conforming to 3.3.1.1 and 3.3.1.2, as applicable.

3.4.4 Bumpers. Style A sandwich units shall be equipped with bumpers to cushion the impact of collisions and prevent damage to equipment. Bumpers shall be fabricated from non-marking rubber or rubber like materials having a

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:36Z
Check the source to verify that this is the currentversion before use.

durometer hardness of 75 + 15 on the A scale or from plastic materials normally used for this purpose. Bumpers shall be assembled to the unit and so located that no part of the unit touches a vertical wall except the bumper. Bumpers shall be capable of being removed and replaced when necessary.

3.4.5 Ventilation louvers. Unless otherwise specified (see 6.2) ventilation louvers shall be located on the attendant's side. The ventilation louvers shall be constructed of stainless steel of the same grade as the adjacent body components.

3.5 Dimensions. The refrigerated sandwich units shall have overall dimensions as listed in table I.

TABLE I. Overall dimensions (inches)

Size	Max. length	Max. width	Working height (Adjustable)	Food pans surface area (square inches)
1	36	34	35-37	360
2	50	34	35-37	480
3	60	34	35-37	720

The refrigerated storage area shall be a minimum of 6 cubic feet for the size 1, a minimum of 9 cubic feet for the size 2, and a minimum of 12 cubic feet for the size 3.

3.6 Insulation installation. All space between the inner liner and outer shell including doors, shall be completely filled with the insulation specified in 3.3.3. Prior to foaming, the inner liner and outer shell shall be treated to assure permanent bonding of the insulation to the liner material.

3.7 Doors. The doors shall have positive safety stops at 120 degrees. Hinges and pulls shall be chrome-plated. Doors may be either locking or non-locking. When locking doors are provided, two door locking units shall have a flush cylinder type lock on each door with one key opening both doors. Each door shall have a one piece, magnetic gasket. The gaskets shall be removable for cleaning. Each door opening shall have odorless, non-toxic, safety beveled, vinyl breaker strips, with no exposed screws or fastenings. Stainless steel fillet pieces shall be provided at each corner. The entire perimeter of all openings shall be provided with concealed dew point compensators.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:36Z
Check the source to verify that this is the current version before use.

3.8 Condensing unit. The condensing unit shall be capable of being removed for cleaning and repairing. The condensing unit shall be filled with the refrigerant specified in 3.3.2 and shall not leak when tested as specified in 4.2.5.3. A condensate evaporator shall be furnished for removal of condensate without the use of plumbing or floor drains.

3.9 Food pans. Sandwich units as specified in 1.2 shall be provided with pans and adapter bars listed in table II. The food pans shall conform to the requirements of MIL-P-43940. The sandwich unit opening shall be completely covered when all pans specified in table II are inserted in normal use position for either the size 1, size 2, or size 3 sandwich unit.

TABLE II. Pan sets and adapter bars

Pan and adapter bar size	Pan style 2/ and size	Quantity per sandwich unit		
		Size 1	Size 2	Size 3
One-quarter size	No. 17	8 (min)	-	-
One-quarter size	No. 14	-	4	4
One-third size	No. 11	-	3	6
Adapter bar(s)	-	1 (min)	1	2
Adapter bars 1/	minimum length 21 inches			

1/ Each adapter bar end to be flanged 1/2 inch minimum to rest on unit top.

2/ Pan style and sizes to be in accordance with MIL-P-43940.

3.10 Finish. The refrigerated sandwich unit shall have the manufacturer's standard commercial finish provided it meets NSF requirements.

3.11 Marking. Identification instructions shall be permanently and legibly marked directly on the item or on an aluminum, brass, or stainless steel plate firmly affixed to the item. Marking shall be stamped, embossed, engraved or applied by photosensitive means. The plate thickness shall be not less than 0.012 inch.

3.11.1 Identification plate. Each sandwich unit identification plate shall include the manufacturer's model and serial number, and name, trade name or trademark of such known character as to be readily identifiable. In addition, such information as required by UL 471 as applicable, shall appear on the identification plate.

3.12 Workmanship. All components and assemblies of the refrigerated sandwich units shall be free from dirt and other extraneous material, burrs, slivers, rough die, tool and grind marks, dents and cracks. Castings, molded parts and stampings, if used, shall be free of sand, fins, pits, blow holes and sprues. External surfaces shall be free from sharp edges and sharp corners.

Source: https://assist.dla.mil -- Downloaded: 20260-21T22:36Z
Check the source to verify that this is the current version before use.

3.12.1 Metal fabrication. Metal used in the fabrication of the refrigerated sandwich units shall be free from kinks. Forming and shearing shall not cause damage to the metal and shall be free from trim marks.

3.12.2 Welding. The surface of parts to be welded shall be free from rust, scale, paint, grease and other foreign matter. Welds shall be smooth and free of cracks, burn holes, undercuts or incomplete fusion. All scale and flux shall be removed from the finish weld area.

3.12.3 Fastening device. Threaded fastener and rivet holes shall be punched or drilled and shall have burrs removed. Threaded fasteners (see 3.4.4) shall not be broken, cracked or stripped and shall be drawn tight. Rivets shall fill the hole completely and the heads shall be in full contact with the surface of the member.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test items to determine the validity of the certification.

* 4.2 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

* 4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document.

Source: https://assist.dla.mil -- Downloaded: 20261O-21T22:36Z
Check the source to verify that this is the currentversion before use.

4.2.1.1 Bumper material hardness testing. The bumper material shall be tested for hardness in accordance with Method 3021 of FED-STD-601 to determine conformance with 3.4.4. The sample shall be one bumper. The lot shall consist of all bumpers offered for acceptance at one time. Failure of the sample to comply with the hardness requirement in 3.4.4 shall be cause for rejection of the lot of bumper material.

4.2.2 In-process inspection. Examination shall be made of the following operations to establish conformance with specified requirements. Whenever nonconformance is noted, correction shall be made to the items affected and to the process.

a. Insulation is installed as specified (see 3.6).
b. Welding is as specified (see 3.12.2).

4.2.2.1 In-process testing of insulation. Prior to each day's production of sandwich units, one free foam sample of the insulation referenced in 3.3.3, a volume equal to 216 cubic inches, shall be cut and weighed. This weight shall be multiplied by 8 and failure of the result to meet the density requirements of 3.3.3. shall be cause for adjustment of equipment to meet the density requirements or for rejection of the material.

In addition, a daily record of the foam insulation shall be kept as follows and the production unit shall not deviate more than plus or minus 5 percent from the data recorded on the unit used for the operation test specified in 4.2.5.1.

Calibration of mix (mix proportions)
Amount of flow (per unit)
Time of flow (per unit)
Mold temperature (per unit)

In ability of samples to conform to density requirement of 3.3.3, or more than 5 percent deviation of data gathered on the production unit and on the unit used for operation test shall constitute failure of the test.

* 4.2.3 End item visual examination. The end item shall be examined for the defects listed in table III, the lot size shall be expressed in sandwich units. The sample shall be one completely assembled sandwich unit. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:36Z
Check the source to verify that this is the current version before use.

TABLE III. End item visual defects

Examine	Defect	Classification Major	Minor
Standard product	Not the manufacturer's standard product (except for changes necessary to comply with document requirements)	X	
Finish	Manufacturer's standard commercial finish not in accordance with NSF	X	
Design, construction and workmanship (general)	Component missing or not specified type	X	
	Burrs, slivers, sharp edges	X	
	Component fractured, buckled, kinked, bent, dented, punctured,		
	Component missing	X	
	Part misplaced, loose, or not in proper alignment	X	
	Storage compartment not provided with two shelves	X	
	Top not full length of unit	X	
	Folding cover does not provide full access to area over pans	X	
	Condensing unit not removable	X	
	Pans not size and amount specified	X	
	Pans not type specified	X	
	Toaster or appliance sector not provided with backsplash	X	
	Appliance receptacle missing	X	
	Materials not as specified	X	
Style A	Casters not as specified	X	
	Caster diagonally opposite not furnished with brakes	X	
Style B	Legs not adjustable	X	
Door(s)	Not furnished with one piece magnetic gasket	X	
	Screws and fastenings exposed in door opening		X
	Corners not furnished with fillet pieces		X
	Entire perimeter not provided with concealed dew point compensator	X	
	Safety stop not as specified		X

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:36Z
Check the source to verify that this is the current version before use.

TABLE III. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Tray rail	Not as specified	X	
	Not adjustable	X	
	Not removable	X	
	Does not extend full length of sandwich unit	X	
	End of tubes not sealed	X	
Pans and adaptors	Pan set does not consist of number required	X	
	Combination of pans does not completely cover pan opening	X	
	Adaptors not full length	X	
Bumper	Not as specified, missing, not removable	X	
Cutting board	Top surface not smooth	X	
	Holes in top surface	X	
Welding	Evidence of oxide, scale, foreign matter in weld	X	
	Not continuous, sound, smooth	X	
	Porosity, cracks, undercuts, burn-through, deformation of materials	X	
Threaded fasteners	Missing, stripped, fractured, broken	X	
	Not tight		X
Rivets	Rivets not tight, not fully peened, not in full contact with joined metal surfaces	X	
Identification marking	Missing, incomplete, incorrect, not legible		X

* 4.2.4 End item dimensional examination. The end item shall be examined for conformance to specified dimensions. Any dimension not as specified shall be classified as a defect. The lot size shall be expressed in units of sandwich units. The sample unit shall be one completely assembled sandwich unit. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.2.5 End item testing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:36Z
Check the source to verify that this is the current version before use.

4.2.5.1 Operation testing. One refrigerated sandwich unit shall be selected at random from the lot and placed in a test room with the ambient temperature controlled at 100°F ± 2°F during this test. After soaking for 1 hour, the refrigerated sandwich unit shall be started and the interior temperature of the refrigerated unit shall be recorded. The refrigerated sandwich unit shall pull down to and maintain a temperature of 38°F (plus of minus 2°F) without cutout on the overload in 8 hours. Any failure to meet the requirements of 3.4 shall be cause for rejection of the lot.

4.2.5.2 Electromagnetic compatibility test. When electromagnetic compatibility is required, the initial production unit, as applicable, shall be tested by the contractor in accordance with test method CE03 and RE02 of MIL-STD-462. The Government reserves the right to witness tests performed by the contractor or an independent testing agency. The contractor shall furnish the contracting officer written certification that the Interference Control Plan, the EMI/EMC Test Plan, the Electromagnetic Test Report and the requirements meet MIL-STD-461.

4.2.5.3 Leakage testing. Each refrigerated sandwich unit shall be tested for leakage using an electronic leak detector. Any sandwich unit having a refrigerant leak greater than 0.5 ounces per year shall be rejected.

4.2.6 Packaging inspection. The inspection shall be in accordance with the quality assurance provisions of MIL-R-3593.

4.3 Certification examination. Certificates of compliance, certified test reports, or listing marks for codes and standards, as applicable, shall be submitted to the contracting officer as proof of compliance with the document.

5. PACKAGING

5.1 Preservation-packaging, packing and marking. Preservation-packaging, packing and marking for levels A, B, or C, shall be in accordance with MIL-R-3593 (see 6.2).

6. NOTES

6.1 Intended use. The refrigerated sandwich units are intended to be used in the serving line in Military messes and dining halls.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Size and style of refrigerated sandwich unit (see 1.2).
c. When electrical characteristics are other than specified (see 3.4.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:36Z
Check the source to verify that this is the current version before use.

d. When 50 hertz operation is required and an ANSI electrical plug is required (see 3.4.1).
e. When electromagnetic compatibility is required (see 3.4.2).
f. When a tray rail is required (see 3.4.3).
g. When tray rail location is on patron's side (see 3.4.3).
h. When ventilation louvers are to be located other than on attendant's side of unit (see 3.4.5).
i. Quantity of adaptor bars, pans and pan sizes when other than specified (see 3.9).
j. Selection of applicable levels of preservation-packaging, packing and marking (see 5.1).

6.3 Contract data requirement. Any data items to be delivered under any contract for items covered by this document should be specifically called for in the contract in accordance with the applicable regulations of the contracting activity.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.4).

6.5 Changes from previous issue. The margins of this document are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Preparing activity:

Army - GL

Project No. 7310-0687

Review activities:

Army - MD
Air Force - 84
DLA - GS

User activities:

Navy - MC, SA

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:36Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:36Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 202610-21T22:36Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-43852B	Sandwich Unit, Mechanically Refrigerated

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 20 Nov 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T22:36Z
Check the source to verify that this is the current version before use.