INCH-POUND

MIL-P-83461B
AMENDMENT 1
24 February 1993

MILITARY SPECIFICATION

PACKING, PREFORMED, PETROLEUM HYDRAULIC FLUID RESISTANT, IMPROVED PERFORMANCE AT 275°F (135°C)

This amendment forms a part of MIL-P-83461B, dated 25 February 1980, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

2.2: Add the following under Society of Automotive Engineers (SAE):

AMS 3020 Oil, Reference, For "L" Stock Rubber Testing

PAGE 5

Table I, column 1: Delete "After aging 70 hours at 275° ± 5°F in MIL-H-5606" and substitute "After aging 70 hours at 275° ± 5°F in ARM 201 (AMS 3020)."

PAGE 6

Table I, column 1: Delete "After aging 60 days at 75° ± 5°F in MIL-H-5606" and substitute "After aging 60 days at 75° ± 5°F in ARM 201 (AMS 3020)."

PAGE 7

Add as new paragraph 4.1.1:

"4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T08:14Z
Check the source to verify that this is the currentversion before use.

PAGE 10

4.4.5: Delete "Fluid aged 70 hours at 275° ± 5°F in MIL–H–5606" and the physical properties immediately under that phrase and substitute:

Fluid aged 70 hours at 275° ± 5°F in ARM 201 (AMS 3020)
Compression set
Temperature retraction
Hardness change
Volume change"

PAGE 10

4.5.1: Delete and substitute:

"4.5.1 Fluid. The fluid aging in this specification shall be conducted using ARM 201 (AMS 3020) standard reference fluid and MIL–H–83282, as applicable. New fluid shall be used for each aging test."

PAGE 12

4.7f: Delete and substitute:

"4.7f. Reference fluid – ARM 201 (AMS 3020)."

4.7.1b: Delete "fresh MIL–H–5606" and substitute "reference ARM 201 (AMS 3020)."

4.7.1d: Delete "MIL–H–5605B" and substitute "reference ARM 201 (AMS 3020)."

PAGE 18

Add as new paragraph 6.4:

"6.4 ARM 201: ARM 201 (AMS 3020) can be ordered from Society of Automotive Engineers, 400 Commonwealth Dr., Warrendale PA 15096–0001, Phone (412) 772–1616."

Custodians:
Air Force – 11
Army – AV
Navy – AS

Preparing activity:
Air Force – 11

(Project 5330–0917)

Review activities:
Air Force – 99
DLA – IS

User activities:
Army – ME

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:14Z
Check the source to verify that this is the current version before use.