MIL-C-46513B (MU)
20 November 1964
SUPERSEDING
MIL-C-46513A (MU)
2 November 1962

MILITARY SPECIFICATION

CARTRIDGE, 81MM, SMOKE, WP,
M370, W/FUZE, PD, M524
ASSEMBLING, MARKING AND PACKING

1. SCOPE

1.1 This specification covers the assembling, marking and packing for one type of smoke cartridge designated as M370, for use with 81MM mortars.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons; General Specification for
MIL-I-45208 - Inspection Requirements, General Specification for
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of
MIL-P-46568 - Primer, Percussion, M71E1, Loading, Assembling and Packing

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:09Z
Check the source to verify that this is the current version before use.

DRAWINGS

U. S. ARMY MUNITIONS COMMAND

7549031 - Container, Ammunition; Fiber, M252A1 for 81MM Mortar Ammunition
7549032 - Box, Packing, Ammunition for 81MM Mortar Ammunition in Fiber Container, M252A1
8848900 - Cartridge, Smoke, WP, M370 W/Fuze M524, for 81MM Mortar

PUBLICATIONS

IEI-8848900 - Index of Inspection Equipment Lists

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with applicable drawings and specifications.

3.2 Cartridges.-The cartridge shall comply with all requirements specified on Drawing (dwg.) 8848900, and with all requirements specified in applicable specifications.

3.3 Proving ground test.-The cartridge shall comply with the following requirements when tested as specified in 4.3.1.

3.3.1 Failure to fire.-The cartridge shall not fail to fire.

3.3.2 Premature functioning.-There shall be no premature functioning in the mortar tube or in flight before impact.

3.3.3 Functioning.-There shall be visible evidence of functioning upon impact as indicated by presence of a flash or smoke cloud (see 6.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:09Z
Check the source to verify that this is the current version before use.

3.3.4 Horizontal range

3.3.4.1 No cartridge shall have a horizontal range less than 80 percent of the average horizontal range.

3.3.4.2 The standard deviation in horizontal range shall be no greater than the max. lot values shown in Table I for the increment charge indicated.

Table I

Increment Charge Zone	Max. Lot Standard Deviation (yards)
1	20
8	55

3.4 Workmanship

3.4.1 All processing and assembly operations of the cartridge shall be correctly performed in a thorough workmanlike manner. Parts shall be free of chips, dirt, grease, rust and other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents.

3.4.2 The painting and marking shall be restored by the assembling contractor in any component furnished to him painted and marked when such painting and marking has been marred or obliterated.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:09Z
Check the source to verify that this is the current version before use.

4.1.1 Contractor inspection system.-The contractor shall provide and maintain an effective inspection system in compliance with the requirements of Specification MIL-I-45208. The contractor's quality assurance system shall contain a procedure for the reporting of critical defectives found during the course of his inspection and during inspection by the Government. Any critical defect encountered, unless annotated by an asterisk (*) to the right of the characteristic code number (see 6.2), will be reported within 48 hours. A monthly summary report covering those critical defects annotated by an asterisk will be furnished. The agencies to whom the reports will be furnished are identified in paragraph 6.7. The reports shall contain, as a minimum, the following information:

a. Contractor and contract number.
b. Number and revision date of specification.
c. Characteristic code number.
d. Lot or serial number.
e. Number of defectives found.
f. Assignable cause or analysis of occurrence.
g. Corrective action taken or recommended. When the corrective action is beyond the control of the contractor or the scope of the contract, the report shall contain the contractor's recommendation to the Government.

4.1.2 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.
b. Number of units of product inspected.
c. Results obtained for all inspection performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificates of compliance on all material purchased by the contractor when such material is controlled by Government specifications referenced in any of the contractual documents.
f. Number of items in the lot.
g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:09Z
Check the source to verify that this is the current version before use.

4.1.3 Government verification.-Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be in accordance with Specification MIL-I-45208 and will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 Inspection provisions

4.2.1 Lot formation.-A lot shall consist of cartridge assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification, and same specification revision. Drawing, specification, and process changes not affecting safety, performance or fit, as determined by the Government, shall not necessitate changing the lot interfix number. Lots shall be submitted for inspection in accordance with Standard MIL-STD-105 (or Standard MIL-STD-1235, when applicable). Each lot shall contain:

a. WP loaded projectile assemblies from one manufacturer in accordance with the same drawing, same drawing revision, same specification and same specification revision of one loading lot interfix number.

b. Loaded ignition cartridges of one lot interfix number from one manufacturer.

c. Fin assemblies of one lot interfix number from one manufacturer.

d. Loaded primers of one lot interfix number from one manufacturer.

e. Propellant increments made from not more than one lot of propellant from one manufacturer.

f. Loaded fuzes of one lot interfix number from one manufacturer.

g. Loaded projectile bursters of one lot interfix number from one manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:09Z
Check the source to verify that this is the current version before use.

4.2.2 Examination.-Inspection for Critical defects shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with Standard MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Projectile loading assembly as received from WP loading facility (see dwg. 8846606 covering a detail of dwg. 8848900)

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:			
1.	WP leakage or evidence of leakage	Visual	01001
Major: None defined.			
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	01002

4.2.2.2 Projectile loading assembly, prior to inserting burster (see dwg. 8846606 covering a detail of dwg. 8848900)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Burster pad missing	Visual	02001
Major: None defined.			
Minor:	AQL 1.00 percent		
201.	Foreign matter in burster cavity	Visual	02002
202.	Evidence of poor workmanship (see 3.4)	Visual	02003

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:09Z
Check the source to verify that this is the current version before use.

4.2.2.3 Projectile loading assembly, prior to inserting fuze (see dwg. 8846606 covering a detail of dwg. 8848900)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Burster charge missing	Visual	03001
102.	Foreign matter in fuze well ...	Visual	03002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	03003

4.2.2.4 Cartridge, prior to inserting primer (see dwg. 8848900)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Ignition cartridge missing or inverted	Visual	04001 *
Major:	AQL 0.40 percent		
101.	Torque test failure of fin assembly	Test	04002
102.	Torque test failure of fuze ...	Test	04003
Minor:	AQL 0.65 percent		
201.	Foreign matter in cavity	Visual	04004

4.2.2.5 Cartridge (see dwg. 8848900)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Primer loose or above flush with rear face of fin relief ..	Manual and Straight-edge	05001 *
2.	Fin broken or distorted	Visual	05002 *

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:09Z
Check the source to verify that this is the currentversion before use.

3.	Warning label missing or unidentifiable	Visual	05003
4.	Fuze safety wire missing or insecure	Visual-Manual	05004
Major:	AQL 0.40 percent		
101.	Total length, max.	Gage	05005
102.	Any component damaged or incorrectly assembled (except as described by Critical defect 2 above)	Visual	05006
Minor:	AQL 1.50 percent		
201.	Protective coating with total damaged area in excess of 1/4 inch square	Visual	05007
202.	Marking misleading or unidentifiable, including incorrect color code	Visual	05008
203.	Fuze not fully seated	Visual	05009
204.	Evidence of poor workmanship (see 3.4)	Visual	05010

4.2.2.6 Unsealed fiber container, when applicable (see dwg. 7118031)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Propellant increment cut, torn or missing	Visual	06001
Major:	AQL 0.40 percent		
101.	Packing stop missing	Visual	06002
102.	Filler assembly missing	Visual	06003
Minor:	AQL 1.50 percent		
201.	Glue or asphalt on round	Visual	06004
202.	Cartridge improperly assembled into container	Visual	06005
203.	Round cannot be removed by hand	Manual	06006

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:09Z
Check the source to verify that this is the current version before use.

4.2.2.7 Sealed fiber container (see dwg. 7549031)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Container damaged or cut through all asphalt impregnated layers	Visual	07001
102.	Tape incomplete or badly wrinkled	Visual	07002
103.	Metal end loose or distorted ..	Visual-Manual	07003
104.	Marking misleading or unidentifiable	Visual	07004
Minor:	AQL 1.50 percent		
201.	Sealing strip improperly applied	Visual	07005
202.	Gap between cover and body of container excessive	Visual	07006
203.	Contents loose	Manual	07007

4.2.2.8 Sealed wood packing box (see dwg. 7549032)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.00 percent		
101.	Contents exposed	Visual	08001
102.	DOD symbol missing or incorrect	Visual	08002
103.	Board broken or split	Visual	08003
104.	Hardware or strapping missing, broken or loose	Visual-Manual	08004
105.	Marking misleading or unidentifiable	Visual	08005

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:09Z
Check the source to verify that this is the current version before use.

Minor:	AQL 1.50 percent		
201.	Hardware improperly engaged ...	Visual-Manual	08006
202.	Car seal missing, unsealed or improperly positioned	Visual-Manual	08007
203.	Contents loose	Visual-Manual	08008
204.	Handle missing or insecure	Visual-Manual	08009

4.2.3 Testing

4.2.3.1 Check test for possible deterioration of Primer, Percussion, M71E1 (see Specification MIL-P-46568) - Code No. 09001.- If the total elapsed time between original acceptance of the M71E1 primer lot and the assembly of that lot into complete round cartridges exceeds two years, or if the M71E1 primers have been subjected to adverse conditions, however brief, at any time since previous tests, the applicable lot shall be subjected to and must satisfactorily pass the check test for deterioration specified in Specification MIL-P-46568 immediately before the M71E1 primer lot is assembled into the cartridges. The test shall be performed by the contractor on assemblies selected by the Government inspector at the facility assembling the complete cartridges (see 6.4).

4.2.3.2 Profile and alignment (see dwg. 8848900) - Major defect - Code No. 05011.-The cartridges, including those which have had the bourrelet repainted (see 3.4.2), shall be gaged 100 percent for profile and alignment. Any cartridge which fails to comply with the applicable requirement shall be classed defective and removed from the lot. Equipment shall be in accordance with 4.2.4.

4.2.3.3 Proving ground test.-The cartridges shall be observed for compliance with the requirements as classified in Talbe II.

Table II

Defect	Defect Classification	Code No.
(a) Failure to fire (see 3.3.1)	Major	05012
(b) Premature functioning (see 3.3.2)	Critical	05013
(c) Impact functioning (see 3.3.3)	Major	05014
(d) Horizontal range less than 80 percent of horizontal range (see 3.3.4.1)	Major	05015

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:09Z
Check the source to verify that this is the current version before use.

4.2.3.3.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, a sample of 80 cartridges shall be selected from each lot for this test. If a premature burst occurs, if two or more cartridges fail to comply with the requirements of 3.3.1, or if four or more cartridges fail to comply with the requirement of 3.3.3 or if one or more cartridges fail to comply with the requirements of 3.3.4.1, the lot shall be rejected. In addition, if the standard deviation in horizontal range for the sample cartridges fired at charge zone one or charge zone eight multiplied by the factor 0.79 exceeds the applicable max. limit specified in Table I (see 3.3.4.2), the lot shall be rejected. The test shall be performed as specified in 4.3.1.

4.2.3.3.2 After three consecutive lots have met the criteria of 4.2.3.3.1, the sampling plan for this test shall be in accordance with Standard MIL-STD-105, Code letter J, Double Plan, utilizing an AQL of 1.00 percent for defect (a), an AQL of 2.50 percent for defect (c) and an AQL of 0.65 percent for defect (d). The lot shall be rejected if a critical defect occurs during any portion of the test or if the number of defectives equals or exceeds the rejection number specified. In addition, if the standard deviation in horizontal range for the sample cartridges fired at charge zone one or charge zone eight multiplied by the factor 0.75 exceeds the applicable max. limit specified in Table I (see 3.3.4.2), the lot shall be rejected. The test shall be performed as specified in 4.3.1.

4.2.4 Inspection Equipment.-Index of Inspection Equipment Number IEL-8848900 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.2.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the IEL may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:09Z
Check the source to verify that this is the current version before use.

4.2.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed on the IEL shall be in accordance with Specification MIL-I-45607.

4.2.4.3 Government use of contractor's inspection and test equipment.-The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of it's accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

4.3 Test methods and procedures

4.3.1 Proving ground test.-The test shall be performed at a Government proving ground in accordance with the applicable Ordnance Proof Manual and Acceptance Test Procedure. The cartridge shall be fired from an 81MM Mortar for which the round is standard. One half of the sample cartridges shall be fired with an ignition cartridge and one propellant increment (charge zone one) and one half of the sample cartridges shall be fired with an ignition cartridge and eight propellant increments (charge zone eight). The individual velocities, max. pressures and impact ranges shall be obtained and recorded. The standard deviation and the arithmetic average of the impact ranges shall be calculated and recorded.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level A.-The cartridges shall be packed in accordance with dwg. 7549031.

5.2 Packing

5.2.1 Level A.-The cartridges shall be packed in accordance with dwg. 7549032.

5.3 Marking.-Marking of the wood box shall be in accordance with dwg. 7549032. The fiber container shall be marked in accordance with dwg. 7549031.

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:09Z
Check the source to verify that this is the current version before use.

5.4 Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Specification MIL-A-2550.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify title, number and date of this specification.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced Inspection Equipment Lists (IEL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.7.

6.3.1 Inspection equipment lists.-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (OO Form 1242-3) the numbers of drawings of existing equipment designs or codes as indicated in paragraph 6.3.2. Design action required of the contractor with respect to the different types of drawings that may be listed is described in paragraphs 6.3.3 and 6.3.4. Action required by the contractor with respect to commercial inspection equipment is described in 6.3.5. The contractor will be required to prepare detailed drawings in accordance with 6.3.6 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3, 6.3.4, 6.3.5 and 6.3.6 will be designed in the IEL by the following codes:

CDAF - Contractor's design responsibility on Army format in accordance with MIL-D-45608.
CDCF - Contractor's design responsibility on contractor format.
AD - Army design.
ADMU - Army design, mandatory for use.
CE - Commercial equipment.
SCD - Specification control drawing.

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:09Z
Check the source to verify that this is the current version before use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications, mandatory and non-mandatory. When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.4 Specification control drawing.-Specification control drawings depict the minimum equipment requirements in outline, descriptive, diagrammatic or pictorial form only and specify the required performance or other characteristics. Contractors must prepare detailed drawings (see 6.3.6) of their designs in support of specification control drawings. These contractor prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirements of specification control drawings may be approved if described in sufficient detail to permit identification and evaluation by the Government. Designs shall be submitted for approval as specified in 6.3.7.

6.3.5 Commercial equipment.-Commercial equipment is inspection equipment that has universal application for a specific function. It is comprised of items commonly used by industry and Government. Contractors are not required to furnish drawings of commercial inspection equipment, but a list of such equipment must be approved by the Government. Lists shall be submitted for approval to the inspection element of the agency administering the contract.

6.3.6 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:09Z
Check the source to verify that this is the current version before use.

to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Contractor designs identified as CDCF may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above. Contractor designs identified as CDAF shall comply with the format and requirements of MIL-D-45608, and in addition, contain the detail and information specified above.

6.3.7 Submission of contractor designs.-Designs shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND. Design review will normally be accomplished within one month after receipt by Picatinny Arsenal. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs.

6.4 Cost of check test.-The contracting officer shall arrange for the contractor to be reimbursed for the expense incurred in the performance of the check tests. The test shall be conducted at Government expense without cost to the contractor who loaded the primers or to the contractor assembling the cartridge, and shall not constitute a basis for rejection against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

6.5 Impact functioning.-The cartridge shall function with sufficient fragmentation of the projectile to adequately disperse the chemical.

6.6 Submission of test data.-In addition to the normal distribution of records, when the cartridge is procured by the Department of the Army, one copy of all ballistic test data shall be forwarded to the following:

Commanding Officer
Picatinny Arsenal
Dover, New Jersey
ATTN: SMUPA-ND2

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:09Z
Check the source to verify that this is the current version before use.

6.7 Critical defect reports

6.7.1 Submission of critical defect reports.-For U. S. Army Munitions Command procurements, one copy of each critical defect report will be furnished the cognizant Government inspection agency; the Army Ammunition Procurement and Supply Agency, ATTN: SMUAP-RO; Picatinny Arsenal, ATTN: SMUPA-ND.

6.7.2 Reporting to other services.-For other than U. S. Army Munitions Command procurements, critical defect reporting shall be as prescribed by the contracting officer.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project No. 1315-A416

Source: https://assist.dla.mil -- Downloaded: 20261O-22T06:09Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-M004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity (as indicated on reverse hereof).

SPECIFICATION

ORGANIZATION (Of submitter) | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)

SUBMITTED BY (Printed or typed name and activity) | DATE

DD FORM 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE PLATE NO. 19410

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:09Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDING OFFICER
PICATINNY ARSENAL
ATTN: SMUPA-DC 7
DOVER, NEW JERSEY

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:09Z
Check the source to verify that this is the current version before use.