MIL-E-46510A (PA)
25 July 1975
SUPERSEDING
MIL-E-46510
30 March 1961 and
NOTICE 1
27 April 1973

MILITARY SPECIFICATION

Explosive Harness Assembly
Missile Rocket, XM84, Parts For

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the parts for one type explosive harness designated as Explosive Harness Assembly, Missile-Rocket, XM84.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-1169- Packaging, Packing and Marking For Shipment of Inert Ammunition Components

DRAWINGS

8850255 - Explosive Harness Assembly, Missile Rocket, XM84
8799615 - Box, Packing, Ammunition, For Explosive Harness Assembly, Missile Rocket XM84

FSC: 1336

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:08Z
Check the source to verify that this is the current version before use.

2.2 Other Publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

Code of Federal Regulations

Title 49 - Transportation Parts 100-199

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts.-The parts shall comply with all requirements specified on drawing 8850255 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Hose assembly pull force.-The assembly shall withstand a pull force as specified on the applicable drawing (dwg.)

3.4 Relay Cup crush force.-The cup shall withstand fracturing when a flattening force is applied as specified on the applicable drawing.

3.5 First Article Inspection.-This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.6 Workmanship.-The parts and assemblies shall be free of dirt, grease, chips, gouges, rust and other foreign matter that may impair proper functioning. The cleaning method used shall not be injurious to any of the parts, nor shall the parts be contaminated.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsiblity for Inspection and Standard Quality Assurance Provisions.-Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:08Z
Check the source to verify that this is the current version before use.

4.2 Classification of Inspections.-The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First Article Inspection

4.3.1 Submission.-The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part	Drawing	Quantity
Cup, Relay	9298135	10
Hose Assembly	8850257	10
Nut	8850257, detail B	10
Connector	8850257, detail A	10

4.3.2 Inspections to be Performed.-See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection.-See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:08Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-46510A

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Inert Parts Components and Assembly				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cup, Relay				
	dwg. 9298135				
	Examination for Defects	10		3.2	4.4.2.1
	Crush Test	10		3.4	4.5.2
	Nut				
	dwg. 8850258				
	Examination for Defects	10		3.2	4.4.2.3
	Connector				
	dwg. 8850259				
	Examination for Defects	10		3.2	4.4.2.2
	Hose Assembly				
	dwg. 8850257				
	Examination for Defects	10		3.2	4.4.2.4
	Pull Test	10		3.3	4.5.1

NOTES:

Source: https://assist.dla.mil -- Downloaded: 20260-22T06:08Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection

4.4.1 Inspection Lot Formation.-Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition each inspection lot shall contain parts from not more than one manufacturer with one lot interfix number.

4.4.2 Examination.-See MIL-A-48078

a. Sampling Plans.-Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-46510A

PARAGRAPH	TITLE	SHEET 1 OF 4	DRAWING NUMBER
4.4.2.1	Cup, relay		9298135
			NEXT HIGHER ASSEMBLY 9298136

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131.	Bottom thickness		0.40%	3.2	Gage
132.	Crush Test	*	2.5%	3.4	4.5.2
Minor					
201.	Outside diameter		0.65%	3.2	Gage
202.	Inside diameter		0.65%	3.2	Gage
203.	Cup damaged		0.65%	3.6	Visual
204.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

* Apply MIL-STD-105, Table IIIA

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-46510A

PARAGRAPH	TITLE	SHEET 2 OF 4	DRAWING NUMBER
4.4.2.2	Connector		8850257
			NEXT HIGHER ASSEMBLY 8850256

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131.	Pitch diameter of thread		0.40%	3.2	Gage
132.	Major diameter of thread		0.40%	3.2	Gage
133.	Length of thread, min.		0.40%	3.2	Gage
134.	Diameter of hole		0.40%	3.2	Gage
Minor					
201.	Length of connector		0.65%	3.2	Gage
202.	Knurl missing		0.65%	3.2	Visual
203.	Protective finish improper		0.65%	3.2	Visual
204.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-22T06:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-46510A

PARAGRAPH	TITLE	SHEET 3 OF 4	DRAWING NUMBER
4.4.2.3	Nut		8850257
			NEXT HIGHER ASSEMBLY 8850256

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major B					
131.	Pitch diamter of thread		0.40%	3.2	Gage
132.	Minor diameter of thread, min.		0.40%	3.2	Gage
133.	Length of thread		0.40%	3.2	GAge
134.	Inside diameter		0.40%	3.2	Gage
Minor					
201.	Total length		0.65%	3.2	Gage
202.	Protective finish improper		0.65%	3.2	Visual
203.	Knurl missing		0.65%	3.2	Visual
204.	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-E-46510A

PARAGRAPH	TITLE	SHEET 4 OF 4	DRAWING NUMBER
4.4.2.4	Hose Assembly		8850257
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major B					
131.	Pull Test	*	2.5%	3.3	4.5.1
Minor					
201.	Distance from flange to flange		0.65%	3.2	Gage
202.	Flange Outside diameter		0.65%	3.2	Gage
203.	Inside diameter of extension		0.65%	3.2	Gage
204.	Inside diameter of tubing		0.65%	3.2	Gage
205.	Distance between hexagonal shoulder and rear face of connector		0.65%	3.2	Gage
206.	Distance between hexagonal shoulder and rear face of nut		0.65%	3.2	Gage
207.	Thickness of connector flange		0.65%	3.2	Gage
208.	Thickness of nut flange		0.65%	3.2	Gage
209.	Evidence of poor workmanship		0.65%	3.2	Visual

NOTES:

*Apply MIL-STD-105, Table III A

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:08Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.-Testing is described in the First Article and Quality Conformance Inspection tables.

4.4 Inspection Equipment.-The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078 and section 6 herein.

4.5 Test Methods and Procedures

4.5.1 Pull Test Hose Assembly.-The hose assembly shall be assembled to the applicable test fixture specified in 4.4.4. The load as specified on the applicable drawing shall be applied between the nut and the connector in a direction so as to tend to separate the nut and the connector from the hose. Any assembly which shows evidence of pulling apart shall be classed defective.

4.5.2 Crush Test of Relay Cup.-The relay cup shall be placed in the applicable test fixture specified in 4.4.4 The force shall be applied as described on the applicable drawings and any cup which fractures shall be classed defective.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking.-The inert parts for Explosive Harness Assembly, Missile Rocket, XM84, shall be packaged, packed and marked in accordance with MIL-STD-1169. Level C shall apply.

6. NOTES

6.1 Intended Use.-The components covered by this specification are intended for use for the Explosive Harness Assembly, Missile-Rocket, XM84.

6.2 Ordering Data.-See MIL-A-48078.

6.3 Submission of Inspection Equipment Designs for Approval.-See MIL-A-48078. Submit equipment designs as required to Commander, Picatinny Arsenal, Attn: SARPA-QA-T, Dover, N.J., 07801.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1336-A252

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:08Z
Check the source to verify that this is the current version before use.