MIL-F-46485D (AR)
16 MARCH 1981
SUPERSEDING
MIL-F-46485C (MU)
13 November 1964

MILITARY SPECIFICATION

FUZE, BASE DETONATING, M534A1 PARTS - WITH DETONATOR

This specification is approved for use by the US Army Armament Research and Development Command, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the parts and sub-assemblies for one type fuze designated as Fuze, Base Detonating, M534A1 Parts, With Detonator.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests For
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

FSC 1390

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 20261Q-22T06:04Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

8860734 - Fuze, Base Detonating, M534A1, Parts With Detonator
8796522 - Marking Diagram and Sealing for Wooden Packing Boxes
8849028 - Carton, Packing, Ammunition for Fuze, BD, M534A1
8849029 - Box, Packing, Ammunition for Fuze, BD, M534A1
9323980 - Envelope Drawing for Spin Tests, Arming Delay Assembly, Fuze M578, Renovation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation of bids or request for proposal shall apply.

ANSI - B46.1 - Surface Texture

(Application for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, New York, New York 10018).

ASTM - E18 - Tests for Rockwell Hardness and Rockwell Superficial Hardness for Metallic Materials

(Application for copies shall be addressed to the American Society for Testing and Materials (ASTM), 1916 Race Street, Philadelphia, Pa 19103).

3. REQUIREMENTS

3.1 Material.-The materials used shall be in accordance with the requirements of the applicable drawings and specifications.

3.2 Fuze parts and assemblies.-Fuze parts and assemblies shall comply with all requirements of Drawing (dwg.) 8860734 and with all requirements specified in the applicable specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

3.3 Embrittlement of springs.-The segment spring, creep spring and safety plunger spring shall not break when pulled to the minimum (min.) point of permanent distortion when tested as specified in 4.5.7.

3.4 Jolt and jumble.-The fuze assembly shall be safe to handle in accordance with the requirements of MIL-STD-331 when tested as specified in 4.5.8.

3.5 Transportation vibration.-The fuze assembly shall be safe to handle and shall remain operable in accordance with the requirements of MIL-STD-331 when tested as specified in 4.5.9.

3.6 Surface preparation and application of protective finish.-Where cleaning and surface pretreatment are required by component details, the process shall apply to all indicated surfaces regardless of contour configuration. The protective finish shall be as specified on the applicable drawings and shall be uniformly applied to the surfaces designated by the applicable drawings. Salt spray and other required testing shall be in accordance with the applicable drawings and specifications.

3.7 Spin tests

3.7.1 Locking segment and striker needle assembly.-When tested as specified in 4.5.6, the locking segments shall not open when spun at 6000 revolutions per minute (RPM). The locking segments shall open when the assembly is spun at 8500 RPM; and, the segments shall close when the assembly stops spinning.

3.7.2 Loaded arming delay assembly.-When tested as specified in 4.5.6, the loaded shutter assembly shall not arm before 0.020 seconds have elapsed and shall arm before 0.040 seconds have elapsed when spun at 15,000 - 200 RPM. The loaded shutter assembly shall remain in the locked, unarmed position when the loaded arming delay assembly is spun at 6,500 RPM; and, shall become armed and remain in the locked, armed position when spun at 9000 RPM.

NOTE: Alternate timing requirement - The loaded shutter assembly shall not arm before 0.036 seconds have elapsed and shall arm before 0.080 seconds have elapsed when the loaded arming delay assembly is spun at 9,000 - 100 RPM.

3.8 Data requirements.-The contractor shall generate data in accordance with the requirements of the data item description cited in 4.4.2.b.

Source: https://assist.dla.mil -- Downloaded: 20260-22T06:04Z
Check the source to verify that this is the currentversion before use.

3.9 First article inspection.-This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.10 Workmanship.-The requirements for workmanship are as shown on the applicable drawings, in the applicable specifications and the following.

3.10.1 Threads.-Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing and shall be in accordance with the provisions of MIL-A-2550.

3.10.2 Burr.-No part shall have a burr.

3.10.3 Foreign matter.-The fuze assembly and components shall not contain chips, dirt, grease, oil, rust, corrosion or other foreign matter. The cleaning method used shall not be injurious to any part nor shall parts be contaminated by the cleaning agent.

3.10.4 Packing and marking.-Packing materials shall be thoroughly dry when used and shall be assembled in accordance with the applicable drawings and specifications. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions.-Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections.-The following types of inspection shall be performed on this item:

a. First Article Inspection
b. Quality Conformance Inspectin

4.3 First article inspection

4.3.1 Submission.-The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in the sample quantities indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

Part Description	Drawing	Quantity
Fuze Metal Parts Assembly	8860734	116
Fuze Body	8860735	50
Cup, Lead, Booster	8860728	50
Cap	8860731	50
Ring, Locking	8860733	50
Sleeve	8860736	60
Screw, Alignment	8860739	50
Holder, Segment	8860742	50
Pin, Holder	8860743	50
Segment Holder Assembly	8860741	50
Spring, Segment	8860744	60
Segment	8860745	50
Plate, Segment Holder	8860746	50
Cover	8860747	50
Segment, Striker Locking Assembly	8860740	50
Body, Striker	8860748	50
Needle, Striker	8860749 or 9207461	50
Spring, Creep	8860750	60
Washer, Striker	8860751	50
Ring, Retaining	8861063	50
Locking Segment and Striker Needle Assembly	8860738	50
Body, Delay	8860754	50
Shaft, Shutter	8860755	50
Pin, Spring	8860756	50
Delay Body Assembly	8860753	50
Escape Wheel	8860758	60
Pinion	8860759	50
Escape Wheel and Pinion Assembly	8860757	60
Pallet	8860760	60
Plate, Cover	8860762	60
Pivot, Tube	8860763	50
Plate, Cover, Assembly	8860761	60
Strip, Retaining Plunger	8860764	50
Washer, Segment, Timing	8860765	50
Segment, Timing	8860766	50
Spring, Plunger, Safety	8860767	60
Plunger, Safety	8860768	50
Plate, Locking	8860773	50
Shutter	8860770/9327305	50
Weight	8860771	50
Pin, Shutter	8860772	50
Washer, Detonator	9204556	50
Shutter Assembly, Loaded	8860769/9327306	50
Arming Delay Assembly, Loaded	8860752	50

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

4.3.2 Inspections to be performed.-See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection.-See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 8		DRAWING NUMBER
	Fuze, Base Detonating, M534A1 Parts - With Detonator				See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Fuze Metal Parts Assembly (Dwg. 8860734)				
	Examination for Defects	50		3.2	4.4.2.46, 4.4.2.47, 4.4.2.48
	Jolt and Jumble Test	36		3.4	4.5.8
	Transportation Vibration Test	30		3.5	4.5.9
	Fuze Body (Dwg. 8860735)				
	Examination for Defects	50		3.2	4.4.2.1
	Cup, Lead, Booster (Dwg. 8860728)				
	Examination for Defects	50		3.2	4.4.2.2
	Cap (Dwg. 8860731)				
	Examination for Defects	50		3.2	4.4.2.3
	Ring, Locking (Dwg. 8860733)				
	Examination for Defects	50		3.2	4.4.2.4
	Sleeve (Dwg. 8860736)				
	Examination for Defects	50		3.2	4.4.2.5
	Hardness	10		3.1	4.5.2

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 8		DRAWING NUMBER
	CONTINUATION SHEET				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Screw, Alignment (Dwg. 8860739)				
	Examination for Defects	50		3.2	4.4.2.6
	Holder, Segment (Dwg. 8860742)				
	Examination for Defects	50		3.2	4.4.2.7
	Pin, Holder (Dwg. 8860743)				
	Examination for Defects	50		3.2	4.4.2.8
	Segment Holder Assembly (Dwg. 8860741)				
	Examination for Defects	50		3.2	4.4.2.9
	Spring, Segment (Dwg. 8860744)				
	Examination for Defects	50		3.2	4.4.2.10
	Embrittlement Test	10		3.3	
	Segment (Dwg. 8860745)				
	Examination for Defects	50		3.2	4.4.2.11

NOTES:

Source: https://assist.dla.mil -- Downloaded: 20260-22T06:04Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 3 OF 8		DRAWING NUMBER
	CONTINUATION SHEET				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Plate, Segment Holder (Dwg. 8860746)				
	Examination for Defects	50		3.2	4.4.2.12
	Cover (Dwg. 8860747)				
	Examination for Defects	50		3.2	4.4.2.13
	Segment, Striker Locking Assembly (Dwg. 8860740)				
	Examination for Defects	50		3.2	4.4.2.14, 4.4.2.15
	Body, Striker (Dwg. 8860748)				
	Examination for Defects	50		3.2	4.4.2.16
	Needle, Striker (Dwg. 8860749/9207461)				
	Examination for Defects	50		3.2	4.4.2.17
	Spring, Creep (Dwg. 8860750)				
	Examination for Defects	50		3.2	4.4.2.18
	Embrittlement Test	10		3.3	4.5.7

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 4 OF 8		DRAWING NUMBER
	CONTINUATION SHEET				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
10	Washer, Striker (Dwg. 8860751)				
	Examination for Defects	50		3.2	4.4.2.19
	Ring, Retainer (Dwg. 8861063)				
	Examination for Defects	50		3.2	4.4.2.20
	Locking Segment and Striker Needle Assembly (Dwg. 8860738)				
	Examination for Defects	50		3.2	4.4.2.21
	Arming and Non-Arming Spin Tests	50		3.7.1	4.5.6
	Body, Delay (Dwg. 8860754)				
	Examination for Defects	50		3.2	4.4.2.22
	Shaft, Shutter (Dwg. 8860755)				
	Examination for Defects	50		3.2	4.4.2.23

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 5 OF 8		DRAWING NUMBER
	CONTINUATION SHEET				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Pin, Spring (Dwg. 8860756)				
	Examination for Defects	50		3.2	4.4.2.24
	Delay Body Assembly (Dwg. 8860753)				
	Examination for Defects	50		3.2	4.4.2.25
	Escape Wheel (Dwg. 8860758)				
	Examination for Defects	50		3.2	4.4.2.26
	Hardness	10		3.1	4.5.2
	Pinion (Dwg. 8860759)				
	Examination for Defects	50		3.2	4.4.2.27
	Escape Wheel and Pinion Assembly (Dwg. 8860757)				
	Examination for Defects	50		3.2	4.4.2.28
	Load and Torque Test	10		3.2	4.5.1
	Pallet (Dwg. 8860760)				
	Examination for Defects	50		3.2	4.4.2.29
	Hardness	10		3.1	4.5.2

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION
CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 6 OF 8		DRAWING NUMBER
	CONTINUATION SHEET				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Plate, Cover (Dwg. 8860762)				
	Examination for Defects	50		3.2	4.4.2.30
	Locating Boss Static Load Test	10		3.2	4.5.4
	Pivot, Tube (Dwg. 8860763)				
	Examination for Defects	50		3.2	4.4.2.31
	Plate, Cover, Assembly (Dwg. 8860761)				
	Examination for Defects	50		3.2	4.4.2.32
	Disassembly Load Test	10		3.2	4.5.5
	Strip, Retaining Plunger (Dwg. 8860764)				
	Examination for Defects	50		3.2	4.4.2.33
	Washer, Segment, Timing (Dwg. 8860765)				
	Examination for Defects	50		3.2	4.4.2.34
	Segment, Timing (Dwg. 8860766)				
	Examination for Defects	50		3.2	4.4.2.35

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 7 OF 8		DRAWING NUMBER
	CONTINUATION SHEET				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Spring, Plunger, Safety (Dwg. 8860767)				
	Examination for Defects	50		3.2	4.4.2.36
	Embrittlement Test	10		3.3	4.5.7
	Plunger, Safety (Dwg. 8860768)				
	Examination for Defects	50		3.2	4.4.2.37
	Plate, Locking (Dwg. 8860773)				
	Examination for Defects	50		3.2	4.4.2.38
	Shutter (Dwg. 8860770/1327305)				
	Examination for Defects	50		3.2	4.4.2.39
	Weight (Dwg. 8860771)				
	Examination for Defects	50		3.2	4.4.2.40
	Pin, Shutter (Dwg. 8860772)				
	Examination for Defects	50		3.2	4.4.2.41

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE		SHEET 8 OF 8		DRAWING NUMBER
	CONTINUATION SHEET				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Washer, Detonator (Dwg. 9204556)				
	Examination for Defects	50		3.2	4.4.2.42
	Shutter Assembly, Loaded (Dwg. 8860769/9327306)				
	Examination for Defects	50		3.2	4.4.2.44
	Arming Delay Assembly, Loaded (Dwg. 8860752)				
	Examination for Defects	50		3.2	4.4.2.45
	Non-Arming Spin Test at 6500 RPM	50		3.7.2	4.5.6.2.1
	Arming Spin Test at 9000 RPM	50		3.7.2	4.5.6.2.2
	Arming Delay Time at 15000 RPM (Note 1)	50			4.5.6.2.3

NOTES:
1. Alternate delay time: 0.036 - 0.080 seconds at 9000 RPM.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation.-Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each lot of fuze assemblies shall contain M61 detonators of one lot interfix of one manufacturer.

4.4.2 Examination.-See MIL-A-48078.

a. Sampling plans.-Unless otherwise specified in the Classification of Defects and Test tables, sampling plans and procedures shall be in accordance with MIL-STD-105, Inspection Level II.

b. Defect reporting.-The contractor shall prepare a monthly report of all critical defects found, including the number of components/assemblies inspected and corrective action taken, in accordance with Data Item Description DI-R-1721, and deliver the reports as specified in the contract.

c. Visual inspections.-When compliance with the applicable requirements is in doubt as a result of visual inspection these characteristics may be measured or gaged to determine acceptability. In the event of a dispute, four power (4X) magnification shall be used in performing visual inspections for such defects as burrs and foreign matter.

d. Surface finish.-The roughness comparison specimens prescribed by ANSI-B46.1 shall be used as a basis for surface roughness determination where feature size allows this determination to be made.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 4		DRAWING NUMBER 8860735
4.4.2.1	Fuze Body				NEXT HIGHER ASSEMBLY 8860734
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of outside diameter at rear with pitch diameter of external thread		0.40%	3.2	Gage
102	True position of arming delay assembly cavity with pitch diameter of internal thread		0.40%	3.2	Gage
103	True position of locking segment and striker needle assembly cavity with pitch diameter of internal thread		0.40%	3.2	Gage
104	True position of locking segment and striker needle assembly pilot cavity with locking segment and striker needle assembly cavity		0.40%	3.2	Gage
105	Pitch diameter of external thread, min.		0.40%	3.2	Gage
106	Major diameter of external thread, min.		0.40%	3.2	Gage
107	Pitch diameter of internal thread, max.		0.40%	3.2	Gage
108	Minor diameter of internal thread, max.		0.40%	3.2	Gage
109	Pitch diameter of tracer cavity thread, max.		0.40%	3.2	Gage
110	Minor diameter of tracer cavity thread, max.		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-4685D(AR)

PARAGRAPH	TITLE		SHEET 2 OF 4		DRAWING NUMBER
4.4.2.1	CONTINUATION SHEET				8860735
					NEXT HIGHER ASSEMBLY
					8860734
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Pitch diameter of internal thread, min.		0.65%	3.2	Gage
202	Pitch diameter of tracer cavity thread, min.		0.65%	3.2	Gage
203	Pitch diameter of external thread, max.		0.65%	3.2	Gage
204	Depth of internal thread, max.		0.65%	3.2	Gage
205	Length of effective thread for internal thread, min.		0.65%	3.2	Gage
206	Length to internal chamfer, min.		0.65%	3.2	Gage
207	True position of internal thread with outside diameter		0.65%	3.2	Gage
208	Perpendicularity of front face with outside diameter		0.65%	3.2	Gage
209	Diameter of locking segment and striker needle assembly cavity		0.65%	3.2	Gage
210	Diameter of locking segment and striker needle assembly pilot cavity		0.65%	3.2	Gage
211	Diameter of sleeve cavity		0.65%	3.2	Gage
212	True position of sleeve cavity with locking segment and striker needle assembly cavity		0.65%	3.2	Gage
213	Pitch diameter of alignment screw hole thread		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	CONTINUATION SHEET	3 OF 4	8860735
			NEXT HIGHER ASSEMBLY: 8860734

CATEGORY	EXAMINATION OR TEST		NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	0.65%	3.2	Gage		223	Diameter of external thread undercut,
	0.65%	3.2	Gage		224	Depth of tracer cavity, max.
	0.65%	3.2	Gage		225	Length of effective thread for tracer cavity thread, min.
	0.65%	3.2	Gage		226	Diameter of tracer cavity
	0.65%	3.2	Gage		227	Diameter of flange
	0.65%	3.2	Gage		228	Thickness of flange, max.
	0.65%	3.2	Gage		229	Diameter of arming delay assembly cavi
	0.65%	3.2	Gage		230	Diameter of internal chamfer at front
	0.65%	3.2	Gage		231	True position of wrench holes with outside diameter at rear
	0.65%	3.2	Gage		232	Diameter of wrench holes

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2024-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	CONTINUATION SHEET	4 OF 4	8860735
			NEXT HIGHER ASSEMBLY: 8860734

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
233	Depth of wrench holes, excluding drill point, max.		0.65%	3.2	Gage
234	Location of wrench holes		0.65%	3.2	Gage
235	Presence of a burr		0.65%	3.10.2	Visual/Manual
236	Surface finish improper		0.65%	3.2	Manual/Gage
237	Chamfer missing or incorrect		0.65%	3.2	Visual/Gage
238	Protective finish damaged, missing or improper		0.65%	3.6	Visual
239	Marking missing, incorrect or illegible		0.65%	3.10.4	Visual
240	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Cup, Lead, Booster	1 OF 2	8860728
			NEXT HIGHER ASSEMBLY: 8860734

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Runout of rear face with pitch diameter of thread		0.40%	3.2	Gage
102	Thickness of bottom of lead charge cavity		0.40%	3.2	Gage
103	Pitch diameter of thread, min.		0.40%	3.2	Gage
104	Major diameter of thread, min.		0.40%	3.2	Gage
105	Surface finish of rear face improper		0.40%	3.2	Manual/Gage
Minor					
201	Diameter of lead charge cavity		0.65%	3.2	Gage
202	True position of lead charge cavity with pitch diameter of thread		0.65%	3.2	Gage
203	Pitch diameter of thread, max.		0.65%	3.2	Gage
204	Depth of booster pellet cavity		0.65%	3.2	Gage
205	Diameter of booster pellet cavity		0.65%	3.2	Gage
206	True position of booster pellet cavity with pitch diameter of thread		0.65%	3.2	Gage
207	Diameter of thread pilot at rear		0.65%	3.2	Gage
208	True position of rear thread pilot with pitch diameter of thread		0.65%	3.2	Gage
209	Diameter of thread pilot at front		0.65%	3.2	Gage
210	True position of front thread pilot with pitch diameter of thread		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.2	CONTINUATION SHEET				8860728
					NEXT HIGHER ASSEMBLY
					8860734
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
211	Length of rear thread pilot		0.65%	3.2	Gage
212	Length of front thread pilot		0.65%	3.2	Gage
213	Length, total		0.65%	3.2	Gage
214	Width across wrench flats		0.65%	3.2	Gage
215	True position of wrench flats with pitch diameter of thread		0.65%	3.2	Manual/Gage
216	Surface finish improper		0.65%	3.2	Gage
217	Protective finish damaged, missing or improper		0.65%	3.6	Visual
218	Radii missing or improper		0.65%	3.2	Visual/Gage
219	Chamfers missing or improper		0.65%	3.2	Visual/Gage
220	Presence of a burr		0.65%	3.10.2	Manual
221	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Cap		8860731
			NEXT HIGHER ASSEMBLY
			8860734

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread, max.		0.40%	3.2	Gage
102	Minor diameter of thread, max.		0.40%	3.2	Gage
Minor					
201	Pitch diameter of thread, min.		0.65%	3.2	Gage
202	Outside diameter		0.65%	3.2	Gage
203	True position of outside diameter with pitch diameter of thread		0.65%	3.2	Gage
204	Length		0.65%	3.2	Gage
205	Diameter of chamfer at rear		0.65%	3.2	Gage
206	Diameter of thread relief		0.65%	3.2	Gage
207	Length of thread relief		0.65%	3.2	Gage
208	Inside depth		0.65%	3.2	Gage
209	Surface finish improper		0.65%	3.2	Manual/Gage
210	Protective coating missing, damaged or improper		0.65%	3.6	Visual
211	Radii missing or incorrect		0.65%	3.2	Visual/Gage
212	Chamfer missing or incorrect		0.65%	3.2	Visual/Gage
213	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Ring, Locking				8860733
					NEXT HIGHER ASSEMBLY
					8860734
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread, max.		0.40%	3.2	Gage
102	Minor diameter of thread, max.		0.40%	3.2	Gage
Minor					
201	Pitch diameter of thread, min.		0.65%	3.2	Gage
202	Length of thread, min.		0.65%	3.2	Gage
203	Outside diameter		0.65%	3.2	Gage
204	Concentricity of outside diameter with pitch diameter of thread		0.65%	3.2	Gage
205	Length		0.65%	3.2	Gage
206	Length from rear to base of wrench slots		0.65%	3.2	Gage
207	Diameter of thread chamfer at rear		0.65%	3.2	Gage
208	Diameter of thread chamfer at front		0.65%	3.2	Gage
209	Width of wrench slots		0.65%	3.2	Gage
210	Surface finish improper		0.65%	3.2	Manual/Gage
211	Presence of a burr		0.65%	3.10.2	Visual/Manual
212	Radii missing or incorrect		0.65%	3.2	Visual/Gage
213	Chamfer missing or incorrect		0.65%	3.2	Visual/Gage
214	Protective finish damaged, missing or improper		0.65%	3.6	Visual
215	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Sleeve				8860736
					NEXT HIGHER ASSEMBLY
					8860734
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Surface finish of inside diameter improper		0.40%	3.2	Manual / Gage
103	Hardness (Note 1)	30		3.1	4.5.2/Test
Minor					
201	Outside diameter		0.65%	3.2	Gage
202	Length		0.65%	3.2	Gage
203	Surface finish improper		0.65%	3.2	Manual/Gage
204	Chamfer missing or incorrect		0.65%	3.2	Visual/Gage
205	Evidence of poor workmanship		0.65%	3.10	Visual
206	Presence of a burr		0.65%	3.10.2	Visual/Manual

NOTES: 1. Sample shall be selected from each lot. If any sleeve fails to comply with the requirements of dwg. 8860736, the lot of sleeves shall be rejected.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Screw, Alignment				8860739
					NEXT HIGHER ASSEMBLY
					8860734
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Pitch diameter of thread		0.65%	3.2	Gage
202	Major diameter of thread, max.		0.65%	3.2	Gage
203	Length		0.65%	3.2	Gage
204	Diameter of shank		0.65%	3.2	Gage
205	Depth of slot		0.65%	3.2	Gage
206	Width of slot		0.65%	3.2	Gage
207	Length to thread shoulder		0.65%	3.2	Gage
208	Chamfer missing or improper		0.65%	3.2	Visual/Gage
209	Radius missing or improper (as applicable)		0.65%	3.2	Visual/Gage
210	Protective finish damaged, missing or improper		0.65%	3.6	Visual
211	Presence of burr		0.65%	3.10.2	Visual/Manual
212	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE	SHEET 1 OF 3	DRAWING NUMBER
4.4.2.7	Holder, Segment		8860742
			NEXT HIGHER ASSEMBLY
			8860741

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Prependicularity of rear face with striker cavity		0.40%	3.2	Gage
102	Front face not parallel with rear face		0.40%	3.2	Gage
103	True position of striker bore with large outside diameter		0.40%	3.2	Gage
104	True position of small outside diameter with large outside diameter		0.40%	3.2	Gage
105	Diameter of segment cavity, min.		0.40%	3.2	Gage
106	True position of segment cavity with large outside diameter		0.40%	3.2	Gage
107	Depth of segment cavity, min.		0.40%	3.2	Gage
108	True position of striker hole with large outside diameter		0.40%	3.2	Gage
109	Diameter of holder pin holes, max.		0.40%	3.2	Gage
110	True position of holder pin holes with segment cavity		0.40%	3.2	Gage
111	True position of segment spring holes with segment cavity		0.40%	3.2	Gage
112	True position of segment spring anchor holes with segment cavity		0.40%	3.2	Gage
113	Surface finish of striker bore cavity improper		0.40%	3.2	Gage
114	Surface finish of segment cavity and inside counter bore improper		0.40%	3.2	Manual/Gage
			0.40%	3.2	Manual/Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER 8860742
4.4.2.7	CONTINUATION SHEET				NEXT HIGHER ASSEMBLY 8860741
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
115	Presence of a burr		0.40%	3.10.2	Visual/Manual
Minor					
201	Diameter of striker bore		0.65%	3.2	Gage
202	Diameter of segment cavity, max.		0.65%	3.2	Gage
203	Depth of segment cavity, max.		0.65%	3.2	Gage
204	Diameter of striker hole		0.65%	3.2	Gage
205	Diameter of holder pin holes, min.		0.65%	3.2	Gage
206	Diameter of segment spring holes		0.65%	3.2	Gage
207	Diameter of small outside diameter		0.65%	3.2	Gage
208	Diameter of inside counterbore		0.65%	3.2	Gage
209	True position of inside counterbore with large outside diameter		0.65%	3.2	Gage
210	Depth from rear face of inside counterbore		0.65%	3.2	Gage
211	Overall length		0.65%	3.2	Gage
212	Depth of spring clearance hole		0.65%	3.2	Gage
213	Thickness at base of striker cavity		0.65%	3.2	Gage
214	Depth of holder pin holes		0.65%	3.2	Gage
215	Outside diameter		0.65%	3.2	Gage
216	Diameter of segment spring anchor holes, min.		0.65%	3.2	Gage
217	Depth of segment spring anchor holes		0.65%	3.2	Gage
218	Diameter of locking ring groove		0.65%	3.2	Gage
219	Width of locking ring groove		0.65%	3.2	Gage
220	Length from locking ring groove to segment spring hole end		0.65%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	CONTINUATION SHEET	3 OF 3	8860742
			NEXT HIGHER ASSEMBLY 8860741

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
221	Depth of segment spring hole from bottom of segment cavity		0.65%	3.2	Gage
222	Diameter of striker bore		0.65%	3.2	Gage
223	Depth of striker bore from rear face		0.65%	3.2	Gage
224	Length of small outside diameter from rear face		0.65%	3.2	Gage
225	Surface finish improper		0.65%	3.2	Manual/Gage
226	Chamfer missing or incorrect		0.65%	3.2	Visual/Gage
227	Radius missing or incorrect		0.65%	3.2	Visual/Gage
228	Protective finish missing, damaged or improper		0.65%	3.6	Visual
229	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.8	Pin, Holder		8860743
			NEXT HIGHER ASSEMBLY
			8860741

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter, min.		0.40%	3.2	Gage
102	Surface finish improper		0.40%	3.2	Manual/Gage
Minor					
201	Diameter, max.		0.65%	3.2	Gage
202	Length		0.65%	3.2	Gage
203	Chamfer missing or incorrect		0.65%	3.2	Visual/Gage
204	Presence of a burr		0.65%	3.10.2	Visual/Manual
205	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Segment Holder Assembly	1 OF 1	8860741
			NEXT HIGHER ASSEMBLY
			8860740

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Holder Pin Protrusion		0.40%	3.2	Gage
Minor					
201	Holder pin loose or missing		0.65%	3.2	Visual/Manual
202	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8860744
4.4.2.10	Spring, Segment				NEXT HIGHER ASSEMBLY 8860740
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Embrittlement test (Note 1)	10		3.2	4.5.7/Test
Major					
101	Length of coiled section, max.		0.40%	3.2	Gage
102	Spring torque at 60 degrees deflection, max.		0.40%	3.2	Gage
103	Spring torque at 40 degrees deflection, min.		0.40%	3.2	Gage
Minor					
201	Inside diameter		0.65%	3.2	Gage
202	Length of long tag		0.65%	3.2	Gage
203	Length of short tag		0.65%	3.2	Gage
204	Wire diameter		0.65%	3.2	Gage
205	Radius missing or incorrect		0.65%	3.2	Visual/Gage
206	Protective finish damaged, missing or improper		0.65%	3.6	Visual
207	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES: 1. Select sample from each heat treatment batch. If one or more segment springs fail to comply with the requirements of dwg. 8860744, the heat treatment batch shall be rejected.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Segment	1 OF 1	8860745
			NEXT HIGHER ASSEMBLY: 8860740

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Profile		0.40%	3.2	Gage
102	Location of pivot hole		0.40%	3.2	Gage
103	True position of spring hole with pivot hole		0.40%	3.2	Gage
104	Diameter of pivot hole		0.40%	3.2	Gage
105	Straightness of front face		0.40%	3.2	Gage
106	Surface finish improper		0.40%	3.2	Manual/Gage
107	Presence of a burr		0.40%	3.10.2	Manual
Minor					
201	Thickness		0.65%	3.2	Gage
202	Diameter of spring hole at front		0.65%	3.2	Gage
203	Diameter of spring hole at rear		0.65%	3.2	Gage
204	Radius missing or improper		0.65%	3.2	Visual/Gage
205	Protective finish missing, damaged or improper		0.65%	3.6	Visual
206	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.12	Plate, Segment Holder	1 OF 1	8860746
			NEXT HIGHER ASSEMBLY: 8860740

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Concentricity of hole with outside diameter		0.40%	3.2	Gage
102	Straightness of rear face		0.40%	3.2	Gage
103	True position of slots (2 places) with outside diameter		0.40%	3.2	Gage
104	Surface finish improper		0.40%	3.2	Manual/Gage
105	Presence of a burr		0.40%	3.10.2	Manual
Minor					
201	Thickness		0.65%	3.2	Gage
202	Length of slots		0.65%	3.2	Gage
203	Width of slots		0.65%	3.2	Gage
204	Diameter of center hole		0.65%	3.2	Gage
205	Outside diameter		0.65%	3.2	Gage
206	Location of slots with respect to center hole		0.65%	3.2	Gage
207	Chamfer missing or incorrect		0.65%	3.2	Visual/Gage
208	Radius missing or incorrect		0.65%	3.2	Visual/Gage
209	Protective finsih missing, damaged or improper		0.65%	3.6	Visual
210	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.13	Cover	1 OF 1	8860747
			NEXT HIGHER ASSEMBLY: 8860740

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Length		0.65%	3.2	Gage
202	Thickness		0.65%	3.2	Gage
203	Inside diameter		0.65%	3.2	Gage
204	Diameter of hole		0.65%	3.2	Gage
205	Concentricity of hole with inside diameter		0.65%	3.2	Gage
206	Radius missing or incorrect		0.65%	3.2	Visual/Gage
207	Surface finish improper		0.65%	3.2	Manual/Gage
208	Presence of a burr		0.65%	3.10.2	Manual
209	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.14	Segment, Striker Locking Assembly (Prior to Assembly of Cover)				8860740
					NEXT HIGHER ASSEMBLY
					8860738
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Distance between segments and centerline when segments are held in armed position		0.40%	3.2	Manual/Gage
102	Spring or segment malassembled or missing		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.15	Segment, Striker Locking Assembly		8860740
			NEXT HIGHER ASSEMBLY 8860735

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of striker needle hole with striker assembly cavity, when segments are held in unarmed position		0.40%	3.2	Manual/Gage
Minor					
201	Diameter, max.		0.65%	3.2	Gage
202	Length, max.		0.65%	3.2	Gage
203	Cover crimp incomplete or improper		0.65%	3.2	Visual
204	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.16	Body, Striker	1 OF 2	8860748
			NEXT HIGHER ASSEMBLY 8860738

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total length		0.40%	3.2	Gage
102	One or more vent holes missing		0.40%	3.2	Visual
103	Flange radius missing or improper		0.40%	3.2	Visual/Gage
104	Surface finish of flange improper		0.40%	3.2	Manual/Gage
105	Pitch diameter of thread, max.		0.40%	3.2	Gage
106	Major diameter of thread, max.		0.40%	3.2	Gage
Minor					
201	Pitch diameter of thread, min.		0.65%	3.2	Gage
202	Concentricity of shank with pitch diameter of thread		0.65%	3.2	Gage
203	Diameter of shank		0.65%	3.2	Gage
204	Concentricity of flange with pitch diameter of thread		0.65%	3.2	Gage
205	Diameter of flange		0.65%	3.2	Gage
206	True position of vent holes		0.65%	3.2	Gage
207	Length from head end to rear face of flange		0.65%	3.2	Gage
208	Thickness of flange		0.65%	3.2	Gage
209	Effective length of thread, min.		0.65%	3.2	Gage
210	Diameter of creep spring cavity		0.65%	3.2	Gage
211	Depth of creep spring cavity		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.16	CONTINUATION SHEET				8860748
					NEXT HIGHER ASSEMBLY 8860738
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
212	Diameter of vent holes		0.65%	3.2	Gage
213	Diameter of head		0.65%	3.2	Gage
214	Surface finish improper		0.65%	3.2	Manual/Gage
215	Presence of a burr		0.65%	3.10.2	Manual
216	Chamfer missing or incorrect		0.65%	3.2	Visual
217	Protective finish missing, damaged or improper		0.65%	3.6	Visual
218	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.17	Needle, Striker		8860749/9207461
			NEXT HIGHER ASSEMBLY
			8860738

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Profile of point		0.40%	3.2	Gage
102	Diameter of shank, max.		0.40%	3.2	Gage
103	Pitch diameter of thread, min.		0.40%	3.2	Gage
104	Major diameter of thread, min.		0.40%	3.2	Gage
105	Surface finish of shank improper		0.40%	3.2	Manual/Gage
Minor					
201	Pitch diameter of thread, max.		0.65%	3.2	Gage
202	True position of shank with pitch diameter of thread		0.65%	3.2	Gage
203	Length of thread		0.65%	3.2	Gage
204	Total length		0.65%	3.2	Gage
205	Diameter of shank, min.		0.65%	3.2	Gage
206	Depth of slot		0.65%	3.2	Gage
207	Width of slot		0.65%	3.2	Gage
208	Surface finish improper		0.65%	3.2	Manual/Gage
209	Presence of a burr		0.65%	3.10.2	Manual
210	Chamfer missing or incorrect		0.65%	3.2	Visual/Gage
211	Protective finish missing, damaged or improper		0.65%	3.6	Visual
212	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.17	CONTINUATION SHEET		8860749/9207461
			NEXT HIGHER ASSEMBLY
			8860738

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
213	Diameter of slotted end, max (P/N 9207461)		0.65%	3.2	Gage
214	True position of slotted end with pitch		0.65%	3.2	Gage
	Diameter of thread (P/N 9207461)				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.18	Spring, Creep				8860750
					NEXT HIGHER ASSEMBLY 8860738
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Load at assembled length, min.			3.2	Gage
2	Embrittlement test (Note 1)	10		3.2	4.5.7/Test
Major					
101	Solid height, max.		0.40%	3.2	Gage
102	Inside diameter, min.		0.40%	3.2	Gage
103	Outside diameter, max.		0.40%	3.2	Gage
Minor					
201	Load at compressed length, max.		0.65%	3.2	Gage
202	Protective finish missing, damaged or improper		0.65%	3.6	Visual
203	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES: 1. Select sample from each heat treatment batch. If one or more creep springs fails to comply with the requirements of dwg. 8860750, the heat treatment batch shall be rejected.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.19	Washer, Striker		8860751
			NEXT HIGHER ASSEMBLY 8860738

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of hole, max.		0.40%	3.2	Gage
Minor					
201	Diameter of hole, min.		0.65%	3.2	Gage
202	Thickness		0.65%	3.2	Gage
203	Outside diameter		0.65%	3.2	Gage
204	Concentricity of outside diameter with hole		0.65%	3.2	Gage
205	Presence of a burr		0.65%	3.10.2	Manual
206	Protective finish missing, damaged or improper		0.65%	3.6	Visual
207	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.20	Ring, Retainer				8861063
					NEXT HIGHER ASSEMBLY
					8860738
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Outside diameter		0.65%	3.2	Gage
202	Width		0.65%	3.2	Gage
203	Thickness		0.65%	3.2	Gage
204	Presence of a burr		0.65%	3.10.2	Manual
205	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.21	Locking Segment and Striker Needle Assembly				8860738
					NEXT HIGHER ASSEMBLY
					8860734
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Creep spring missing			3.2	Manual
2	Non-arming spin test			3.7.1	4.5.6/Test
Major					
101	Length of striker needle protrusion		0.40%	3.2	Gage
102	Sealing compound missing or improperly applied		0.40%	3.2	Visual
103	Striker body bound (after sealing compound has cured)		0.40%	3.2	Manual
104	Striker needle loose or damaged		0.40%	3.2	Manual/Visual
105	Any component missing or malassembled		0.40%	3.2	Visual
106	Arming spin test	a.		3.7.1	4.5.6/Test
Minor					
201	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

a. See 4.4.3.6.1 for sampling plan.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE	SHEET 1 OF 3	DRAWING NUMBER
4.4.2.22	Body, Delay		8860754
			NEXT HIGHER ASSEMBLY
			8860753

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness of body		0.40%	3.2	Gage
102	Location of shutter cavity, safety plunger slot, locking plate recess and armed position stop, including true position with outside diameter		0.40%	3.2	Gage
103	Depth of shutter cavity		0.40%	3.2	Gage
104	Location of shutter shaft hole, including true position with pivot tube hole		0.40%	3.2	Gage
105	Diameter of shutter shaft hole, max.		0.40%	3.2	Gage
106	Location of cover plate locating holes, including true position with pivot tube hole		0.40%	3.2	Gage
107	Diameter of cover plate locating holes		0.40%	3.2	Gage
108	Location of escape wheel and pinion assembly bearing hole, including true position with pivot tube hole		0.40%	3.2	Gage
109	Diameter of escape wheel and pinion assembly bearing hole		0.40%	3.2	Gage
110	Location of escape wheel and pinion assembly cavity, including true position with outside diameter		0.40%	3.2	Gage
111	Diameter of escape wheel and pinion assembly cavity, max.		0.40%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER
4.4.2.22	CONTINUATION SHEET				8860754
					NEXT HIGHER ASSEMBLY
					8860753
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
112	Location of spring pin hole, including true position with shutter cavity and front face of body		0.40%	3.2	Gage
113	Diameter of spring pin hole, max.		0.40%	3.2	Gage
114	Depth of safety plunger slot from front face		0.40%	3.2	Gage
115	Depth of timing assembly cavity from rear face		0.40%	3.2	Gage
116	Depth of escape wheel and pinion assembly cavity from rear face		0.40%	3.2	Gage
117	Location of plunger retaining strip slot, including true position with shutter cavity		0.40%	3.2	Gage
118	Location of pivot tube hole, including true position with outside diameter of body		0.40%	3.2	Gage
119	Diameter of pivot tube hole, max.		0.40%	3.2	Gage
120	Presence of porosity in pinion bearing area		0.40%	3.2	Visual
121	Pitch dia. of threaded holes, max. (2 holes)		0.40%	3.2	Gage
122	Minor diameter of threaded holes, min. (2 holes)		0.40%	3.2	Gage
123	Surface finish improper		0.40%	3.2	Manual/Gage
124	Presence of a burr		0.40%	3.10.2	Manual
125	True position of pitch diameter of threaded holes with cover plate locating holes (2 holes)		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER
4.4.2.22	CONTINUATION SHEET				8860754
					NEXT HIGHER ASSEMBLY 8860753
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Pitch diameter of threaded holes, min. (2 holes)		0.65%	3.2	Gage
202	Width of plunger retaining strip slot		0.65%	3.2	Gage
203	Height of bottom of plunger retaining strip slot above safety plunger slot		0.65%	3.2	Gage
204	Length of plunger retaining strip slot		0.65%	3.2	Gage
205	Outside diameter		0.65%	3.2	Gage
206	Distance to base of locating slot		0.65%	3.2	Gage
207	Width of locating slot		0.65%	3.2	Gage
208	Symmetry of locating slot with outside diameter		0.65%	3.2	Gage
209	Diameter of shutter shaft hole, min.		0.65%	3.2	Gage
210	Height of armed position stop above bottom of shutter cavity		0.65%	3.2	Gage
211	Depth of cover plate locating holes, min.		0.65%	3.2	Gage
212	Diameter of escape wheel and pinion assembly cavity, max.		0.65%	3.2	Gage
213	Diameter of spring pin hole, min.		0.65%	3.2	Gage
214	Length of effective thread in cover plate holes, min. (2 holes)		0.65%	3.2	Gage
215	Chamfer missing or improper		0.65%	3.2	Visual/Gage
216	Radius missing or improper		0.65%	3.2	Visual/Gage
217	Protective finish missing, damaged or improper		0.65%	3.6	Visual
218	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.23	Shaft, Shutter		8860755
			NEXT HIGHER ASSEMBLY
			8860753

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Large diameter below head		0.40%	3.2	Gage
102	Small diameter below head		0.40%	3.2	Gage
103	Length of large diameter below head, max.		0.40%	3.2	Gage
104	Surface finish of diameters below head improper		0.40%	3.2	Manual/Gage
Minor					
201	Total length below head		0.65%	3.2	Gage
202	Length of large diameter below head, min.		0.65%	3.2	Gage
203	Thickness of head		0.65%	3.2	Gage
204	Diameter of head		0.65%	3.2	Gage
205	Concentricity of head diameter with small diameter below head		0.65%	3.2	Gage
206	Concentricity of large diameter below head with small diameter below head		0.65%	3.2	Gage
207	Chamfer missing or incorrect		0.65%	3.2	Visual/Gage
208	Radius missing or incorrect		0.65%	3.2	Visual/Gage
209	Presence of a burr		0.65%	3.10.2	Manual
210	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.24	Pin, Spring	1 OF 1	8860756
			NEXT HIGHER ASSEMBLY: 8860753

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of head, max.		0.40%	3.2	Gage
102	Diameter of body, max.		0.40%	3.2	Gage
103	Radius missing or incorrect		0.40%	3.2	Visual/Gage
104	Surface finish improper		0.40%	3.2	Manual/Gage
Minor					
201	Diameter of head, min.		0.65%	3.2	Gage
202	Diameter of body, min.		0.65%	3.2	Gage
203	Length of head		0.65%	3.2	Gage
204	Length of pin		0.65%	3.2	Gage
205	Presence of a burr		0.65%	3.10.2	Manual
206	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8860753
4.4.2.25	Delay Body Assembly				NEXT HIGHER ASSEMBLY 8860752
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any component loose or missing		0.40%	3.2	Manual/Visual
102	Length of spring pin protrusion, max.		0.40%	3.2	Gage
Minor					
201	Length of spring pin protrusion, min.		0.65%	3.2	Gage
202	Height of shutter shaft head, max.		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.26	Escape Wheel		8860758
			NEXT HIGHER ASSEMBLY
			8860757

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness		0.40%	3.2	Gage
102	Profile of teeth and wheel, including true position of teeth with center hole		0.40%	3.2	Gage
103	Incorrect number of teeth		0.40%	3.2	Visual
104	Presence of a burr		0.40%	3.10.2	Manual
105	Hardness (Note 1)	30		3.1	4.5.2/Test
Minor					
201	Surface finish improper		0.65%	3.2	Manual/Gage
202	Radius missing or incorrect		0.65%	3.2	Visual/Gage
203	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES: 1. Select sample from each lot. If one or more escape wheels fail to comply with the requirements on dwg. 8860758, the lot of escape wheels shall be rejected.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.27	Pinion				8860759
					NEXT HIGHER ASSEMBLY
					8860757
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of delay body bearing surface		0.40%	3.2	Gage
102	Diameter of delay body bearing surface		0.40%	3.2	Gage
103	Length of cover plate bearing surface		0.40%	3.2	Gage
104	Diameter of cover plate bearing surface		0.40%	3.2	Gage
105	Thickness of shoulder at delay body bearing end		0.40%	3.2	Gage
106	Length from face of shoulder at delay body bearing end to end of pinion teeth		0.40%	3.2	Gage
107	Length from face of shoulder at delay body bearing end to face of shoulder at cover plate bearing end		0.40%	3.2	Gage
108	Concentricity of pitch diameter of pinion teeth with bearing diameters at cover plate and delay body ends		0.40%	3.2	Gage
109	Concentricity of escape wheel shoulder diameter with cover plate bearing diameter		0.40%	3.2	Gage
110	Gear teeth profile		0.40%	3.2	Gage
111	Surface finish improper		0.40%	3.2	Manual/Gage
112	Presence of a burr		0.40%	3.10.2	Manual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 8860759
4.4.2.27	CONTINUATION SHEET				NEXT HIGHER ASSEMBLY 8860757
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Diameter of shoulder adjacent to bearing surface at delay body end		0.65%	3.2	Gage
202	Diameter of shoulder adjacent to bearing surface at cover plate end		0.65%	3.2	Gage
203	Length of escape wheel shoulder		0.65%	3.2	Gage
204	Chamfer missing or incorrect		0.65%	3.2	Visual/Gage
205	Radius missing or incorrect		0.65%	3.2	Visual/Gage
206	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.28	Escape Wheel and Pinion Assembly		8860757
			NEXT HIGHER ASSEMBLY 8860752

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Load and torque test	a.		3.2	4.5.3/Test
Major					
101	Perpendicularity of rear face of escape wheel with cover end bearing surface of pinion		0.40%	3.2	Gage
102	Concentricity of escape wheel diameter with cover end bearing surface of pinion		0.40%	3.2	Gage
Minor					
201	Ring stake missing or not 360° complete		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES: a. See 4.4.3.3 for sampling plan.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.29	Pallet		8860760
			NEXT HIGHER ASSEMBLY 8860752

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of hole		0.40%	3.2	Gage
102	True position of hole with profile of pallet		0.40%	3.2	Gage
103	Profile of pallet		0.40%	3.2	Gage
104	Thickness		0.40%	3.2	Gage
105	Radius missing or incorrect		0.40%	3.2	Visual/Gage
106	Chamfer missing or incorrect		0.40%	3.2	Visual/Gage
107	Surface finish improper		0.40%	3.2	Manual/Gage
108	Presence of a burr		0.40%	3.10.2	Manual
109	Hardness (Note 1)	30		3.1	4.5.2/Test
Minor					
201	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES: 1. Select samples from each lot. If one or more pallets fail to comply with the requirements of dwg. 8860760, the lot of pallets shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 8860762
4.4.2.30	Plate Cover				NEXT HIGHER ASSEMBLY 8860761
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Flatness of seating surface		0.40%	3.2	Gage
102	Diameter of locating bosses (2 places)		0.40%	3.2	Gage
103	Location of bosses, including true position with pivot tube hole		0.40%	3.2	Gage
104	Diameter of pivot tube hole, max.		0.40%	3.2	Gage
105	Diameter of escape wheel and pinion assembly bearing hole		0.40%	3.2	Gage
106	Location of escape wheel and pinion assembly bearing hole, including true position with pivot tube hole		0.40%	3.2	Gage
Minor					
201	Thickness		0.65%	3.2	Gage
202	Protrusion of locating bosses (2 places)		0.65%	3.2	Gage
203	Diameter of pivot tube hole counterbore		0.65%	3.2	Gage
204	True position of pivot tube counterbore with pivot tube hole		0.65%	3.2	Gage
205	Diameter of screw hole		0.65%	3.2	Gage
206	Location of screw hole including true position with pivot tube hole		0.65%	3.2	Gage
207	Outside diameter		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.30	CONTINUATION SHEET	2 OF 2	8860762
			NEXT HIGHER ASSEMBLY: 8860761

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
208	True position of outside diameter with pivot tube hole		0.65%	3.2	Gage
209	Diameter of shutter shaft head hole		0.65%	3.2	Gage
210	Location of shutter shaft head hole, including true position with pivot tube hole		0.65%	3.2	Gage
211	Width of locating slot		0.65%	3.2	Gage
212	Location of locating slot, including true position with pivot tube hole		0.65%	3.2	Gage
213	Diameter of pivot tube hole, min.		0.65%	3.2	Gage
214	Thickness from bottom face to bottom of pivot tube hole counterbore, max.		0.65%	3.2	Gage
215	Locating boss fails to withstand application of minimum static load	a.		3.2	4.5.4/Test
216	Diameter of screw hole counterbore (2 places)		0.65%	3.2	Gage
217	Chamfer missing or incorrect		0.65%	3.2	Visual/Gage
218	Radius missing or incorrect		0.65%	3.2	Visual/Gage
219	Surface finish improper		0.65%	3.2	Manual/Gage
220	Presence of a burr		0.65%	3.10.2	Manual
221	Protective finish missing, damaged or improper		0.65%	3.6	Visual
222	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:
a. See 4.4.3.4 for sample size.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.31	Pivot, Tube				8860763
					NEXT HIGHER ASSEMBLY
					8860761
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness of flange		0.40%	3.2	Gage
102	Concentricity of flange with outside diameter at front end		0.40%	3.2	Gage
103	Outside diameter of front and rear ends		0.40%	3.2	Gage
104	Concentricity of outside diameter at rear end with outside diameter at front end		0.40%	3.2	Gage
105	Length of both ends		0.40%	3.2	Gage
106	Diameter of hole, min.		0.40%	3.2	Gage
107	Concentricity of hole with outside diameter at front end		0.40%	3.2	Gage
108	Perpendicularity of front face of flange with outside diameter at front end		0.40%	3.2	Gage
109	Perpendicularity of rear face of flange with outside diameter at rear end		0.40%	3.2	Gage
110	Surface finish improper		0.40%	3.2	Manual/Gage
Minor					
201	Diameter of flange		0.65%	3.2	Gage
202	Diameter of hole, max.		0.65%	3.2	Gage
203	Chamfer missing or incorrect		0.65%	3.2	Visual/Gage
204	Radius missing or incorrect		0.65%	3.2	Visual/Gage
205	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.32	Plate, Cover, Assembly	1 OF 1	8860761
			NEXT HIGHER ASSEMBLY: 8860752

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Perpendicularity of cover plate face with outside diameter of pivot tube		0.40%	3.2	Gage
102	Height of pivot tube flange above cover plate face, max.		0.40%	3.2	Gage
103	Inside diameter of pivot tube, min.		0.40%	3.2	Gage
104	Assembly fails to withstand application of disassembly load	a.		3.2	4.5.5/Test
Minor					
201	Crimp missing or not complete		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:
a. See 4.4.3.5 for sampling plan.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.33	Strip, Retainer Plunger	1 OF 1	8860764
			NEXT HIGHER ASSEMBLY: 8860752

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Width		0.65%	3.2	Gage
202	Length		0.65%	3.2	Gage
203	Thickness		0.65%	3.2	Gage
204	Radius missing or incorrect		0.65%	3.2	Visual/Gage
205	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4,4.2.34	Washer, Segment, Timing		8860765
			NEXT HIGHER ASSEMBLY
			8860752

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness, max.		0.40%	3.2	Gage
102	Concentricity of outside diameter with inside diameter		0.40%	3.2	Gage
Minor					
201	Thickness, min.		0.65%	3.2	Gage
202	Outside diameter		0.65%	3.2	Gage
203	Inside diameter		0.65%	3.2	Gage
204	Radius or chamfer missing or incorrect		0.65%	3.2	Visual/Gage
205	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.35	Segment, Timing		8860766
			NEXT HIGHER ASSEMBLY
			8860752

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location of gear teeth		0.40%	3.2	Gage
102	True position of tooth pitch diameter with pivot hole		0.40%	3.2	Gage
103	Location of striker needle slot including true position with pivot hole		0.40%	3.2	Gage
104	Profile of outside surface, including drive slot and gear teeth		0.40%	3.2	Gage
105	True position of outside diameter with pivot hole		0.40%	3.2	Gage
106	Profile of striker needle slot		0.40%	3.2	Gage
107	Diameter of drive hole		0.40%	3.2	Gage
108	Location of drive slot		0.40%	3.2	Gage
109	Location of drive hole including true position with pivot hole		0.40%	3.2	Gage
110	Incorrect number of gear teeth		0.40%	3.2	Visual
111	Thickness, max.		0.40%	3.2	Gage
112	Presence of a burr		0.40%	3.10.2	Manual
113	Diameter of pivot hole, min.		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.35	CONTINUATION SHEET				8860766
					NEXT HIGHER ASSEMBLY
					8860752
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Thickness, min.		0.65%	3.2	Gage
202	Diameter of pivot hole, max.		0.65%	3.2	Gage
203	Radius missing or incorrect		0.65%	3.2	Visual/Gage
204	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.36	Spring, Plunger, Safety	1 OF 1	8860767
			NEXT HIGHER ASSEMBLY: 8860752

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Solid height, max.		0.40%	3.2	Gage
102	Outside diameter, max.		0.40%	3.2	Gage
103	Inside diameter, min.		0.40%	3.2	Gage
104	Embrittlement test (Note 1)	10		3.3	4.5.7/Test
Minor					
201	Protective coating missing, damaged or incorrect		0.65%	3.6	Visual
202	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES: 1. Select samples from each lot and test as specified in 4.5.7. If one or more samples fail to comply with the requirements of dwg. 8860767, the lot of safety plunger springs shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 8860768
4.4.2.37	Plunger, Safety				NEXT HIGHER ASSEMBLY 8860752
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of stud, max.		0.40%	3.2	Gage
102	True position of stud with thickness and width of plunger		0.40%	3.2	Gage
103	Diameter of spring cavity, min.		0.40%	3.2	Gage
104	True position of spring cavity with thickness and width of plunger		0.40%	3.2	Gage
105	Width, max.		0.40%	3.2	Gage
106	Thickness, max.		0.40%	3.2	Gage
107	Width to retaining strip recess, max.		0.40%	3.2	Gage
108	Thickness to retaining strip recess, max.		0.40%	3.2	Gage
109	Length, max.		0.40%	3.2	Gage
110	Depth of spring cavity, min.		0.40%	3.2	Gage
111	Chamfer missing or incorrect		0.40%	3.2	Visual/Gage
112	Radius missing or incorrect		0.40%	3.2	Visual/Gage
113	Presence of a burr		0.40%	3.10.2	Manual
Minor					
201	Length, min.		0.65%	3.2	Gage
202	Length, excluding stud		0.65%	3.2	Gage
203	Depth of spring cavity, max.		0.65%	3.2	Gage
204	Diameter of stud, min.		0.65%	3.2	Gage
205	Diameter of spring cavity, max.		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
4.4.2.37	CONTINUATION SHEET		SHEET 2 OF 2		8860768
					NEXT HIGHER ASSEMBLY 8860752
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
206	Width, min.		0.65%	3.2	Gage
207	Thickness, min.		0.65%	3.2	Gage
208	Width to retaining strip recess, min.		0.65%	3.2	Gage
209	Thickness to retaining strip recess, min.		0.65%	3.2	Gage
210	Diameter of counterbore		0.65%	3.2	Gage
211	True position of counterbore with spring cavity		0.65%	3.2	Gage
212	Diameter of drill point in spring cavity, max.		0.65%	3.2	Gage
213	Protective finish missing, damaged or improper		0.65%	3.6	Visual
214	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.38	Plate, Locking				8860773
					NEXT HIGHER ASSEMBLY
					8860752
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Width, max.		0.40%	3.2	Gage
102	Thickness, max.		0.40%	3.2	Gage
103	Diameter of hole, min.		0.40%	3.2	Gage
104	True position of hole with width		0.40%	3.2	Gage
105	Clearance at inside edge of hole, min.		0.40%	3.2	Gage
106	Surface finish improper		0.40%	3.2	Manual/Gage
107	Presence of a burr		0.40%	3.10.2	Manual
Minor					
201	Inside length		0.65%	3.2	Gage
202	Length of short tab		0.65%	3.2	Gage
203	Length of long tab		0.65%	3.2	Gage
204	Diameter of hole, max.		0.65%	3.2	Gage
205	Clearance at inside edge of hole, max.		0.65%	3.2	Gage
206	Radius missing or improper		0.65%	3.2	Visual/Gage
207	Chamfer missing or improper		0.65%	3.2	Visual/Gage
208	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET OF		DRAWING NUMBER
4.4.2.39	Shutter				8860770, 9327305
					NEXT HIGHER ASSEMBLY
					8860769, 9327306
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Profile		0.40%	3.2	Gage
102	Concentricity of flash hole with detonator cavity		0.40%	3.2	Gage
103	Location of detonator cavity including true position with pivot hole		0.40%	3.2	Gage
104	Thickness, max.		0.40%	3.2	Gage
105	Location of weight cavity including true position with shutter profile (if applicable)		0.40%	3.2	Gage
106	Diameter of pivot hole		0.40%	3.2	Gage
107	Location of pivot hole including true position with shutter profile (if applicable)		0.40%	3.2	Gage
108	Width of safety plunger slot, min.		0.40%	3.2	Gage
109	Width of locking plate slot, min.		0.40%	3.2	Gage
110	Location of locking plate slot including true position with shutter profile or true position with pivot hole and detonator cavity (as applicable)		0.40%	3.2	Gage
111	Diameter of shutter pin holes, max. (if applicable)		0.40%	3.2	Gage
112	Location of shutter pin holes including true position with pivot hole (if applicable)		0.40%	3.2	Gage
113	Thickness at base of detonator, cavity		0.40%	3.2	Gage
114	Thickness from base to bottom of locking plate slot, max.		0.40%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER
4.4.2.39	CONTINUATION SHEET				8860770, 9327305
					NEXT HIGHER ASSEMBLY
					8860769, 9327306
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
115	Presence of a burr		0.40%	3.10.2	Manual
116	Surface finish improper		0.40%	3.2	Manual/Gage
117	Height of protrusion (if applicable)		0.40%	3.2	Gage
118	Width of protrusion (if applicable)		0.40%	3.2	Gage
119	True position of protrusion with pivot hole and detonator cavity (if applicable)		0.40%	3.2	Gage
120	Distance from pivot hole center to protrusion edge (if applicable)		0.40%	3.2	Gage
121	Thickness of shutter containing safety plunger slot (if applicable)		0.40%	3.2	Gage
122	Porosity in detonator cavity zone (if applicable)		0.40%	3.2	Visual
123	Flash or gate not removed (if applicable)		0.40%	3.2	Gage
Minor					
201	Diameter of detonator cavity		0.65%	3.2	Gage
202	Diameter of flash hole cavity		0.65%	3.2	Gage
203	Diameter of weight cavity (if applicable)		0.65%	3.2	Gage
204	Width of safety plunger slot, max.		0.65%	3.2	Gage
205	Diameter of shutter pin holes, min. (if applicable)		0.65%	3.2	Gage
206	Depth of shutter pin holes		0.65%	3.2	Gage
207	Thickness, min.		0.65%	3.2	Gage
208	Width of locking plate slot, max.		0.65%	3.2	Gage
209	Thickness from base to bottom of lock plate slot, min.		0.65%	3.2	Gage
210	Diameter of weight cavity counterbore at top (if applicable)		0.65%	3.2	Gage

NOTES: One sample per shift shall be sectioned through the detonator cavity and microscopically (100 X min) examined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 3 OF 3	DRAWING NUMBER
4.4.2.39	CONTINUATION SHEET		8860770, 9327305
			NEXT HIGHER ASSEMBLY
			8860769, 9327306

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
211	Depth of weight cavity counterbore at bottom (if applicable)		0.65%	3.2	Gage
212	Radius missing or incorrect		0.65%	3.2	Visual/Gage
213	Chamfer missing or incorrect		0.65%	3.2	Visual/Gage
214	Protective finish missing or improper		0.65%	3.6	Visual
215	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8860771
4.4.2.40	Weight				NEXT HIGHER ASSEMBLY 8860769
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Length		0.65%	3.2	Gage
202	Diameter		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.41	Pin, Shutter				8860772
					NEXT HIGHER ASSEMBLY
					8860769
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter, min.		0.40%	3.2	Gage
Minor					
201	Diameter, max.		0.65%	3.2	Gage
202	Length		0.65%	3.2	Gage
203	Chamfer missing or incorrect		0.65%	3.2	Visual/Gage
204	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.42	Washer, Detonator	1 OF 1	9204556
			NEXT HIGHER ASSEMBLY: 8860769

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Outside diameter		0.65%	3.2	Gage
202	Inside diameter		0.65%	3.2	Gage
203	Concentricity of outside diameter with inside diameter		0.65%	3.2	Gage
204	Thickness		0.65%	3.2	Gage
205	Presence of a burr		0.65%	3.10.2	Manual
206	Surface finish improper		0.65%	3.2	Manual/Gage
207	Protective finish missing, damaged, or improper		0.65%	3.6	Visual
208	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.43	Detonator, Stab, M61				8865554
					NEXT HIGHER ASSEMBLY
					886C769
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Detonator check test	a.		3.1	Test
Minor	None defined				

NOTES:

a. See 4.4.3.2 for sampling plan and frequency of check test.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.44	Shutter Assembled, Loaded				8860769, 9327306
					NEXT HIGHER ASSEMBLY
					8860752
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness, max.		0.40%	3.2	Gage
102	Projection of shutter pins (if applicable)		0.40%	3.2	Gage
103	One or more shutter pins loose (if applicable)		0.40%	3.2	Manual
104	Ring stake of weight improper or not complete (both sides), (if applicable)		0.40%	3.2	Visual
105	Detonator washer missing any material above flush (excluding shutter pins if applicable)		0.40%	3.2	Visual
106	Detonator improperly staked		0.40%	3.2	Visual
107	Any material above flush excluding shutter pins		0.40%	3.2	Visual/Manual
Minor					
201	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.45	Arming Delay Assembly, Loaded	1 OF 1	8860752
			NEXT HIGHER ASSEMBLY 8860734

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Assembly arms when spun at 6500 RPM under a dead load of 800 ± 50 lbs.			3.7.2	4.5.6.2.1/Test
2	Arming delay time less than 0.020 seconds when spun at 15,000 RPM under a dead load of 800 ± 50 lbs. (Note 1)			3.7.2	4.5.6.2.3/Test
Major					
101	Arming delay time greater than 0.040 seconds when spun at 15000 RPM under a dead load of 800 ± 50 lbs. (Note 1)		100%	3.7.2	4.5.6.2.3/Test
102	Assembly does not arm when spun at 9000RPM under a load of 800 ± 50 lbs. (Note 2)			3.7.2	4.5.6.2.2/Test
103	Any component except screw above flush (Note 3)		0.40%	3.2	Visual/Manual
104	Protrusion of safety plunger retaining strip, max.		0.40%	3.2	Gage
105	Thickness, max.		0.40%	3.2	Gage
106	Detonator missing or inverted		0.40%	3.2	Visual
107	Any component missing		0.40%	3.2	Visual
Minor					
201	Lubricant missing or excessively applied		0.65%	3.2	Visual
202	Screw above flush		0.65%	3.2	Visual/Manual
203	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:
1. When spun at 9000 RPM, arming delay time to be between 0.036 and 0.080 seconds.
2. See 4.4.3.6.2 for sampling plan.
3. Inspection to be performed before and after spin test.

Source: https://assist.dla.mil -- Downloaded: 20240-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.46	Fuze Assembly, Prior to Assembling Alignment Screw and Loaded Arming Delay Assembly				8860734
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Locking segments missing or not fully closed			3.2	Visual
Major					
101	Any component missing or damaged		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

77

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.47	Fuze Assembly, Prior to Assembling Booster Lead Cup	1 OF 1	8860734
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Shutter not in unarmed position			3.2	Visual
Major					
101	Alignment screw missing or loose		0.40%	3.2	Visual/Manual
102	Any component missing		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8860734
4.4.2.48	Fuze Metal Parts Assembly				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Jolt and jumble test	a.		3.4	4.5.8/Test
2	Transportatation vibration test	b.		3.5	4.5.9/Test
Major					
101	Any component missing		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.10	Visual

NOTES:
a. See 4.4.3.7 for sampling plan.
b. See 4.4.3.8 for sampling plan.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.49	Carton, Packing, Prior to Sealing	1 OF 1	8849028
			NEXT HIGHER ASSEMBLY: 8849029

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Fuze assembly missing		0.65%	3.2	Visual
202	Any packing material missing		0.65%	3.2	Visual
203	One or more separators damaged to the extent that fuzes touch each other		0.65%	3.2	Visual
204	Evidence of poor workmanship		0.65%	3.10.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-46485D (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.50	Sealed Carton				8849028
					NEXT HIGHER ASSEMBLY 8849029
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Corners not blunted prior to insertion into barrier bag		0.65%	3.2	Visual/Manual
202	Contents loose		0.65%	3.2	Manual
203	Carton torn, cut or punctured		0.65%	3.2	Visual
204	Sealing strip fails to completely seal the box		0.65%	3.2	Visual
205	Marking missing, illegible or incorrect		0.65%	3.2	Visual
206	Evidence of poor workmanship		0.65%	3.10.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.51	Sealed Barrier Bag		8849028
			NEXT HIGHER ASSEMBLY 8849029

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Waterproofness of barrier bag destroyed by rupture, puncture or separation of heat seal		0.40%	3.2	Visual
102	Box crushed (Note 1)		0.40%	3.2	Visual
103	Excess air not exhausted prior to sealing		0.40%	3.2	Visual
104	Heat seal test(Note 2)			3.2	4.5.10/Test
Minor					
201	Heat seal located so that one or more subsequent seals cannot be applied		0.65%	3.2	Visual
202	Marking missing, illegible or incorrect		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.10.4	Visual

NOTES:
1. Package should be opened if there is evidence of crushing.
2. See 4.4.3.9 for sampling plan.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.52	Box, Packing				8849029
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Board broken or split		0.40%	3.2	Visual
102	Contents exposed		0.40%	3.2	Visual
103	Strapping missing, broken or loose		0.40%	3.2	Visual/Manual
Minor					
201	Marking missing, illegible or incorrect		0.65%	3.2	Visual
202	Strapping improperly assembled		0.65%	3.2	Visual/Manual
203	Contents move when box is tilted		0.65%	3.2	Manual
204	Evidence of poor workmanship		0.65%	3.10.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T06:04Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Surface preparation and application of protective finish.-The sample size and acceptance criteria for the inspection of surface preparation and the application of protective finish shall be in accordance with the applicable specifications. Failure to comply with the applicable specification and drawing requirements shall be cause for taking the corrective action recommended therein (see 4.5.1).

4.4.3.2 Check test for deterioration of detonator, Major Defect.-If the total elapsed time between the acceptance of a detonator lot and assembly of that lot into fuze lots exceeds two years, or if the detonators have been subjected to adverse conditions, however brief, at any time since previous tests, the detonator lot shall be subjected to and must satisfactorily pass the check test for deterioration specified in the applicable detonator specification immediately before the detonator lot is assembled into fuzes. The test shall be performed by the contractor on detonators selected by the Government at the facility assembling the detonators into fuzes. The test shall be conducted at Government Expense without cost to the contractor who loaded the detonator or the contractor assembling the detonator into the fuze, and shall not constitute a basis for rejection against either contractor except where deterioration has occurred as a direct result of carelessness in handling, storage, etc. permitted while the detonator lot was under the responsibility of either contractor (see 6.4).

4.4.3.3 Escape wheel and pinion load and torque test, Critical Defect.-This test shall be performed as specified in 4.5.3.

4.4.3.3.1 Initial production.-Beginning with the first lot produced and continuing until three consecutive lots have complied with the requirements of dwg. 8860757, one hundred fifty sample assemblies shall be selected from each lot for this test.

4.4.3.3.2 Subsequent production.-After three consecutive lots have met the criteria specified in 4.4.3.3.1, fifty sample assemblies shall be selected from each lot for this test.

4.4.3.4 Cover plate locating boss static load test, Minor Defect.-Fifty cover plate samples shall be selected for this test and tested as specified in 4.5.4. If five or more cover plate samples fail to withstand the application of the minimum static load specified on dwg. 8860762, the lot of cover plates shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T06:04Z
Check the source to verify that this is the currentversion before use.

4.4.3.5 Plate cover assembly - disassembly load test, Major Defect.-Fifty plate cover assemblies from each lot shall be selected for this test and tested as specified in 4.5.5. If three or more sample assemblies fail to comply with the requirements of dwg. 8860761, the lot of plate cover assemblies shall be rejected.

4.4.3.6 Spin tests.-The following tests shall be performed as specified in 4.5.6.

4.4.3.6.1 Locking segment and striker needle assembly arming, Major Defect.

4.4.3.6.1.1 Initial production.-Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified herein, four hundred fifty sample assemblies shall be selected from each lot for this test. If five or more assemblies fail to comply with the requirements of dwg. 8860738, the lot shall be rejected.

4.4.3.6.1.2 Subsequent production.-After three consecutive lots have met the acceptance criteria of 4.4.3.6.1.1, one hundred fifty samples shall be selected from each lot for this test. If two or more assemblies fail to comply with the requirements of dwg. 8860738, the lot shall be rejected.

4.4.3.6.2 Loaded arming delay assembly

4.4.3.6.2.1 Initial production.-Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified herein, four hundred fifty sample assemblies shall be selected from each lot for this test. If five or more arming delay assemblies fail to comply with the requirement specified on dwg. 8860752, the lot shall be rejected.

4.4.3.6.2.2 Subsequent production.-After three consecutive lots have met the criteria specified in 4.4.3.6.2.1, one hundred fifty sample assemblies shall be selected from each lot for this test. If two or more arming delay assemblies fail to comply with the requirement specified on dwg. 8860752, the lot shall be rejected.

4.4.3.7 Jolt and jumble, Critical Defect.-These tests shall be performed as specified in 4.5.8. The fuze assemblies selected for these tests shall be subjected to the Jolt test and then followed by the Jumble test as specified in MIL-STD-331. Upon disassembly of each fuze assembly, the locking segment and striker needle assemblies shall be examined for evidence of open or inoperable segments, and an operable creep spring; and, the loaded arming delay assemblies shall be examined for evidence of the shutter not being in the locked, unarmed position. If any assembly fails to comply with the requirements specified herein, the lot represented by the fuze assembly samples shall be rejected. Assemblies subjected to these tests shall not be returned to the lot and shall be disposed in accordance with local approved procedures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

4.4.3.7.1 Initial production.-Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified herein, a sample of thirty six fuze assemblies shall be selected from each lot for these tests.

4.4.3.7.2 Subsequent production.-After three consecutive lots have met the criteria specified in 4.4.3.7.1, a sample of twelve fuze assemblies shall be selected from each lot for these tests.

4.4.3.8 Transportation vibration, Critical Defect.-This test shall be performed as specified in 4.5.9. The fuze assemblies selected for this test shall be subjected to the Transportation Vibration test as specified in MIL-STD-331. The fuze assemblies tested shall be disassembled following this test and each locking segment and striker needle assembly and loaded delay assembly shall be manually and visually inspected as prescribed in 4.4.3.7. Following these inspections, each assembly shall be subjected to the applicable arming, non-arming and arming delay time spin tests prescribed herein. If any assembly fails to comply with the requirements specified, the fuze assembly lot represented by the samples shall be rejected. Fuze assemblies subjected to this test shall not be returned to the lot and shall be disposed in accordance with local approved procedures.

4.4.3.8.1 Initial production.-Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified, a sample of thirty fuze assemblies shall be selected from each lot for this test.

4.4.3.8.2 Subsequent production.-After three consecutive lots have met the criteria of 4.4.3.8.1, a sample of ten fuze assemblies shall be selected from each lot for this test.

4.4.3.9 Heat seal test of barrier bag, Major Defect.-Sampling and acceptance criteria for this test shall be as prescribed in MIL-P-116 for the "Heat Seal Test", when tested as specified in 4.5.10.

4.4.4 Inspection equipment.-The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.2 herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

4.5 Test procedures

PRECAUTION: This specification covers sampling and testing of chemical, toxic or explosive materials which are potentially hazardous to personnel. Accordingly, it is emphasized that all applicable safety rules, regulations and procedures must be followed in handling and processing these materials.

4.5.1 Surface preparation and application of protective finish.-The procedures for testing the cleaning and surface pretreatment methods for components shall be in accordance with the methods and acceptance criteria for testing as specified in the applicable specification.

4.5.2 Hardness of sleeve, escape wheel and pallet.-This test will be performed on the components themselves; but, the contractor may choose to perform this test on the materials used in the manufacture of each component. The test shall be performed in accordance with the procedures prescribed for Rockwell Hardness Testing by ASTM E18.

4.5.3 Escape wheel and pinion assembly torque test.-The escape wheel and pinion assembly shall be placed in a suitable supporting fixture, cover plate end down and the escape wheel shall be firmly held to prevent rotation. A compressive load of twenty pounds shall be applied without impact to the assembly and the assembly shall be observed for relative movement when a torque of seven inch-ounces is applied to the pinion. The assembly may be marked to aid in this determination and shall be visually or manually examined after the test under not less than four - power (4X) magnification. Following the test, the assemblies shall be scrapped in accordance with approved local procedures.

4.5.4 Cover plate locating boss static load test.-The cover plate is to be held by its locating bosses in a suitable supporting fixture and a load of fifty pounds, minimum, is to be applied to both of the locating bosses. Each cover plate shall be examined for evidence of mechanical failure of its locating bosses. Cover plates which have been tested shall be scrapped in accordance with approved local procedures.

4.5.5 Cover plate assembly load test.-The cover plate assemblies shall be held in a suitable fixture to prevent movement of the cover plate. A tensile load of ten pounds shall be applied to the pivot tube in a direction to effect disassembly of the pivot tube from the cover plate. Assemblies which have been tested shall be scrapped in accordance with approved local procedures.

Source: https://assist.dla.mil -- Downloaded: 20260-22T06:04Z
Check the source to verify that this is the current version before use.

4.5.6 Spin testing.-When both arming and non-arming tests are to be performed on samples, the non-arming test shall be performed, in all cases, after the performance of the arming test. All spin tests shall be performed with a dead compressive load of eight hundred, plus or minus fifty, pounds applied to each assembly to simulate loading under assembled conditions in completed fuzes.

4.5.6.1 Locking segment and striker needle assembly

4.5.6.1.1 Arming.-When placed in a suitable fixture and spun at 8500 RPM the locking segment and striker needle assembly shall be observed for the segments moving to and remaining in the fully opened position. When the assemblies have come to rest, the segments shall be observed for their return to the fully closed position.

4.5.6.1.2 Non-arming.-The locking segment and striker needle assemblies shall be spun at 6000 RPM and observed for the segments not moving from the fully closed position.

4.5.6.2 Loaded arming delay assembly

4.5.6.2.1 Non-arming.-When placed in a suitable fixture and spun at 6500 RPM, the assembly shall be observed for being in the locked, unarmed position. The locked unarmed position is defined as the condition in which the safety plunger remains in physical contact with the locking plate which prevents movement of the shutter assembly (See dwg. 8860752).

4.5.6.2.2 Arming.-When spun at 9000 RPM, the loaded arming delay shall be observed for attaining the locked, armed position (see dwg. 8860752 for definition of this position).

4.5.6.2.3 Arming delay time.-When spun at 15,000 RPM, the arming delay assembly shall be observed for an arming delay time of 0.020 seconds, minimum, and 0.040 seconds, maximum; or, when spun at 9,000 RPM, a delay time of 0.036 seconds, minimum, and 0.080 seconds, maximum in a device similar to that specified on dwg. 9323980. Arming delay time is the interval between the start of rotation and the engagement of the locking plate in the recess of the delay body as defined on dwg. 8860752. The measuring device shall be modified with a mechanism to restrain the safety plunger until the specified rotational speed is attained.

4.5.6.3 Calibration.-The spin equipment prescribed herein shall, as a minimum, be calibrated at the beginning and end of each shift of inspection; and, the completion of any unscheduled maintainance. Standards, prepared in accordance with dwg. 9323980, shall be used for the calibration procedure. If the spin equipment does not satisfactorily pass the calibration criteria, all accepted delay assemblies tested since the last acceptable calibration shall be reinspected prior to assembling into fuzes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

4.5.7 Embrittlement of springs.-The creep and safety plunger springs selected for this test shall be pulled to the minimum point of permanent distortion without breaking. The segment spring shall be twisted to the minimum point of permanent distortion in the direction which simulates normal functioning of the spring without breaking. The springs tested shall be disposed in accordance with local approved procedures.

4.5.8 Jolt and jumble tests.-The equipment and procedures for the Jolt and Jumble tests shall be as prescribed by MIL-STD-331, Method 101.1 for the Jolt test and MIL-STD-331, Method 102.1 for the Jumble test.

4.5.9 Transportation vibration test.-The equipment and procedures for the performance of the Transportation Vibration testing of fuze assemblies shall be as prescribed by MIL-STD-331, Method 104.

4.5.10 Security of barrier bag heat seal.-The procedures for the performance of the barrier bag heat seal security test shall be as prescribed for the "Heat Seal Test" in MIL-P-116.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.-The fuze assemblies shall be preserved and packaged in accordance with dwg. 8849028.

5.2 Packing.-The package fuze assemblies shall be packed in accordance with dwg. 8849029.

5.3 Marking.-Packing boxes shall be marked in accordance with dwg. 8796522.

6. NOTES

6.1 Ordering data

6.1.1 Procurement requirements.-See MIL-A-48078.

6.1.2 Data requirements.-Deliverable data required by this specification is cited in the following paragraphs:

Paragraph	Data Requirement	Applicable DID
4.4.2.b	Quality Inspection Defect Report	DI-R-1721

(Copies of data item descriptions required by the contractor in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

6.1.2.1 Delivery of data to the technical activity.-The following address is to be added to those listed in the contract (Form DD 1423) for the delivery of one copy, each, to the technical agency of the Ammunition Data Cards and Quality Inspection Defect Reports prepared by the contractor for the duration of the contract: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-E, Dover, New Jersey 07801.

6.2 Submission of designs for approval.-Submit equipment designs as required to: Commander, US Army Armament Research and Development Command, DRDAR-QAR-I, Dover, New Jersey 07801.

6.3 Changes from previous issue.-Due to the extensiveness of the changes, asterisks are not used in this revision to identify changes with respect to the previous issue of this specification.

6.4 Cost of check test.-The Contracting Officer will arrange for the contractor to be reimbursed for the expense incurred in performance of the check test. The test shall be performed at government expense without cost to the contractor who loaded the detonators or to the contractor assembling the fuze, and shall not constitute a basis for rejection against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the detonator lot was under the jurisdiction of either contractor.

Custodian:
ARMY-AR

Preparing Activity:
ARMY-AR

Project Number: 1390-A226

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-F-46485D FUZE, BASE DETONATION, M534A1 PARTS WITH DETONAROR

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202640-22T06:04Z
Check the source to verify that this is the current version before use.

:OLD

)EPARTMENT OF THE ARMY

OFFICIAL BUSINESS
:NALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament R & D Command
ATTN: DRDAR-QAR
Dover, New Jersey 07801

)LD

Source: https://assist.dla.mil -- Downloaded: 202640-22T06:04Z
Check the source to verify that this is the current version before use.