INCH-POUND

MIL-I-46497B
11 January 1994
SUPERSEDING
MIL-I-46497A(MU)
30 June 1966

MILITARY SPECIFICATION

INITIATOR, CARTRIDGE ACTUATED, DELAY M4A1, M12A1, M45A1, and M49A1 METAL PARTS ASSEMBLY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for the M4A1, M12A1, M45A1, and M49A1 Delay Cartridge Actuated Initiator Metal Parts Assembly (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplements thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-A-2550 Ammunition, General Specification For

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Standardization Branch (Code 8420), 101 Strauss Avenue, Indian Head, MD 20640-5035, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by sending a letter.

AMSC N/A FSC 1377

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

STANDARDS

FEDERAL

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:06Z
Check the source to verify that this is the current version before use.

FED-STD-151 Metals, Test Methods

MILITARY

MIL-STD-105 Sampling Procedures And Tables For Inspection By Attributes

MIL-STD-109 Quality Assurance Terms And Definitions

MIL-STD-413 Visual Inspection Guide for Elastomeric O-rings

MIL-STD-1167 Ammunition Data Card

(Unless otherwise indicated, copies of federal and military specifications and standards are available from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government drawings. The following Government drawings form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation (see 6.2).

DRAWINGS

Naval Surface Warfare Center, Indian Head (CAGE Codes 19200 and 19203)

8595817 Initiator, Cartridge Actuated, Delay, Metal Parts Assembly

8796826 Box, Fiberboard (Inner) Packing, Ammunition, for Initiator, Cartridge Actuated, Delay, M4A1, M6A1, M12A1, M26, M33, M44, M45A1, or M49A1

8796827 Box, Packing, Ammunition, for Initiator, Cartridge Actuated, Delay, M4A1, M6A1, M12A1, M26, M33, M44, M45A1, or M49A1

9216824 Box, Fiberboard (Outer) Alternative, Packing, Ammunition, for Initiator, Cartridge Actuated, Delay, M4A1, M6A1, M12A1, M26, M33, M44, M45A1, or M49A1

(Application for copies should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Attn: Data Control Branch (Code 8410), Indian Head, MD 20640-5035.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.4) in accordance with 4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:06Z
Check the source to verify that this is the current version before use.

3.2 Materials. All materials used in the manufacture of the initiators shall conform to the specifications referred to on the respective drawings unless specific approval in writing covering a departure therefrom has been obtained from the cognizant Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.2.1 Raw material. The contractor shall be responsible for selecting from the classification list contained in the raw material specification the surface and physical condition of the raw material intended for use in manufacture.

3.3 Hardness and other physical properties. Hardness and other physical properties required by the drawing shall be uniform throughout the part within specified tolerances. Requirements for all alloy and steel parts shall be achieved by quenching and tempering.

3.4 Hydrostatic pressure. The initiator chamber and cap shall withstand a hydrostatic pressure of 5500 to 6500 pounds per square inch (psi) for 15 seconds minimum, without deformation or mechanical failure (see 4.6.2 and 6.3.1).

3.5 Firing pin release. The firing pin of the metal parts assembly, less safety pin, chamber, and cartridge retainer, shall release from the cocked position when the application of an axial load of 20 to 35 pounds has withdrawn the initiator pin 3/4 inch, maximum (see 4.6.3).

3.6 Initiator pin security. Application of an axial load of 200 to 220 pounds to the initiator pin of the metal parts assembly shall not withdraw the initiator pin past the safety pin. Load application shall cause no permanent deformation of the safety pin (see 4.6.4).

3.7 Metal parts assembly. Parts shall be combined to produce an assembly conforming to the requirements of the metal parts assembly drawing. All threaded joints shall be assembled handtight.

3.8 Protective finish. Protective finish shall be in accordance with the applicable specifications and shall apply to all surfaces of the component regardless of contour configuration (see 4.6.5).

3.9 Residual magnetism. The metal parts assembly shall not deflect the indicator of the compass more than 5 degrees in either direction (see 4.6.6).

3.10 Workmanship. Assemblies shall be free of cracks, splits, or other defects which might prevent proper mating with connecting parts or proper functioning of the device.

3.10.1 Metal defects. All components shall be free from cracks, splits, cold shuts, inclusions, porosity, or any similar defect.

3.10.2 Burr. No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.10.3 Foreign matter. No part or assembly shall contain chips, dirt, grease, rust, corrosion, or other foreign matter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:06Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements (see 6.2).

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements; however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Quality assurance terms and definitions. Reference shall be made to MIL-STD-109 to define the quality assurance terms used.

4.1.3 Inspections. Inspections shall be in accordance with MIL-A-2550.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4)
b. Quality conformance inspection (see 4.5)

4.3 Inspection conditions. Unless otherwise specified (see 6.2), all inspections shall be performed under the following conditions:

a. Temperature: Room ambient (68 to 77•F)
b. Altitude: Sea level
c. Humidity: 50 percent relative, maximum
d. Atmospheric pressure: 14.7 psi

4.4 First article inspection. At the beginning of regular production, the contractor shall submit an initial production sample to a Government approved facility for evaluation. The sample shall consist of five metal parts assemblies and ten sets of unassembled parts. The sample shall be manufactured in the same manner and using the same materials, equipment, processes, and procedures used in regular production. All parts and materials, including packaging and packing, must be the same as will be used for regular production and shall be obtained from the regular source of supply. After inspection and provisional inspection at source, the first

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:06Z
Check the source to verify that this is the current version before use.

article sample shall be inspected for all requirements of the drawings and specifications. The Government reserves the right to require new first article samples until such time as an acceptable sample is submitted (see 6.4).

4.5 Quality conformance inspection.

4.5.1 Lot.

4.5.1.1 Submission of product. Unless otherwise specified by the contracting activity, formation and identification of lots shall be in accordance with MIL-STD-105.

4.5.1.2 Size of lot. For the purpose of identification and shipment, the shipping lots of metal parts assemblies shall consist of 1200 assemblies maximum, provided the homogeneity requirement of inspection lots have been retained.

4.5.2 Examination. One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed in accordance with the classification of defects. Four power (4x) magnification may be used for inspection of such defects as burr and foreign matter. Inspection for rubber O-rings shall be in accordance with MIL-STD-413. When compliance with the applicable requirement is in doubt as a result of visual examination, the characteristic shall be measured or gaged to determine acceptability. All nonconforming material shall be rejected.

4.5.2.1 Pin, Initiator, Drawing 8595403, covering a detail of Drawing 8595817.

Characteristics	Defect	Method of Inspection
Critical		
None defined		
Major		
101	Concentricity of groove in head with body	Gage
102	Symmetry of head with body	Gage
103	Diameter of body	Gage
104	Diameter of groove in body	Gage
105	Diameter of groove in head, min	Gage
106	Length to shoulder at head, min	Gage
107	Location of groove in head	Gage
108	Location of groove in body	Gage
109	Profile of groove in body	Measure
110	Profile of groove in head	Measure
111	Metal defective	Visual
112	Protective finish inadequate or defective	Visual
113	Surface finish on body and body groove improper	Visual
114	Burr	Visual
115	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:06Z
Check the source to verify that this is the current version before use.

Minor		
201	Diameter of groove in head, max	Gage
202	Diameter of pull hole	Gage
203	Diameter of undercut, min (if applicable)	Gage
204	Width of head	Gage
205	Width of shoulder at body groove	Gage
206	Thickness of head	Gage
207	Total length	Measure
208	Width of undercut, max	Measure
209	Location of pull hole	Measure
210	Radius or chamfer missing or incorrect	Visual
211	Surface finish improper, except as otherwise classified	Visual

4.5.2.2 Spring, Initiator, Drawing 8595406, covering a detail of Drawing 8595817.

Critical
None defined

Major		
101	Load at specified heights	Gage
102	Height solid, max	Gage
103	Ends incorrect	Visual
104	Protective finish inadequate or defective	Visual
105	Burr or sharp edges	Visual
106	Foreign matter	Visual
Minor		
201	Diameter outside, closed, max	Gage
202	Diameter inside, min	Gage
203	Free length	Gage

4.5.2.3 Cap, Drawing 8595404, covering a detail of Drawing 8595817.

Critical
None defined

Major		
101	Pitch diameter of large thread, max	Gage
102	Minor diameter of large thread, max	Gage
103	Pitch diameter of small thread, max	Gage
104	Minor diameter of small thread, max	Gage
105	Concentricity of pitch diameter of large thread with pitch diameter of small thread, including perpendicularity with base of large thread cavity	Gage
106	Concentricity of hole counterbore with hole	Gage
107	Concentricity of hole with pitch diameter of small thread	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:06Z
Check the source to verify that this is the current version before use.

	including perpendicularity with base of large thread cavity	Gage
108	Symmetry of flats with pitch diameter, large thread	Gage
109	Diameter of hole Gage	
110	Diameter of hole counterbore	Gage
111	Diameter of pin holes	Gage
112	Depth of large thread cavity	Gage
113	Depth of small thread cavity	Gage
114	Length of effective large thread, min	Gage
115	Length of effective small thread, min	Gage
116	Height, max	Gage
117	Thickness of wall	Measure
118	Internal radius at base of large thread cavity missing or incorrect	Visual
119	Thread damaged or not full	Visual
120	Metal defective	Visual
121	Protective finish inadequate or defective	Visual
122	Surface finish of hole improper	Visual
123	Burr	Visual
124	Foreign matter	Visual
Minor		
201	Pitch diameter of large thread, min	Gage
202	Pitch diameter of small thread, min	Gage
203	Pitch diameter of setscrew thread	Gage
204	Minor diameter of setscrew, max	Gage
205	Diameter of boss Gage	
206	Diameter of flange holes	Gage
207	Depth of hole counterbore	Gage
208	Total length	Gage
209	Length between flange holes	Gage
210	Width across body flats	Gage
211	Width of groove Gage	
212	Location of pin holes	Gage
213	Location of groove	Measure
214	Diameter of groove	Measure
215	Length of flange Measure	
216	Width of flange	Measure
217	Thickness of flange	Measure
218	Location of flange hole	Measure
219	Location of setscrew holes	Measure
220	Location of initiator pin hole	Measure
221	Marking missing, incorrect, or illegible	Visual
222	Radius or chamfer missing or incorrect, except as otherwise classified	Visual
223	Surface finish improper, except as otherwise classified	Visual

4.5.2.4 Pin, Safety, Drawing 8595405, covering a detail of Drawing 8595817.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:06Z
Check the source to verify that this is the current version before use.

Critical
None defined

Major

101	Diameter of wire	Measure
102	Profile incorrect	Visual
103	Metal defective	Visual
104	Protective finish inadequate or defective	Visual
105	Burr or sharp edges	Visual
106	Foreign matter	Visual

Minor

201	Diameter of head	Measure
202	Total length	Measure
203	Radius missing or incorrect	Visual

4.5.2.5 Housing, Firing Pin, Drawing 8595408, covering a detail of Drawing 8595817.

Critical
None defined

Major

101	Pitch diameter of small thread, min	Gage
102	Major diameter of small thread, min	Gage
103	Pitch diameter of large thread, min	Gage
104	Major diameter of large thread, min	Gage
105	Concentricity of counterbore with cavity	Gage
106	Concentricity of flange with pitch diameter of small thread	Gage
107	Concentricity of groove with flange	Gage
108	Concentricity of striker hole with cavity	Gage
109	Concentricity of pitch diameter of large thread with cavity	Gage
110	Concentricity of cavity with pitch diameter of small thread, including perpendicularity with face of flange	Gage
111	Concentricity of boss cavity with cavity	Gage
112	Perpendicularity of boss face with pitch diameter of large thread	Gage
113	Diameter of cavity, max	Gage
114	Diameter at datum location	Gage
115	Diameter of groove	Gage
116	Diameter of flange, min	Gage
117	Length from rear flange to cavity	Gage
118	Width of rear flange	Gage
119	Angle at datum diameter	Gage
120	Height of boss	Gage
121	Diameter of small thread undercut, min	Measure
122	Profile of groove	Measure
123	Radius at root of boss	Measure

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:06Z
Check the source to verify that this is the current version before use.

124	Thread damaged or not full	Visual
125	Metal defective	Visual
126	Protective finish inadequate or defective	Visual
127	Surface finish of cavity improper	Visual
128	Burr or sharp corners	Visual
129	Foreign matter	Visual
Minor		
201	Pitch diameter of small thread, max	Gage
202	Pitch diameter of large thread, max	Gage
203	Diameter of cavity, min	Gage
204	Diameter of boss cavity	Gage
205	Diameter of flange, max	Gage
206	Diameter of body	Gage
207	Diameter of counterbore	Gage
208	Diameter of undercut in cavity (if applicable)	Gage
209	Diameter of striker hole	Gage
210	Diameter of small thread pilot	Gage
211	Depth to bottom of cavity	Gage
212	Thickness of striker hole	Gage
213	Total length	Gage
214	Length from small thread pilot flange	Gage
215	Length across flanges	Gage
216	Length of body	Gage
217	Location of flange	Gage
218	Width of undercut in cavity (if applicable)	Measure
219	Width of undercut, small thread	Measure
220	Width of groove Measure	
221	Variation at groove, max	Measure
222	Marking missing, incorrect, or illegible	Visual
223	Radius or chamfer missing or incorrect, except as otherwise classified	Visual
224	Surface finish improper, except as otherwise classified	Visual

4.5.2.6 Pin, Firing, Drawing 8595407, covering a detail of Drawing 8595817.

Critical
None defined

Major		
101	Concentricity of cavity with body	Gage
102	Concentricity of striker with body	Gage
103	Concentricity of shoulder with body	Gage
104	Diameter of body	Gage
105	Diameter of cavity	Gage
106	Diameter of striker	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:06Z
Check the source to verify that this is the current version before use.

107	Diameter of ball hole, max	Gage
108	Diameter of ball hole counterbore, max	Gage
109	Length from striker to body	Gage
110	Radial profile of striker	Gage
111	Radial location of ball holes	Visual
112	Metal defective	Visual
113	Protective finish inadequate or defective	Visual
114	Surface finish on body and striker improper	Visual
115	Burr	Visual
116	Foreign matter	Visual

Minor

201	Diameter of cavity counterbore	Gage
202	Diameter of ball hole, min	Gage
203	Diameter of ball hole counterbore	Gage
204	Diameter of shoulder	Gage
205	Depth of cavity counterbore	Gage
206	Depth of cavity	Gage
207	Depth of ball hole counterbore, min	Gage
208	Total length	Gage
209	Length to ball hole	Gage
210	Length to ball hole counterbore	Gage
211	Drill point in cavity, max	Gage
212	Marking missing, incorrect, or illegible	Visual
213	Radius or chamfer missing or incorrect, except as otherwise classified	Visual
214	Surface finish improper, except as otherwise classified	Visual

4.5.2.7 Chamber, Initiator, Drawing 8593314, covering a detail of Drawing 8595817.

Critical
None defined

Major

101	Pitch diameter of large thread, min	Gage
102	Major diameter of large thread, min	Gage
103	Pitch diameter of small thread, min	Gage
104	Major diameter of small thread, min	Gage
105	Concentricity of counterbore with pitch diameter of large thread Gage	
106	Concentricity of datum diameter with small thread	Gage
107	Diameter of counterbore	Gage
108	Depth of cavity, min	Gage
109	Thickness of wall, min	Gage
110	Location of datum diameter	Gage
111	Profile of gas port	Gage
112	Thread damaged or not full	Measure
113	Chamfer at base of cavity missing or incorrect	Visual
114	Metal defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:06Z
Check the source to verify that this is the current version before use.

115	Protective finish inadequate or defective	Visual
116	Surface finish, end of gas port, improper	Visual
117	Burr	Visual
118	Foreign matter	Visual
Minor		
201	Pitch diameter of large thread, max	Gage
202	Pitch diameter of small thread, max	Gage
203	Diameter of cavity	Gage
204	Diameter of hole Gage	
205	Diameter of small thread pilot	Gage
206	Diameter of large thread pilot	Gage
207	Length of large thread pilot	Gage
208	Length of gas port	Gage
209	Thickness of wall, max	Gage
210	Location of small thread	Gage
211	Depth of counterbore	Measure
212	Total length	Measure
213	Length to end of large thread	Measure
214	Marking missing, incorrect, or illegible	Visual
215	Radius or chamfer missing, incorrect, except as otherwise classified	Visual

4.5.2.8 Retainer, Cartridge, Drawing 8593313, covering a detail of Drawing 8595817.

Critical		
1	Metering slots in base missing	Visual
Major		
101	Pitch diameter of thread, max	Gage
102	Minor diameter of thread, max	Gage
103	Concentricity of cavity with pitch diameter of thread	Gage
104	Concentricity of counterbore with cavity	Gage
105	Perpendicularity of pitch diameter of thread with base	Gage
106	Symmetry of metering slots in base with body	Gage
107	Diameter of cavity, max	Gage
108	Depth of cavity	Gage
109	Depth to bottom of counterbore	Gage
110	Depth of metering slots in base	Gage
111	Length of effective thread, min; or diameter of undercut, max	Gage
112	Length of thread, max	Gage
113	Internal radius at mouth of cavity	Gage
114	Total length	Measure
115	Width of metering slots in base	Measure
116	Drill point in base, max	Measure
117	Number of metering slots incorrect	Visual
118	Thread damaged or not full	Visual
119	Metal defective	Visual
120	Protective finish inadequate or defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:06Z
Check the source to verify that this is the current version before use.

121	Surface finish on internal radius and base improper	Visual
122	Burr	Visual
123	Foreign matter	Visual

Minor

201	Pitch diameter of thread, min	Gage
202	Diameter of cavity, min	Gage
203	Diameter of counterbore	Gage
204	Diameter of head	Gage
205	Depth of counterbore	Gage
206	Diameter of body	Measure
207	Length of elongated slots	Measure
208	Length of head	Measure
209	Width of elongated slots	Measure
210	Location of elongated slots	Measure
211	Angle between base and body	Measure
212	Angular location of elongated slots	Visual
213	Marking missing, incorrect, or illegible	Visual
214	Profile of elongated slots	Visual
215	Radius missing or incorrect	Visual
216	Surface finish improper, except as otherwise classified	Visual

4.5.2.9 Metal Parts Assembly, Drawing 8595817, less Drawings 8595403, 8595405, 8593314, and 8593313.

Critical

1	Protrusion of firing pin	Gage
2	Steel ball missing	Gage

Major
None defined

Minor
None defined

4.5.2.10 Metal Parts Assembly, Drawing 8595817.

Critical
None defined

Major

101	Initiator pin not free to rotate	Manual
102	Safety pin loose or deformed	Manual/Visual
103	Any part missing, except as otherwise classified	Visual
104	Improper assembly	Visual
105	Thread damaged or not full	Visual
106	Marking missing, incorrect, or illegible	Visual
107	Burr	Visual
108	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:06Z
Check the source to verify that this is the current version before use.

Minor

201	O-ring not lubricated	Visual
202	Shipping cap missing	Visual
203	Protective finish or black molybdate coating inadequate or defective	Visual

4.5.2.11 Box, Fiberboard (Inner) Packing, Ammunition, Drawing 8796826.

Critical
None defined

Major
None defined

Minor

201	Contents loose	Manual
202	Box damaged	Visual
203	Marking missing, incorrect, or illegible	Visual
204	Cut, damaged, or improperly sealed bag	Visual

4.5.2.12 Box, Packing, Ammunition, Drawing 8796827.

Critical
None defined

Major
None defined

Minor

201	Contents loose	Visual/Manual
202	Strapping missing, loose, broken, or improperly assembled	Visual/Manual
203	Contents of box exposed	Visual
204	Box damaged	Visual
205	Marking missing, incorrect, or illegible	Visual
206	Number of units incorrect	Visual

4.5.2.13 Box, Fiberboard (Outer) Alternative, Packing, Ammunition, Drawing 9216824.

Critical
None defined

Major
None defined

Minor

201	Contents loose	Manual\Visual
202	Carton broken or damaged	Visual
203	Number of units incorrect	Visual
204	Marking missing, incorrect, or illegible	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:06Z
Check the source to verify that this is the current version before use.

205 Tape incomplete Visual

4.5.3 Inspection testing. The following tests shall be performed in accordance with 4.6.

4.5.3.1 Hardness. Fifty units from each heat treated lot of components shall be tested for compliance with the requirements on the applicable drawing. Failure of any unit to comply with the drawing requirements shall be cause for rejection of the lot of components.

4.5.3.2 Hydrostatic pressure. Each chamber and cap shall be subjected to the hydrostatic pressure test. Failure of any cap or chamber subassembly to comply with 3.4 shall be cause for rejection of the subassembly.

4.5.3.3 Firing pin release. The initiator pin and firing pin of each partial assembly shall be subjected to the firing pin release test. Failure of any partial assembly to comply with the requirements of 3.6 shall be cause for rejection of the partial assembly.

4.5.3.4 Initiator pin security. The initiator pin of each partial assembly shall be subjected to the initiator pin security test. Failure of any unit to comply with the requirements of 3.6 shall be cause for rejection of the partial assembly.

4.5.3.5 Protective finish. The number of units for protective finish tests shall be in accordance with the applicable specification. Failure of any unit in the inspection sample to comply with the requirements of the applicable specification shall be cause for rejection of the lot.

4.5.3.6 Residual magnetism. Each assembly shall be subjected to the test for excessive residual magnetism specified in 4.6.6. Failure of any unit in the inspection sample to comply with the requirements of 3.9 shall be cause for rejection of the assembly.

4.6 Test methods and procedures.

4.6.1 Hardness. Prior to the application of protective finish, a hardness tester shall be used to determine compliance with the requirements of the applicable drawing.

4.6.2 Hydrostatic pressure. Prior to the application of protective finish, the cap and chamber shall be mounted in a device and subjected to hydrostatic pressure to determine compliance with 3.4.

4.6.3 Firing pin release. The subassembly shall be secured in the fixture with the safety pin in place. A pull shall be applied to the initiator pin in the longitudinal direction in conjunction with the device which registers the amount of pull.

4.6.4 Initiator pin security. The subassembly shall be secured in the fixture with the safety pin in place. A pull shall be applied to the initiator pin in the longitudinal direction in conjunction with the fixture which registers the amount of pull. The test shall be performed with the safety pin in each position.

4.6.5 Protective finish. The procedures for protective finish shall be in accordance with the applicable specification referenced on the applicable drawing.

4.6.6 Residual magnetism. The assembly shall be tested for excessive residual magnetism using an approved compass in an area free of local magnetic effects by placing the assembly 5 inches from the end, and

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:06Z
Check the source to verify that this is the current version before use.

at the same height as the compass, in the north-south horizontal position (cap end at south) with the compass set in an east-west heading. The assembly shall be moved at a speed no greater than 10 feet per minute past the compass for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis, and moved slowly back past the compass. This procedure shall be repeated for each 90 degree rotation of the assembly for four full passes.

4.6 Inspection of packaging. The sampling and inspection of the packaging, packing, and container marking shall be in accordance with section 5.

5. PACKAGING

5.1 Packing and marking. Packing and marking shall be Level A or B, as specified by the contracting activity (see 6.2). Level A shall be in accordance with Drawings 8796826 and 8796827. Level B shall be in accordance with Drawings 8796826 and 9216824.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The assembly is used in conjunction with other propellant actuated devices in Aircrew Emergency Escape Systems.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and revision letter of this specification

b. Issue of DODISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced (see 2.1.1 and 2.1.2)

c. If first article inspection is required (see 3.1 and 6.4)

d. Production test activity and lot size (see 4.5.1.2)

e. The responsible inspection activity (see 4.1)

f. Any special inspection conditions (see 4.3)

g. Level of packing and marking (see 5.1)

6.3 Definition.

6.3.1 Mechanical failure. Mechanical failure is any deformation or breakage of a part, the occurrence of which is other than a design function.

6.4 First article. When a first article inspection is required, the contracting officer should provide specific guidance to offerors that the items should be a first article sample. A first article sample is required from each supplier who has not produced this initiator. If production has been interrupted for more than 6

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:06Z
Check the source to verify that this is the current version before use.

months or changes are requested in production methods, a first article sample may be required. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examination, approval of first article test results, and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.5 Subject term (keyword) listing.

Ejection systems, aircrew
Emergency escape systems, aircrew
Escape systems, aircrew
Life-saving systems, aircrew

6.6 Changes from previous issue. Marginal notations are not used to identify changes with respect to the previous issue because of the extensiveness of the changes.

Custodian:

Preparing activity
Navy - OS

Navy - OS

Air Force - 99

(Project 1377-0E62)

Review activity:
Air Force - 70

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:06Z
Check the source to verify that this is the current version before use.