AMENDMENT 1
29 JANUARY 1964

MILITARY SPECIFICATION

PROJECTILE BODY, METAL PARTS ASSEMBLY FOR CARTRIDGE, HE, 81MM M362A1

This Amendment forms a part of Military Specification MIL-P-46502B(MU), 5 December 1962.

Page 3, paragraph 3.9.1: Delete and substitute:

"**3.9.1** *Security.* There shall be no evidence of breakup of the body assembly in the gunbore or in flight when examined after recovery. An attempt will be made to recover all projectile fired in this phase."

Page 11, paragraph 4.3.4.1, table I under Phase: Delete "Security" and substitute "Recovery."

Page 11, paragraph 4.3.4.2: Delete and substitute:

"**4.3.4.2** Production sample. The quantities listed in table II will be ballistically tested in the phases indicated.

TABLE II

Phase	*Quantity*
Recovery	10 each lot
Velocity and Accuracy	10 each lot

Failure of any round fired for recovery to comply with 3.9.1 shall be cause for rejection of the lot. Velocity-accuracy will be recorded for informational purposes only (see 6.1)."

Page 13, paragraph 4.4.7: Delete and substitute:

"**4.4.7** *Protective coating.* The procedures for testing the cleaning of components and the application of protective coating shall be in accordance with the requirements of the applicable drawing and the specifications listed thereon. The salt spray test shall be performed utilizing the equipment and procedures prescribed by Federal Test Method Standard No. 151."

Page 13, all the following:

"**4.4.8** *Functional.*"

Page 13, paragraph 4.4.7.1: Delete and substitute:

"**4.4.8.1** *Recovery.* The samples furnished in accordance with 4.3.4.1 or 4.3.4.2 inert loaded to the service weight, will be assembled into complete rounds and fired in a mortar for which the round is standard. The propellant charge will be adjusted to

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:
Check the source to verify that this is the current version before use.