MILITARY SPECIFICATION

PROJECTILE FOR CARTRIDGE, 81-MILLIMETER MORTAR, SMOKE, M370; WP FILLING ASSEMBLY

This amendment forms a part of Military Specification MIL-P-46512A, dated 12 January 1962, and has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

Page 2, paragraph 3.4: Add after nose-up "(filling end)."

Page 2, paragraph 3.6: Delete and substitute:

3.6 **Leakage.** The projectile shall not leak when maintained at a temperature of 130° to 135° F. for a minimum period of 16 hours and tested as specified in 4.6.2. After the projectile has been accepted for leakage, the WP shall be allowed to solidify with the projectile in the nose-up position.

Page 3, paragraph 4.6.2: Delete and substitute:

4.6.2 *Leakage.* Following the final cleaning operation, the projectile shall be maintained at the required temperature for the specified time and then rolled on its side for a period of no less than 1 minute. The emission of smoke constitutes a leak.

Custodians:
Army—MU
Navy—Wep

Review interest:
Navy—Wep

User interest:
Navy—MC

Preparing activity:
Army—MU
Project No. 1315-0256

FSC 1315

Source: https://assist.dla.mil -- Downloaded: 202610-22T06:09Z
Check the source to verify that this is the current version before use.