INCH-POUND

A-A-55830A
29 April 97
SUPERSEDING
A-A-55830
7 March 1997

# COMMERCIAL ITEM DESCRIPTION

## RACKS, TRAY BUSSING, MOBILE

The General Services Administration has authorized the use of this commercial item description as a replacement for MIL-R-43825B(1) for all federal agencies.

1. SCOPE. This commercial item description (CID) covers two-compartment mobile racks for bussing trays of soiled dishes.

2. CLASSIFICATION. The design shall meet the manufacturer's current design and manufacturing requirements for bussing racks, with standard accessories offered by the manufacturer, to meet all the requirements specified. Racks covered by this description shall be of the following types and sizes as specified.

Type I - To carry 14 by 18 inch rectangular trays
Size 1 Capacity 22 trays
Size 2 Capacity 44 trays

Type II - To carry 15 by 20 inch rectangular trays
Size 1 Capacity 22 trays
Size 2 Capacity 44 trays

Type III - To carry 14 by 18 inch trapezoidal trays, capacity 44 trays

Type IV - To carry $10\frac{3}{4}$ by $13\frac{7}{8}$ inch rectangular trays, capacity 48 trays

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent by letter to: Commander, Defense Supply Center Richmond, ATTN: DSCR-VBD, 8000 Jefferson Davis Highway, Richmond VA 23297-5610.

AMSC N/A FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.

## 3. SALIENT CHARACTERISTICS

3.1 Configuration. All racks, except type IV, shall be of double compartment configuration, fully enclosed, consisting of an aluminum alloy frame, extruded aluminum alloy tray slides, aluminum alloy panels and doors and four swivel casters. Unless otherwise specified (see 8.3), the type IV rack shall be the same except it shall have an open frame construction and shall be supplied with a push handle. The basic frame of the rack shall be an all welded assembly including caster plates. The base plate shall be an integral part of the rack, but the panels may be removable. The frame shall be constructed perpendicular to the base and the top of the frame shall be parallel to the base. The rack shall accept the applicable size tray of standard commercial configuration without binding and, when fully loaded with trays, no part of any tray shall extend beyond the planes established by the outside surface of the corner posts. The rack capacities shall be as defined in section 2 with the loading configuration and overall dimension (excluding bumpers) of table I.

TABLE I. Tray configuration and overall dimensions.

| Type and Size | Tray Loading Configuration | Minimum Vertical Tray Spacing (inches) | Maximum Overall Dimensions (inches) | | |
|---|---|---|---|---|---|
| | | | Width | Depth | Height |
| Type I, Size 1 | End loaded 1/slide pair | 5.5 | 38.5 | 21.5 | 72.5 |
| Type I, Size 2 | Side loaded 2/slide pair | 5.5 | 44.5 | 33.5 | 72.5 |
| Type II, Size 1 | End loaded 1/slide pair | 5.5 | 38.5 | 33.5 | 72.5 |
| Type II, Size 2 | Side loaded 2/slide pair | 5.5 | 48.5 | 33.5 | 72.5 |
| Type III | Side loaded 2/slide pair | 5.5 | 44.5 | 33.5 | 72.5 |
| Type IV | Side loaded 2/slide pair | 4.5 | 35.5 | 24.5 | 72.5 |

3.2 Codes and standards. Racks shall comply with the applicable requirements of NSF Standard 2, “Food Equipment.”

3.3 Panels. All panels, except the bottom, of the rack shall have a decorative exterior coating of vinyl-metal laminates. Unless otherwise specified (see 8.3), the coating shall be a walnut wood grain. Panels shall be securely fastened at the bottom, top and sides by threaded fasteners and shall not rattle if tested in accordance with paragraph 4.

3.4 Vinyl-metal laminates. Vinyl-metal laminates shall consist of a sheet metal base, either ferrous or nonferrous, with one or both sides completely covered with vinyl securely bonded to the metal. The laminate shall be self-extinguishing in nature. The vinyl shall be as free as is commercially practicable of visual defects such as streaks, blisters, pinholes, particles of foreign matter and undispersed raw materials. The vinyl shall be stain resistant to orange and lemon peels, 10% nitric, sulfuric or citric acids, mineral oils, sodium hypochlorite (Clorox), colas, coffee or hot bacon grease. The metal finish and temper shall be suitable for good film adhesion. The



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.

adhesive shall be uniform in consistency and free of undispersed particles and foreign matter that would interfere with good bonding.

3.5 Doors. All racks except type IV shall be provided with two equally sized, full length vertical doors at one end, along the width dimension of the rack. Doors shall have the same decorative exterior coating as the panels and shall be reinforced for rigidity. The doors shall have means to facilitate opening and shall close tightly against the door jamb or rack frame and shall be supported by a minimum of three hinges or a full length hinge located at the corners of the rack. The rack shall have provisions for holding the doors open against the sides.

3.6 Casters. Casters shall be 5" swivel with each rated for at least a 190-pound load. Two casters on one side of the rack shall be equipped with locking brakes. Brakes for the type IV racks shall be located on the same side as the push handle.

3.7 Push handle. A push handle shall be attached to one side of the type IV rack. The handle shall be a rigid metal tube of no less than 1 inch diameter or $\frac{3}{4}$ inch diameter solid rod and shall have no less than $1\frac{1}{2}$ inches space between the handle and the side panel of the rack. If aluminum is used, it shall be anodized or polyvinyl coated. The handle shall be located $42 \pm 2$ inches above the floor.

3.8 Tray slides. Tray slides shall be of manufactured with angle or channel and be configured to prevent trays from tipping.

3.9 Bumpers. Racks shall be equipped with perimeter bumpers mounted at the top and bottom of the unit. The bumpers shall be fabricated from rubber or rubber-like material capable of being easily replaced. Bumpers shall protrude 0.75 to 1.13 inches beyond any part of the rack.

3.10 Finish. Aluminum alloy finish shall be the manufacturer's standard finish.

3.11 Marking. Each rack shall be permanently and legibly marked with the manufacturer's name or trademark, the NSN, and the applicable contract number.

3.12 Workmanship. The finished busing racks shall be clean and free of scratches, dents, breaks, sharp edges, sharp corners, deformities, burrs, and slivers. Rivets shall be tight and the rivet heads and peened ends shall be round and concentric and shall be in full contact with the joined metal surfaces. Use of hollow rivets and self-expanding pop rivets are not acceptable. Fusion welds shall be clean, continuous, free of pits, scale, slag and splatter. Threaded fasteners shall be drawn tight using self locking nuts in accordance with the manufacturer's standards.

4. PERFORMANCE. Each bussing rack shall be capable of completing the testing of 4.1 through 4.3 with no rattle or vibration of side panels, no tray slide shall be damaged, no tray shall fall through the tray slides, and no part of the rack, except the bumpers, shall touch the wall during testing. Following testing the rack shall show no evidence of breakage, looseness of parts, parts separation, unevenness of casters with rack standing unloaded on a level surface, caster damage, or permanent deformation in excess of $\frac{3}{16}$ inch.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.

4.1 Impact load testing. The rack shall be loaded to its full capacity with trays. Each tray shall contain a distributed load so the total weight of the tray and load is not less than $7\frac{1}{2}$ pounds. The rack shall be propelled into a hard, rigid wall at a speed not less than 3 feet per second (fps) in the following manner.

a) Both sides shall impact the wall head-on so that both corners strike the wall simultaneously. This procedure shall be repeated five times.
b) Each of the four corners shall impact the wall with the rack approaching the wall at a 30 degree angle. These procedures shall be repeated five times.

4.2 Shock load testing. The rack shall be loaded as in 4.1. The loaded rack shall be placed on a raised platform having vertical faces not less than 2 inches in height. The loaded rack shall be rolled completely off the platform onto a level concrete surface at a speed not less than 3 fps. This procedure shall be repeated five times for each side adjacent to the loading side, with the rack positioned so the side is parallel to the step, and with the direction of rack travel perpendicular to the step.

4.3 Obstacle test. The rack shall be loaded as in 4.1. The loaded rack shall pass over a 0.25 inch obstacle 10 times at a minimum speed of 3 fps.

## 5. REGULATORY REQUIREMENTS

5.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with public law 94-580 or CFR 41CFR 1-1.25.

5.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest version of Federal Standard No. 376, and all other requirements of this commercial item description are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable. The contracting officer has the option of accepting or rejecting the product.

## 6. QUALITY ASSURANCE PROVISIONS

6.1 Product conformance. The racks provided shall meet the salient characteristics of this commercial item description; conform to the producer's own drawings, specifications, standards, and quality assurance practices; and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance.

6.2 Warranty. The racks supplied shall be warranted for a minimum of one year against defects in material or workmanship.

7. PACKAGING. Preservation, packing and marking shall be as specified in the contract or order.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.

8. NOTES. This section contains information of a general or explanatory nature which is helpful, but is not mandatory.

8.1 Intended use. These racks are intended for temporary storage of trays containing soiled dishes.

8.2 Sources of documents. Copies of industry documents may be obtained from the following addresses.

ASME documents may be obtained from the American Society of Mechanical Engineers, United Engineering Center, 345 East 47th Street, New York NY 10017.

NSF documents may be obtained from NSF International, P. O. Box 130140, Ann Arbor, MI 48113-0140.

8.3 Ordering data. Acquisition documents must specify the following.

a. Title, number, and date of this CID.
b. The type and size required (see 2.).
c. When fully enclosed type IV rack is required (see 3.1).
d. The color and texture of vinyl laminate when other than walnut wood grain is required (see 3.3).
e. Packaging requirements (see 7).

8.4 Part identification number (PIN). The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.

AA55830 - XX

Size: 1-Size 1
2-Size 2
0-Not sized

Type: 1-Type I
2-Type II
3-Type III
4-Type IV

CID number

8.5 National stock numbers (NSNs). The following is a list of NSNs assigned which correspond to this CID. The list may not be indicative of all possible NSNs associated with this document.

| PART NO | NSN |
|---|---|
| A55830-1-1 | 7320-01-104-4401 |
| A55830-1-2 | 7320-01-104-4402 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.

| | |
|---|---|
| A55830-2-1 | 7320-01-104-4403 |
| A55830-2-2 | 7320-01-104-4404 |

8.6 Known sources of supply. The following is a list of sources whose products are known to meet the requirements of this CID. This list may not be indicative of all possible sources.

a. CNC Co., 3541 Rockbridge Road, Avondale Estates GA 30002; phone: 404-292-2237.

b. Load King Manufacturing Co., 1357 W. Beaver Street, P.O. Box 40606, Jacksonville FL 32203; phone: 904-354-8882.

c. Serv-Queen Inc., 405 N Charles Street, Daytona Beach FL 32114; phone: 904-257-7795.

d. Bayonne Stainless Products, 98 Avenue E, Bayonne NJ 07002-2526; phone: 201-339-5655.

e. Brake Funderburk Enterprises Inc., D.B.A.: BFE Inc., 12855 Phillips Highway, Jacksonville FL 32224; phone: 904-268-5531.

f. Piper Industries of Wisconsin, 2025 E. Birchwood Avenue, P. O. Box 227, Cudahy WI 53110; phone: 1-800-492-3431.

g. Dietary Equipment Co., Inc., 2205 Main Street, P. O. Box 7254, Columbia SC 29202; phone: 1-800-772-4777.

MILITARY INTERESTS:

Custodians
Army - GL
Navy - SA
Air Force - 99

Reviewers
Army - MD1, QM1
Navy - MC, YD1

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS (7FXE)

PREPARING ACTIVITY:

DLA - IS

AGENT:

DLA - GS

(Project No: 7320-0959)



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:58Z
Check the source to verify that this is the current version before use.