MIL-F-13893E (PA)
Amendment 5
20 April 1976
SUPERSEDING
Amendment 4
17 May 1974

MILITARY SPECIFICATION

FIRING DEVICE, DEMOLITION, DELAY TYPE, M1
PARTS FOR AND LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-F-13893E (MU), dated 1 July 1969. This specification is approved for use by Picatinny Arsenal, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

Paragraph 2.1, Delete PUBLICATIONS, Delete U.S. ARMY MUNITIONS COMMAND, Delete ET-8846784 - Equipment Tabulation.

Add Paragraph 4.3.2.5.1:

4.3.2.5.1 Ampoule (see dwg. 8846782 covering a detail of dwg. 8846783).

| Categories | Defects | Method of Inspection | Code No. |
|---|---|---|---|
| Critical: | None defined | | |
| Major: | AQL 0.40 percent | | |
| 101. | Inside diameter minimum ..... | Gage | 18001 |
| 102. | Evidence of poor workmanship (see 3.6) ..... | Visual | 18002 |
| Minor: | None defined | | |

Paragraph 4.3.2.6, Delete Major Defect 101; Substitute: Major None defined.

Add paragraph 4.3.2.6.1:

4.3.2.6.1 Primer Percussion M27 Assembly (Selected) see dwg. 9294750 covering a detail of dwg. 8846784.

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:33Z
Check the source to verify that this is the current version before use.

| Categories | Defects | Method of Inspection | Code No. |
|---|---|---|---|
| Critical: | None defined | | |
| Major: | AQL 0.40 percent | | |
| 101. | Primer flange diameter ..... | Gage | 19001 |
| Minor: | AQL 0.65 percent | | |
| 201. | Evidence of poor workmanship (see 3.6) ..... | Visual | 19002 |

*Paragraph 4.3.2.8 Critical Defect: Delete None Defined and add:

| | | | |
|---|---|---|---|
| "Critical | | | |
| 1 | Safety strip color code improper ..... | Visual | 08012" |

Paragraph 4.3.2.8, Delete Major Defect 102 in its entirety.

Add Paragraph 4.3.3.11:

"4.3.3.11 Ampoule Volume. - Major Defect. - Code No. 06004. - Sampling for this test shall be in accordance with MIL-STD-105, using code letter M and an AQL of 0.40 percent. Failure of the sample to meet requirements shall result in rejection of the lot. Testing shall be performed as specified in 4.4.8 using equipment in accordance with 4.3.4. (Destructive test).

Paragraph 4.3.4: Delete in its entirety and substitute:

"4.3.4 Inspection Equipment. - Inspection equipment required to perform the inspection prescribed in this specification is identified in the Examination (4.3.2) and Test Method (4.4) paragraphs herein. See 6.3 for details concerning responsibilities for inspection equipment design and approval".

Add Paragraph 4.4.8:

"4.4.8 Ampoule Volume. - The ampoule assembly shall be opened and the delay charge solution extracted using a hypodermic syringe. The syringe shall be graduated in 0.01 C.C. units. The syringe point shall be modified to assure the minimum volume, and the syringe shall be cleaned and dried between each test."



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:33Z
Check the source to verify that this is the current version before use.

Section 6: Delete paragraphs 6.2, 6.3, 6.3.1, 6.3.2, 6.3.3, 6.3.4 and 6.3.5 in their entireties and substitute as follows:

6.2 Inspection Code Numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. They should be cited as references on drawings of equipment designs submitted by the contractor to the Government for approval (see 6.3.3).

6.3 Inspection Equipment Designs.-Inspection equipment designs are of two types - Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers under the "Method of Inspection" headings in Section 4. Design responsibility for all other inspection equipment is assigned to the contractor. The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should he elect to do so.

6.3.1 SIE designs.-SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.

b. A source control drawing or a specification control drawing as defined in MIL-STD-100.

c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detailed design shall meet. When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is cataloged and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:33Z
Check the source to verify that this is the current version before use.

and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs if not otherwise covered thereby (see 6.3.1c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirements Lists (DD Form 1423). The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and the applicable five digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design together with the component or assembly drawing number and revision letter to which the specific design applies.

6.3.3 Submission of Designs for Approval.-Contractor designs shall be approved by the Government prior to fabricating or procuring the equipment. Designs shall be submitted for approval to Picatinny Arsenal, ATTN: SARPA-QA-A-M, Dover, New Jersey 07801 in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423) or in the contract. The contractor must include in his submission of designs a listing of any and all Government SIE designs which will be utilized. Partial submission of inspection designs is permissible and encouraged. However, the completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will normally be accomplished within one month after receipt.

Asterisk (*) denotes change made by Amendment 5 dated 20 April 1976. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1375-A-162



Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:33Z
Check the source to verify that this is the current version before use.