INCH-POUND

MIL-F-13926B(AR)
AMENDMENT 3
20 August 1990
SUPERSEDING
AMENDMENT 2
28 April 1989

MILITARY SPECIFICATION

FIRE CONTROL MATERIEL
MANUFACTURE AND INSPECTION,
GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification MIL-F-13926B(AR), dated 26 March 1984, and is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1, Specifications, Military, delete entry for MIL-C-6021.

DD Form 1426 note, third through fifth lines, delete address and substitute: "Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000".

PAGE 2

* 2.1.1, Specifications, Military, delete entry for MIL-W-13773, MIL-S-45743, and MIL-S-46844.

* 2.1.1, Standards, Military, delete entries for MIL-STD-34, MIL-STD-109, MIL-STD-171, MIL-STD-194, MIL-STD-275 and MIL-STD-1460.

2.1.1, Standards, Military, add the following new entries:

"DOD-STD-100 - Engineering Drawing Practices
MIL-STD-1261 - Arc Welding Procedures for Constructural Steels
MIL-STD-1943 - Welding, Repair of Steel Castings (other than Armor), Metal Arc, Manual
* MIL-STD-2000 - Standard Requirements for Soldered Electrical and Electronic Assemblies.
MIL-STD-2175 - Castings, Classification and Inspection of"

PAGE 3

2.2, American Gear Manufacturer's Association, delete address and substitute: "1500 King Street, Suite 201, Alexandria, VA 22314".

2.2 American National Standards Institute, delete entry for ANSI Y14.36.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:35Z
Check the source to verify that this is the current version before use.

PAGE 3

2.2, American National Standards Institute, add the following new entry:

"ANSI B94.11M - Twist Drills, Straight Shank Combined Drills and Countersinks".

PAGE 4

2.2, American Society for Testing and Materials, add the following new entry:

"ASTM D3951 - Commercial Packaging, Practice for".

3.1.3, following this paragraph, add new 3.1.4 to read:

"3.1.4 Drawing requirements. Drawing types and requirements pertaining thereto, including but not limited to source and specification control drawings, shall be in accordance with DOD-STD-100 and the contract."

PAGE 5

3.2.1, following this paragraph, add new 3.2.1.1 to read:

"3.2.1.1 Effect of protective coating on dimensions. Unless otherwise specified, dimensional limits and surface roughness apply after the application of inorganic type coatings, such as electro-plated or chemically displaced metals, ceramic, anodized, chromated or oxide conversion type finishes, etc. Unless otherwise specified, dimensional limits and surface roughness apply before the application of organic type coatings, such as paints, lacquer, epoxy urethane, enamels, phosphate coating, dry film lubrication, or other non-integral barrier-type coatings. When both types (inorganic and organic) are specified, such as when an inorganic type is complimented by an enamel or other top coating, it is understood that part tolerances apply after initial surface treatment."

PAGE 6

3.2.3, first line, following "The provisions of", delete "3.2.3" and substitute "3.2.2".

3.2.4, third line, delete "3.2.3" and substitute "3.2.2".

PAGE 9

3.2.12, following this paragraph, add new 3.2.12.1 to read:

"3.2.12.1 Threads. Unless otherwise specified, threads shall conform to the requirements of FED-STD-H28 and the applicable drawing."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:35Z
Check the source to verify that this is the current version before use.

3.2.12.7, add a last sentence to read:

"When used for any purpose other than manufacture, centers shall conform to the requirements of ANSI B94.11M."

3.2.12.7, following this paragraph, add new 3.2.12.8 through 3.2.12.10 to read:

"3.2.12.8 Cast and machined finishes. Unless otherwise specified, cast finish shall be 250 and machined finish shall be 125 .

"3.2.12.9 Blind holes for tap drills. Tap drills for threaded holes shall not break through unless specifically permitted on drawing or tolerances accumulate causing minimum material thickness less than .030 inch. The requirement to hold pressure shall take precedence over the .030 inch minimum thickness requirement.

"3.2.12.10 Worms. Unless otherwise specified on the drawing, break the sharp corner .005 to .015 inch radius or bevel .005 to .015 inch x 45°. Worms shall not bottom in the mating gear or segment."

3.2.13.1, following this paragraph, add new 3.2.13.1.1 to read:

"3.2.13.1.1 Insulation resistance. Unless otherwise specified, the insulation resistance between ungrounded electrical circuits and the body or frame of individual units and between isolated circuits shall not be less than 10 megohms at a DC potential of 500 volts."

* 3.2.13.5, delete and substitute:

"3.2.13.5 Soldering of Electrical Connections. Unless otherwise specified by drawing, specification or procuring document, soldering of electrical connections shall be accomplished in accordance with the visual illustrations, procedures and standards outlined in MIL-STD-2000 Task G. Soldering of printed wiring assemblies shall be in accordance with MIL-STD-2000 Task G."

3.2.16, fifth line, delete "MIL-W-13773" and substitute: "MIL-STD-1943".

3.2.19, add new 3.2.19 to read:

"3.2.19 Optical components. Unless otherwise specified on the applicable drawing, all optical components shall meet the requirements of MIL-O-13830 and the applicable drawing."

Redesignate former 3.2.19 to 3.2.19.1.

3.2.19.1, second line, following "with", add: "MIL-B-48611 and".

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:35Z
Check the source to verify that this is the current version before use.

PAGE 13

3.2.21.2, delete and substitute:

"3.2.21.2 Identification application. Methods of identification application shall be as specified on the drawing. If the method of application is not specified on the drawing, the application shall be applied by stamping, etching, engraving, cast, or molded. All other methods of application shall require the approval of the Government Technical Agency."

PAGE 14

3.2.23, second and fifth lines, delete "MIL-C-6021" and substitute: "MIL-STD-2175".

PAGE 15

3.2.28, second line, delete the period and add: "and to the workmanship provisions of applicable specifications."

Add new paragraph 4.1.1:

"4.1.1 Responsibility for compliance. All items shall meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material."

4.2.2.1, fourth line, delete the period and add: "for conformance or interchangeability."

PAGE 16

4.2.2.1, fourth line of page, following "requirements", delete the period and add: "of the applicable specification."

4.2.2.1, sixth line of page, before "results obtained", add: "quantitative and qualitative".

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:35Z
Check the source to verify that this is the current version before use.

Add the following paragraphs:

"4.2.2.1.1 First article inspection for components and subassemblies covered by QAPs/QARs. When required by contract, a first article sample consisting of 3 items (unless otherwise specified) shall be submitted for inspection and approval in accordance with the terms of the contract. As determined by the Government, the sample items shall be subjected to all of the examinations and tests specified in the applicable QAP/QAR and be inspected for compliance with all of the requirements of the applicable drawings.

4.2.2.1.2 First article rejection. If any sample item fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate inspection upon any failure to comply with any of the requirements."

4.2.2.2.1, first line, delete "Major defects." and substitute: "Major characteristics."

4.2.2.2.1, fourth and fifth lines, delete "listing of types of defect characteristics" and substitute: "drawing characteristics,".

4.2.2.2.1, fifth line, last word, delete "defects" and substitute: "characteristics".

4.2.2.2.1.g., delete "Class 3" and substitute: "Class 2".

4.2.2.2.2, first line, delete "Minor defects." and substitute: "Minor characteristics." After "specified," delete "defect".

4.2.2.2.2, second line, delete "defects" and substitute: "characteristics".

4.2.2.2, (incorrectly numbered) delete and substitute 4.2.2.3 to read:

"4.2.2.3 Test methods and procedures. Test methods and procedures applicable to Critical and Major Characteristics shall be established by the contractor and included in his written inspection plan. The contractor's written inspection plan for each characteristic shall be carefully analyzed, and a determination made as to the methods, procedures, equipment, sequence of inspection, and tests for that characteristic that will best insure the acceptance of those products which meet the requirement, and the rejection of those which do not conform."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:35Z
Check the source to verify that this is the current version before use.

4.2.2.4.1, second line, delete "defects" and substitute: "characteristics".

4.2.2.4.1, fourth line, delete "defects" and substitute: "characteristics".

4.2.2.4.1, sixth line, delete "defects" and substitute: "characteristics". (2 places).

4.2.2.4.1, add a last sentence to read: "AQL's apply to each characteristic".

PAGE 18

4.3, delete first sentence and substitute: "Environmental tests shall apply only to the extent specified on the drawing or product specification."

PAGE 32

6.6, redesignate to 6.7 and add new 6.6 to read:

"6.6 Submission of test equipment designs. When the submission of test equipment designs by the contractor to the Government for approval is required by the contract, the contractor is referred to MIL-HDBK-204 for the design of inspection equipment."

*The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment."

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 12GP-A009)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:35Z
Check the source to verify that this is the current version before use.