INCH-POUND
MIL-PRF-3098/32G
w/AMENDMENT 2
4 June 2025
SUPERSEDING
MIL-PRF-3098/32G
w/AMENDMENT 1
22 July 2019

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR54/U

INACTIVE FOR NEW
DESIGN AFTER 4 JUNE 2025

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-3098.

Pertinent characteristics: 50 MHz to125 MHz; fifth mechanical overtone; noncontrolled; series resonance.




FIGURE 1. Crystal unit - CR54/U.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 5955

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:25Z
Check the source to verify that this is the current version before use.

Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.352	---	8.94
B	---	.725	---	18.42
C	.030	.037	0.76	0.94
D	.478	.494	12.14	12.55
E	---	.757	---	19.23
F	.030	.040	0.76	1.02
G	.015	.025	0.38	0.64
H	---	.317	---	8.05
J	---	.775	---	19.69
K	.223	.248	5.66	6.30
L	.048	.052	1.22	1.32
M	.075	.141	1.91	3.58
N	.015	.025	0.38	0.64

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. The pin undercut may be omitted.
4. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Crystal unit - CR54/U - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:25Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 50 MHz to 125 MHz, inclusive.

Capacitance, shunt: 7 pF, maximum.

Frequency tolerance: ±50 parts per million (ppm).

Equivalent resistance: 50 MHz to 90 MHz: 50 ohms, maximum.
90+ MHz to 125 MHz: 60 ohms, maximum.

Mode of oscillation: Fifth mechanical overtone.

Temperature range:

Operating (noncontrolled): -55°C to +105°C, inclusive.

Calibration values:

Resistance: 60 ohms.

Voltage drop: 0.35 volt.

Rated drive level: 1.0 mW, maximum.

Resonance: Series.

Shock: (specified pulse):

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Vibration: MIL-STD-202-201.

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Temperature run:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Aging:

Frequency change permitted: ±5 ppm.

Part or Identifying Number (PIN): CR54/U (followed by specified frequency), see 1.2 of MIL-PRF-3098.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:25Z
Check the source to verify that this is the current version before use.

Qualification inspection is not applicable for this specification sheet. Acceptance testing shall consist of screening, Group A and Group B inspection of MIL-PRF-3098.

Referenced documents. In addition to MIL-PRF-3098, this document references the following:

MIL-STD-202-201

Amendment notations. The margins of this specification sheet are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - EC
Air force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5955-2025-005)

Review activities:
Army - AR, MI
Navy - AS, MC
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:25Z
Check the source to verify that this is the current version before use.