INCH-POUND
MIL-PRF-3098/34H
9 December 2004
SUPERSEDING
MIL-PRF-3098/34G
27 August 1997

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR56/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-3098.

Pertinent characteristics: 50 MHz to 125 MHz; fifth mechanical overtone; noncontrolled; series resonance.




| Inches | mm | Inches | mm |
|---|---|---|---|
| .001 | 0.03 | .192 | 4.88 |
| .002 | 0.05 | .402 | 10.21 |
| .008 | 0.20 | .445 | 11.30 |
| .017 | 0.43 | .500 | 12.70 |
| .150 | 3.81 | .530 | 13.46 |
| .190 | 4.82 | | |

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Crystal unit - CR56/U.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:26Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 50 MHz to 125 MHz, inclusive.

Capacitance, shunt: 7 pF, maximum.

Frequency tolerances:

Operating temperature range: ±50 ppm.

Equivalent resistance:

| MHz | Ohms, maximum |
|---|---|
| 50 to 90 | 50 |
| 90+ to 125 | 60 |

Mode of oscillation: Fifth mechanical overtone.

Operating temperature ranges (noncontrolled): -55°C to +105°C, inclusive.

Drive level, rated: 1.0 mW, maximum.

Resonance: Series.

Shock (specified pulse):

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Vibration: Method 204 of MIL-STD-202, test condition A.

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Thermal shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Aging:

Frequency change permitted: ±5 ppm.

* Reference documents. In addition to MIL-PRF-3098, this document references the following:

MIL-STD-202



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:26Z
Check the source to verify that this is the current version before use.

* The margins of this specification sheet are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR, MI, SM
Navy - AS, CG, MC, OS, SH
Air Force - 19, 99

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5955-0774)

* NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.



Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:26Z
Check the source to verify that this is the current version before use.