INCH-POUND
MIL-PRF-3098/34J
w/AMENDMENT 1
7 January 2020
SUPERSEDING
MIL-PRF-3098/34J
13 April 2010

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR56/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-3098.

Pertinent characteristics: 50 MHz to 125 MHz; fifth mechanical overtone; noncontrolled; series resonance.




FIGURE 1. Crystal unit - CR56/U.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:26Z
Check the source to verify that this is the current version before use.

Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.183	---	4.65
B	---	.435	---	11.05
C	---	.402	---	10.21
D	---	.530	---	13.46
E	.500	---	12.70	---
F	.016	.019	0.41	0.48
G	---	.150	---	3.81
H	.184	.200	4.67	5.08

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Crystal unit - CR56/U - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:26Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 50 MHz to 125 MHz, inclusive.

Capacitance, shunt: 7 pF, maximum.

Frequency tolerances:

Operating temperature range: ±50 ppm.

Equivalent resistance:

MHz	Ohms, maximum
50 to 90	50
90+ to 125	60

Mode of oscillation: Fifth mechanical overtone.

Operating temperature ranges (noncontrolled): -55°C to +105°C, inclusive.

Drive level, rated: 1.0 mW, maximum.

Resonance: Series.

Shock (specified pulse):

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Vibration: MIL-STD-202-204, test condition A.

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Thermal shock:

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Aging:

Frequency change permitted: ±5 ppm.

Part or Identifying Number (PIN): CR56/U (followed by specified frequency), see 1.2 of MIL-PRF-3098.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:26Z
Check the source to verify that this is the current version before use.

Reference documents. In addition to MIL-PRF-3098, this document references the following:

MIL-STD-202-204.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Army - AR, MI, SM
Navy - AS, CG, MC, OS, SH
Air Force - 19

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5955-2020-002)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:26Z
Check the source to verify that this is the current version before use.