A-A-50466
January 24, 1983

COMMERCIAL ITEM DESCRIPTION

OVEN, MICROWAVE, ELECTRIC
(2000 WATT MICROWAVE POWER OUTPUT)

The General Services Administration has authorized the use of this Commercial Item Description in preference to type II, size 2000, class 2 of Federal Specification S-O-1425.

Intended use. This commercial item description covers a 2000 watt (W) commercially rated and approved microwave oven intended for use as a means of preparing and reconstituting food. Household and shipboard use microwave ovens are specifically excluded.

Salient characteristics:

Description. The microwave oven shall include oven enclosure, microwave energy source, power supply, cooking cavity, timer, air filter and other necessary components to make a total serviceable unit. Means shall be provided for protection of the magnetron(s) from damage caused by excessive reflected microwave energy from the cooking cavity under small or no load conditions. The power supply shall be protected against overload conditions by fuses or resettable circuit breakers. The oven shall be designed to permit easy accessibility for maintenance and service.

Standards compliance. The microwave oven shall conform to the applicable requirements of UL 197, UL 923, NFPA No. 70, 21 CFR subchapter J, subparts A and H of 47 of CFR 18, and NSF No. 4.

Cooking power. The oven shall deliver a minimum of 2000 W cooking power.

Cooking cavity. The cooking cavity shall be constructed of stainless steel, rectangular in shape and have a capacity of not less than 24 inches wide, 14 inches in depth and 10 inches in height. The cooking cavity shall have provisions for exhausting cooking vapors.

Electrical characteristics. The microwave oven shall be designed for operation on 208/240 volts (V), 60 Hertz (Hz), single phase, or 220 V, 50 Hz, single phase power as specified. Maximum input power shall be 5500 W. The maximum input power shall be 5500 W. The power cord for 208/240 V units shall be 6 feet and equipped with a 3 wire grounding type plug conforming to NEMA 6-30P.

FSC 7310

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

Controls. All controls shall be located in the front of the oven except the main power disconnect which may be located on the side but readily accessible from the front of the oven. The oven shall be furnished with a main power mechanical ON-OFF switch, a dial type timer, and a push button (or touchplate) timer. The oven shall also have provisions for operation on half power or 1000 W. The dial type timer shall shall range from 0 to a minimum of 20 minutes in intervals of 1 minute or less. The pushbutton type timer shall have not less than six buttons ranging from 10 seconds to a minimum of 2 minutes. The timers shall automatically shut the oven off and indicate this by an audible signal after the completion of the time cycle. The microwave energy source shall be inoperative when the door is opened.

Weight and dimensions. The weight of the microwave oven shall not exceed 220 pounds and oven dimensions shall not exceed the following:

32 inches wide
28 inches high
28 inches deep

Certification. The contractor shall certify that the product offered meets the salient characteristics of the description and conforms to the producers own drawings, specifications, standards, quality assurance practices, and is the same as the product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery, and thereafter, as may be otherwise provided for under the provisions of the contract.

Recovered materials. Manufacturers are encouraged to utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. Unless otherwise specified in the contract or purchase order, the packaging and packing shall be in accordance with the contractors standard commercial practice and shall assure acceptance by common carrier and provide product protection against deterioration, loss, and damage during shipment. The shipping container shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification. Marking shall be as specified in the contract or purchase order.

NOTES:

Acquisition activity should specify electrical requirement.

Code of Federal Regulations (CFR) are available from the Superintendent of Documents, Government Printing Office, Washington, DC 20402.

NEMA Standards are available from the Superintendent of Documents, 2101 L Street, NW., Washington, DC 20037.

NFPA Standards are available from the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.

NSF Standards are available from the National Sanitation Foundation, P. O. Box 1468, Ann Arbor, MI 48106.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

UL Standards are available from the Underwriters' Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.

National Motor Freight Classification Standards are available from the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N. W., Washington, DC 20036.

Uniform Freight Classification Standards are available from the Uniform Clasification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review Activity

Army - MD

User Activities

Army - CE
Navy - MS

CIVIL AGENCY COORDINATING ACTIVITY:

VA-OSS

PREPARING ACTIVITY:

Navy - YD

Project No. 7310-0652

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.