A-A-50467
January 24, 1983

COMMERCIAL ITEM DESCRIPTION

OVEN, MICROWAVE, ELECTRIC
(1300-1400 WATT MICROWAVE POWER OUTPUT)

The General Services Administration has authorized the use of this Commercial Item Description in preference to type II, size 1200, groups 1 and II, size 1200, groups 1 and 2, classes 1 and 2, styles 2 and 3 of Federal Specification S-O-1425.

Intended use. This commercial item description covers a 1300 or 1400 watt (W) commercially rated and approved microwave oven intended for use as a means of preparing and reconstituting food. Household and shipboard use microwave ovens are specifically excluded.

Salient characteristics:

Description. The microwave oven shall include oven enclosure, microwave energy source, power supply, cooking cavity, controls/timer, air filter and other necessary components to make a total serviceable unit. Means shall be provided for protection of the magnetron(s) from damage caused by excessive reflected microwave energy from the cooking cavity under small or no load conditions. The power supply shall be protected against overload conditions by fuses or resettable circuit breakers. The oven shall be designed to permit easy accessibility for maintenance and service.

Standards compliance. The microwave oven shall conform to the applicable requirements of UL 197, UL 923, NFPA No. 70, 21 CFR subchapter J, subparts A and H of 47 of CFR 18, and NSF No. 4.

Cooking power. The oven shall deliver a minimum of 1300 W cooking power.

Cooking cavity. The cooking cavity shall be constructed of stainless steel, rectangular in shape and have a capacity of not less than 1320 cubic inches. The cooking cavity shall have provisions for exhausting cooking vapor.

Electrical characteristics. The microwave oven shall be operated on 208/240 volts, 60 Hertz, single phase, alternating current. The maximum input power shall be 3500 W. The power cord shall be 6 feet minimum fitted with a 3 wire grounding type plug conformed to UL 498.

Controls. Each oven shall be equipped with a main power ON-OFF switch, and/or timer with ON, OFF, and timed functions. The timer shall automatically shut the oven off and indicate by an audible signal after the completion of the timing cycle. The microwave energy source shall be inoperative when the door is opened.

FSC 7310

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:42Z
Check the source to verify that this is the current version before use.

Style 1, pushbutton (or touchplate) timer. The style 1 timer shall have a minimum of six different time selection buttons or touchplates. The timer setting shall be capable of being adjusted anywhere from 5 seconds to not less than 90 seconds cooking duration.

Style 2, combination dial and pushbutton timer. The style 2 timer shall include a style 1 timer and a dial timer. The dial timer shall be provided with a minimum time setting of 1 through 8 minutes in 15 second intervals.

Power level selector. The oven with a style 2 timer shall be provided with a minimum of three power level selections: Full Power, one-half rated power, and a defrosting cycle.

Certification. The contractor shall certify that the product offered meets the salient characteristics of the description and conforms to the producers own drawings, specifications, standards, quality assurance practices, and is the same as the product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery, and thereafter, as may be otherwise provided for under the provisions of the contract.

Recovered materials. Manufacturers are encouraged to utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. Unless otherwise specified in the contract or purchase order, the packaging and packing shall be in accordance with the contractors standard commercial practice and shall assure acceptance by common carrier and provide product protection against deterioration, loss, and damage during shipment. The shipping container shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification. Marking shall be as specified in the contract or purchase order.

NOTES:

Acquisition activity should specify style of timer required.

Code of Federal Regulations (CFR) are available from the Superintendent of Documents, Government Printing Office, Washington, DC 20402.

NFPA Standards are available from the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.

NSF Standards are available from the National Sanitation Foundation, P. O. Box 1468, Ann Arbor, MI 48106.

UL Standards are available from the Underwriters' Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:42Z
Check the source to verify that this is the current version before use.

National Motor Freight Classification Standards are available from the American Trucking Associations, Inc., Traffic Department, 1616 P Street, N. W., Washington, DC 20036.

Uniform Freight Classification Standards are available from the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

User Activity

Navy - MS

CIVIL AGENCY COORDINATING ACTIVITY:

VA - OSS

PREPARING ACTIVITY:

Navy - YD

Project No. 7310-0652

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:42Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:42Z
Check the source to verify that this is the current version before use.