A-A-50469
June 1, 1983

COMMERCIAL ITEM DESCRIPTION

HOOK, REGULAR EYE, LATCH TYPE

The General Services Administration has authorized the use of this commercial item description in preference to style B, type I, class I of Military Specification MIL-H-19253C.

Intended use. This commercial item description applies to latch type hooks that support a load in a direct-pull configuration, and such load is carried in the base (bowl-saddle) of the hook. The hook is intended for use in material handling operations.

Salient characteristics:

Requirements. Hoist hooks shall be as specified herein and shall be in accordance with the basic requirements shown in table I for the rated capacity and throat openings. Hooks of a rated capacity greater than specified in this table will be acceptable provided they meet all other requirements. The hook shall have a latch type closure device to bridge the throat opening of the hook. The hook shall be constructed with a fixed lifting eye in the same plane as the throat opening.

TABLE I. Basic requirements.

Rated capacity Short tons (2000 pounds)	Inside eye diameter (minimum) (inches)		Throat opening w/latch (minimum) (inches)
	Carbon steel	Alloy steel	
1.5	1.125	0.875	0.875
2.0	1.250	1.125	0.937
2.5	1.250	1.250	1.000

Material. The hooks shall be constructed of carbon steel or of an alloy steel that will produce hooks conforming to the requirements specified herein. The hook material shall have sufficient ductility to permanently deform before failure. The hook shall be zinc-coated in accordance with the manufacturer's standard practice.

Defects. There shall be no defects when magnetic particle inspected over the entire area of the hook in accordance with ASTM A275, Magnetic Particle Examination of Steel Forgings. A defect is defined as a linear indication revealed by magnetic particle inspection that is greater than 0.125 inch long and whose length is equal to or greater than three times its width.

Rated capacity. The hooks, when used in various material handling operations in lifting and turning moving cargo, shall not be utilized with loads greater than the rated capacity specified in table I.

Tested capacity. The hooks shall lift and hold a load equal to not less than two times the rated capacity of the hook. Tests and examinations shall be in accordance with ANSI B30.10-1.1.2.

Hook-latch assembly. The latch assembly shall be manufactured of noncorrosive metal or have an all weather anticorrosive finish. The latch assembly shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

bridge the throat opening in the closed position and retain loose slings or other hoisting devices under slack conditions. Unlocking the latch may be accomplished manually or by other methods.

Identification marking. Each hook shall be permanently and legibly marked with the rated capacity in short tons (2,000 pound/ton).

Contractor certification. The contractor shall certify that the product offered meets the salient characteristics of this description; that the product conforms to the manufacturer's own drawings, specifications, standards, and quality assurance practices; and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Regulatory requirements. Manufacturers are encouraged to utilize recovered materials to the maximum extent possible.

Preservation, packaging, packing, labeling, and marking. Unless otherwise specified in the contract or purchase order, the preservation, packaging, and packing shall be in accordance with the contractor's standard commercial practice and shall assure acceptance by common carrier and provide product protection against deterioration, loss, and damage during multiple shipments, handling, and storage. The shipping container shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification. Labeling and marking shall be as specified in the contract or purchase order.

Notes. Purchasers should specify size.

ANSI standards are available from the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.

ASTM standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

National Motor Freight Classification standards are available from American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.

Uniform Freight Classification standards are available from Uniform Classification Committee, Tariff Publishing Officer, Room 2206, 222 South Riverside Plaza, Chicago, IL 60606.

MILITARY INTERESTS:

Custodians

Navy - YD
Air Force - 99

Review Activities

Air Force - 82
DLA - IS

User Activities

Navy - SH, OS

PREPARING ACTIVITY:

Navy - YD

Project No. 4030-0184

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.