A-A-50481
15 November 1985

COMMERCIAL ITEM DESCRIPTION

DISHWASHING MACHINES, COMMERCIAL (RACK, STATIONARY)

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification OO-D-431E.

This Commercial Item Description covers the requirements for single tank manually fed, spray type, stationary rack, automatically controlled, commercial dishwashing machines.

The dishwashing machines are intended to be used to uniformly wash and rinse eating and drinking utensils in installations requiring large-scale service of food to governmental employees (Federal and Military).

Requirements. The dishwashing machine shall conform to the requirements of ASTM F857 with the following exceptions:

a. Steam, electric and gas boosters must raise the final rinse temperature a minimum of 60 degrees fahrenheit.

b. Acceptable evidence of meeting the requirements of NSF No. 3 or Criteria C-2 shall be as follows:

(1) A listing in the current edition of the NSF Listing of Food Service Equipment and display of the NSF seal on the finished dishwasher.

(2) A certification for the dishwasher issued by NSF under their special one-time contract evaluation/certification service; or

(3) A certified test report acceptable to the contracting officer with the advise of the Army Surgeon General from an independent testing laboratory indicating that the dishwasher has been tested and conforms to NSF.

c. Machine identification shall include a stainless steel identification plate showing the manufacturer's name or trademark, model number, serial number, contract number and a national stock number. Use of removable labels or plates is not permitted.

d. Requirements for machine manuals supplied with equipment to DoD agencies shall be outlined in the DLA contract.

FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

AMSC N/A

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:43Z
Check the source to verify that this is the current version before use.

Quality assurance provisions.

Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the government.

Examination. Each dishwasher shall be examined for compliance with the requirements of ASTM F857 and those specified herein. This element of inspection shall encompass all visual examinations and dimensional measurements.

Operational test. Each dishwashing machine shall be operated at least one hour without dishes or racks to determine compliance with the requirements of this Commercial Item Description. The test shall reveal that the assembly of component parts is complete and properly interrelated; that moving parts evidence no undue vibration, noise, or overheating of bearings, and that controls operate smoothly and positively.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practical.

Packaging, packing, palletization, and marking.

Domestic shipments. Each dishwasher shall be packaged in accordance with the contractor's standard practice in a manner to prevent corrosion, deterioration, and damage. Each dishwasher shall be packed in a container for arrival at destination in a satisfactory condition. Preparation for delivery shall comply with applicable carrier rules and regulations.

Export shipments. Each dishwasher shall be packaged in accordance with the contractor's standard practice in a manner to prevent corrosion, deterioration and damage. Parts removed shall be packaged in a fiberboard box conforming to PPP-B-636, class weather-resistant, and closed method IV in accordance with the appendix of PPP-B-636. Each dishwasher and any removed parts shall be packed in an exterior shipping container conforming to one of the following:

(1) PPP-B-601, overseas type, style A or J, grade B, type 2 load
(2) PPP-B-621, class 2, style 2 or 4, grade B
(3) MIL-C-104, type I, class 1 or 2, style A

The contents shall be cushioned, blocked, braced, and waterproofed in accordance with MIL-STD-1186. Boxes shall be closed and strapped in accordance with the appendix of the applicable box specification.

Palletization (for domestic and export shipments). Loads shall be palletized in accordance with MIL-STD-147.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

Marking. Marking shall be in accordance with FED-STD-123.

NOTES: Purchaser shall specify type, style, class, and group machine required.

ASTM standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

NSF Standards are available from the National Sanitation Foundation, 3475 Plymouth Road, P. O. Box 1468, Ann Arbor, MI 48106.

Copies of Uniform Freight Classification are available at the Uniform Classification Committee, Tariff Publishing Officer, Room 2206, 222 South Riverside Plaza, Chicago, IL 60606.

MILITARY INTEREST:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review Activities

Army - MD
Navy - SA
Air Force - 84

User Activities

Navy - MS, CG, MC
DLA - GS

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - 9FC
HHS - FDA
EPA - PM-215

PREPARING ACTIVITY

Navy - YD

DoD Project 7320-0776

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.