| INCH-POUND |

A-A-50486A
November 23, 1992
SUPERSEDING
A-A-50486
June 23, 1987

COMMERCIAL ITEM DESCRIPTION

CONTAINER, INSULATED, SHIPPING

The General Services Administration has authorized the use of this commercial item description.

Abstract The containers covered by this commercial item description are used for temporary storage of frozen food for periods up to 24 hours.

Salient characteristics

1. Classification. The containers covered by this commercial item description shall be essentially cube shaped and of the following minimum sizes as specified in the contract or order·

   Size I. 5 cubic feet interior.

   Size II: 43 cubic feet interior

   Size III: 56 cubic feet interior The Size III container shall be of the following styles as specified in the contract or order:

   Style A Mounted on steel legs on runners

   Style B Mounted on wheels

2. Construction The containers shall be so designed and be of such material and workmanship as to be smooth, easily cleanable, and durable In addition, all interior surfaces shall be easily accessible for cleaning, nontoxic corrosion-resistant, and consist of nonabsorbent material

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to· Commanding Officer (Code 156), Naval Construction Battalion Center, 621 Pleasant Valley Road, Port Hueneme, CA 93043-4300.

FSC 8145

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

3 Insulation The type of insulation used shall be such that when the containers are fully loaded with chopped frozen vegetables, the interior temperature of all containers specified herein shall not raise more than 10 degrees Fahrenheit in a 24 hour period, with an outside temperature-differential of 90 degrees Fahrenheit

4 Size I The container shall be collapsible Interior volume of the container shall be not less than 5 cubic feet and not greater than 8 cubic feet. The walls, top, and underside of the container shall be constructed of heavy duty nylon reinforced with vinyl. The bottom shall reinforced to maintain the container's floor shape The opening of the container shall be secured by two locking buckles Two carrying straps made of nylon webbing shall be attached. The carrying straps shall be strong enough to permit lifting a fully loaded container without cracking, breaking, or permanent distortion

5 Size II The inner and outer walls of the container shall be constructed of sheet steel The container shall be equipped with two side-by-side doors mounted on steel hinges Doors shall be capable of opening 270 degrees and shall be equipped with positive self-locking latches. Four securely mounted wheels shall be mounted to the underside of the container. The two rear wheels shall be fixed and the two forward wheels shall be of free swiveling type and all wheels shall be equipped with foot operated locking brakes. All wheels shall be not less than 6 inches in diameter and 2 inches in width and shall be leveled to minimize superstructure twisting and flexing

6. Size III The outer walls of the container shall be constructed of steel and the inner walls constructed of aluminum. The container shall be equipped with side-by-side doors mounted on hinges. Doors shall be capable of opening 270 degrees and shall be equipped with positive self-locking latches The Size III shall be Style A or Style B as specified in the contract or order When Style A is required, the underside of the Size III container shall be mounted on steel legs on runners When Style B is required, the underside of the Size III container shall be mounted on four securely mounted wheels with solid rubber tires. The two rear wheels shall be fixed and the two forward wheels shall be of the free swiveling type and all wheels shall be equipped with foot operated locking brakes All wheels shall be not less than 6 inches in diameter and 2 inches in width and shall be leveled to minimize superstructure twisting and flexing

Regulatory requirements The offerer/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Quality assurance provisions. The contractor shall certify, and maintain objective quality evidence, that the product offered meets the CID, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practice The Government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.

ITY

Pres
pacl
or c

CID
numt
requ

F

INCH-POUND

A-A-50486A
November 23, 1992
SUPERSEDING
A-A-50486
June 23, 1987

COMMERCIAL ITEM DESCRIPTION

CONTAINER, INSULATED, SHIPPING

erviçes Administration has authorized the use of this
em description.

Note

iners covered by this commercial item description are used
e of frozen food for periods up to 24 hours

a

ics

b

n The containers covered by this commercial item
nall be essentially cube shaped and of the following minimum

c

ified in the contract or order

cubic feet interior

MILI

cubic feet interior.

Mili

cubic feet interior. The Size III container shall be of

Na

e following styles as specified in the contract or order.

Cust

Mounted on steel legs on runners

Ar
Na
tract

Mounted on wheels

Revi

The containers shall be so designed and be of such
orkmanship as to be smooth, easily cleanable, and durable
all interior surfaces shall be easily accessible for

Ar
DL

toxic corrosion-resistant, and consist of nonabsorbent

(recommendations, additions, deletions) and any pertinent
f use in improving this document should be addressed to
(Code 156), Naval Construction Battalion Center,
Road, Port Hueneme, CA 93043-4300.

FSC 8145

NT A. Approved for public release; distribution is

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:43Z
Check the source to verify that this is the current version before use.