COMMERCIAL ITEM DESCRIPTION

PUBLIC ADDRESS SET, SOLID STATE, 100 WATT

The General Services Administration has authorized the use of this commercial item description.

This Commercial Item Description covers a complete Public Address Set encompassing amplifier, loudspeakers, microphone with stand, and interconnecting cabling.

Design. The Address Set shall consist of one 100 watt (minimum), solid state amplifier, four trumpet speakers with drivers, two paging speakers, one dynamic microphone with adjustable floor stand, and required accessory terminal fittings and hardware. The set shall conform to the design and functional test requirements of Underwriters Laboratory (UL) 813 Standard and the wiring and design requirements of National Fire Protection Association (NFPA) 70.

Salient characteristics. The set shall have the following physical and performance characteristics:

A. Amplifier

Construction - Solid state with integral power supply transformer isolated from the power supply.
Output voltage - 25 or 70.7 volt speaker lines.
Microphone precedence - Wire for microphone precedence over other inputs.
Minimum signal inputs - High and low impedance microphone, high impedance auxiliary input.
Minimum outputs - Four output terminals with sufficient circuit protective provisions to protect against shorted or partially shorted circuits.
Response - Frequency response flat to within plus or minus 2.0 decibles (db) over 80 to 1,200 Hertz (Hz) at full rated load impedance.
Distortion - Less than 3 percent at full rated power over the frequency response range.
Hum and noise - Not greater than -65 db for microphone and -70 db for auxiliary.
Controls - ON/OFF switch, power on indicator, independent volume control each input, master volume control, treble and bass control.
Voltage input - 120 volt AC 60 Hz.

FSC 5830

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:43Z
Check the source to verify that this is the currentversion before use.

Power cord - Type SJO with minimum size Number 18 American Wire Gage stranded copper conductors, connectors conforming to NEMA WD-1 configuration 5-15P.
Input jacks - XLR type compatible with cable connector.
Signal to noise ratio - 75 to 110 db.

B. Loudspeakers

Horns

Dispersion angle - not less than 110 degrees (°).
Low frequency cutoff - equal to or less than 300 hz.
Built-in driver or mounting provisions for compatible driver unit.

Horn drivers

Input impedance - matched to amplifier output.
No damage to speakers at maximum driver ouput power.
Frequency response - flat within plus or minus 3 db from 300 hz to 12,000 hz.

Paging loudspeakers

Dispersion angle - Not less than 110°.
frequency response - 300 hz to 12,000 hz.
Impedance - matched to amplifier output impedance.

Construction - Weatherproof with adjustable mounting brackets.

C. Microphone

Type - dynamic.
Control - ON/OFF switch.
Connecting cable - minimum 24 foot shielded with XLR type male connector.
Pickup pattern - Semidirectional or cardiod.
Frequency response - Flat within plus or minus 3 db from 80 to 12,000 hz.
Mounting - Adjustable height floor stand with variable tilting provisions for microphone.

Wiring diagrams. A wiring diagram of the address set and amplifier shall be suitably protected and attached within the amplifier enclosure and be readily accessible.

Operating instructions. Complete operating and maintenance instructions shall be provided with each set.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:43Z
Check the source to verify that this is the currentversion before use.

Workmanship. The sets shall be free of imperfections that may affect appearance, serviceability, or durability. All parts shall be cleaned and free of extraneous materials. Burrs and sharp edges shall be removed.

Certification. The contractor shall specify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial market place. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under provisions of the contract.

Packing. Each set shall be packaged for shipment in accordance with commercial practices that shall assure acceptance by common carrier and provide product protection against loss and damage during multiple shipment, handling, and storage. Marking for shipment shall be as specified in the contract or order.

MILITARY INTEREST:

Custodian

Navy - YD

PREPARING ACTIVITY

Navy - YD

Project No. 5830-0072

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:43Z
Check the source to verify that this is the current version before use.