INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

CUTTER, CABLE, HAND OPERATED

This Interim Amendment was developed by the U.S. Army Natick Laboratories (GL), Natick, Massachusetts, based on currently available technical information. This Interim Amendment has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy and the Air Force. It is recommended that Federal Agencies use it in procurement. The General Services Administration has authorized the use of this Interim Amendment as a valid exception to Federal Specification GGG-C-749a, dated March 29, 1954, and Interim Amendment 1 (NAVY-Ships), dated August 7, 1959.

Page 1, paragraph 2.1—Add the following:

"FEDERAL STANDARDS

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels

Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies)

Fed. Test Method Std. No. 151—Metals; Test Methods"

Delete "Federal Specifications," and all the specifications listed under this heading.

Add the following:

"MILITARY SPECIFICATIONS

MIL–H–15424—Hand Tools, Packaging Of"

Under "Military Standards," add the following:

MIL–STD–129—Marking for Shipment and Storage

MIL–STD–130—Identification Marking of U.S. Military Property"

Page 1, paragraph 3.1.1: Add at end of sentence "or shall have a corrosion-resisting finish."

Page 2, paragraph 3.3, line 2—Delete "29" and substitute "32".

Page 2, paragraph 3.4, line 10—Delete "three-fourths of an" and substitute "15/32".

Page 3, add the following new paragraph

"**3.15 Marking for identification.** The cable cutters shall be marked for identification in accordance with Standard MIL–STD–130."

Pages 3, 4 and 5, paragraphs 4.1 thru 4.6—Delete and substitute the following:

FSC 5110

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:42Z
Check the source to verify that this is the current version before use.

"**4.1 Responsibility for inspection.** Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in Standard MIL-STD-105, except where otherwise indicated herein.

4.2.1 *Inspection of materials and components.* In accordance with 4.1 above, the supplier is responsible for insuring that materials and components used were manufactured, tested and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified herein, or, if none, in accordance with this specification.

4.2.1.1 *Intermediate testing.* The cutting blades shall be tested for hardness as specified in 4.4.1 prior to assembly. A lot shall consist of all the blades of one type offered for acceptance at one time. The sample unit shall be one completely fabricated cutting blade. Any determination not within the specified requirements shall constitute a defect. The inspection level shall be L4, with an acceptable quality level (AQL) of 4.0, expressed in terms of defects per hundred units.

4.2.2 *Inspection of the end item.* Inspection of the cutters shall be performed as specified in paragraphs 4.2.2.1 and 4.2.2.2. A lot shall consist of all the cutters of one type offered for acceptance at one time. The sample unit shall be one completely fabricated and assembled cutter.

4.2.2.1 *Visual examination.* Each sample unit shall be visually examined for the defects set forth below. The inspection level shall be level II, with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

4.2.2.2 *Examination for dimensions and weight.* Each sample unit shall be examined for defects in dimensions and weight. Any deviation from specified requirements shall constitute a defect. The inspection level for the dimensional examination shall be L6, with an acceptable quality level (AQL) of 4.0, expressed in terms of defects per hundred units. The inspection level for the weight examination shall be I, with an acceptable quality level (AQL) of 1.5, expressed in terms of defects per hundred units.

4.2.3 *End item testing.* The cutters shall be tested as specified in 4.4.2. A lot shall consist of all the cutters of one type offered for acceptance at one time. The sample unit shall be one completely fabricated and assembled cutter. Any determination not within the specified requirements shall constitute a defect. The inspection level shall be L4, with an acceptable quality level (AQL) of 4.0 defects, expressed in terms of defects per hundred units.

4.3 Inspection of preparation for delivery. Unless otherwise specified (see 6.1), the inspection to determine compliance with preparation for delivery requirements shall be performed in accordance with Specification MIL-H-15424 (see 6.1).

4.4 Tests.

4.4.1 *Blade hardness test.* The cutting blade shall be subjected to the Rockwell hardness test, Method 243.1 of Federal Test Method Standard No. 151, to determine compliance with 3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification	
		Major	Minor
Finish	Indication of rust	X	
	Scratch or mar		X
	Not smoothly finished; color not as specified		X
	Area of no film		X
Design	Any characteristic not in accordance with the specified requirements.	X	
Construction and workmanship general (applicable to all components and assemblies).	Part missing, or not specified type	X	
	Fractured, split, punctured, sprung, malformed, or otherwise impaired.	X	
	Sharp bur or sliver	X	
	Functioning component that is inoperative, or will not function as intended.	X	
	Not connected or joined as specified	X	
	Adjustable assembly that cannot be adjusted	X	
	Hydraulic system leaks	X	
	Cutting blades not replaceable		X
Rivets	Missing, not approved type, loose, broken or inadequately peened.		X
Bolts, nuts, screws, and other types of threaded components.	Missing, not approved type, broken, threads stripped, or fractured	X	
Marking	Missing or illegible		X
Assembly	Component not properly assembled e.g., threaded component cross threaded.	X	
	Assembly or component improperly located e.g., gasket improperly fitted causing leakage.	X	

4.4.2 *Performance test.* The cutter shall be tested for performance to determine compliance with 3.6, 3.7, 3.12.1, 3.13.1, and 3.13.3."

Page 5—Delete section 5 in its entirety and substitute:

"5. PREPARATION FOR DELIVERY

Federal Standard No. 102 shall be referred to for definitions and application of the various levels of preservation, packaging and packing for civilian agency procurements.

5.1. Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.2).

5.1.1 *Level A.* Each cable cutter shall be preserved and packaged in accordance with the level A requirements of Specification MIL–H–15424.

5.1.2 *Level C.* Cable cutters shall be preserved and packaged in accordance with the industry's practice.

5.2. Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 *Level A.* Cable cutters, preserved and packaged as specified in 5.1, shall be packed in accordance with the level A requirements of Specification MIL–H–15424.

5.2.2 *Level B.* Cable cutters, preserved and packaged as specified in 5.1, shall be

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:42Z
Check the source to verify that this is the currentversion before use.

packed in accordance with the level B requirements of Specification MIL-H-15424.

5.2.3 *Level C.* Cable cutters, preserved and packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

5.3 Marking.

5.3.1 *Civilian agencies.* In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Federal Standard No. 123.

5.3.2 *Military requirements.* In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Standard MIL-STD-129."

Page 5, paragraph 6.1—Delete subparagraph "(c)" and substitute:

"(c) Selection of applicable levels of preservation and packaging and packing (see 5.1 and 5.2)."

Add the following:

"(d) When different method of inspection of preparation for delivery is required (see 4.3)."

Page 6, section 7—Delete in its entirety.

Custodian:
Army—GL
Navy—Ships
Air Force—MOA

Project No. 5110-0143

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.