GGG-D-694a
AMENDMENT—2
November 18, 1963

SUPERSEDING
Interim Amendment—1
February 16, 1961

FEDERAL SPECIFICATION

DRILL, MASONRY, ROTARY DRIVEN

This amendment, which forms a part of Federal Specification GGG-D-694a, dated May 27, 1960, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

Page 1, paragraph 2.1: Delete MIL-P-15424 in its entirety and substitute the following:

"MIL-H-15424—Hand Tools, Packaging of."

Page 2, paragraph 3.3: Delete the fourth, fifth and sixth sentences, and substitute the following: "The shank shall be concentric with the body within a maximum of 0.025 inch run out (total indicator reading). The outer edge of each carbide tip shall be in a circle, concentric with the body diameter at the drilling end."

Page 3, table I: Delete and substitute new table I.

Page 5, paragraph 4.6: Delete and substitute:

4.5.3 *Concentricity test.* The shank and body shall be tested for concentricity, using a V-block and dial indicator gage, or any other equally accurate method to determine compliance with 3.3. Drills having a run out greater than 0.025 inch (total indicator reading) shall be considered defective.

Page 5, paragraphs 5.1.1, 5.2.1, 5.2.2 and 5.3.2, last line: Delete "MIL-P-15424" and substitute "MIL-H-15424".

Pages 5 and 6, paragraph 6.2: Delete and substitute the following:

6.2 Transportation description. Transportation descriptions and minimum weights applicable to this commodity are:

Rail:

Tools, not otherwise indexed by name. Carload minimum weight 30,000 pounds.

Motor:

Tools, hand, not otherwise indexed. Truckload minimum weight 30,000 pounds, subject to Rule 115, National Motor Freight Classification.

FSC 5130

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.

TABLE I.—*Drills, masonry, carbide tipped, core type, rotary*

Size	Body diameter		Carbide tip diameter[1]	Shank diameter ± 0.010	Overall length
Nominal	Min.	Max.			Min.
Inches	*Inches*	*Inches*	*Inches*	*Inch*	*Inches*
1/2	0.470	0.500	0.525	0.375	6
9/16	.532	.562	.587	.375	6
5/8	.595	.625	.650	.375 or .500	8
5/8	.595	.625	.650	.500	6
11/16	.657	.687	.712	.375 or .500	8
11/16	.657	.687	.712	.500	6
3/4	.720	.750	.775	.500	8
13/16	.720	.812	.837	.500	8
7/8	.802	.875	.900	.500	10
1	.928	1.000	1.025	.500	10
1-1/8	1.055	1.125	1.155	.500	10
1-1/4	1.176	1.250	1.280	.500	10
1-3/8	1.301	1.375	1.405	.500	10
1-1/2	1.425	1.500	1.525	.500	11
1-5/8	1.550	1.625	1.655	.500	11
1-3/4	1.720	1.750	1.780	.500	11
1-7/8	1.720	1.875	1.905	.500	11
2	1.970	2.000	2.030	.500 or .750	11
2-1/8	2.095	2.125	2.157	.750	12
2-1/4	2.220	2.250	2.281	.750	15
2-3/8	2.345	2.375	2.406	.750	15
2-1/2	2.470	2.500	2.531	.750	15
2-5/8	2.595	2.625	2.656	750	15
2-3/4	2.720	2.750	2.781	.750	15
2-7/8	2.845	2.875	2.906	.750	15
3	2.970	3.000	3.312	.750 or 1.000	15
3-1/4	3.220	3.250	3.281	.750 or 1.000	15
3-1/2	3.470	3.500	3.531	.750 or 1.000	15
3-3/4	3.720	3.750	3.781	.750 or 1.000	15
4	3.970	4.000	4.031	.750 or 1.000	15

[1] Drills with a carbide tip diameter of up to 3/4-inch drill diameter shall have a tolerance of $^{+\ 0.010}_{-\ 0.000}$, drills with carbide tip diameters from 13/16 inch to 1-1/2 inches shall have a tolerance of $^{+\ 0.015}_{-\ 0.000}$, and drills with a carbide tip diameter 1-5/8 inches and above drill diameter shall have a tolerance of $^{+\ 0.031}_{-\ 0.000}$.

MILITARY CUSTODIANS:

Navy—Sh
Air Force—MOA

☆ U.S. GOVERNMENT PRINTING OFFICE: 1963—703350/181

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.