INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

DRILL, MASONRY, ROTARY DRIVEN

This Interim Amendment was developed by the General Services Administration, Federal Supply Service, Standardization Division, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use this Interim Amendment in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized Federal agencies to use this Interim Amendment as a valid exception to Federal Specification GGG-D-694A, dated May 27, 1960, and Amendment-2 thereto, dated November 18, 1963.

PAGE 1

Paragraph 2.1 Under "Military Specification:" delete "MIL-P-15424" in its entirety and substitute the following:

"MIL-H-15424 - Hand Tools, Packaging of."

PAGE 2

Paragraph 3.3 Delete the fourth, fifth and sixth sentences, and substitute the following:

"The shank shall be concentric with the body within a maximum of 0.025 inch run out (total indicator reading). The outer edge of each carbide tip shall be in a circle, concentric with the body diameter at the drilling end."

Paragraph 3.3 Delete the seventh sentence and substitute the following:

"The design of the shank shall be straight, either round or hexagonal, and of sufficient length to function efficiently in performing satisfactory work within its size range."

Paragraph 3.4, line 2. Delete "92" and substitute "90.5".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.

PAGE 3

Table 1. Delete and substitute new table 1:

TABLE I. Drills, masonry, carbide tipped, core type, rotary

Size	Body diameter		Carbide tip diameter[1]	Shank diameter or distance across flats ±0.010	Overall length Min.
Nominal	Min.	Max.			
Inches	Inches	Inches	Inches	Inch	Inches
1/2	0.470	0.500	0.525	0.375	6
9/16	.532	.562	.587	.375	6
5/8	.595	.625	.650	.375 or .500	8
5/8	.595	.625	.650	.500	6
11/16	.657	.687	.712	.375 or .500	8
11/16	.657	.687	.712	.500	6
3/4	.720	.750	.775	.500	8
13/16	.720	.812	.837	.500	8
7/8	.802	.875	.900	.500	10
1	.928	1.000	1.025	.500	10
1-1/8	1.055	1.125	1.155	.500	10
1-1/4	1.176	1.250	1.280	.500	10
1-3/8	1.301	1.375	1.405	.500	10
1-1/2	1.425	1.500	1.525	.500	11
1-5/8	1.550	1.625	1.655	.500	11
1-3/4	1.720	1.750	1.780	.500	11
1-7/8	1.720	1.875	1.905	.500	11
2	1.970	2.000	2.030	.500 or .750	11
2-1/8	2.095	2.125	2.157	.750	12
2-1/4	2.220	2.250	2.281	.750	15
2-3/8	2.345	2.375	2.406	.750	15
2-1/2	2.470	2.500	2.531	.750	15
2-5/8	2.595	2.625	2.656	.750	15
2-3/4	2.720	2.750	2.781	.750	15
2-7/8	2.845	2.875	2.906	.750	15
3	2.970	3.000	3.312	.750 or 1.000	15
3-1/4	3.220	3.250	3.281	.750 or 1.000	15
3-1/2	3.470	3.500	3.531	.750 or 1.000	15
3-3/4	3.720	3.750	3.781	.750 or 1.000	15
4	3.970	4.000	4.031	.750 or 1.000	15

[1] Drills with a carbide tip diameter of up to 3/4-inch drill diameter shall have a tolerance of + 0.010 - 0.000,

drills with carbide tip diameters from 13/16 inch to 1-1/2 inches shall have a tolerance of + 0.015 - 0.000,

and drills with a carbide tip diameter 1-5/8 inches and above drill diameter shall have a tolerance of ..... + 0.031 - 0.000.

PAGE 4

Paragraph 4.5.2.1 (d) line 6. Delete "18" and substitute "50".

PAGE 5

Paragraph 4.6 Delete and substitute:

4.5.3 Concentricity test. The shank and body shall be tested for concentricity, using a V-block and dial indicator gage, or any other equally accurate method to determine compliance with 3.3. Drills having a run out greater than 0.025 inch (total indicator reading) shall be considered defective.

Paragraphs 5.1.1, 5.2.1, 5.2.2 and 5.3.2, last line. Delete "MIL-P-15424" and substitute "MIL-H-15424".

PAGES 5 AND 6

Paragraph 6.2 Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.