GGG-G-670
INTERIM AMENDMENT 2
April 9, 1976
SUPERSEDING
INTERIM AMENDMENT 1
November 20, 1961

INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

GRASS HOOKS, WHIP GRASS CUTTERS, AND WHIP WEED CUTTERS

This Interim amendment was developed by the General Services Adminstration, Federal Supply Service, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim amendment as a valid exception to Federal Specification GGG-G-670, dated April 19. 1956.

PAGE 3

Paragraph 3.7: Delete last sentence and substitute: "Exposed surfaces of short handles equipped with metal ferrules shall be protected with a durable coating of paint, enamel, varnish, lacquer or lacquer wax. Exposed surfaces of short handles equipped with non-metallic ferrules shall be protected with a durable clear coating of varnish, lacquer or lacquer wax."

PAGE 6

Paragraph 3.12.1: Delete last sentence and substitute: "Unless otherwise specified (see 6.2), the blade shall be securely fastened either with rivets or bolts (see 6.4). Bolted-on blades shall be readily detachable for resharpening or replacement. Rivets securing blades to the handles shall fit snugly into the rivet holes and have heads neatly peened."

Paragraph 3.12.2: Delete the last sentence and substitute: "The shank shall extend into the handle sufficiently to permit secure and permanent attachment. In the event that round shanks without riveted-on handles are furnished, the shank portion extending into the handle snall be provided with at least one wing-type lug projecting from each side of the shank to prevent the handle from twisting or loosening."

PAGE 7

Paragraph 3.12.4: Delete paragraph and substitute the following:

3.12.4 Ferrules. Ferrules shall be made of steel other suitable metals or nigh impact strength plastic and shall be of such design that, when attached, the ferrule shall prevent the handle from splitting in the shank area (see 4.2.1). Unless otherwise specified (see 6.2), the ferrule shall be fastened by (a) riveting through the ferrule, handle and shank, (b) staking metal ferrules into the wooden handle, or (c) any equivalent method to prevent the ferrule from loosening. Staked on ferrules shall be at least 2-1/2 inches long and shall fit approximately flush on the undercut wood handle."

PSC 3750

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:41Z
Check the source to verify that this is the current version before use.

Paragraph 6.2: Add the following options:

(d) If optional method of fastening the blade of type III grass whips is not permissible, state method required (see 6.4 and 3.12.1).
(e) If a specific method for fastening the ferrule is required for type III grass whips, state the method required (see 3.12.4).

Add paragraph 6.4 as follows:

6.4 Blade fastening option. For civil agency procurements, it is recommended that option "(d)" in paragraph 6.2, the specification of bolt or rivet fastening of the blade, not be exercised. Each of these methods has marginal advantages over the other. Bolted on blades provide ease in resharpening whereas riveted blades hold firmer. The warehousing of blades for type III grass whips is not recommended. Designs differ and the initial cost of the tool is low.

GSA DC 76-8869

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:41Z
Check the source to verify that this is the current version before use.