INTERIM AMEMDMENT

TO

FEDERAL SPECIFICATION

GUN, AIR BLOW, (BLAST CLEANING)

This interim amendment was developed by the Naval Facilities Engineering Command, Naval Construction Battalion Center, Davisville, RI 02854, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Service Administration has authorized the use of this amendment as a valid exception to GGG-G-770B, dated May 9, 1973.

PAGE 3

Paragraph 2.2: Above parenthesized address for Superintendent of Documents insert:

"Occupational Safety and Health Act (OSHA) of 1970

Title 29, Code of Federal Regulations, Chapter XVII, Part 1910, and amendments.

Occupational Safety and Health Administration Standards."

PAGES 3 AND 4

Paragraph 3.5, Delete in its entirety and substitute:

"3.5 Each gun shall consist essentially of a body, a control valve, and a nozzle having an orifice air opening. The gun shall be capable of providing for the automatic reduction of air in the nozzle to a pressure less than 30 psi. The control valve, which shall be easily operatable with one hand and a minimum of hand pressure, shall permit the delivery of air for cleaning purposes in short blasts or in a continuous flow.

FSC 4940

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.

Unless otherwise specified (see 6.2), the nozzle shall be detachable. The gun shall seal completely against the air flow at all operating pressures. For protection of the operator from chip fly-back, each gun shall have a nozzle capable of providing a cone of air around the main air stream, or a shatter-proof see-through chip guard attached near the tip, unless one of these protective measures is definitely specified (see 6.2)"

PAGE 5

Add new paragraph as follows:

"3.5.5 Safety and Health requirements. Safety devices shall be provided for the gun where safety hazards are possible. Such devices, as used, shall not cause substantial interference to operation of the gun. Except as otherwise specified by the procuring activity, the gun shall comply with paragraph 1910.242, promulgated under OSHA applicable to the gun itself. Exceptions and additional requirements for safety and health shall be as specified (see 6.2)."

PAGE 7

Table I: Delete major catagory "104" in its entirety.

PAGE 8

Paragraph 4.6.2: Delete in its entirety and substitute:

"4.6.2 Performance. The gun shall deliver air in a range from 0 to a pressure not to exceed a maximum of 30 psig in quick bursts or continuous flow with the valve fully opened. At an inlet pressure of 100 psig minimal air flow capacity shall be at least 10 cubic feet per minute. Protective measures against chip fly-back, as applicable, shall be effective in protecting the operator."

Add new paragraphs as follows:

"4.6.3 Dynamic pressure test. At an inlet pressure of 100 psig, and with the control valve of the gun fully opened, the dynamic pressure at the nozzle tip shall be 30 psig or less.

"4.6.4 Static pressure test. At an inlet pressure of 100 psig, and with the nozzle tip orifice blocked (dead ended), the indicated gage pressure at the nozzle tip shall be 30 psig or less."

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:42Z
Check the source to verify that this is the current version before use.

Paragraph 6.2: Delete (f) in its entirety and substitute:

"(f) Requirement of tip attachment, if different, and when a specific chip fly-back protection is required (see 3.5)."

Add the option "Exceptions and additional safety and health requirements (see 3.5.5).", in the proper sequence.

Preparing activity:

Navy - YD

Project No. 4940-N353

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:42Z
Check the source to verify that this is the current version before use.