GGG-S-735/3
October 5, 1976

# FEDERAL SPECIFICATION SHEET

## STAMPING AND MARKING EQUIPMENT; RUBBER STAMP, HAND, FIXED AND REMOVEABLE TYPE, FOOD INSPECTION, VETERINARY

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

The complete requirements for procuring the rubber stamps described herein shall consist of this document and the issue in effect of Federal Specification GGG-S-735/GEN.

REQUIREMENTS:

Configuration: The stamp shall conform to the requirements specified on US Army Natick Research and Development Command (GL) Drawing 6-1-1746.

Material: The stamp pattern and cushion shall be rubber which shall have a durometer hardness of 50 $\pm$ 5 when tested for conformance with component and material inspection requirements of the general specification. The handle and block shall be stained and then coated with a finish that shall not soften or peel when tested for conformance with component and material requirements of the general specification.

The stamp handle and block shall be one piece of wood, the moisture content of which shall not exceed 14 percent when tested for conformance with component and material inspection requirements of the general specification. The handle and block shall be stained and then coated with a finish that shall not soften or peel when tested for conformance with component and material requirements of the general specification.

The metal cover and troughs for the removable type shall be corrosion-resistant steel with brass as an option for the troughs. The cover shall be finished in accordance with the manufacturer's standard commercial practice.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:42Z
Check the source to verify that this is the current version before use.

Material: (cont'd) The pattern and cushion shall be glued together and to the bottom surface of the block. Prior to nailing, the pattern and cushion shall evidence no more than 1/4-inch separation from the block edge when tested for conformance with the end item requirements of the general specification. The pattern and cushion shall be nailed to the bottom of the block so that the nails do not protrude through block.

Part Number: GGGS735-3P - Partial Inspection Approval
GGGS735-3C - Complete Inspection Approval

Custodians:

Army - GL
Navy - MS
Air Force - 99

Review activities:

Army - MD
Navy - SA
DSA-CS

Preparing activity:

Army - GL

Civil Agency Coordinating Activity:

GSA-FSS

Project No. 5120-0862-3

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 25 cents each.



Source: https://assist.dla.mil -- Downloaded: 202610-26T12:42Z
Check the source to verify that this is the current version before use.