INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

WRENCH, SPANNER

This interim amendment was developed by Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification 000-W-665b, dated October 30, 1963.

PAGES 1 and 2

Delete parenthetical paragraphs at bottom of page 1 and top of page 2 and insert the following:

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

PAGE 4

Paragraph 3.6.2: Delete and substitute:

3.6.2 Class 2, variable pivot point. The class 2 wrench shall cover a range of capacities from 5 to 12 inches in diameter. The wrench shall consist of a handle, a bolt and nut, and two interchangeable jaws of nominal thickness 3/8 and 3/4 inch. Each jaw shall have a minimum of eleven holes to provide the necessary adjustment. The handle shall have a minimum length of 22 inches. The wrench shall have a minimum weight of 10 pounds and be similar to figure 2.

PAGE 11

Paragraph 6.2: Delete in its entirety.

PAGE 12

Delete "Notice" paragraph in its entirety.

FSC 5120

GSA DC 67-16002

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:41Z
Check the source to verify that this is the current version before use.