UU-B-335A
INT. AMENDMENT-2(GSA-FSS)
April 3, 1969
SUPERSEDING
INT. AMENDMENT-1(GSA-FSS)
November 17, 1967

INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

BINDERS, LOOSE LEAF,

(WITH OR WITHOUT FLEXIBLE PRONG)

This interim amendment was developed by the General Services Administration, Federal Supply Services, Standardization Division, Washington, D.C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification UU-B-335A, dated August 9, 1957.

PAGE 1

Paragraph 1.2.1, delete and substitute:

1.2.1 Types, classes, and thicknesses. Binders covered by this specification shall be of the following types, classes, and thicknesses, as specified (see 3.1.1 and 6.2):

	Thickness
Type I. High density, nonprinting grade	0.020 inch
Class I. Without metal prong fastener and compressor.	
Class II. With metal prong fastener and compressor.	
Type II. Medium density, nonprinting grade	0.025 inch
Class I. Without metal prong fastener and compressor.	
Class II. With metal prong fastener and compressor.	

PAGE 3

Paragraph 3.6, delete and substitute:

3.6 Workmanship. The binder shall be finished in a neat workmanlike manner. All edges and surfaces shall be clean, smooth, free from any slime, oil, dye, tears, holes, ply separation, blow, blister, check, lump, warp, buckle, wave, wrinkle, crease, or any other defects which might impair its appearance or serviceability.

Section 4, delete and substitute:

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Examination and testing of components and material. In accordance with 4.1, the supplier is responsible for insuring that the following components and materials used in fabricating binders were manufactured, examined, and tested in accordance with this specification or referenced subsidiary specifications. Each component test report must be conducted within the period of the contract.

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:20Z
Check the source to verify that this is the current version before use.

4.1.1.1 Pressboard. Each shipment of pressboard received at one time, of the same type and color, and from the same source of supply and manufacturer's lot, shall be examined and tested in accordance with the requirements of UU-P-701 (see 3.1.1), except the sample size shall be limited to 2 sample units (800 square inches each) taken at random from the lot.

4.1.1.2 Metal fasteners. Each shipment of metal fasteners received at one time, and from the same source of supply and manufacturer's lot, shall be examined and tested in accordance with the requirements of FF-F-111 (see 3.1.2). Metal fasteners manufactured by the supplier shall be grouped by manufacturer's lot and examined and tested in accordance with the requirements of FF-F-111.

4.1.1.3 Cloth. Each shipment of cloth received at one time, of the same type, and from the same source of supply and manufacturer's lot, shall be tested for warp tear in accordance with test method 5132 of CCC-T-191 (see 3.1.3). Sample units of one yard each shall be taken from each lot in accordance with table I. Failure to meet the average sample unit requirement shall constitute rejection of the entire lot.

TABLE I. Sample Size

Linear yards of cloth	Sample Unit
50 or less	1
51 to 150	2
151 and over	3

4.1.1.4 Record of examination and testing of components and material. The supplier shall maintain records of components and material examination and testing. These records shall be available to the authorized Government representative, and shall include the component material designation, date of test(s), test data, and quantity of material represented by the test report.

4.2 Sampling

4.2.1 Lot. For purposes of sampling, a lot shall consist of all loose leaf binders of the same type, size and color offered for delivery at one time.

4.2.2 Sampling for end item examination. A random sample of binders shall be taken from each lot in accordance with MIL-STD-105, inspection level S-4. The acceptable quality level (AQL) shall not exceed 4.0 percent defective. The sample unit shall be one binder.

4.3 Examination of end item. Each sample taken in accordance with 4.2.2 shall be inspected for compliance with this specification with respect to size, color, construction, capacity, workmanship, packaging and packing, marking, and other requirements of this specification which may be determined by visual examination.

PAGE 4

Paragraph 6.2 (b), delete and substitute:

(b) Type of pressboard (see 1.2.1 and 3.1.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.