UU-B-00366b(GSA-FSS)
August 30, 1966
INTERIM REVISION OF
Fed. Spec. UU-B-366a
December 27, 1962

INTERIM FEDERAL SPECIFICATION

BINDER, LOOSE-LEAF, SECTIONAL-POST-TYPE

This Interim Federal Specification was prepared by the General Services Administration, Federal Supply Service, Standardization Division, Washington, D. C., 20406, based upon currently available technical information. It is recommended that Federal agencies use this document in procurement and forward recommendations for changes to the preparing activity. The General Services Administration has authorized Federal agencies to use this interim document as a valid exception to Federal Specification UU-B-366a, dated December 27, 1962.

1. SCOPE AND CLASSIFICATION

1.1 Scope. The loose-leaf, bound binders covered by this specification consist essentially of separable covers and sectional-type screw posts, with either an end- or a top-locking mechanism. Each binder is furnished with a key or a wrench-type device, or with a device having both of these characteristics. Inner sectional posts, covered herein, may be procured individually, when specified.

1.2 Classification.

1.2.1 Types and classes. The binders shall be of the following types and classes, as specified (see 6.2):

Type I — Top-locking mechanism.
Type II — End-locking mechanism.
Class 1 — Cloth hinges.
Class 2 — Metal hinges.

1.2.2 Dimensions (sizes). Unless otherwise specified, the binders shall be furnished in the dimensions listed in table I, under "Sheet size," as specified (see 3.2 and 6.2).

TABLE I. Dimensions (sizes)

Sheet size 1/	Center-to-center of posts, plus or minus 1/32 inch	Diameter of posts, plus or minus 1/64 inch
Inches	Inches	Inch
8-1/2 by 11	4-1/4	3/8
8-1/2 by 14	4-1/4	3/8
9-1/2 by 12	7	3/8
11 by 8-1/2	7	3/8
11 by 14	7	3/8
11 by 17	7	3/8
12 by 9-1/2	7	3/8
8-1/2 by 14	6-3/8	5/16
9-1/4 by 11-7/8	7-1/8	5/16
11 by 14	8-1/4	5/16

1/ The first dimension is the binding edge.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

1.2.3 Colors. Colors of binders shall be as specified (see 6.2).

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

UU-B-623 -- Book Cover Board.
CCC-T-191 -- Textile Test Methods.
PPP-B-566 -- Boxes, Folding, Paperboard.
PPP-B-576 -- Box, Wood, Cleated, Veneer, Paper Overlaid.
PPP-B-591 -- Boxes, Fiberboard, Wood-Cleated.
PPP-B-601 -- Boxes, Wood, Cleated-Plywood.
PPP-B-621 -- Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 -- Box, Fiberboard.
PPP-B-640 -- Boxes, Fiberboard, Corrugated, Triple Wall.
PPP-B-665 -- Boxes, Paperboard, Metal-Stayed (Including Stay Material.
PPP-B-676 -- Boxes, Setup.
PPP-T-60 -- Tape: Pressure-Sensitive Adhesive, Waterproof, for Packaging.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).
Federal Test Method Std. No. 151 - Metals; Test Methods.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-L-10547 -- Liners, Case, and Sheet, Overwrap, Water-Vaporproof or Waterproof, Flexible.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. Materials shall be as specified hereinafter.

3.2 General construction and outside dimensions. The binders shall consist of two covers held together by means of sectional posts and a locking mechanism (see 3.7 through 3.7.2.1). The outside dimensions of the binders shall be sufficiently larger than the "Sheet size," indicated in table I, to protect filler sheets and index tabs (see 3.9) contained in the binders. The outside dimensions of binders of the same sheet size shall be approximately the same.

3.3 Covers. Each cover shall be of book cover board conforming to UU-B-623, and having an average thickness of not less than 0.220 inch and a minimum bursting strength of 800 points. Covers shall be bound as specified in 3.4 and these, together with post assemblies, shall align evenly when locked. Corners of covers at the index edge shall be rounded.

3.4 Binding. Covers and post housing shall be bound with a continuous piece of Army duck having two-ply yarns (two single yarns twisted together) in both the warp and the filling directions, or of latex fiber made from new cotton rag fibers impregnated with latex. The Army duck and latex fiber materials shall each weigh not less than 7 ounces per square yard. The binding material shall be carried over the post housing and over the inside face of covers at least 5/8 inch beyond the edges. The binding material shall be securely glued in place. (See 3.6.1 and 3.7.)

3.4.1 Army duck.

3.4.1.1 Colorfastness to crocking. The duck shall have a rating of at least "fair" when tested as specified in 4.3.1.1.

3.4.1.2 Breaking strength. The duck shall have a breaking strength of 100 pounds warp and 60 pounds filling with a minus tolerance of 5 percent when tested as specified in 4.3.1.1.

3.4.2 Latex fiber.

3.4.2.1 Colorfastness. The fiber shall not show any appreciable change in color when tested as specified in 4.3.1.2.1.

3.4.2.2 Tearing and breaking strength. The fiber shall not tear or break in either a wet or dry condition when tested as specified in 4.3.1.2.2.

3.4.2.3 Flexure. The fiber shall show no undue wear when tested as specified in 4.3.1.2.3.

3.4.2.4 Moisture. The fiber shall not tear or show other adverse effects when tested as specified in 4.3.1.2.4.

3.4.2.5 Abrasion. The latex fiber shall not show any evidence of excessive wear when tested as specified in 4.3.1.2.5.

3.5 Paper lining. Paper lining for the inside of covers shall be a suitable paper having a minimum weight of 60 pounds per 500 sheets, 24 by 36 inches, sheet size, securely glued to the cover. Color of lining shall be in accordance with good commercial practice.

3.6 Hinge. The hinge shall connect the binding post housing to the cover.

3.6.1 Class 1. Class 1 hinges shall consist of three thicknesses of binding material securely glued together and to the binding post housing.

3.6.2 Class 2. Class 2 hinges shall be of the continuous piano type made of cold-rolled steel.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

3.7 Post assembly. The post assembly shall consist of a metal housing hinged to each cover. The lower housing shall be fitted with threaded base sockets into which post sections can be screwed. The upper housing shall hold the end- or top-locking mechanism, as applicable. Upper and lower housings shall be constructed so that covers and post assemblies will align properly when locked.

3.7.1 Housings. The lower housing shall be a continuous metal tube or a continuous flat metal plate. If of the tube type, the lower housing shall be made of steel not less than 0.035 inch thick. The ends of housing tubes shall be capped with aluminum, steel, plastic, or rubber end plugs. If of the plate type, the lower housing shall be of steel having a cross section of not less than 0.0625 inch by 0.875 inch or 16-gage strip steel. The plate shall be backed by two sheets of not less than 0.120-inch-thick book cover board, securely glued together and to the housing plate. The upper housing shall be a continuous metal tube similar to the lower housing, fitted with either a top-locking mechanism as specified in 3.7.1.1 or an end-locking mechanism as specified in 3.7.1.2, capable of holding the housing firmly at any desired position on the posts. Locking mechanisms shall operate smoothly and efficiently and when binders are locked they shall be secure to the extent that the locking mechanism cannot be opened manually without damage to the mechanism.

3.7.1.1 Type I binders. The top-locking mechanism for type I binders shall be operated by either a knurled thumb knob, slide button on top of the housing, or other device in accordance with good, acceptable commercial practice.

3.7.1.2 Type II binders. The end-locking mechanism for type II binders shall be located at one end of the housing and shall be operated by means of a key (see 3.7.1.3). The locking device shall be constructed of cold-rolled steel. All surfaces of the locking device shall be casehardened.

3.7.1.3 Types I and II binders. Each binder shall be furnished with a key or a wrench-type device, or with a device having both of these characteristics, as applicable. Keys shall lock and unlock binders effectively. The wrench-type device shall be of a material and so designed that it will engage and tighten the posts in accordance with good commercial practice. Each device shall be secured to binder for safekeeping in shipment (see 5.1).

3.7.2 Posts. Unless otherwise specified, the center-to-center location and the diameter of the posts shall be as shown in table I and as specified in the invitation for bids. Posts shall be made up of sections assembled by means of male and female threads. Posts shall be made of steel having a hardness of not less than 65 on the Rockwell B scale. Posts shall be placed equidistant from edges of binder within 1/8-inch tolerance. Unless otherwise specified, posts furnished with each binder shall consist of two 1/2-inch smooth top sections, two 1/2-inch base sections, and two 1-inch inner sections. The two 1/2-inch smooth top sections shall be positioned in the binder and the binding mechanism shall be locked, when received. The remaining sectional posts and the key, or other device as specified in 3.7.1.3, shall be furnished with the binder as specified in 5.1.

3.7.2.1 Inner sectional posts. Inner posts as specified in 3.7.2 shall be furnished individually, when specified. The posts shall be threaded externally on one end and internally on the other end, and shall be designed and constructed in a manner to fit and function satisfactorily with top and base sectional posts and additional inner posts where applicable. Quantity and diameter of posts shall be as specified (see 5.1.1.1, 5.1.2.1, 5.2.1.1, 5.2.2.1, and 6.2).

3.8 Finish. Unless otherwise specified, all exposed metal parts shall be zinc-coated or shall be given a black oxide finish covered overall with a suitable drying oil or shall be otherwise treated to resist corrosion in accordance with good commercial practice. (See 6.2.)

3.9 Index-tab allowance. Binders shall have an index-tab allowance of 7/8 inch, plus or minus 1/16 inch.

3.10 Identification of product marking. The manufacturer's name or trademark, or both, shall be legibly printed or stamped on the inside of one cover of the binder. When specified, "Property U. S. Government" or words to this effect, shall be included in the marking. Envelopes or bags containing accessory key or other device (3.7.2) shall be marked or identified in accordance with the manufacturer's normal commercial practice.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

3.11 Workmanship. The binders shall be well finished, clean, and all edges shall be smooth. All metal parts shall be free from burrs and rough or sharp edges. The finished binders shall be a good quality and grade of product as established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. (See 6.2.)

4.2 Sampling for inspection and tests. Sampling for inspection shall be performed in accordance with the provisions of MIL-STD-105, except where otherwise indicated. For purposes of sampling, an inspection lot shall consist of all end items of like classification (1.2) submitted for acceptance at one time.

4.2.1 Inspection of materials, components, and accessories. In accordance with 4.1, the supplier is responsible for insuring that materials, components, and accessories used in the end item(s) were manufactured, inspected, and tested in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified, or if none, in accordance with this specification. In the event of conflict, this specification shall govern. The supplier shall inspect and test components, accessories, and materials for the characteristics as specified herein. Sample materials requested for test shall be furnished when and as specified by the procuring officer (see 6.2). Lot sizes of materials, components, and accessories for purposes of determining the sample size shall be expressed in the same units as the test sample units and shall consist of all lots of materials, components, and accessories required to make the number of complete binders submitted for test and acceptance at one time. The sample size shall be S-1 of MIL-STD-105. The acceptable quality level (AQL) shall be 6.5 defects per 100 units. All requirements are applicable to the sample unit. Tests on canvas duck shall be conducted in accordance with the test methods of CCC-T-191 specified in 4.3.1.1, applicable test method of Federal Test Method Std. No. 151 for Rockwell hardness of steel posts, and section 4, as applicable, for latex fiber.

4.2.2 Inspection of end item(s).

4.2.2.1 Examination of end item(s). The end item(s) shall be examined in accordance with the classification of defects at the inspection levels and AQL's set forth in 4.2.2.1.5. Random samples shall be taken from each lot of binders, each with accessory key or other device, of the same classification (1.2) for visual, dimensional, operational, count, and preparation for delivery inspection for defects. The lot size for the purpose of determining the sample size in accordance with MIL-STD-105 shall be expressed in units of complete binders (each with accessory item as applicable) of the same classification (1.2) for the examinations in 4.2.2.1.1 and 4.2.2.1.2; in units of packages for examination in 4.2.2.1.3; and in units of shipping containers for the inspection specified in 4.2.2.1.4.

4.2.2.1.1 Visual and dimensional examination. Examination of the binders and accessory items shall be in accordance with the list of defects in table II. The sample unit for either visual or dimensional examination shall be one complete binder with accessory item as specified herein. In dimensional examination, a defect shall be any deviation from a specified dimension, within tolerances.

TABLE II. Visual and dimensional examination of end item(s)

Examine	Defects
End item(s).	Construction and dimensions not as specified. Component or accessory item missing; accessory item (key or wrench-type device, as applicable) not furnished with and secured to binder as specified.

(Continued)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

TABLE II. Visual and dimensional examination of end item(s) (cont'd)

Examine	Defects
End item(s) (cont'd.)	Inner sectional posts, ordered individually, not quantity or diameter specified. (See table IV.)
Covers and binding.	Covers not as specified; binding material not one continuous piece; not canvas or latex fiber material; binding not carried over the post housing and covers as specified; not secured as required. Lining not as specified; not securely glued to cover. Corners of covers not rounded at the index edge as specified.
Hinges.	Do not connect the binding post housing to cover as required. Class 1 hinges do not consist of three thicknesses of binding material and not glued as specified. Class 2 hinges not type or material specified.
Post assembly and housing.	Housing plate or tube not as specified; lower housing plate not backed as specified; any part of post assembly and housing, as applicable, not as specified. Top-locking mechanism of type I binder not as required. End-locking mechanism of type II binder not as specified. (See table III.)
Posts and accessory key or other device, as applicable.	Missing; not as specified; threads of posts do not join sectionally with ease and rigidity. One-half-inch smooth top posts not positioned in binder and covers locked as required. Covers will not lock properly. Wrench-type device does not engage posts properly; keys do not fit or perform satisfactorily. Center-to-center location and diameter of posts not as specified; posts not placed equidistant from edges of binder within tolerance permitted.
Index tab allowance --	Not as specified.
Identification of product marking.	Not as specified.
Workmanship ----------	Not as specified.

4.2.2.1.2 Operational examination of binding mechanism. The end item(s) shall be examined for defects involving operational performance of the binding mechanism as indicated in table III. The sample unit for this examination shall be one complete binder with accessory item.

TABLE III. Operational examination of binding mechanism

Examine	Defects
Binding and locking mechanisms—— The binder shall be opened, all posts shall be assembled in the binder, covers shall be closed and locked. Effort shall	Locking mechanism does not operate smoothly and efficiently. Covers and post assembly do not lock--or can be opened manually after locking with key or other device, as applicable (see 3.7.1); key to end-locking binder or device on top-locking binder does not open or lock binder. Wrench-type device does not engage and tighten posts. Locking mechanism does not hold the housing firmly at any desired position on the posts. Binder covers are misaligned when locked.

(Continued)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

TABLE III. Operational examination of binding mechanism (cont'd)

Examine	Defects
Binding and locking mechanisms—(cont'd) then be made to open or release the covers and post assembly manually. This operation shall be repeated a consecutive time. Assemble and lock binder at various positions on posts.	(See pg. 6.)

4.2.2.1.3 Examination for count of items in interior containers. Binders with accessory items packaged for shipment, and inner sectional posts ordered individually and packaged for shipment, shall be examined to determine conformance with specified quantities. The sample unit for this examination shall be one box (interior package). Any box containing less than the specified or marked quantities shall be classified as a defect.

4.2.2.1.4 Inspection of preparation for delivery. *Inspection shall be made to determine compliance* with the packing, packaging, and marking for shipment requirements of this specification. Defects shall be scored in accordance with table IV. The sample unit shall be one shipping container prepared for delivery and selected just prior to the closing operation. Defects of closure listed in table IV shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL, 4.0 defects per 100 units.

TABLE IV. Inspection of preparation for delivery

Examine	Defects
Shipping containers.	Not type, class, grade and other classification required.
Marking (exterior and interior).	Omitted, incorrect, illegible, of improper size, location, sequence, or method of application; not as specified.
Materials and workmanship.	Any component missing, or damaged sufficiently to affect the serviceability. Bulging or distortion of containers which adversely affects the contents. Inadequate application of components, such as incomplete closure of case liners and container flaps; loose strapping; inadequate stapling.
Contents and closure—	Not as specified. (See 4.2.2.1.3.)

4.2.2.1.5 Inspection levels and acceptable quality levels (AQL's) for examinations of end item(s). The inspection levels for determining the sample size and the AQL's expressed in defects per 100 units shall be as specified in table V.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

TABLE V. Inspection and AQL's

Examination paragraph	Inspection levels	AQL's
4.2.2.1.1:		
Visual examination	II	2.5
Dimensional	S-2	4.0
4.2.2.1.2	S-2	2.5
4.2.2.1.3	S-2	4.0

4.3 Tests.

4.3.1 Materials. (See 4.2.1.)

4.3.1.1 Army duck. Army duck shall be tested for colorfastness to crocking and for breaking strength in accordance with CCC-T-191, methods 5650 and 5100, respectively.

4.3.1.2 Latex fiber.

4.3.1.2.1 Colorfastness. The latex fiber shall be wet thoroughly with water and then completely dried. After drying, the test sample shall be inspected for any appreciable change in color.

4.3.1.2.2 Tearing or breaking strength. The latex fiber shall not tear or break when subjected to a breaking force of approximately 25 pounds. The sample shall be tested in both a wet and a dry condition. (See 4.3.1.2.4.)

4.3.1.2.3 Flexure. The latex fiber shall be flexed 8,000 to 10,000 times without failure. The material shall be flexed through a minimum bend radius of 135 degrees.

4.3.1.2.4 Moisture. The latex fiber shall be thoroughly soaked in water and subjected to the test specified in 4.3.1.2.2.

4.3.1.2.5 Abrasion. The latex fiber shall be subjected to continuous cycles of abrasion for approximately 5 minutes. The abrasive material shall be a medium grade of sandpaper.

4.3.1.3 Book cover board. Book cover board shall be tested, as applicable, in accordance with UU-B-623.

4.3.1.3 Metals.

4.3.1.4.1 Corrosion resistance. All exposed metal parts shall be tested for corrosion resistance by placing them in a boiling 10 percent (by weight) aqueous solution of sodium chloride for a period of 15 minutes. Upon being removed from this solution, metal parts shall be immediately immersed in 10 percent (by weight) aqueous solution of sodium chloride at room temperature. They shall then be removed from this solution, without having the adhering liquid wiped off, and allowed to dry for 24 hours at room temperature. The metal parts shall then be rinsed in lukewarm water, allowed to dry, and examined for evidence of corrosion.

4.3.1.4.2 Rockwell hardness. Rockwell hardness of steel sectional posts shall be determined in accordance with method 243.1 of Fed. Test Method Std. No. 151.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. The component parts, including specified number of sectional posts and locking device, shall be placed in a plastic bag and secured. Four binders and components of the same type,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

class, size, and color shall be packaged in a close-fitting fiberboard box conforming to class weather-resistant of PPP-B-636; grade to conform to the normal requirements of table II of PPP-B-636.

5.1.1.1 Inner sectional posts. Inner sectional posts, furnished individually, of the sizes and quantities as specified (see 6.2), shall be packaged in a close-fitting paperboard or fiberboard box conforming to PPP-B-566; PPP-B-665; PPP-B-676, or PPP-B-636. Each box shall be closed in accordance with the applicable container specification.

5.1.2 Level B. The component parts, including specified number of sectional posts and locking device, shall be placed in a paper envelope or plastic bag and secured. Four binders and components of the same type, class, size, and color shall be packaged in a close-fitting fiberboard box conforming to class domestic of PPP-B-636; grade to conform to the normal requirements of table I of PPP-B-636.

5.1.2.1 Inner sectional posts. Inner sectional posts, when furnished individually, of one size and in quantities of one hundred, shall be packaged in a close-fitting fiberboard or paperboard box conforming to PPP-B-566, PPP-B-665, PPP-B-676, or PPP-B-636. Each box shall be closed in accordance with the applicable container specification.

5.1.3 Level C. Binders shall be packaged to afford protection from damage from source of supply to first using activity. Supplier's commercial practice may be used if it meets this requirement.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Binders, packaged as specified in 5.1, shall be packed in a close-fitting overseas container conforming to PPP-B-576, PPP-B-591, PPP-B-601, PPP-B-621, PPP-B-640, or PPP-B-636. Fiberboard containers shall be waterproof sealed by the application of a 3-inch-minimum-width pressure sensitive tape conforming to class 3 of PPP-T-60, to all seams, corners, manufacturer's joints and staples. Wood and wood-cleated containers shall be provided with a type I or II, grade B or C, sealed case liner conforming to MIL-L-10547. Each shipping container shall be closed and reinforced in accordance with the appendix to the applicable container specification.

5.2.1.1 Inner sectional posts. Inner sectional posts, packaged as specified in 5.1, in quantities as specified (see 6.2), shall be packed in a fiberboard box conforming to class weather-resistant of PPP-B-636; grade to conform to the normal requirements of table II of PPP-B-636. Closure shall be in accordance with the container specification requirements.

5.2.2 Level B. Four unit packages of binders of one type, class, size, and color, packaged as specified in 5.1, shall be packed in a fiberboard box conforming to class domestic of PPP-B-636; grade to conform to the normal requirements of table I of PPP-B-636. Closure shall be in accordance with the requirements of the container specification.

5.2.2.1 Inner sectional posts. Twenty unit packages of inner sectional posts, packaged as specified in 5.1.2.1, shall be packed in a close-fitting fiberboard box conforming to class domestic of PPP-B-636; grade to conform to the normal requirements of table I of PPP-B-636. Closure shall be in accordance with the requirements of the container specification.

5.2.3 Level C. The binders shall be packed to insure carrier acceptance and safe delivery at receiving activity. Shipping containers shall comply with the carrier rules and regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123, including specification classification (such as type, class, size, etc.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

5.3.2 Military agencies. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

5.3.3 Levels A, B, and C. Shipping containers shall be marked "THIS SIDE UP——TOP" with binders in interior boxes so placed in shipping container that they are vertical top to bottom (on end).

6. NOTES

6.1 Intended use. The binders covered by this specification are intended for general office use and are commercially known as accounting binders.

6.2 Ordering data. Purchasers should select the preferred options permitted herein (see 3.7.2, 3.7.2.1, 3.8, and 3.10) and include the following information in procurement documents (see 4.2.1):

(a) Title, number, and date of this specification.

(b) Type, class, and dimensions (size) of binder required (see 1.2.1 and 1.2.2).

(c) Center-to-center dimensions and the diameter of posts if other than those shown in table I are required (see 1.2.2).

(d) Color of binder required (see 1.2.3).

(e) Quantity and diameter of inner sectional posts, when ordered individually (see 3.7.2.1).

(f) Inspection responsibility if other than as specified herein (see 4.1).

(g) Selection of applicable levels of packing and packaging required and any special marking for shipment desired (see 5.1, 5.2, and 5.3).

GSA DC 67-4328

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.