UU-B-368a
July 2, 1964
SUPERSEDING
Int. Fed. Spec. UU-B-00368 (GSA-FSS)
February 7, 1964

FEDERAL SPECIFICATION

BINDER, LOOSE-LEAF, SPRING BACK

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. The loose-leaf binder covered by this specification is a side opening, closed (nonseparable) spring-back type, designed for firm retention of papers when closed. The binder is equipped with a pressboard folder.

1.2 Classification.

1.2.1 *Type, grade, size, capacity, and color.* The binder shall be of but one type, grade, size, capacity, and color (see 3.1.3.7 and 3.3).

2. APPLICABLE SPECIFICATIONS AND STANDARDS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

UU-B-623—Book Cover Board.
UU-P-31 — Paper; General Specifications and Methods of Testing.
UU-P-701—Pressboard; Colored.
CCC-T-191—Textile Test Methods.
PPP-B-566 — Boxes, Folding, Paperboard.
PPP-B-576—Box, Wood, Cleated, Veneer, Paper Overlaid.
PPP-B-591—Boxes, Fiberboard, Wood-Cleated.
PPP-B-601—Boxes, Wood, Cleated-Plywood.
PPP-B-621—Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636—Box, Fiberboard.
PPP-B-665—Boxes; Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676—Boxes, Set-Up, Paperboard.
PPP-T-60 — Tape, Pressure-Sensitive Adhesive, Waterproof — for Packaging and Sealing.

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging and Packing Levels.
Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).
Fed. Test Method Std. No. 151—Metals; Test Methods.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Washington.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-L-10547—Liners, Case, and Sheet, Overwrap, Water-Vaporproof or Waterproof, Flexible.

Military Standards:

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials.

3.1.1 *Book cover board.* Book cover board shall conform to the requirements of Specification UU-B-623 and shall be not less than 0.120 inch thick.

3.1.2 *Pressboard.*

3.1.2.1 *Back.* Pressboard shall be 0.030 inch in thickness (average), conforming to type I of Specification UU-P-701.

3.1.2.2 *Folder.* Pressboard shall be 0.015 inch in thickness, conforming to type III of Federal Specification UU-P-701, except that a minus tolerance of 0.003 inch in thickness will be permitted.

3.1.3 *Coated cloth.*

3.1.3.1 *Base cloth.* The base cloth shall be cotton drill coated on the face side as specified in 3.1.3.2.

3.1.3.2 *Coating compound.* The coating compound shall be virgin plastic formulated from ethyl cellulose, cellulose acetate, polyvinyl chloride or polyvinyl chloride-acetate.

3.1.3.3 *Breaking strength and finished weight.* The breaking strength (Grab method) of coated cloth shall be a minimum of 34 pounds in both the warp and the filling directions. The finished weight of coated cloth shall be 11.07 ounces per square yard. A tolerance of plus 2 or minus 1 ounce per square yard in the finished weight will be permitted.

3.1.3.4 *Colorfastness to crocking.* The colorfastness of coated cloth to crocking shall have a rating of at least "good" when tested in accordance with test method of Specification CCC-T-191, specified in table IV.

3.1.3.5 *Flexibility.* The coated cloth shall be sufficiently soft and pliable for binder operations. The coating shall not crack through to the base cloth when tested in accordance with 4.3.2.1.

3.1.3.6 *Adhesion of coating to base cloth.* The pull necessary to separate the coating from the base cloth shall be not less than 3 pounds per inch when tested in accordance with 4.3.2.2.

3.1.3.7 *Color and finish.* The coated cloth shall be black and shall have a grain or finish simulating that of genuine leather.

3.1.4 *Steel (springs).* Steel shall be 1075 annealed spring steel, 0.017 ± 0.001 inch in thickness, hardened and tempered to a Rockwell superficial hardness rating of 69 to 72 on the 30-N scale. (See table IV.)

3.1.5 *Canvas.* Canvas shall be cotton (Army) duck consisting of 2-ply yarns in both the warp and the filling directions. The duck shall have a finished weight of not less than 7.0 ounces per square yard. Canvas shall be black.

3.1.5.1 *Colorfastness to crocking.* The colorfastness of canvas duck to crocking shall have a rating of at least "fair" when tested in accordance with test method specified in table IV.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

3.1.5.2 *Breaking strength.* The canvas duck shall have a breaking strength (Grab method) of 100 pounds in the warp direction and 60 pounds in the filling direction, with a minus tolerance of 5 percent when tested as specified in table IV.

3.1.6 *Red flexible board (reinforcement).* Red flexible board reinforcement material of back shall be at least 0.030 inch thick (see table IV).

3.1.7 *Paper lining.* Paper lining shall have a basis weight of 60 pounds per 500 sheets, 24 by 36 inches (see table IV). The color of the lining shall harmonize with the binding material.

3.2 Design, construction, and operational performance. Each binder shall be constructed to withstand the strains, jars, and other conditions incident to shipping, storage, and severe office service. The binder shall consist of two stiff covers and a closed, rounded back, containing four steel springs. Back and covers shall be bound with coated cloth. Coated cloth shall be one piece of material without splices, scratches, tears, or cuts. Binders shall be side-opening and shall be designed and constructed in a manner that the back expands or opens sufficiently to permit insertion and removal of sheets of a quantity in accordance with the full capacity of the binder, or less, when covers are bent back parallel with the width or capacity of the binder, or more, and closes when the covers are released, in a manner to firmly retain one sheet or up to and including the full capacity of the binder. Covers shall open and spring back to closed position in the normal manner. Each binder shall be equipped with an inner removable pressboard folder.

3.2.1 *Covers.* Covers shall be of book cover board bound with coated cloth securely glued to the entire area of contact with the back and covers. The binding material shall be carried over the inside surfaces of the covers at least 5/8 inch beyond the edges. A paper lining shall be securely glued to the inner surfaces of the covers and shall overlap the edges of the binding material at least 3/8 inch and the edges of canvas reinforcement extending from the back, approximately 2 inches (see 3.2.2). All corners of the non-binding side of the binder shall be rounded.

3.2.2 *Back and springs (binding mechanism).* Back shall be of pressboard, rounded, and joined to the covers by the binding material and canvas lining of the back. The interior of the back shall be lined with a double thickness of canvas which shall extend over the inner surfaces of the covers at least 2-1/4 inches. The exterior of the back, under the binding material, shall be cushioned with red flexible board which shall extend over entire pressboard back and the metal strips. The binder shall contain four round, steel springs spaced along the binding edge of the pressboard back, encased in the red flexible board, and sealed with two metal strips mounted on edges of the pressboard back. Springs shall be at least 1-1/4 inches long (along binding edge) with ends terminating on the two metal strips along the pressboard back. Spacing of the springs shall be in accordance with normal commercial practice.

3.2.3 *Pressboard folders.* Folders shall be of one-piece construction and shall be approximately 11 by 19 inches in size, shaped and scored parallel to the binding edge of binder in a manner to fit the back and remainder of the binder, as applicable, in a snug manner and to accept and enclose applicable size and number of sheets ranging to the full capacity of the binder. Folders shall be inserted in the binder and shall be the manufacturer's normal commercial color.

3.3 Size and capacity. Binder shall be 11 by 8-1/2-inch (sheet) size (the first dimension being the binding side), and 2-inch capacity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

3.4 **Identification marking.** The manufacturer's name of trademark of such known character as to be readily identifiable, shall be printed, heat stamped, or otherwise permanently marked on the inside of one cover of the binder. When specified, the words "Property U S Government," or any additional marking specified in the invitation for bids, contract, or order, shall be included in the marking (see 6.2).

3.5 **Workmanship.** The binders shall be well finished, clean, and all edges shall be smooth. Binders shall not contain any defects which might affect the serviceability or which affect the appearance (see table I). Corners shall be neatly pleated or turned in accordance with the manufacturer's normal commercial practice. Folders shall be clean and free from any defects which affect the appearance or which might effect the serviceability of the product.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 **Responsibility for inspection.** Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. (See 6.2.)

4.2 **Sampling for inspection.** Sampling for inspection shall be performed in accordance with the provisions of MIL-STD-105, except where otherwise indicated. An inspection lot shall consist of all end items submitted for delivery at one time.

4.2.1 *Inspection of materials and components.* In accordance with 4.1, the supplier is responsible for insuring that materials and components used in the end item were manufactured, inspected, and tested in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified, or if none, in accordance with this specification. In the event of conflict this specification shall govern. The supplier shall inspect and test components and materials for the characteristics listed in table IV. The sample unit used or submitted by the contractor for tests shall be 1 yard full width of the coated cloth, 1/2 yard full width of canvas duck, 1 each steel spring as used in binder, and one 11 by 8/2-inch-size piece each of book cover board, pressboard (as applicable), and red flexible board. The lot sizes of the various components and materials for purposes of determining the sample size shall be expressed in the same units as the test sample units and shall consist of all lots of components and materials required to make the number of complete binders submitted for test and delivery at one time. The sample size shall be S-1 of MIL-STD-105. The acceptable quality level (AQL) shall be 6.5 defects per one hundred units. All requirements are applicable to the sample unit. Tests on canvas duck and coated cloth shall be conducted in accordance with the method of testing specified in CCC-T-191. Spring steel shall be tested in accordance with applicable test method of Fed. Test Method Std. No. 151; paper lining in accordance with Specification UU-P-31.

4.2.2 *Inspection of end item.*

4.2.2.1 *Examination of end item.* The end item shall be examined in accordance with the classification of defects at the inspection levels and acceptable quality levels (AQL's) set forth in 4.2.2.1.6. Random samples of items prepared for delivery as specified, shall be selected from each lot for visual, demensional, operational, count, and preparation for delivery defects. The lot size for the purposes of determining the sample size in accordance with MIL-STD-105 shall be expressed in units of binders for the examinations in 4.2.2.1.1, 4.2.2.1.2, and 4.2.2.1.3; in units of intermediate packages under 4.2.2.1.4; and in units of shipping containers under 4.2.2.1.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

4.2.2.1.1 *Visual examination.* Examination of the binders shall be for defects specified in table I. The sample unit for the examination shall be one complete binder. (See 4.2.2.1.6.)

TABLE I.—*Examination for defects*

Examine	Defects
Binder (for visual and dimensional defects, as applicable)	Not size or capacity specified.
	Binding material (coated cloth) and canvas not color specified; finish does not simulate that of leather.
	Binder not side-opening.
	Binding material not one-piece construction; not securely glued to area of contact with back and covers.
	Binding material not carried over the inside surfaces of covers at least 5/8 inch beyond the edges.
	Paper lining not securely glued to inner surfaces of covers; does not overlap edges of binding material at least 3/8 inch and the edges of canvas reinforcement at least 2 inches; color does not harmonize with binding material.
	Corners of non-binding side of covers not rounded.
	Back not closed and rounded; not cushioned with red flexible board as specified.
	Back not joined to covers by binding material and canvas lining of back as specified.
	Interior of back not lined with double thickness of canvas.
	Canvas does not extend from the back and over inner surfaces of the covers at least 2-1/4 inches.
	Less than four steel springs contained in back.
	Steel springs not encased and sealed in back as specified.
	Steel springs not dimension specified.
	One or both metal strips missing from back; strips not metal.
	Ends of steel springs do not terminate on metal strips.
	Any dimension, within tolerances permitted, not as specified.
	Identification marking missing; not as specified.
	Pressboard folder missing; not one-piece construction; not inserted in binder.
	Folders not clean; not free from defects affecting the appearance; evidence of defects which might affect the serviceability of the product.
	Binders not well finished (in good workmanlike manner); not clean.
	Binding material spliced, scratched, torn, or cut; or otherwise damaged to the extent that appearance of binders is affected or that the serviceability of the binder might be affected.

4.2.2.1.2 *Examination of end item for dimensional defects.* The sample unit for this examination shall be one complete binder. A defect shall be any deviation from specified dimension, within tolerances, as indicated in table I. (See 4.2.2.1.6.)

4.2.2.1.3 *Examination for operational performance of binding mechanism.* The sample unit for this examination shall be one complete binder (see 4.2.2.1.6). The sample item shall be examined for defects as listed below. While examination is made for the specified defects, the binder shall be opened and closed in the normal manner. One sheet of paper shall be inserted when the binder is opened by pressing the covers back as indicated in 3.2 and allowed to remain when the binder is closed as indicated in 3.2. This operation shall be repeated three consecutive times with each binder, once with one sheet of paper and two times with a sufficient quantity of sheets to equal the capacity of the binder.

Defects:

Binders do not accept the full capacity (number of sheets) for which the binder is intended when opened (see 3.3).

Binder, when closed, does not firmly retain one sheet of paper.

Binder does not firmly retain the full capacity (number of sheets) for which the binder is intended, when closed.

Back and covers do not open and spring back to closed position in the normal manner.

4.2.2.1.4 *Examination for count of binders in interior containers.* Binders, packaged for shipment, shall be examined to determine conformance with package marking and specified quantity requirements. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

sample unit for this examination shall be one box (interior package). Any box containing less than the specified or marked quantity of binders shall be classified a defect. (See table II and 4.2.2.1.6.)

4.2.2.1.5 *Examination of preparation for delivery requirements.* An examination shall be made to determine compliance with the packaging, packing, and marking requirements of this specification. Defects shall be scored in accordance with table II. The sample unit shall be one shipping container fully prepared for delivery, selected just prior to the closing operation. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL, 4.0 defects per one hundred units.

TABLE II.

Examine	Defects
Marking (exterior and interior).	Omitted, incorrect, illegible, of improper size, location, sequence, or method of application; not as specified.
Materials.	Not as specified. Any component missing. Any component damaged, affecting serviceability.
Workmanship.	Inadequate application of components, such as incomplete closure of case liners, container flaps, loose strapping, inadequate stapling. Bulging or distortion of containers.
Content.	Number per container is more or less than required.

4.2.2.1.6 *Inspection levels and acceptable quality levels (AQL's) for examinations.* The inspection levels, for determining the sample size, and the acceptable quality levels (AQL's) expressed in defects per one hundred units, shall be as shown in table III.

TABLE III.

Examination paragraph	Inspection levels	AQL's
4.2.2.1.1	II	2.5
4.2.2.1.2	S-2	4.0
4.2.2.1.3	S-2	2.5
4.2.2.1.4	S-2	4.0

4.3 Tests.

4.3.1 *End item.* Testing of the completely fabricated binder shall be performed in accordance with table IV for the characteristics shown therein. The sample unit shall be one binder or material, as applicable, furnished as specified in 4.2.1. (See note[2] to table IV.) The lot size shall be expressed in units of binders. The inspection level for tests shall be S-1 and the AQL, 4.0 defects per one hundred units. There shall be no evidence of failure to meet specified requirements.

4.3.2 *Coated cloth (see table IV).*

4.3.2.1 *Flexibility.* The coated cloth shall be tested for flexibility as follows: A specimen from each sample unit, approximately 2-1/2 inches by 3 inches, shall be exposed to the radiation from a glass-enclosed carbon-arc lamp, such as the Fadeometer, with a current of approximately 13 amperes and 140 volts at the arc. The specimen, coated side toward the lamp, shall be placed 10 inches from the arc and the lamp so ventilated that the temperature of the air at the specimen is maintained at approximately 105°F. during the test. The specimen shall be exposed for 125 hours. The specimen shall be allowed to cool for at least 1 hour and then bent, coated side out, over a 1/8-inch-diameter rod. Examine for cracking of the coating compound through to the cloth base.

4.3.2.2 *Adhesion of coating to base cloth.* Not less than two specimens shall be taken from each sample unit with the long dimension in the direction of the warp and not less than two with the long dimension in the direction of the filling. Each specimen shall measure approximately 4 inches by 9 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

TABLE IV.

Instructions for testing of components

Component (See note[2].)	Characteristic	Specification reference		Number determinations per sample unit	Results reported as—	
		Requirement par.	Test method		Pass or fail	Numerically to nearest—
Coated cloth:	Base cloth	3.1.3.1	[1]			
	Coating compound	3.1.3.2	[1]			
	Breaking strength	3.1.3.3	5100	5		pound
	Finished weight per sq. yd.	3.1.3.3	5041 (See 4.2.1)	5		0.1 ounce
	Colorfastness to crocking	3.1.3.4	5650	1		rating
	Cracking	3.1.3.5	4.3.2.1	1	X	
	Coating adhesion	3.1.3.6	4.3.2.2	3		0.1 pound
Spring steel:	Material	3.1.4	[1]			
	Rockwell superficial hardness	3.1.4	Std. No. 151 (See 4.2.1)		-	
Canvas:	Weight per sq. yd.	3.1.5	5041	5		0.1 ounce
	Colorfastness to crocking	3.1.5.1	5650	1		rating
	Breaking strength	3.1.5.2	5100	5		pound
Red flexible board:	Material	3.1.6	[1]			
	Thickness	3.1.6	[1]			
Paper lining ...	Basis weight	3.1.7	No. 110	5		0.1 pound

[1] *Certificate of compliance*: Certificate of compliance shall be furnished by the contractor, accompanied by actual test and inspection report or other verifiable data.

[2] Materials furnished in accordance with 4.2.1 shall be certified by the contractor as the same as those furnished in the end item.

The coating shall be carefully cut through to the cloth on two parallel lines, 2 inches apart running lengthwise of the piece, but extending so that one cut ends 2 inches from one end of the piece, and the other cut ends 3 inches from the same end. The ends of these lines shall be joined with a diagonal cut through the coating but not the cloth. The edge of the knife shall be carefully worked under the point of the angle thus obtained, lifting the coating at the edge of the 2-inch strip for a distance of 2 inches from the point. If necessary, a small amount of acetone, ethyl acetate, or other suitable solvent may be used between the cloth and the coating as an aid in lifting the coating. If a solvent is used, a period of 24 hours should elapse before testing the specimen.

The raised end of the coating and the end of the piece shall be clamped in a tensile testing machine equipped with jaws not less than 2 inches wide. The coating shall be pulled from the cloth by the machine which is operated at a speed of separation of the jaws of 12 ± 1 inch per minute. If necessary, for satisfactory operation, the coating strip may be reinforced by cementing to it a 2-inch strip of the cloth. The load necessary to strip the 2-inch width of coating from the cloth shall be noted.

The results on warp specimens of each sample shall be averaged and divided by 2 to obtain the load per inch of width necessary to separate the coating from the base cloth, warp direction, for the sample. The results for the filling specimens shall be computed in the same way.

5. PREPARATION FOR DELIVERY

For civil agency procurement, the definitions and applications of the levels of packaging and packing specified hereinafter shall be in accordance with Fed. Std. No. 102.

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

5.1.1 *Level A.* Two binders shall be packaged in a snug-fitting paperboard box conforming to the requirements of Specification PPP-B-566, PPP-B-665, or PPP-B-676. Binders shall be arranged in the box with the backs alternated. Each box shall be secured to prevent accidental opening.

5.1.2 *Level B.* Packaging for level B shall be as specified in 5.1.1 for level A.

5.1.3 *Level C.* Binders shall be packaged in accordance with normal industry practice.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 *Level A.* Twelve boxes (24 binders), packaged as specified in 5.1.1, shall be packed in a snug fitting, fiberboard shipping container conforming to class 2, V3c or V3s, style RSC of Specification PPP-B-636. Each shipping container shall be provided with a type I or II, grade B or C, class 2 sealed case liner conforming to Specification MIL-L-10547. In lieu of the waterproof case liner, fiberboard containers shall have all seams, corners, and manufacturer's joints sealed by the application of a 3-inch-minimum-width olive-drab-color tape conforming to type III, class 1 of Specification PPP-T-60. Alternatively, shipping containers may be used that conform to style A or B, class 2 of Specification PPP-B-576; overseas type, Specification PPP-B-591 or PPP-B-601; or class 2, style 2 or 4, of Specification PPP-B-621. The alternate specified for the fiberboard containers shall also be provided with a sealed case liner as specified for the fiberboard container. Each shipping container shall be closed and strapped with flat steel strapping or tape banding in accordance with the appendix to the applicable container specification.

5.2.2 *Level B.* Twelve boxes (24 binders), packaged as specified in 5.1.2, shall be packed in a snug-fitting fiberboard shipping container conforming to type I or II, class 1, style RSC or Specification PPP-B-636. The minimum bursting strength of the fiberboard shall be 175 p.s.i. Closure shall be in accordance with the appendix to PPP-B-636. When specified, shipping containers may be used that conform to style A or B, class 1 of Specification PPP-B-576; domestic type, style A or B of Specification PPP-B-591 or PPP-B-601; or class 2, style 2 or 4 of Specification PPP-B-621.

5.2.3 *Level C.* Binders, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination. Shipping containers shall comply with the carrier rules and regulations applicable to the mode of transportation.

5.3 Standard pack (civil agencies). The standard pack (for civil agencies) for the item covered by this specification shall be as specified for level B in 5.1.2 and 5.2.2, interior and exterior containers, respectively.

5.4 Marking.

5.4.1 *Civil agencies.* In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.4.2 *Military agencies.* In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

5.4.3 *Levels A, B, or C.* Containers shall be marked "THIS SIDE UP—TOP" with binders in intermediate boxes so placed in shipping container that they are vertical top to bottom (on end).

6. NOTES

6.1 Intended use. The binder covered by this specification is intended for use in filing papers when it is desirable that they be readily removed or inserted.

6.2 Ordering data. Purchasers should exercise any desired options offered herein

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

(see 5.2.2) and procurement documents should specify the following (see table IV, note [1]):

(a) Title, number, and date of this specification.

(b) Data; inspection responsibility, if other than as specified in 4.1.

(c) Any identification marking required in addition to that specified in 3.4.

(d) Level of packaging, level of packing, and any special marking for shipment required (see 5.1, 5.2, and 5.4).

6.2.1 *Standard pack (for civil agencies).* The standard pack requirements specified for level B, section 5 (Preparation for Delivery), are intended for use in procurement of Stores Stock replenishments. Procuring officers should use the standard pack provisions when it is known that the material will be shipped from a supplier to a domestic warehouse, supply depot, or intermediate storage point for temporary storage, subsequent issue, and/or shipment to eventual user. (See 5.3.)

6.3 *Transportation data.* Transportation descriptions and minimum weights applicable to this commodity are:

Rail:

Binders, looseleaf, cloth and plastic combined.
Carload minimum weight 30,000 pounds.

Motor:

Binders, looseleaf, cloth and plastic combined.
Truckload minimum weight 30,000 pounds, subject to Rule 115, National Motor Freight Classification.

Copies of this specification may be purchased for 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.