UU-B-368A
AMENDMENT-5
August 4, 1975
SUPERSEDING
Amendment-4
June 5, 1973

FEDERAL SPECIFICATION

BINDER, LOOSE-LEAF, SPRING BACK

This amendment, which forms a part of Federal Specification UU-B-368A dated July 2, 1964, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 1

Paragraph 2.1, under "Federal Specification", delete:

"UU-B-623 - Book Cover Board,
CCC-T-191 - Textile Test Methods."

Paragraph 2.1, under "Federal Standards", delete:

"Fed. Std. No. 102 - Preservation, Packaging and Packing Levels.
Fed. Test Method Std. No. 151 - Metals; Test Methods."

Paragraph 2.1, under "Federal Standards", add:

"Fed. Test Method Std. No. 191/GEN (General Provisions) - Textile Test Methods.
Fed. Test Method 191/5041 - Determination of Weight of Textile Materials: Small Specimen Method.
Fed. Test Method 191/5100 - Breaking Strength and Elongation, of Woven Cloth; Grab Method.
Fed. Test Method 191/5651 - Crocking of Woven and Knitted Cloth; Standard Sample Munsell Scale Method."

PAGE 2

Add new paragraph 2.2, as follows:

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM) Standard:

E 18 - Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Technical Association of the Pulp and Paper Industry (TAPPI) Publications:

T 410 - Weight Per Unit Area (Basis Weight or Substance) of Paper and Paperboard.
T 807 - Bursting Strength of Paperboard and Linerboard.

(Application for copies should be addressed to the Technical Association of the Pulp and Paper Industry, 360 Lexington Avenue, New York, NY 10017.)

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

PAGE 2 (con.)

Delete paragraph 3.1.1 and substitute:

"3.1.1 Book cover board. Book cover board shall be not less than 0.117 inch thick, and shall have a bursting strength of not less than 415 points."

Paragraph 3.1.3.2, line 3: Following "from" insert "pyroxylin,".

Paragraph 3.1.3.4, delete "Specification CCC-T-191," and substitute "Fed. Test Method Std. No. 191".

PAGE 4

Paragraph 4.2.1, last two sentences, delete and substitute:

"Tests on canvas duck and coated cloth shall be conducted in accordance with the methods of testing specified in Fed. Test Method Std. No. 191. Spring steel shall be tested in accordance with ASTM E 18; and paper lining in accordance with specification UU-P-31."

PAGE 7

Table IV, delete and substitute as follows:

TABLE IV.

Instructions for testing of components

Component (See note 2.)	Characteristic	Specification reference		Number determinations per sample unit	Results reported as-	
		Requirement par.	Test method		Pass or fail	Numerically to nearest-
Coated cloth:	Base cloth	3.1.3.1	1/			
	Coating compound	3.1.3.2	1/			
	Breaking strength	3.1.3.3	5100	5		pound
	Finished weight per sq. yd.	3.1.3.3	5041 (See 4.2.1)	5		0.1 ounce
	Colorfastness to crocking	3.1.3.4	5651	1		rating
	Cracking	3.1.3.5	4.3.2.1	1	X	
	Coating adhesion	3.1.3.6	4.3.2.2	3		0.1 pound
Spring steel:	Material	3.1.4	1/			
	Rockwell superficial hardness	3.1.4	ASTM E 18 (See 4.2.1)			
Canvas:	Weight per sq. yd.	3.1.5	5041	5		0.1 ounce
	Colorfastness to crocking	3.1.5.1	5650	1		rating
	Breaking strength	3.1.5.2	5100	5		pound
Red flexible board:	Material thickness	3.1.6	T410			
		3.1.6	T410			
Paper lining:	Basis weight	3.1.7	No. 110	5		0.1 pound
Book coverboard:	Thickness	3.1.1	T410			
	Bursting Strength	3.1.1	T807			

1/ Certificate of compliance: Certificate of compliance shall be furnished by the contractor, accompained by actual test and inspection report or other verifiable data.

2/ Materials furnished in accordance with 4.2.1 shall be certified by the contractor as the same as those furnished in the end item.

Between Section 5 heading and paragraph 5.1, delete "For civil agency procurement ... 102.".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

PAGE 8

Paragraph 5.2.1, line 4, delete "class 2" and substitute "class weather resistant".

Paragraph 5.2.2, lines 4 and 5, delete "type I or II, class 1," and substitute "type CF or SF, class domestic,".

Paragraph 5.3, delete in its entirety.

PAGE 9

Paragraph 6.2.1, delete in its entirety.

Paragraph 6.3, delete in its entirety.

DOD WAIVED COORDINATION

User Interest:

Army - GL

Preparing Activity:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.