UU-P-405c
December 9, 1965

SUPERSEDING
Fed. Spec. UU-P-405b
June 11, 1963

FEDERAL SPECIFICATION

PAPER, NEWSPRINT

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers newsprint paper and reflects item requirements parallel to the specifications of the Joint Committee on Printing (JCP A10).

1.2 Classification.

1.2.1 *Type and grade.* Newsprint paper in accordance with this specification shall be of the type and grade as specified hereinafter.

1.2.2 *Size and trim—sheets.* Paper shall be furnished in the size(s) ordered (see 3.1.1).

1.2.2.1 *Size and trim rolls.* Paper furnished in roll form shall be not less than specified (see 3.1.2).

1.2.3 *Weight.* Newsprint paper in accordance with this specification shall be furnished in the weight shown in table I.

1.2.4 *Color.* Newsprint paper in accordance with this specification shall be furnished in white (see 3.2).

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification:

Federal Specifications:

PPP-P-25—Printing and Stationery Paper, Packaging and Packing of.
UU-P-268—Paper, Kraft, Untreated, Wrapping.
UU-P-271—Paper, Wrapping, Waterproofed Kraft.

Federal Standard:

Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specification:

MIL-A-140—Adhesive, Water-Resistant, Waterproof, Barrier-Material.

Military Standards:

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

procuring activity or as directed by the contracting officer).

2.2 **Other publications.** The following publication forms a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

Joint Committee on Printing Publication:

Government Paper Specification Standards.

(Copies may be obtained from the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C., 20402.)

3. REQUIREMENTS

3.1 **Material.** Newsprint shall be made from such material and by such process as to insure compliance with the requirements of this specification.

3.1.1 *Size and trim—sheet.* Paper must be flat, trimmed square on four sides with clean, smooth edges, and evenly jogged. Paper must not be undersize and not more than 1/8 inch oversize in either direction, except for sheets 8-1/2 by 14 inches or smaller. On sheets up to and including 8-1/2 by 14 inches, paper shall not be undersize and not more than 1/16 inch oversize in either direction, and no successive sheets within any package shall differ from each other by more than 1/64 inch. Paper with the long dimension 32 inches or less will be considered square if the variation does not exceed 1/32 inch; over 32 inches, 1/16 inch (see 6.2).

3.1.2 *Size and trim—roll.* Roll width shall be not less than specified and not more than 1/8 inch oversize and shall have clean trimmed edges. Roll diameter shall be as specified with a tolerance of minus 1 inch or plus 1/2 inch (see 6.2).

3.1.3 *Roll winding.* Roll paper shall be tightly wound at even tension on fiberboard cores having an inside diameter of 3 plus or minus 1/16 inches, and shall not contain more than three splices. Splices must be neatly and securely overlapped (not taped) and flagged at both ends of the roll with projecting colored markers, not pasted to the splice. Core length shall be not less than the width of the roll material, nor greater by more than 1/4 inch. Cores shall be plugged at both ends with tightly fitted plugs.

3.2 **Color, finish, formation, and cleanliness.** Paper delivered under this specification must conform to the standard sample as adopted by the JCP (see 6.3).

3.3 **Weight tolerance.** Weight shall be figured in even pounds, the fraction being dropped if less than one-half; if one-half pound or over, 1 pound shall be added. Weight for rolls of newsprint and cut sheets up to and including 16 by 21 inches shall be calculated to the nearest one-tenth of a pound; if the weight calculates to a fraction of one-tenth equal to or greater than 0.05 the next higher tenth will be allowed; if 0.04 or less, the next lower tenth will be used. Variation tolerance shall be not more than 5 percent above or below the 1,000 sheet weight.

3.4 **Thickness tolerance.** A plus or minus tolerance of 0.0005 inch will be allowed.

3.5 **Grain.** Direction of the grain on flat paper shall be as ordered (see 6.2).

3.6 **Curl.** Paper must lie flat with either no tendency to curl or with a curl which can be overcome under reasonable working conditions.

3.7 **Pressroom conditions.** When paper will be used in air-conditioned pressrooms, the level of temperature and relative humidity maintained shall be stated in the invitation for bid (see 6.2).

3.8 **Weight, tensile strength, thickness,** and opacity shall comply with the requirements of table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

TABLE I. *Weight, tensile strength, thickness, and opacity for paper newsprint*

Weight 24 by 36 1000	Tensile strength average not less than		Thickness average	Opacity; not less than
	Machine direction	Across machine direction		
Pounds	*Kilograms*		*Inch*	*Percent*
64	2.5	1.2	0.0035	90

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may use his facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 *Inspection.* Inspection shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

4.2 Component and material inspection. In accordance with 4.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase documents.

4.3 Inspection of the end item.

4.3.1 *Examination of the end item.* The end item shall be examined for the defects set forth in the applicable subparagraphs at the inspection levels and acceptable quality levels (AQLs) shown in table II.

TABLE II.

Examination paragraph	End item	Lot size in units of	Sample unit	Inspection level	AQL	Defects in 100 units of
4.3.1.1	8 by 10-1/2 inch sheets	Reams	One 8 by 10-1/2 inch sheet	III	4.0	8 by 10-1/2 inch sheets
	Larger than 8 by 10-1/2 inch sheets	Reams	One 8 by 10-1/2 inch sheet	I and III[1]	4.0	8 by 10-1/2 inch sheets
4.3.1.2	Sheets	Reams	Full size sheet	III	1.5	Full size sheets
4.3.1.3						
4.3.1.3.1	Rolls	Rolls	Roll	S-1[2]	2.5	Rolls
4.3.1.3.2	Rolls	Rolls	Roll	S-1[2]	2.5	Rolls
4.3.1.3.3	Rolls	Rolls	8 by 10-1/2 inch area	S-1 and III[2]	4.0	8 by 10-1/2 inch areas
4.3.1.4	Sheets or rolls	Reams or rolls	Full size sheet or roll			
4.3.1.5	Sheets or rolls	Reams or rolls	Ream or roll	S-2	—	Reams (500 sheets)
				S-2	—	Rolls
4.3.1.6	Sheets	Shipping containers	Shipping container	S-2	2.5	Shipping containers
4.3.1.7	Sheets or rolls	Shipping containers or rolls	Shipping container or roll	S-2	2.5	Shipping container or roll

[1] For sheets larger than 8 by 10-1/2 inches, full size sheets shall be selected at level I and cut into as many sheets as possible 8 by 10-1/2 inches and randomly arranged for selection of the examination sample at level III.

[2] The same rolls shall be used for these examinations. The examination for visual defects shall be performed by examining 8 by 10-1/2 inch areas of the roll at level III, randomly spaced throughout the rolls selected at the S-1 level. Insofar as practicable, the areas examined shall be divided equally among the rolls.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

4.3.1.1 *Examination of the end item in sheet form, for visual defects.* No more than one sheet, 8 by 10-1/2 inches or larger, selected in accordance with table II, shall be taken from any ream. Both sides of the sample unit shall be examined.

Examine	Defect
Appearance	Color not as specified; not uniform on both sides; does not compare favorably with the standard sample.
	Cleanliness, finish, or formation does not compare favorably with the standard sample.
	Presence of holes, dirt, or oil spots; lumps, foreign or undigested matter, shives, slivers, scales, or slime spots larger than or more in number than in standard sample.

4.3.1.2 *Examination of the end item in sheet form for workmanship defects.* No more than one sheet selected in accordance with table II shall be taken from a ream.

Examine	Defect
Workmanship	Any tear, cuts, wrinkles, folds, chafed, or scuff marks.
	Not trimmed clean; ragged, torn, uneven, or crushed edges.
	Paper curls, does not lie flat after reasonable flexing.

4.3.1.3 *Examination of the end item, in roll form, for visual, construction, workmanship and color uniformity defects.*

4.3.1.3.1 *Roll construction.*

Examine	Defect
Assembly of roll	Not suitably restrained to prevent unwinding.
	Material not wound evenly and tightly on roll, causing soft or uneven edges or telescoping of the roll.
	Material not wound on a substantial core; core broken, collapsed, crushed, or mutilated.
	Plugs omitted from one or both ends; do not fit properly.
Unwinding of roll	Paper slips over core when unwinding.
	More than 3 splices per roll.
	Splices come apart during unwinding.
Unwinding of roll (cont'd)	Splice not evenly and neatly made; not flagged, does not cover entire width of material, tape used for making splices.
Workmanship	Any tear, cut, crease, wrinkle, fold, chafed, or scuff mark.
	Not trimmed clean; ragged, torn, uneven, or crushed edges.

4.3.1.3.2 *Color uniformity.* Color not uniform throughout the roll or between rolls.

4.3.1.3.3 *Visual defects.* Roll surfaces examined shall be within the rolls selected for examination under 4.3.1.3.1 and 4.3.1.3.2.

Examine	Defect
Appearance	Color not as specified; does not compare favorably with standard sample.
	Cleanliness, finish, or formation does not compare favorably with the standard sample.
	Presence of holes, dirt, or oil spots, lumps, foreign or undigested matter, shives, slivers, scales, or slime spots larger than or more in number than in standard sample.

4.3.1.4 *Examination of the end item, rolls or sheets, as applicable, for dimensional defects.*

Examine	Defect
Sheets:	
Sheet size	Less than specified along any edge.
Sheets 8-1/2 by 14 or less	Oversize by more than 1/16 inch along any edge from size specified.
Sheets over 8-1/2 by 14 inches	Oversize by more than 1/8 inch along any edge from size specified.
Squareness	Variation exceeds 1/32 inch for sheets 32 inches or less in length, or exceeds 1/16 inch for sheets over 32 inches in length.
Rolls:	
Width	Less than specified.
	Oversize by more than 1/8 inch.
Diameter	More than 1 inch less or 1/2 inch greater than specified.
Core	Inside diameter varies from 3 inches by more than 1/16 inch.
	Width less than width of roll material or greater by more than 1/4 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

4.3.1.5 *Examination of the end item for average count (sheets) or weight (rolls) as applicable.* The average number of sheets per ream of all sample units examined shall be not less than the specified quantity. The average weight per roll (including nonreturnable core, plugs, and wrapper) shall be not less than the indicated weight.

4.3.1.6 *Examination of the end item, in sheet form, for color uniformity.* Color not uniform within the reams and throughout the contents of the shipping container.

4.3.1.7 *Examination of preparation for delivery.* An examination shall be made to determine that the requirements of section 5 are met. Shipping containers, fully packed, shall be selected prior to the closing operation. Closed shipping containers shall be examined for closure defects.

Examine	Defect
Markings (exterior and interior)	Incorrect; incomplete; illegible; omitted; of improper size, location, sequence, or method of application.
Materials	Any nonconforming component; component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of components such as: incomplete closure of case liners, container flaps, loose or inadequate sealing, strapping or stapling.
	Bulged or distorted containers.
Contents	Number of packages or reams per shipping container more or less than specified or indicated.
Weights	Gross and net weight, as applicable, exceed requirement.

4.3.2 *Testing of the end item.* The end item shall be tested for the applicable characteristics as specified in section 3 for each lot presented for examination for each form of material. The characteristics tested, number of determinations, acceptance criteria and applicable test procedures shall be as specified in Part 2—Testing Standards of the Joint Committee on Printing Paper Specification Standards, dated May 1, 1965. For those quality characteristics applicable to the sample unit (thickness and grain direction), all sample units must pass for the quality of the lot to be acceptable.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 *Level A.* Sheets of newsprint shall be packaged in accordance with the level A packaging requirements of PPP-P-25 for "Paper, newsprint" of the applicable size.

5.1.2 *Level C.* Sheets of newsprint shall be packaged in accordance with the industry's practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 *Level A.*

5.2.1.1 *Sheets.* Sheets of newsprint, packaged as specified in 5.1, shall be packed in accordance with the level A packing requirements of PPP-P-25 for "Paper, newsprint" of the applicable size.

5.2.1.2 *Rolls.* Each roll of newsprint (see 3.1.3) shall be wrapped overall with waterproof barrier material conforming to UU-P-271, except when class C-1 is used, two thicknesses shall be required. The wrapper shall be closed at the ends by means of inside and outside headers of the same material as the wrapper. Seams and headers shall be sealed with a water-resistant adhesive conforming to MIL-A-140, using sufficient adhesive to effect a watertight seal.

5.2.2 *Level B.*

5.2.2.1 *Sheets.* Sheets of newsprint, packaged as specified in 5.1, shall be packed in accordance with the level B packing requirements of PPP-P-25 for "Paper, newsprint" of the applicable size.

5.2.2.2 *Rolls.* Each roll of newsprint (see 3.1.3) shall be wrapped overall with kraft paper having a minimum basis weight of 80 pounds per ream in accordance with UU-P-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.

3.6.8. The wrapper shall be closed at the ends by means of inside and outside headers. The seams of the wrapper and the headers shall be securely sealed with an adhesive commercially used for this purpose.

3.6.8 *Level C.* Sheets of newsprint, packaged as specified in 5.1, or rolls of newsprint (see 3.1.3) shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Shipments shall be in accordance with rules or regulations of carriers applicable to the mode of transportation.

5.3 Marking.

5.3.1 *Civil agencies.* In addition to any special marking required by the contract or order, interior packages and shipping containers, and rolls shall be marked in accordance with Fed. Std. No. 123.

5.3.2 *Military activities.* In addition to any special marking required by the contract or order, interior packages and shipping containers, and rolls shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. This paragraph is informational only and is not exclusively definitive of the end use. For minimum quality face and back letterpress printing of catalogs, pamphlets, newsletters, newspapers, etc., of a temporary nature. Printed matter may include text, line illustrations, and 65-line screen half-tones.

6.2 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(*a*) Title, number, and date of this specification.
(*b*) Form and size required (see 1.2.2 and 1.2.2.1).
(*c*) Grain direction (see 3.5).
(*d*) Pressroom conditions (see 3.7).
(*e*) Level of packaging, packing, and marking required (see section 5).

6.3 Standard comparison samples may be obtained upon application to the procuring agency issuing the invitation for bids.

6.4 Transportation descriptions. Transportation descriptions and minimum weights applicable to this commodity are:

Rail:

Newsprint paper, fibre content consisting of not less than 60% ground wood.
Carload minimum weight 40,000 pounds.

Motor:

Newsprint paper, fibre content consisting of not less than 60% ground wood.
Motor volume minimum weight 40,000 pounds.

MILITARY INTERESTS:

Army—GL

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:20Z
Check the source to verify that this is the current version before use.