UU-P-548b
September 3, 1965

SUPERSEDING
Int. Fed. Spec. UU-P-00548a (Army-GL)
January 12, 1965 and
Fed. Spec. UU-P-548
January 28, 1957

FEDERAL SPECIFICATION

PAPER, TELETYPEWRITER, ROLL FORM, FOR DUPLICATION BY SPIRIT PROCESS

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 This specification covers one type of roll-form teletypewriter paper for spirit process duplication.

2. APPLICABLE SPECIFICATIONS AND STANDARDS

2.1 The following specifications and standards of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

O-D-825—Duplicating Fluid, Direct Process (Spirit Type).
UU-P-150—Paper, Carbon, Duplicating Spirit-Process.
UU-P-232—Paper, Duplicating, Copy, Liquid Process.
UU-P-233—Paper, Duplicating, Master Spirit-Process.
PPP-B-566—Boxes, Folding, Paperboard.
PPP-B-636—Box, Fiberboard.
PPP-B-676—Boxes, Set-up, Paperboard.

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.
Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105—Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. The roll-form teletypewrit-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

er paper for spirit process duplication shall consist of a master paper and a coated duplicating paper (carbon).

3.1.1 *Master paper.* The paper shall conform to the requirements for master paper of UU-P-233, except that it shall be in roll form.

3.1.2 *Carbon paper.* The paper shall conform to the requirements of grade A, class 1 of UU-P-150 and shall not smear, blur, or otherwise discolor the master paper when tested as specified in 4.3.2.

3.2 Width. The width of the roll shall be not less than 8-25/64 inches and no more than 8-31/64 inches.

3.3 Diameter and length. The diameter of the roll shall be not more than 4-1/2 inches and shall contain 190 ± 5 feet of rolled material.

3.4 Color. The color of the master paper shall be white and the color of the carbon paper shall be purple, black, blue, red, or green as specified (see 6.2).

3.5 Construction. The master and carbon paper shall be one continuous length wound on a rigid fiber or cardboard core having an inside diameter of 0.95 to 1.05 inches and a wall thickness of 0.125 (1/8) inch with a tolerance of plus 0.063 (1/16) inch minus zero. The core shall have round plugs or discs, snugly fitted at each end, to prevent the core from collapsing. The carbon paper shall have the coated side in contact with the master for the full length of the roll and shall be narrower than the master by not more than 0.125 inch on each side of the roll. The paper shall be wound evenly and tightly and shall have clean cut edges, free from lint or fuzz. One splice on the master or carbon shall be permitted providing such splice does not impair the reproductive quality. A red signal not less than 0.25 (1/4) inch wide shall be applied to the paper in the long direction, running a distance of 10 ± 1 foot from the end nearest the core to warn the operator of the approaching end of the paper; the red signal shall be placed on the outer sheet only. The roll shall be banded and taped to prevent unrolling.

3.6 Performance.

3.6.1 *Duplicating quality, interrupted operation.* Copies produced from a properly prepared master sheet and tested as specified in 4.3.2 and 4.4.1.3 shall produce the following number of clearly legible copies, free from smudges, blurs or smears.

Carbon paper color	Initially	After 1 hour drying
Black	50	50
Purple	150	150
Blue	100	100
Other colors	125	125

3.6.2 *Duplicating quality, continuous operation.* Copies produced from a properly prepared master sheet and tested as specified in 4.3.2 and 4.4.1.4 shall produce the following number of clearly legible copies, free from smudges, blurs, or smears.

Carbon paper color	Total copies
Black	100
Purple	300
Blue	200
Other colors	250

3.7 Workmanship. The master and carbon paper forming the roll shall be clean, uniformly coated and free from pinholes or any other defects which might affect the appearance or quality of reproduction. Edges of roll shall be smooth-cut and clean.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may use his own facilities or any commercial laboratory ac-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

ceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 *Sampling for inspection and tests.* Sampling for inspection and tests shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated herein.

4.2 Component and material inspection. In accordance with 4.1, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase documents.

4.3 Inspection of the end item.

4.3.1 *Examination of the end item.* The end item shall be examined for the defects set forth in the applicable subparagraphs at the inspection levels and acceptable quality levels (AQLs) in 4.3.1.4. The lot size, for purpose of determining the sample size in accordance with MIL-STD-105, shall be expressed in units of rolls for examination under 4.3.1.1 and 4.3.1.2 and in units of shipping containers for examination under 4.3.1.3.

4.3.1.1 *Examination of the end item for defects in appearance, construction, and workmanship.* The sample unit for this examination shall be one roll of teletypewriter paper. No more than one sample unit shall be selected from a shipping container.

Examine	Defect
Appearance:	
Paper	Master paper not white.
Carbon paper	Not color specified (see 6.2). Not overcoated with protective film.
Construction .	Coated side of carbon not in contact with master paper.
Assembly of forms	Carbon paper missing.
Assembly of rolls	Not suitably restrained to prevent unwinding. Not wound uniformly and smoothly on roll causing uneven edges or telescoping. Not wound on a rigid core; core broken, collapsed, crushed or mutilated. Plugs or discs, as applicable, omitted from one or both ends; do not fit properly; too loose to the extent that plugs or discs fall in or out of opening.
Unwinding of roll	Paper and carbon not continuous; more than one splice in either carbon or paper. Roll wound unevenly causing wrinkles, sharp creases, or folds within roll.
Warning signal	Missing. Less than 9 feet or more than 11 feet from end or roll nearest the core.
Workmanship	Edges of roll ragged; not clean cut.

4.3.1.2 *Examination for defects in dimension.* The sample unit for this examination shall be one roll of teletypewriter paper. No more than one sample unit shall be selected from a shipping container.

Examine	Defect
Roll:	
Width	Less than 8-25/64 inches or more than 8-31/64 inches.
Length	More than 195 feet or less than 185 feet.
Diameter ...	More than 4-1/2 inches.
Core:	
Inside diameter ...	Less than 0.95 inch or more than 1.05 inches.
Thickness ...	Less than 1/8 inch, more than 3/16 inch.
Carbon paper	Coated side of carbon paper narrower than the master sheet by more than 1/8 inch on each side.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

4.3.1.3 *Examination of preparation for delivery.* An examination shall be made to determine that markings, materials, and workmanship comply with the requirements of section 5. The sample unit shall be one shipping container, fully packed, selected just prior to the closing operation. Shipping containers fully prepared for delivery shall be examined for closure defects.

Examine	Defect
Markings (exterior and interior) ...	Incorrect; incomplete; illegible; omitted, of improper size location, sequence, or method of application.
Materials ...	Any nonconforming component; component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of components, such as: incomplete closure of case liners, container flaps, loose or inadequate sealing, strapping, or stapling.
	Distorted or punctured containers.
Contents	Number of packages per shipping container not as specified.

4.3.1.4 *Inspection levels and AQLs for examinations.* The inspection levels, for determining the sample size, and the AQLs expressed in defects per 100 units shall be as follows:

Examination paragraph	Inspection levels	AQLs
4.3.1.1	I	4.0
4.3.1.2	S-2	4.0
4.3.1.3	S-2	2.5

4.3.2 *Testing of the end item.* The sample unit for this test shall be one roll of teletypewriter paper and no more than one sample unit shall be taken from any one shipping container. The lot shall be expressed in units of rolls in the end item inspection lot. The sample size shall be selected in accordance with table I and there shall be no failure to meet any performance requirement. Performance tests, as indicated in table II, shall be performed using the master and carbon papers covered by this specification, as a test set.

TABLE I. *Sampling plan*

Lot size (rolls)	Sample size
800 or less	2
801 up to and including 22,000	3
22,001 or more	5

4.4 Tests.

4.4.1 *Performance.*

4.4.1.1 *Apparatus.* The preparation of the duplicating master shall be made on an electric typewriter with pica type and in good operating condition. The typewriter shall be equipped with a typewriter ribbon not more than 0.0050 inch thick and a platen having a Shore durometer reading of between 89 to 93 or an equivalent platen designed for the preparation of duplicating masters on the machine being used. The type faces shall be thoroughly cleaned before each test.

4.4.1.2 *Procedure.* Place a sufficient length of the assembled master and carbon paper as required by the duplicating machine in the typewriter and type the master using the entire keyboard; small letters, capitals, numerals, and other characters. Type all material twice in unrelated order

TABLE II. *Instructions for testing of the end item*

Characteristic	Specification reference		Requirements applicable to individual unit	Number determinations per sample unit	Results reported as pass or fail
	Requirement	Test method			
Performance:					
Interrupted operation	3.6.1	4.4.1.3	X	1	X
Continuous operation	3.6.2	4.4.1.4	X	1	X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

with the stroke of the typewriter set at one-fourth of its full pressure. Repeat the same typing with the stroke of the typewriter set at one-half of its full pressure.

4.4.1.3 *Interrupted operation.* The typed master prepared as specified in 4.4.1.2 shall be placed on a spirit process duplicating machine. Using type II duplicating fluid conforming to O-D-825 and copy paper conforming to UU-P-232 reproduce the number of copies, for the applicable color of carbon paper, as follows: black—50, purple—150, blue—100, other colors—125. Remove the master and allow to dry for 1 hour, then replace the master and reproduce an equal number of copies. To be considered satisfactory, all copies produced shall be clean and legible.

4.4.1.4 *Continuous operation.* Using another portion of the sample unit, prepare a master sheet as specified in 4.4.1.2. Place the master on a spirit process duplicating machine and using the fluid and copy paper specified in 4.4.1.3 reproduce 10 copies, continue operating the machine for 5 revolutions without feeding copy paper, then reproduce an additional number of copies, in accordance with the applicable color of carbon paper, as follows: black—90, purple—290, blue—190, other colors—240. To be considered satisfactory all copies produced shall be clean and legible.

5. PREPARATION FOR DELIVERY

For civil agency procurement, the definitions and application of levels of packaging and packing shall be in accordance with Fed. Std. No. 102.

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 *Level A.* Each roll of typewriter paper shall be packaged in a snug-fitting folding or set-up paperboard box conforming to PPP-B-566 or PPP-B-676, respectively. Closure of the box shall be in accordance with the appendix of the applicable box specification.

5.1.2 *Level C.* The teletypewriter rolls shall be packaged in accordance with the industry's practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 *Level A.* Twelve rolls of teletypewriter paper, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to class weather resistant, V3c or V3s, style RSC of PPP-B-636. Each shipping container shall be closed, waterproofed by means of tape, and reinforced with flat steel strapping or tape banding in accordance with the appendix of the container specification.

5.2.2 *Level B.* Twelve rolls of teletypewriter paper, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to class domestic, style RSC of PPP-B-636. Closure shall be in accordance with the appendix of the container specification.

5.2.3 *Level C.* Teletypewriter paper rolls, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with the rules or regulations of carriers applicable to the mode of transportation.

5.3 Marking.

5.3.1 *Civil agencies.* In addition to any special marking specified in the contract or order, shipments shall be marked in accordance with Fed. Std. No. 123 and shall include date of manufacture and the note, "Deteriorative Material-Issue Stocks by Earliest Date".

5.3.2 *Military requirements.* In addition to any special marking required by the contract or order, interior packages and shipping containers shall be marked in accordance with MIL-STD-129. Markings on the shipping container shall additionally, in-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.

clude date of manufacture and the note, "Deteriorative Material-Issue Stocks by Earliest Date".

6. NOTES

6.1 **Intended use.** The teletypewriter paper described in this specification is used for recording messages to be reproduced by spirit process duplication.

6.2 **Ordering data.** Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(*a*) Title, number, and date of this specification.
(*b*) Color of carbon paper (see 3.4).
(*c*) Level of packaging and packing and any special marking for shipment required (see 5.1, 5.2, and 5.3).

6.3 **Transportation description.** Transportation descriptions and minimum weights applicable to this commodity are:

Rail:

Paper, teletype, printed or interleaved with carbon paper.
Carload minimum weight 36,00 pounds.

Motor:

Paper, teletype, printed or interleaved with carbon paper.
Truckload minimum weight 36,000 pounds, subject to Rule 115, National Motor Freight Classification.

MILITARY CUSTODIANS:

Army—GL
Navy—SA
Air Force—69

Review activities:

Army—GL, EL
Navy—SA
Air Force—69

User activities:

Navy—MC, CG

Preparing activity:

Army—GL

Review and User information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current Federal Supply Classification Listing Of DOD Standardization Documents.

Copies of this specification may be purchased for 5 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:21Z
Check the source to verify that this is the current version before use.