MILITARY SPECIFICATION

BAG, PILOT RELIEF

1. SCOPE

1.1 Scope. This specification covers the requirements for one type of disposable plastic bag suitable for the collection, retention and temporary storage of urine.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal

PPP-B-26	Bag, Plastic Polyethylene
L-P-375	Plastic Film, Flexible, Vinyl Chloride
L-P-378	Plastic Sheet and Strip (Polyolefin)
PPP-B-566	Boxes, Folding Paperboard
PPP-B-636	Box, Fiberboard
PPP-B-676	Box, Paperboard, Set-up

Military

MIL-P-116	Preservation, Methods of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:14Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material.

3.1.1 Bag. The bag shall be fabricated from a flexible (non-rigid) plastic film conforming to L-P-375, Type II, Class 1, colorless.

3.1.2 Thickness of film. The wall thickness for the bag shall be no less than 6 mils.

3.1.3 Absorbent. Bag shall contain an absorbent of either sponge type cellulose (compressed) or granular material not less than 4.75 cubic inches and capable of absorbing 500 cc. of urine.

3.1.4 Tubing or sheets. Tubing or sheets used shall be clean and free from pinholes, tears, cracks, blisters, creases, nicks and cuts or other defects which will impair its usefulness for the intended purpose.

3.2 Design and construction.

3.2.1 Design. The finished bag shall be of a simple flat plain rectangular or flask-like shape. Both sides and one end shall be sealed. The opening, or neck, of the bag shall incorporate means for preventing spillage when bag is inverted and shall not impede the normal flow input.

3.2.2 Dimensions. The dimensions of the bag in the flat, dry condition shall be 7 inches wide by 12 inches long with a tolerance of plus or minus 1/2-inch. Thickness shall not exceed 1/2-inch.

3.2.3 Closure. Closure shall be by means of a 28-gage steel (corrosion resistant), 3/8-inch wide band or wire of equal strength and flexibility imbedded or laminated in vinyl plastic so as to enable ease of folding or rolling in producing a positive closure.

3.2.4 Seams. All seams shall be made by heat (thermal) sealing.

3.2.5 Directions for use. Brief instructions for opening of bag and closure after use shall be printed on one side of bag.

3.3 Workmanship. The bag shall be uniformly constructed. The bag shall open easily so as not to impede its use. The finished product shall conform to the levels of quality established herein and shall be free from defects which detract from its appearance or impair its serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Inspection responsibility. The supplier is responsible for the perform-

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:14Z
Check the source to verify that this is the current version before use.

ance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection of materials. In accordance with 4.1, the supplier is responsible for insuring that materials used were manufactured, tested and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified, or, if none, in accordance with this specification.

4.2 Classification of tests. The inspection and testing of the bags shall be classified as acceptance tests. Bags used in testing shall not be used to fulfill quantity required by the contract or order.

4.3 Sampling. Sample bags shall be selected at random from each lot in accordance with MIL-STD-105. The inspection level shall be S-1 with an AQL of 10.

4.4 Tests.

4.4.1 Examination of product. Each sample bag shall be tested in sequence hereunder and shall be examined to determine conformance with this specification with respect to materials, workmanship and general requirements.

4.4.2 Inverted leakage test. The bag shall be filled with a minimum of 550 cc. of water and, without closing, quickly inverted. There shall be no more than 30 cc. of liquid spilled from the opening during a one-minute period.

4.4.3 Performance leakage test. After completion of test in 4.4.2, the opening, or top, of bag shall be closed by rolling or folding down to within approximately 1/2-inch of main body of bag. Fold metal tabs to secure rolled or folded end. The bag shall be laid in a horizontal position on a flat, smooth, level surface. A dead weight with smooth edges and corners, 6 inches by 10 inches and weighting 12 pounds shall be placed centrally on top of the bag. After allowing the bag to remain in this position for a period of one hour, the bag shall show no evidence of leakage.

4.4.4 Drop test. Three consecutive drops shall be made from a height of 6 feet to a smooth, hard surface. There shall be no failure of the seams, closure or leakage of water.

5. PREPARATION FOR DELIVERY

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:14Z
Check the source to verify that this is the current version before use.

5.1 Packaging. Packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Cleaning will be in accordance with MIL-P-116, Method C-1.

5.1.1.2 Drying. Drying will be by any method that will not adversely affect the material.

5.1.1.3 Preservation application. (Not applicable).

5.1.1.4 Unit packaging. Five bags will be packaged in a plastic envelop/bag fabricated from L-P-378 conforming to PPP-B-26. Closure shall be by heat sealing. Unit protection shall be Method III of MIL-P-116.

5.1.1.5 Intermediate packaging. The bags shall be packaged in intermediate containers conforming to specification PPP-B-566 or PPP-B-676. Quantity shall be limited to size and limitations of the container.

5.1.2 Level C. Cleaning, drying, preservation and packaging shall be in accordance with the manufacturers' commercial practices.

5.2 Packing. Packing shall be Level A, B, or C, as specified.

5.2.1 Level A. Bags packaged as specified in 5.1 shall be packed in a box conforming to PPP-B-636, Class Weather-Resistant.

5.2.2 Level B. Bags packaged as specified in 5.1 shall be packed in a box conforming to PPP-B-636, Class Domestic.

5.2.3 Level C. Bags packaged as specified in 5.1 shall be packed in a manner to insure carrier acceptance and safe delivery at destination. Containers shall be in accordance with Uniform Freight Classification Rules or regulations of other carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages, intermediate packages and shipping containers shall be marked in accordance with the requirements of MIL-STD-129.

6. NOTES

6.1 Intended use. Plastic bags furnished under the provisions of this specification are intended (but not limited) for use in fighter type aircraft lacking built-in relief facilities.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:14Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.

b. Quantity.

c. Applicable level of packaging and packing.

Preparing Activity

AIR FORCE 69

Project No. 8105-F190

Custodian:

AIR FORCE 69

Reviewer:

AIR FORCE 84, 85

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:14Z
Check the source to verify that this is the current version before use.