MIL-B-83665A
Dec 13, 1972
SUPERSEDING
MIL-B-83665 (USAF)
16 April 1968

MILITARY SPECIFICATION

BAG, PILOT RELIEF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the requirements for one type of disposable plastic bag suitable for the collection, retention, and temporary storage of urine.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal

L-P-375	Plastic Film, Flexible, Vinyl Chloride
PPP-B-26	Bag, Plastic, Polyethylene
PPP-B-566	Boxes, Folding, Paperboard
PPP-B-636	Box, Shipping, Fiberboard
PPP-B-676	Box, Paperboard, Set-up

Military

MIL-P-116	Preservation, Methods of

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 8105

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:14Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INCORPORATED, AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, N.W., Washington D.C. 20036.)

3. REQUIREMENTS

3.1 Material.

3.1.1 Bag. The bag shall be fabricated from a flexible (non-rigid) plastic film conforming to L-P-375, type II, class 1, colorless.

3.1.2 Thickness of film. The wall thickness for the bag shall be no less than 6 mils.

3.1.3 Absorbent. Bag shall contain an absorbent of either sponge type cellulose (compressed) or granular material not less than 4.75 cubic inches and capable of absorbing 500 cc of urine.

3.1.4 Tubing or sheets. Tubing or sheets used shall be clean and free from pinholes, tears, cracks, blisters, creases, nicks, and cuts or other defects which will impair its usefulness for the intended purpose.

3.2 Design and construction.

3.2.1 Design. The finished bag shall be of a simple flat plain rectangular or flask-like shape. Both sides and one end shall be sealed. The opening or neck of the bag shall incorporate means for preventing spillage when bag is inverted and shall not impede the normal flow input.

3.2.2 Dimensions. The dimensions of the bag in the flat, dry condition shall be 7 inches wide by 12 inches long. The bag will be so fabricated to provide a reservoir of 7 inches wide by 7-1/2 inches long incorporating a neck opening of 3-3/4 inches wide by 4-1/2 inches long. Tolerance shall be plus or minus 1/2 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:14Z
Check the source to verify that this is the current version before use.

3.2.3 Closure. Closure shall be by means of a 28 gage steel (corrosion resistant), 3/8 inch wide band or wire of equal strength and flexibility imbedded or laminated in vinyl plastic so as to enable ease of folding or rolling in producing a positive closure. The wire or band shall form an integral part of the bag during fabrication.

3.2.4 Seams. All seams shall be made by heat (thermal) sealing.

3.2.5 Directions for use. Brief instructions for opening of bag and closure after use shall be printed (see 5.3) on one side of bag.

3.3 Workmanship. The bag shall be uniformly constructed. The bag shall open easily so as not to impede its use. The finished product shall conform to the levels of quality established herein and shall be free from defects which detract from its appearance or impair its serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection of materials. In accordance with 4.1, the supplier is responsible for insuring that materials used were manufactured, tested, and inspected in accordance with the requirements of referenced specifications and standards to the extent specified, or if none, in accordance with this specification.

4.2 Classification of tests. The inspection and testing of the bags shall be classified as acceptance tests. Bags used in testing shall not be used to fulfill quantity required by the contract or order.

4.3 Sampling. Sample bags shall be selected at random from each lot in accordance with MIL-STD-105. The inspection level shall be S-1 with an acceptable quality level (AQL) of 10.

4.4 Tests.

4.4.1 Examination of product. Each sample bag shall be tested in sequence hereunder and shall be examined to determine conformance with this specification with respect to materials, workmanship, and general requirements.

4.4.2 Inverted leakage test. The bag shall be filled with a minimum of 550cc of water and, without closing, quickly inverted. There shall be no more than 30cc of liquid spilled from the opening during a one-minute period.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:14Z
Check the source to verify that this is the current version before use.

4.4.3 Performance leakage test. After completion of test in 4.4.2, the opening or top of bag shall be closed by rolling or folding down to within approximately 1/2 inch of main body of bag. Fold metal tabs to secure rolled or folded end. The bag shall be laid in a horizontal position on a flat, smooth level surface. A dead weight with smooth edges and corners, 6 inches by 10 inches and weighing 12 pounds, shall be placed centrally on top of the bag. After allowing the bag to remain in this position for a period of one hour, the bag shall show no evidence of leakage.

4.4.4 Drop test. Three consecutive drops shall be made from a height of 6 feet to a smooth, hard surface. There shall be no failure of the seams, closure, or leakage of water.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Cleaning will be in accordance with MIL-P-116, method C-1.

5.1.1.2 Drying. Drying will be by any method that will not adversely affect the material.

5.1.1.3 Unit packaging. Each bag will be unit packaged in a plastic bag conforming to Type II, Grade A, Style 1 of PPP-B-26. Closure shall be by heat sealing. Unit protection shall be method III of MIL-P-116.

5.1.1.4 Intermediate packaging. The bags shall be packaged in intermediate containers conforming to specification PPP-B-566 or PPP-B-676. Quantity shall be limited to size and limitations of the container.

5.1.2 Level C. Cleaning, drying, preservation, and packaging shall be in accordance with the manufacturer's commercial practices.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Bags packaged as specified in 5.1 shall be packed in a box conforming to PPP-B-636, Class Weather-Resistant.

5.2.2 Level B. Bags packaged as specified in 5.1 shall be packed in a box conforming to PPP-B-636, Class Domestic.

5.2.3 Level C. Bags packaged as specified in 5.1 shall be packed in a manner to insure carrier acceptance and safe delivery at destination. Containers shall be in accordance with Uniform Freight Classification Rules or regulations of other carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages, intermediate packages, and shipping containers shall be marked in accordance with the requirements of MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:14Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. Plastic bags furnished under the provisions of this specification are intended (but not limited) for use in fighter type aircraft lacking built-in relief facilities.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.

b. Quantity.

c. Applicable level of packaging (see 5.1).

d. Applicable level of packing (see 5.2).

6.3 Storage. Store in a dry, cool place.

Custodian:

Air Force - 69
Army - GL

Reviewer:

Air Force - 84
Army - MD

PREPARING ACTIVITY:

Air Force - 69

Project No: 8105-F220

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:14Z
Check the source to verify that this is the current version before use.